

SPARC COMPLIANCE DEFINITION 2.2

**SCD
2.2**

SPARC International

FINAL RELEASE

2/26/99

© 1990-1999 SPARC International Inc.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without the prior permission of the copyright owners.

The manual pages for socket functions are

© 1992, 1993 The Regents of the University of California. All rights reserved

Includes material copyrighted by UNIX System Laboratories, Inc., a subsidiary of SCO, Inc. Reprinted with permission.

The SPARC Compliance Definition 2.4 is published and printed by SPARC International.

Any comments relating to the material contained herein may be submitted to:

SPARC International Inc.

3333 Bowers Ave., Suite 280

Santa Clara, CA 95054-2913

TEL: (408) 748-9111 (Ext 228)

FAX: (408) 743-9777

URL: www.sparc.org

ATTN: Ghassan Abbas (abbas@sparc.org)

Trademarks

SPARC® is a registered trademark of SPARC International, Inc.

SPARCstation™ is a trademark of SPARC International, Inc.

Products bearing SPARC® trademarks are based on an architecture developed by Sun Microsystems, Inc.

ONC™ and SunOS™ are trademarks of Sun Microsystems, Inc.

NFS® is a registered trademark of Sun Microsystems, Inc.

UNIX® and OPEN LOOK® are registered trademarks of UNIX System Laboratories, Inc.

The X-Window System™ is a trademark of Massachusetts Institute of Technology.

OSF/Motif™ is a trademark of the TOG (X/Open + Open Software Foundation, Inc).

All other products or services mentioned in this document are identified by the trademarks or service marks of their respective companies or organizations. SPARC International, Inc. disclaims any responsibility for specifying which trademarks are owned by which companies or organizations.

This product contains intellectual property of Sun Microsystems, Inc., and any user of this product will be required to obtain a license from Sun Microsystems, Inc., prior to use.

SPARC COMPLIANCE DEFINITION 2.2

Preface

Audience and Purpose	7
Organization and Content	7
Publication Conventions	7
Other Publication Conventions	7

CHAPTER 1: Introduction

Overview	1-1
Definitions of Terms	1-1
Interface Set	1-1
Interface Member	1-1
Interface	1-1
Required	1-1
Optional	1-1
Deprecated	1-1
Rationale	1-2
Experimental	1-2
Normative References	1-2
Relationship to other Standards	1-3
Upward Compatibility	1-3
Summary of Changes	1-3
Organizational Changes to the SPARC Compliance Definition	1-3
Additional Library Interfaces	1-4
Updated Windowing Interfaces	1-4
Structure of the SPARC Compliance Definition	1-4
System Feature Interfaces	1-4
Library Interfaces	1-4
Command Interface	1-5
Definition of SPARC Compliance	1-5
Conforming Implementations	1-5
Conforming Application Programs	1-6
Compliance Testing	1-6

CHAPTER 2: Software Installation

Overview	2-1
CD-ROM Medium	2-1
Software Installation Changes	2-1

CHAPTER 3: Low-Level System Information**CHAPTER 4: Object Files**

Object Files Changes	4-1
----------------------------	-----

CHAPTER 5: Program Loading and Dynamic Linking

Program Loading and Dynamic Linking Changes	5-1
---	-----

CHAPTER 6: Libraries

Overview	6-1
The System Library	6-2
The libsys Interfaces	6-2

System Library Changes	6-6
System Library Changes (continued)	6-7
ABI Extensions	6-8
The C Library	6-10
The libc Interfaces	6-10
C Library Changes	6-13
C Library Changes (continued)	6-14
ABI Extensions	6-15
The Network Services Library	6-20
Overview	6-20
Transport Providers	6-20
The libnsl Interfaces	6-20
Network Services Changes	6-23
ABI Extension	6-24
The Socket Library	6-25
Structures and Manifest Constants	6-27
Dynamic Object File Loading	6-59
Introduction	6-59
ABI Extensions	6-62
Large File Support	6-68
Overview	6-68
Miscellaneous ABI Changes	6-77
Miscellaneous ABI Changes (continued)	6-78
Miscellaneous ABI Changes (continued)	6-79

CHAPTER 7: Formats and Protocols

Formats and Protocols Changes	7-1
Interconnecting SCD Conforming Systems	7-2
Overview	7-2
Transport Providers	7-2
Additional Interfaces	7-2

CHAPTER 8: System Commands

Overview	8-1
System Commands Changes	8-3
System Commands Changes (continued)	8-4

CHAPTER 9: Execution Environment

Execution Environment Changes	9-1
-------------------------------------	-----

CHAPTER 10: Windowing and Terminal Interfaces

The X Library Interfaces	10-1
Unsafe Macros	10-9
Overview	10-79
The Extension Library Interfaces	10-79
Overview	10-82
The libXt Interfaces	10-82
Deprecated X Toolkit Functions	10-86
Unsafe Macros	10-87
Subclassing Xt Widgets	10-107
Overview	10-125

The libXol Interfaces	10-125
Overview	10-141
The Motif Interfaces	10-141
Windowing and Terminal Interfaces Changes	10-236

Index

Preface

Preface

Audience and Purpose

The SPARC International *SPARC Compliance Definition* (SCD) is intended for use by anyone who is creating interoperable SPARC systems or applications.

The intended audience of the SCD documents consists of two groups: system implementors, and application developers. For system implementors, the SCD provides a reference to those interfaces and features which must be supplied by a SPARC compliant system. For application developers, the SCD provides a reference to interfaces and features that may be relied upon in all SPARC compliant systems.

This publication is intended to fulfill the following purposes:

- *Identify areas beyond the System V Application Binary Interface (gABI) and the System V Application Binary Interface, SPARC Processor Supplement (psABI) that the SPARC community deems important.*
- *Address ambiguous and/or loose specifications in current ABI documents.*

Organization and Content

The SCD 2.2 has been divided into chapters, as follows:

- Chapter 1 Introduction
- Chapter 2 Software Installation
- Chapter 3 Low-Level System Information
- Chapter 4 Object Files
- Chapter 5 Program Loading and Dynamic Linking
- Chapter 6 Libraries
- Chapter 7 Formats and Protocols
- Chapter 8 System Commands
- Chapter 9 Execution Environment
- Chapter 10 Windowing and Terminal Interfaces
- Index

This new organization follows the organization of the *System V Application Binary Interface* and *System V Application Binary Interface, SPARC Processor Supplement* documents. Having a parallel organization makes this document easier to use than previous editions of the SCD.

Publication Conventions

This publication uses page format and typographic variances to highlight particular kinds of information. These conventions of usage are generally consistent with publication conventions used by other UNIX publications, such as the AT&T *System V Interface Definition*, Third Edition.

Other Publication Conventions

The following typographical conventions are used within the text of this publication:

- *Filenames, pathnames, and system messages are shown in:*
typewriter font like this.
- *Titles of chapters in this publication are shown in plain Roman font, inside quotation marks like this: “Intro-*

duction."

- *Document titles are shown in plain, nonbold italic font like this:
System V Interface Definition (Third Edition).*

CHAPTER 1: Introduction

Introduction

Overview

This document is version 2.2 of the SPARC Compliance Definition.

The SPARC Compliance Definition, or SCD, defines a set of interfaces that all SPARC Compliant systems must provide in their implementations. The SCD provides information for binary-level compatibility, encompassing both the *System V Application Binary Interface* (gABI), and the *System V Application Binary Interface*, SPARC Processor Supplement (psABI) documents.

Definitions of Terms

Interface Set

The term “interface set” refers to a named collection of facilities, defined in the SPARC Compliance Definition, that is provided by a platform and can be used by an application. These collections, or “interface sets”, are listed in the section below titled “Structure of the SPARC Compliance Definition”.

An example is: the X11 Library Interface Set.

Interface Member

The term “interface member” is also used as a generic reference to any single facility that is provided by a platform for use by an application program.

Examples are: the `printf` function; the `errno` global data item.

Interface

The unadorned term “interface” means either “interface set” or “interface member” depending on the immediate context of its use. Any REQUIRED or OPTIONAL interface defined in this document will be part of the SCD for at least three years.

Required

The term “required” in this document is a qualifier for the terms “interface set,” “interface member,” and “interface.” When the term “REQUIRED interface set” is used in this document, SPARC conforming systems must provide the interface set; conformant applications can rely on the designated interface set always being available on any conforming system. The terms “REQUIRED interface member” and “REQUIRED interface” are defined similarly.

Optional

The term “optional” in this document is a qualifier for the terms “interface set,” “interface member,” and “interface.” When the term “OPTIONAL interface set” is used in this document, SPARC conforming systems may, but need not, supply the interface set; if a conforming system does supply the interface, the interface set must be present in its entirety, as defined by this document; applications can not rely on the designated interface set being available on any conforming systems, but if the interface set is available on a particular conforming system, a conforming application can rely on the interface set being available in its entirety on that particular conforming system. The terms “OPTIONAL interface member” and “OPTIONAL interface” are similarly defined.

Deprecated

The term “deprecated” in this document is a qualifier for the terms “interface set,” “interface member,” and

“interface.” When the term “DEPRECATED interface set” is used in this document, programmers are discouraged from using the designated interface set in new applications because the “DEPRECATED interface set” may not be supported in future versions of the SCD. The qualifier “deprecated” is orthogonal to the qualifiers “required” and “optional”. When an “interface set” is designated as “deprecated” the date of deprecation will be stated by the specification. “Interface sets,” marked as “deprecated,” will be kept in the SCD for at least three (3) years from the original deprecation date. The “DEPRECATED interface set” will also include in its specification, the earliest date at which the designated “interface set” may be removed from the specification. No required or optional interface will be removed from the standard without first being deprecated. The terms “DEPRECATED interface member” and “DEPRECATED interface” are defined similarly.

Rationale

Paragraphs labeled “rationale” in this document are non-normative and are for information only. An example of a Rationale paragraph follows below.

Rationale

The SPARC International Compliance and Compatibility Committee agreed that it would be more useful to intersperse rationale comments throughout the document than to confine them to an appendix.

Experimental

The term “experimental” in this document is a qualifier for the terms “interface set,” “interface member,” and “interface.” When the term “EXPERIMENTAL interface set” is used in the document, applications programmers are warned that 1) the designated interface set may not be available on any SPARC conforming systems, and, 2) the specification of the designated interface may change at any time or be deleted from the SCD at the sole discretion of SPARC International; SPARC International makes no commitment of a three-year stable period for any “EXPERIMENTAL interface set.”

Rationale

As an example, this release of the SPARC compliance definition includes the EXPERIMENTAL Large File Support Library. This interface set is completely new. Because the Large File Support Library is new, we have no experience with the correctness of the interface. Field experience may require that certain portions of the interface change to make the interface more useful or practical.

Normative References

The normative references called out in the SPARC Compliance Definition are:

- *System V Application Binary Interface*
Prentice Hall, ISBN 0-13-880410-9
- *System V Application Binary Interface SPARC Processor Supplement*
Prentice Hall, ISBN 0-13-8777630-X
- *The SPARC Architecture Manual, Version 8*
Prentice Hall, ISBN 0-13-825001-4
- *System V Interface Definition, Third Edition, Volumes 1 - 4*
AT&T Select Code 320-136 (Volume 1), 320-137 (Volume 2), 320-138 (Volume 3), 320-139 (Volume 4)
- *The X Window System (Third Edition)*
by Robert W. Scheifler and James Gettys
Digital Press, ISBN 1-55558-088-2
- *OSF/Motif Programmer's Guide (Rel. 1.2- Revised)*

Prentice-Hall, ISBN 0-13-643115-1

□ *OLIT Reference Manual*

Sun Microsystems, Part No. 800-6055-10, Revision A

□ *ISO 9660-1988: Volume and file structure of CD-ROM for information interchange*
1988-09-01

□ *ISO/IEC 10149: Data Interchange for read-only 120mm optical data disk (CD-ROM)*
1989-09-01

The definition of each interface in the SPARC Compliance Definition may reference one or more of the above documents. In those cases, the portion of the normative reference that is called out is part of this standard.

The definition of each Interface in the SPARC Compliance Definition may list errata to any of the above documents. In each such listed erratum, the definition contained in the erratum supersedes the corresponding portion of the normative reference.

These documents may be acquired from most technical book stores; additionally, SPARC International provides assistance in acquiring these references. If you require assistance in acquiring these references, call SPARC International at (415) 321-8692.

Rationale

The SCD represents a proper superset of the required interfaces and features described in the two ABI documents. One of the purposes of this document is to serve as the conduit through which features may migrate first into the processor specific ABI (SPARC psABI), and finally into the generic ABI (gABI). Consequently, the SCD includes a set of features and their associated interfaces that are beyond the ABI definitions. These features, and their associated interfaces have been included, in some cases to correct deficiencies in the ABI specifications, and in others to standardize functionality already in common use throughout the SPARC community.

Relationship to other Standards

As the SCD is a specification for binary level compatibility, it is important that it not conflict with already existing standards work, either de facto or de jure. To this end, the SCD 2.x draws upon the *System V Interface Definition (Third Edition)*, (indirectly through references to the *System V ABI*) as the specification to which it will remain functionally consistent. As a consequence, the conformance of SCD 2.x to other standards documents/agencies is minimally the same as that of the *System V Interface Definition*. Examples of standards to which this pertains are *POSIX 1003.1-1990 (ISO 9945-1)* and the *X/Open Portability Guide, Issue 3 (XPG3)*.

Upward Compatibility

The interfaces in SCD 2.2 are upwardly compatible with the interfaces in SCD 2.1, which in turn are upwardly compatible with the interfaces in SCD 2.0. That is to say, an application written to the interfaces defined in SCD 2.0 will run successfully without change or recompilation on a system that implements SCD 2.1 or SCD 2.2.

Summary of Changes

Organizational Changes to the SPARC Compliance Definition

Beginning with this issue, the SPARC Compliance Definition has been reorganized to parallel the *System V Application Binary Interface* and *System V Application Binary Interface, SPARC Processor Supplement* documents from USL.

Additional Library Interfaces

Chapter 6, which describes the required System Libraries, includes new functions in several libraries.

The C Library, `/usr/lib/libc.so.1`, is now required to provide the functions `crypt`, `encrypt`, `getitimer`, `gettimeofday`, `modf`, `sbrk`, `setitimer`, `setkey`, and `sysinfo`.

The Network Services Library, `/usr/lib/libnsl.so.1`, is now required to provide the function `rpc_broadcast_exp`.

In order to support sockets one library has been added to the SCD and several functions have been added to the existing library, `/usr/lib/libnsl.so.1`. The new library is `/usr/lib/libsocket.so.1`.

The Dynamic Linking Services Library, `/usr/lib/libdl.so.1` has been added to the specification, allowing applications to access the facilities of the dynamic linking directly at run time.

A Large File Support Library has been added on an experimental basis. This library allows applications to build and use files which are larger than two gigabytes.

Updated Windowing Interfaces

The X Library and X Toolkit Libraries have been updated to support X Version 11, Release 5 from the X Consortium.

Support for the X shape extension has been added as a required interface set.

The Motif Libraries has been updated to support Motif Version 1.2. This version includes internationalization support.

Structure of the SPARC Compliance Definition

The Application Binary Interface defined by the SCD consists of a set of System Feature Interfaces, a set of Library Interfaces, and a Command Interface.

Each such named Interface is designated as either Required, Optional, or Experimental.

System Feature Interfaces

The System Feature Interfaces are:

- Object File Format
- Program Loading and Linking
- Low-level System Information
- Formats and Protocols
- Software Installation

Library Interfaces

Each Library Interface is a collection of facilities that is implemented as one or more shared objects. (Shared objects are defined in the Object File Format.)

The Library Interfaces are:

- System Library Interface
- C Library Interface
- Network Services Interface
- Socket Services Interfaces

- Network Address Resolution Library Interface
- Dynamic Linking Library Interface
- X Library Interface
- X Extensions Interface
- X Toolkit Library Interface
- Open Look Library Interface
- Motif 1.2 Library Interface
- Large File Support

Each Library Interface consists of

- Function entry points and their names
- Function arguments for each function entry point
- Global data and their names
- Manifest constants used in definitions of function arguments and global data
- Visible data structures used in function arguments and global data
- One or more shared objects, each having a particular name, each accessible through a particular pathname, and each containing the function entry points, function entry point names, global data, and global data names defined for that Library Interface.

Command Interface

The Command Interface is the set of commands available to application programs. The Command Interface is defined in the chapter titled “Commands”.

Definition of SPARC Compliance

The terms “SPARC-compliant” and “conforming” are used interchangeably in this document. Their meaning is:

Conforming Implementations

A conforming implementation is one that provides all of the Required Interfaces, in their entirety.

A conforming implementation may provide one or more of the Optional Interfaces. Each Optional Interface that is provided must be provided in its entirety. The product documentation must state which Optional Interfaces are provided.

A conforming implementation, when provided with standard data formats and values at a named interface, will provide the behavior defined for those values and data formats at that interface. However, a conforming implementation may consist of separately packaged and/or sold components. For example, a vendor of a conforming implementation might sell the hardware, operating system and windowing system as separately packaged items.

A conforming implementation may provide additional interfaces with different names. It may also provide additional behavior corresponding to data values outside the standard ranges, for standard named interfaces. Such additional interfaces, or additional inputs to standard interfaces, are called extensions to the standard. If an implementation provides extensions to the standard, its documentation must clearly identify the extensions as such.

Conforming Application Programs

A conforming application program has the following characteristics:

Its executable files are either Bourne shell scripts or object files in the format defined for the Object File Format System Interface.

Its object files participate in dynamic linking as defined in the Program Loading and Linking System Interface.

It employs only the instructions, traps, and other low-level facilities defined in the Low-Level System Interface as being for use by application programs.

It does not require or use any interface, facility, or implementation-provided extension that is not defined in this standard in order to be installed or to execute successfully.

If it requires any Optional Interface defined in this standard in order to be installed or to execute successfully, the requirement for that Optional Interface is stated in the application's documentation.

It does not use any interface or data format that is not required to be provided by a conforming implementation; unless:

1. if any such interface or data format is used, it is generally available to anyone who wants to purchase or acquire it; and
2. if such an interface or data format is supplied by another program through direct invocation of that program during execution, that program is in turn a SPARC-compliant application; and
3. the use of that interface or data format, as well as its source, is identified in the documentation of the application program.

Rationale

A SPARC-compliant application is expected to have no dependencies on any vendor extensions to the standard. The most common such extensions are additional function entry points and additional libraries other than the ones defined in the SCD. If an application requires such extensions it is not portable, since other SCD-compliant platforms may not provide those extensions.

A SPARC-compliant application is required to use system services on the platform it's running on, rather than importing system routines from some other platform. Thus it must link dynamically to any routines in the platform that perform system traps to kernel services.

It is to be expected that some programs may be companion programs to other programs. For example, a query program may be a companion to a data base program; a pre-processor may be an adjunct to one or more compilers; a data re-formatter may convert data from one document manager to another. In such cases, the program may or may not be SPARC-compliant regardless of whether the other program it's dependent on is SPARC-compliant.

If such an application merely uses data produced by another program, the application's compliance is independent of the other program's compliance.

If such an application actually invokes another program during execution (as, for example, a third-party math library), the invoking program is SPARC-compliant only if it also constitutes a SPARC-compliant application in combination with the invoked program.

Compliance Testing


Test suites will be used in conjunction with this standard to verify the conformance of applications and platforms to this standard. Contact SPARC International for additional test suite information at (415)321-8692.

The System Compliance Test (SCT) will be used to verify a system's implementation of all the Interfaces defined in the SPARC Compliance Definition.

The SPARC Application Verifier (SAV) will be used to verify an application's adherence to the Interfaces defined in the SPARC Compliance Definition.



CHAPTER 2: Software Installation



Software Installation

Overview

Most information regarding software installation may be found in Chapter 2 of the gABI and Chapter 2 of the psABI. This section is an addendum to Chapter 2, page 2-1, of the psABI. This section adds support for using CD-ROM medium for physical distribution of SCD-conforming software. It is an OPTIONAL INTER-FACE. If software is distributed on CD-ROM, it must be in one of the formations specified below. SPARC-compliant systems need support for CD-ROM, some vendors are already shipping all their software on CD-ROM's.

CD-ROM Medium

CD-ROM medium recorded in the format specified in *ISO/IEC 10149: Data Interchange for read-only 120mm optical data disk (CD-ROM)* is added to the list of approved media on page 2-1 of the *System V Application Binary Interface, SPARC Processor Supplement*.

The information on the media must be represented either

- serially as the data stream created using `dd(AU_CMD)` or `cpio(BU_CMD)` utilities; or
- as file structured data that must be represented as described in *ISO 9660: 1988 - Volume and file structure of CD-ROM for information interchange*.

Rationale

The most common format for CD-ROM's is the ISO 9660 format, which supports MS-DOS filesystem semantics only. The ISO 9660 format is robust and stable, and has a huge installed base. That is why the ISO 9660 format has been included in SCD2.2 as an OPTIONAL standard for SPARC-compliant systems.

Support for ISO 9660 format CD-ROM's is already available from several other operating system vendors.

Since the restrictions placed on a filesystem by the ISO 9660 format are too restrictive for most UNIX users, a POSIX conforming filesystem is needed. The Rock Ridge Interchange Protocol was created to fill this gap. The Rockridge filesystem is actually an extension to (and compliant with) the ISO 9660 specification.

The Rock Ridge filesystem appears to be stable at this time. However there are some issues concerning bootability, security, and sparse files which are still being addressed by the IEEE working group on CD-ROM filesystems. There will be some minor changes made before the Rock Ridge filesystem is adopted as a NIST (National Institute of Science and Technology) standard.

For these reasons, the Rock Ridge filesystem is being excluded from SCD 2.2.

Upon adoption as a standard by NIST, it is expected that the Rock Ridge format will be included in the standard.


Software Installation Changes

The following are changes to the *System V Application Binary Interface*, and the *System V Interface Definition (Third Edition)* as reported to SPARC International.

#	Facility	Location	Description
	pkginfo(AS_CMD)	SVID, Vol. II	Delete "-r" from the list of supported options for pkginfo.



CHAPTER 3: Low-Level System Information




Low-Level System Information

Low-level system information pertinent to SPARC platforms may be found in Chapter 3 of the *System V ABI, SPARC Processor Supplement*. Information such as page size restrictions, as well as stack management, function calling sequence and data representations may be found there.



CHAPTER 4: Object Files



Object Files

Processor independent descriptions of the object file format for System V Release 4 may be found in Chapter 4 of the *System V ABI*. Information specific to SPARC platforms may be found in Chapter 4 of the *System V ABI, SPARC Processor Supplement*.


Object Files Changes

The following are changes to the *System V Application Binary Interface* as reported to SPARC International.

#	Facility	Location	Description
	SHT_DYNSYM	gABI	On page 4-15 add before the last sentence: "However this minimal set of symbols will always include all symbols of STB_GLOBAL binding."



CHAPTER 5: Program Loading and Dynamic Linking



Program Loading and Dynamic Linking

Processor independent descriptions of program loading and linking for SCD compliant systems may be found in Chapter 5 of the *System V Application Binary Interface*. Information specific to the SPARC platforms may be found in Chapter 5 of the *System V Application Binary Interface, SPARC Processor Supplement*.

Program Loading and Dynamic Linking Changes

The following are changes to the *System V Application Binary Interface*, and the *System V Application Binary Interface, SPARC Processor Supplement* as reported to SPARC International.

#	Facility	Location	Description
	LD_LIBRARY_PATH	gABI	Change the order of the bullets at the bottom of page 5-21 such that the influence of LD_LIBRARY_PATH takes precedence over DT_RPATH specifications.
	Dynamic Linking	gABI	Add a new third bullet to the entries on pages 5-20: "DT_RPATH specifications influence search operations for their own DT_NEEDED objects. Each evaluation of a given object's set of DT_NEEDED specification uses <i>that object's</i> DT_RPATH. Thus, if an executable specifies a set of DT_NEEDED objects (e.g., a , b , and c) and a DT_RPATH specification of x:y , then the search for a , b , and c will involve the paths x and y . If, when later evaluating the DT_NEEDED object for a (e.g., d), then x and y will not be used for that search unless a also specifies a DT_RPATH containing them."
	Initialization and Termination Functions	gABI	Add the following new third paragraph: "Initialization and Termination functions can expect to use all libsys and libc ABI-defined services in their execution."
	Dynamic linking	psABI	Add a section entitled "Dynamic Linker" as the first subsection of the "Dynamic Linking" section, which is: "The value of the program header element PT_INTERP in an ABI-conforming program is the reference name for libsys. As a special case, the reference name for version 1 of the C library reference name is also accepted as a legitimate PT_INTERP specification."

CHAPTER 6: Libraries

Libraries

Overview

This chapter defines the interfaces sets for the System Library, the C Library, the Network Services Library, the Socket Library, the Dynamic Object File Loading Library, and the Large File Library. The System Library, the C Library, the Network Services Library, the Socket Library, and the Dynamic Object File Loading Library are REQUIRED interface sets. The Large File Library is an EXPERIMENTAL interface set and conforming systems need not supply it.

Some of the entries in the tables which define the function interfaces provided by various libraries have a superscript and some are also marked with a “strike-through” line. All entries with a superscript have an entry in the changes table describing differences in the SCD definition of the function and its base document (gABI, psABI, or SVID) definition. Entries marked with a “strike-through” line (~~strike through~~) are called out in the base documents but are excluded in the SCD.

The System Library

The libsys Interfaces

This section contains the REQUIRED `libsys` interfaces to basic system services listed in the *System V Application Binary Interface* and described in sections BA_OS, BA_LIB, BA_ENV, KE_OS, and RT_OS of the *System V Interface Definition, Third Edition*.

Effective November 1st, 1993, the `sbrk` function interface is DEPRECATED. Reasons for this can be found in the `sbrk` description on page 6-9. The interface may be removed from the SCD as early as November 1st, 1996.

The interfaces listed below in Table 6-1 and 6-2 have been included in SCD 2.2 because they are REQUIRED to be present in the system library **libsys**. **libsys** is the entity obtained through the use of the *reference name* `/usr/lib/ld.so.1`. Table 6-3 contains the exported data which are also REQUIRED to be present in `/usr/lib/ld.so.1`. The format of these entries is: `data[size]`, where `size` is a hexadecimal byte count. Issues regarding synonyms and global data symbols associated with this library can be found in the *System V Application Binary Interface*.

Table 6-1. libsys Contents

_exit	getpmsg	remove	sync
access	getppid	rename	sysconf
acct	getpwnam	rewinddir	system
alarm	getpwuid	rmdir	tellmdir
atexit	getrlimit	sbrk ⁶	time
calloc	getsid	seekdir	times
catclose	gettxt	semctl	ttyname
catgets	getuid	semget	ulimit
catopen	grantpt	semop	umask
chdir	initgroups	setcontext	umount
chmod	ioctl	setgid	uname
chown	isastream	setgroups	unlink
chroot	kill	setlocale	unlockpt
close	lchown	setpgid	utime
closedir	link	setpgrp	wait
creat	localeconv	setrlimit	waitid ⁸
dup	lseek	setsid	waitpid
execl	lstat	setuid	write ⁵
execle	malloc	shmat	writew ⁵
execvp	memcntl	shmctl	
execv	mkdir	shmdt	
execve	mknod	shmget	
execvp	mlock	sigaction	
exit	mmap ⁴	sigaddset	
fattach	mount	sigaltstack	
fchdir	mprotect	sigdelset	
fchmod	msgctl	sigemptyset	
fchown	msgget	sigfillset	
fcntl ^{1,2}	msgrcv	sighold	
fdetach	msgsnd	sigignore	
fork	msync	sigismember	
fpathconf	munlock	siglongjmp	
free	munmap	signal	
fstat	nice	sigpause	
fstatvfs	open	sigpending	
fsync	opendir	sigprocmask	
ftok ³	pathconf	sigrelse	
getcontext	pause	sigsend	
getcwd	pipe	sigsendset	
getegid	poll	sigset	
geteuid	profil	sigsetjmp	
getgid	ptrace	sigsuspend	
getgrgid	ptsname	stat	
getgrnam	putmsg	statvfs	
getgroups	putpmsg	stime	
getlogin	read ⁵	strcoll	
getmsg	readdir	strerror	
getpgid	readlink	strftime	
getpgrp	readv ⁵	strxfrm	
getpid	realloc	symlink ⁷	

Table 6-2. `libsys` SPARC Support Routines

<code>.div</code>	<code>.urem</code>	<code>_Q_fle</code>	<code>_Q_qtou</code> ⁹
<code>.mul</code>	<code>_Q_add</code>	<code>_Qflt</code>	<code>_Q_sqrt</code>
<code>.rem</code>	<code>_Q_cmp</code>	<code>_Q_fne</code>	<code>_Q_stoq</code>
<code>.stret1</code>	<code>_Q_cmpe</code>	<code>_Q_itoq</code>	<code>_Q_sub</code>
<code>.stret2</code>	<code>_Q_div</code>	<code>_Q_mul</code>	<code>_Q_utoq</code>
<code>.stret4</code>	<code>_Q_dtoq</code>	<code>_Q_neg</code>	<code>__dtou</code> ¹⁰
<code>.stret8</code>	<code>_Q_feq</code>	<code>_Q_qtod</code>	<code>__ftou</code> ¹¹
<code>.udiv</code>	<code>_Q_fge</code>	<code>_Q_qtoi</code>	
<code>.umul</code>	<code>_Q_fgt</code>	<code>_Q_qtos</code>	

Table 6-3. Exported Data for libsys.

```
__ctype[0x209]  
__huge_val[0x8]  
_altzone[0x4]  
_daylight[0x4]  
_numeric[0x2]  
_timezone[0x4]  
_tzname[0x8]  
daylight[0x4]  
timezone[0x4]  
tzname[0x8]
```

System Library Changes

The following are changes to the *System V Application Binary Interface*, *SPARC Processor Supplement*, and the *System V Interface Definition* as reported to SPARC International.

#	Facility	Location	Description
1	fcntl(BA_OS)	SVID, Vol. I	Add a description of the command <code>F_FREESP</code> which reads: "Free storage space associated with a section of the ordinary file <i>fil</i> des. The section is specified by a variable of data type <code>struct flock</code> pointed to by the third argument <i>arg</i> . <i>l_whence</i> is <code>SEEK_SET</code> , <code>SEEK_CUR</code> , or <code>SEEK_END</code> to indicate that the relative offset <i>l_start</i> will be measured from the start of the file, the current position, or the end of the file, respectively. <i>l_start</i> is the offset from the position specified in <i>l_whence</i> . <i>l_len</i> is the size of the section. An <i>l_len</i> of 0 frees up to the end of the file; in this case, the end of file (i.e., file size) is set to the beginning of the section freed. Any data previously written into this section is no longer accessible."
2	fcntl(BA_OS)	SVID, Vol. I	Change - The <code>EAGAIN</code> error return value only applies to files for which mandatory locking is enabled.
3	ftok	SVID, Vol.I	Add description of function <code>ftok</code> . See the following man page for this function.
4	mmap(KE_OS)	SVID, Vol. I	Add to the paragraph which begins "Not all implementations ..." insert "No implementation will permit an access to succeed where <code>PROT_NONE</code> has been set." after "... where <code>PROT_WRITE</code> has not been set."
5	read, readv(BA_OS) write, writev(BA_OS)	SVID, Vol. I	Addition - The SVID specifies that the length of the <code>struct iovec[]</code> in calls to <code>readv()</code> / <code>writev()</code> must be in the range $0 \leq \text{iovcnt} \leq \text{IOV_MAX}$. However, <code>IOV_MAX</code> is never defined. SCD compliant systems will support a minimum of 16 elements in a <code>struct iovec[]</code> .
6	sbrk	SVID, Vol.I	Add description of the function <code>sbrk</code> . See the following man page for this function.
6	sbrk	gABI	Add the function <code>sbrk</code> to Table 6-3 on page 6-5.
7	symlink(BA_OS)	SVID, Vol. I	Change description of <code>ENAMETOOLONG</code> to "if the length of <i>path2</i> exceeds <code>{PATH_MAX}</code> , or pathname component of <i>path2</i> is longer than <code>{NAME_MAX}</code> while <code>{_POSIX_NO_TRUNC}</code> is in effect."
8	waitid(BA_OS)	SVID, Vol. I	Change - The flag <code>WTRACED</code> should be replaced with <code>WTRAPPED</code> .
9	_Q_qtou	psABI	Change - On page 6-5, replace the description of exceptions for <code>_Q_qtou</code> with "If $0 \leq a < 2^{32}$ then the operation is successful. If <i>a</i> is not a whole number, the inexact exception is raised. "If $-2^{31} \leq a < 2^{32}$ then the operation is successful. If <i>a</i> is not a whole number, the inexact exception is raised. "Otherwise, the value returned by <code>_Q_qtou</code> is unspecified, and the invalid exception is raised. Note that negative values of <i>a</i> , in a successful operation, are first converted to integer and then cast to an unsigned integer."

System Library Changes (continued)

#	Facility	Location	Description
10	<code>__dtou</code>	psABI	Change - On page 6-7, replace the description of exceptions for <code>__dtou</code> with "If $0 \leq a < 2^{32}$ then the operation is successful. If a is not a whole number, the inexact exception is raised. "If $-2^{31} \leq a < 2^{32}$ then the operation is successful. If a is not a whole number, the inexact exception is raised. "Otherwise, the value returned by <code>_Q_gtou</code> is unspecified, and the invalid exception is raised. Note that negative values of a , in a successful operation, are first converted to integer and then cast to an unsigned integer."
11	<code>__ftou</code>	psABI	Change - On page 6-7, replace the description of exceptions for <code>__ftou</code> with "If $0 \leq a < 2^{32}$ then the operation is successful. If a is not a whole number, the inexact exception is raised. "If $-2^{31} \leq a < 2^{32}$ then the operation is successful. If a is not a whole number, the inexact exception is raised. "Otherwise, the value returned by <code>_Q_gtou</code> is unspecified, and the invalid exception is raised. Note that negative values of a , in a successful operation, are first converted to integer and then cast to an unsigned integer."
	<code><dirent.h></code>	psABI	Change the declaration of <code>DIR</code> , in Figure 6-5, to be an opaque pointer type. Application programs can know neither the size nor the layout of this type.
	<code><fcntl.h></code>	psABI	The following manifest constants are needed for implementing <code>ftruncate()</code> and <code>truncate()</code> operations but are missing from Figure 6-7: <pre>#define F_FREESP 11</pre>
	<code><signal.h></code>	psABI	Change - On page 6-44, in Figure 6-33 for the <code>struct sigaction</code> type declaration change <code>sigdisp_t sa_disp</code> to <code>void (*sa_handler)()</code> .
	Global Data Symbols	gABI	Change the description of <code>_altzone</code> . Replace " <code>tzset(BA_LIB)</code> " with " <code>tzset()</code> . See <code>ctime(BA_LIB)</code> ."
	Additional Entry Points	psABI	Page 6-5 of the <i>System V Application Binary Interface</i> states "ABI-conforming systems must provide a <code>libs</code> entry point for each of [<code>fstat</code> , <code>lstat</code> , <code>mknod</code> , <code>stat</code> , and <code>uname</code>]. The name and syntax of [these entry points] may be the same as those characteristics of the source-level service or they may vary across processor architectures. The actual names of the entry points are specified in each processor's supplement to the ABI, together with the entry points' syntax information if names differ from those of the source-level services." The <i>System V Application Binary Interface, SPARC Processor Supplement</i> (psABI) is missing the required specification. A section titled <i>Additional Entry Points (Processor-Specific)</i> should be added to the beginning of chapter 6 of the psABI which states "The binary entry points for <code>fstat</code> , <code>lstat</code> , <code>mknod</code> , <code>stat</code> , <code>uname</code> exist with these names and with the same calling sequence as described in their source-level interface. Synonyms exist for each of these entry points."

ABI Extensions

The SCD includes several extra functions. These functions are not described in any of the base documents. A man page for each the functions follows.

NAME

`ftok` - standard interprocess communication package

SYNOPSIS

```
#include <sys/types.h>
#include <sys/ipc.h>

key_t ftok(char *path, int id);
```

DESCRIPTION

All interprocess communication facilities require the user to supply a key to be used by the `msgget`, `semget`, `shmget` system calls to obtain interprocess communication identifiers. One suggested method for forming a key is to use the `ftok` subroutine described below. Another way to compose keys is to include the project ID in the most significant byte and to use the remaining portion as a sequence number. There are many other ways to form keys, but it is necessary for each system to define standards for forming them. If some standard is not adhered to, it will be possible for unrelated processes to unintentionally interfere with each other's operation. It is still possible to interface intentionally. Therefore, it is strongly suggested that the most significant byte of a key in some sense refer to a project so that keys do not conflict across a given system.

`ftok` returns a key based on *path* and *id* that is usable in subsequent `msgget`, `semget`, and `shmget` system calls. *path* must be the path name of an existing file that is accessible to the process. *id* is a character that uniquely identifies a project. Note that `ftok` will return the same key for linked files when called with the same *id* and that it will return different keys when called with the same file name but different *ids*.

DIAGNOSTICS

`ftok` returns (`key_t`) -1 if *path* does not exist or if it is not accessible to the process.

NOTES

If the file whose *path* is passed to `ftok` is removed when keys still refer to the file, future calls to `ftok` with the same *path* and *id* will return an error. If the same file is recreated, then `ftok` is likely to return a different key than it did the original time it was called.

NAME

`sbrk` - query the current break value

SYNOPSIS

```
#include <unistd.h>

void *sbrk (const int 0);
```

DESCRIPTION

The function `sbrk` is used to query the amount of space allocated for the calling process's data segment [see `exec(BA_OS)`].

STATUS

This function is DEPRECATED effective November 1st, 1993. It may be removed from the SCD as early as November 1st, 1996.

DIAGNOSTICS

Upon successful completion, `sbrk` returns the current break value. Otherwise, a value of -1 is returned and `errno` is set to indicate the error. If `sbrk` is called with a non-zero value, the application is not portable.

Rationale

Calling `sbrk(0)` yields a value that, at one time, had a predictable, well defined interpretation. It has not had this property for many years, since the wide-spread usage of sparse, demand-paged address spaces. Its use is deprecated because the interpretation of the value returned is so highly variable as to be non-portable. It is more appropriately regarded as a function yielding a value relevant to one of many attributes of memory occupancy.

`sbrk(non-zero)` is not specified in any relevant standard, as its interactions with and dependencies upon other memory allocation mechanisms (e.g., `malloc`) are undefined. The use of `sbrk(non-zero)` is non-conforming since the implementation of system supplied functions may freely use such memory allocation mechanisms.

Applications desiring memory allocation functionality should use `malloc` for this purpose. Alternatively, applications may construct their own memory allocation arenas by building upon `mmap` and mappings to `/dev/zero`.

The C Library

The libc Interfaces

This section contains the REQUIRED `libc` interfaces listed in the *System V Application Binary Interface* and described in the *System V Interface Definition, Third Edition*.

Interfaces listed below in Table 6-4 have been included because they are REQUIRED on all systems conforming to the *System V Application Binary Interface*, made available through the reference name `/usr/lib/libc.so.1`.

Table 6-5 contains the exported data which are also REQUIRED to be present in `/usr/lib/libc.so.1`. The format of these entries is: `data[size]`, where size is hexadecimal byte count.

Issues regarding synonyms and global data symbols associated with this library can be found in the *System V Application Binary Interface*.

Table 6-4. `libc` Contents

<code>__assert</code> ¹	<code>getc</code>	<code>modf</code> ¹⁰	<code>tcflush</code>
<code>__filbuf</code>	<code>getchar</code>	<code>monitor</code>	<code>tcgetattr</code>
<code>__flsbuf</code>	<code>getdate</code>	<code>nftw</code>	<code>tcgetpgrp</code>
<code>_tolower</code>	<code>getenv</code>	<code>nl_langinfo</code>	<code>tcgetsid</code>
<code>_toupper</code>	<code>getopt</code>	<code>pclose</code>	<code>tcsendbreak</code>
<code>_xftw</code>	<code>getpass</code>	<code>perror</code>	<code>tcsetattr</code>
<code>abort</code>	<code>gets</code>	<code>popen</code>	<code>tcsetpgrp</code>
<code>abs</code>	<code>getsubopt</code>	<code>printf</code>	<code>tdelete</code>
<code>addseverity</code> ²	<code>getitimer</code> ⁶	<code>putc</code>	<code>tell</code> ¹⁵
<code>asctime</code>	<code>gettimeofday</code> ⁷	<code>putchar</code>	<code>tempnam</code>
<code>atof</code>	<code>getw</code>	<code>putenv</code>	<code>tfind</code>
<code>atoi</code>	<code>gmtime</code>	<code>puts</code>	<code>tmpfile</code>
<code>atol</code>	<code>hcreate</code>	<code>putw</code>	<code>tmpnam</code>
<code>bsearch</code>	<code>hdestroy</code>	<code>qsort</code>	<code>toascii</code>
<code>cfgetispeed</code>	<code>hsearch</code>	<code>raise</code>	<code>tolower</code>
<code>cfgetospeed</code>	<code>isalnum</code>	<code>rand</code>	<code>toupper</code>
<code>cfsetispeed</code>	<code>isalpha</code>	<code>rewind</code>	<code>tsearch</code>
<code>cfsetospeed</code>	<code>isascii</code>	<code>scanf</code>	<code>twalk</code>
<code>clearerr</code>	<code>isatty</code>	<code>setbuf</code>	<code>tzset</code>
<code>clock</code>	<code>iscntrl</code>	<code>setitimer</code> ¹¹	<code>ungetc</code>
<code>crypt</code> ³	<code>isdigit</code>	<code>setjmp</code>	<code>vfprintf</code>
<code>ctermid</code>	<code>isgraph</code>	<code>setkey</code> ¹²	<code>vprintf</code>
<code>ctime</code>	<code>islower</code>	<code>setlabel</code> ¹³	<code>vsprintf</code>
<code>cuserid</code>	<code>isnan</code>	<code>setvbuf</code>	<code>wcstombs</code>
<code>difftime</code>	<code>isnand</code> ⁸	<code>sleep</code>	<code>wctomb</code>
<code>div</code>	<code>isprint</code>	<code>sprintf</code>	
<code>dup2</code>	<code>ispunct</code>	<code>srand</code>	
<code>encrypt</code> ⁴	<code>isspace</code>	<code>sscanf</code>	
<code>fclose</code>	<code>isupper</code>	<code>strcat</code>	
<code>fdopen</code> ⁵	<code>isxdigit</code>	<code>strchr</code>	
<code>feof</code>	<code>labs</code>	<code>strcmp</code>	
<code>ferror</code>	<code>ldexp</code>	<code>strcpy</code>	
<code>fflush</code>	<code>ldiv</code>	<code>strcspn</code>	
<code>fgetc</code>	<code>lfind</code>	<code>strdup</code>	
<code>fgetpos</code>	<code>localtime</code>	<code>strlen</code>	
<code>fgets</code>	<code>lockf</code> ⁹	<code>strncat</code>	
<code>fileno</code>	<code>longjmp</code>	<code>strncmp</code>	
<code>fmtmsg</code>	<code>lsearch</code>	<code>strncpy</code>	
<code>fopen</code>	<code>mblen</code>	<code>strpbrk</code>	
<code>fprintf</code>	<code>mbstowcs</code>	<code>strrchr</code>	
<code>fputc</code>	<code>mbtowc</code>	<code>strspn</code>	
<code>fputs</code>	<code>memccpy</code>	<code>strstr</code>	
<code>fread</code>	<code>memchr</code>	<code>strtod</code>	
<code>freopen</code>	<code>memcmp</code>	<code>strtok</code>	
<code>frexp</code>	<code>memcpy</code>	<code>strtol</code>	
<code>fscanf</code>	<code>memmove</code>	<code>strtoul</code>	
<code>fseek</code>	<code>memset</code>	<code>swab</code>	
<code>fsetpos</code>	<code>mkfifo</code>	<code>sysinfo</code> ¹⁴	
<code>ftell</code>	<code>mktemp</code>	<code>tcdrain</code>	
<code>fwrite</code>	<code>mktime</code>	<code>tcflow</code>	

Table 6-5. Exported Data for libc.

```
__iob[0x140]  
_getdate_err[0x4]  
getdate_err[0x4]  
optarg[0x4]  
opterr[0x4]  
optind[0x4]  
optopt[0x4]
```

C Library Changes

The following are changes against the *System V Application Binary Interface*, *System V Application Binary Interface*, *SPARC Processor Supplement*, and the *System V Interface Definition (Third Edition)* as reported to SPARC International.

#	Facility	Location	Description
1	<code>__assert(BA_LIB)</code>	gABI	Addition - The description of function <code>__assert</code> is missing. Add the description: <code>void __assert(char *assertion, char *file, int line)</code> Writes a message to the standard error stating that the <i>assertion</i> in <i>file</i> at <i>line</i> has proved to be false, then calls <code>abort()</code> .
1	<code>__assert(BA_LIB)</code>	gABI	Change - The function <code>__assert</code> is erroneously listed as a function with a synonym in Figure 6-7 on page 6-11 of the gABI. The function should be removed from Figure 6-7 and added to Figure 6-6 on page 6-10 of the gABI. Figure 6-6 lists the functions without synonyms.
2	<code>addseverity(BA_OS)</code>	SVID, Vol. I	Addition - Function <code>addseverity</code> is missing. Add the description: <code>int addseverity(int value, const char *string)</code> The function <code>addseverity</code> adds a new severity level of <i>value</i> . <i>value</i> must be greater than 4. The function associates <i>string</i> with the level <i>value</i> so that <i>string</i> is produced with messages of that <i>value</i> yielded by <code>fmsg()</code> . If a severity of <i>value</i> already exists it is replaced by the new description. If <i>string</i> is <code>(char *)0</code> then the severity level is deleted. <i>value</i> \leq 4 results in a -1 return with <code>errno</code> set to <code>EINVAL</code> , as does an attempt to delete a currently undefined severity level.
2	<code>addseverity(BA_OS)</code>	gABI	Add the function <code>addseverity</code> to Figure 6-7 on page 6-11.
3	<code>crypt(BA_LIB)</code>	gABI	Add the function <code>crypt</code> to Figure 6-7 on page 6-11.
4	<code>crypt(BA_LIB)</code>	gABI	Add the function <code>encrypt</code> to Figure 6-7 on page 6-11.
5	<code>fdopen(BA_OS)</code>	SVID, Vol. I	Change - The requirement that the <i>files</i> argument be open is incorrect.
6	<code>getitimer(RT_OS)</code>	gABI	Add the function <code>getitimer</code> to Figure 6-7 on page 6-11. Hardware platforms must provide at least 60 Hz resolution. Platforms may provide greater than 60 Hz resolution, but applications that rely on a faster clock will not be portable.
7	<code>gettimeofday(RT_OS)</code>	gABI	Add the function <code>gettimeofday</code> to Figure 6-7 on page 6-11.
8	<code>isnand(BA_LIB)</code>	SVID, Vol. I	Addition - Function <code>isnand</code> is missing. Add the description: <code>int isnand(double d)</code> The function returns 1 if <i>d</i> is an IEEE "NaN" and returns 0 otherwise.
8	<code>isnane(BA_LIB)</code>	gABI	Add the function <code>isnand</code> to Figure 6-7 on page 6-11.
9	<code>lockf(BA_OS)</code>	SVID, Vol. I	Addition - The <code>EAGAIN</code> error return value only applies to files for which mandatory locking is enabled.
10	<code>frexp(BA_LIB)</code>	gABI	Add the function <code>modf</code> to Figure 6-6 on page 6-10.

C Library Changes (continued)

#	Facility	Location	Description
11	getitimer(RT_OS)	gABI	Add the function <code>setitimer</code> to Figure 6-7 on page 6-11.
12	crypt(BA_LIB)	gABI	Add the function <code>setkey</code> to Figure 6-7 on page 6-11.
13	C Library	gABI	Remove the function <code>setlabel</code> from Figure 6-7 on page 6-11.
14	sysinfo	gABI	Add the function <code>sysinfo</code> to Figure 6-7 on page 6-11.
15	tell(BA_OS)	SVID, Vol. I	Addition - Function <code>tell</code> is missing. Add the description: <code>long tell (int f)</code> Returns the current position of the file associated with <code>f</code> . Equivalent to <code>lseek(f, 0L, SEEK_CUR)</code> .
15	tell(BA_OS)	gABI	Add the function <code>tell</code> to Figure 6-7 on page 6-11.
	<sys/param.h>	psABI	Remove definition of <code>HZ</code> from Figure 6-23.

ABI Extensions

The SCD requires `/usr/lib/libc.so.1` to have functions which are not specified by the gABI. These extra functions are either not defined in the SVID, or, are defined differently in the SCD than in the SVID.

These functions are `crypt`, `setkey`, `encrypt`, and `sysinfo`. Manual pages for these additional/modified function definitions follow.

Rationale

The following man pages are for interfaces which do not have specifications in any of the base documents.

The library version number has remained 1, as these functions are correctly included in existing SCD conformant systems.

NAME

`crypt`, `setkey`, `encrypt` - generate string encoding

SYNOPSIS

```
char *crypt(char *key, char *salt);  
void setkey(char *key);  
void encrypt(char *block, int edflag);
```

DESCRIPTION

The function `crypt` is a string-encoding function.

The argument *key* is a string to be encoded. The argument *salt* is a two-character string chosen from the set [a-zA-Z0-9. /]; this string is used to perturb the encoding algorithm, after which the string that *key* points to is used as the key to repeatedly encode a constant string. The returned value points to the encoded string. The first two characters are the *salt* itself, the remaining characters shall not be identical to the original value of *key*.

The functions `setkey` and `encrypt` provide (rather primitive) access to the encoding algorithm. The argument to `setkey` is a 64-bit string represented by a character array of length 64 containing only the characters with numerical value 0 and 1. The string is divided into groups of 8 and the low-order bit in each group is ignored; this gives a 56-bit key. This is the key that may be used with the above mentioned algorithm to encode the string *block* with the function `encrypt`; the encryption algorithm provided by the system may not actually use *key*.

The argument *block* to `encrypt` is a character array of length 64 containing only the characters with numerical value 0 and 1. The argument array is modified in place to a similar array representing the bits of the argument after having been subjected to the encoding algorithm using the key set by `setkey`.

If the argument *edflag* is zero, the string *block* is encoded. If the *edflag* is non-zero and the implementation supports decryption then the string *block* is decoded. If the *edflag* is non-zero and the implementation does not support decryption then `errno` is set to `ENOSYS`.

DIAGNOSTICS

Under the following conditions, these functions fail, and set `errno` to:

<code>ENOSYS</code>	<code>encrypt</code> was called with a non-zero value for <i>edflag</i> on a system that does not support decryption.
---------------------	---

USAGE

The return value of the function `crypt` points to static data that are overwritten by each call. A portable application shall not depend on portability of encrypted data, nor assume that decryption is supported on all SCD conforming platforms. Also, portable applications must set `errno` to zero before calling any of the functions since there are no function return values for `setkey` or `encrypt`.

Rationale

Encryption capability is often needed by an application that wants to provide some of its own license protection. The application needs to be able to depend on the system to provide an encryption service to do this even if the system does not provide a mechanism for decryption.

This standard does not require any particular underlying encryption algorithm, but only requires that the `crypt` function return a value that is not identical to the original. This leaves it to the system vendors to choose whatever algorithm they find to be appropriate, and alleviates any requirement for a system vendor to choose one that has export restrictions.

NAME

`sysinfo` - get system information strings

SYNOPSIS

```
#include <sys/systeminfo.h>
```

```
long sysinfo (int command, char *buf, long count);
```

DESCRIPTION

`sysinfo` copies information relating to the UNIX system on which the process is executing into the buffer pointed to by *buf*. *count* is the size of the buffer.

The *commands* available are:

<code>SI_SYSNAME</code>	Copy into the array pointed to by <i>buf</i> the string that would be returned by <code>uname</code> [see <code>uname(BA_OS)</code>] in the <i>sysname</i> field. This is the name of the implementation of the operating system, for example, <code>UNIX_SV</code> .
<code>SI_HOSTNAME</code>	Copy into the array pointed to by <i>buf</i> a string that names the present host machine. This is the string that would be returned by <code>uname</code> in the <i>nodename</i> field. This hostname or nodename is often the name the machine is known by locally. The <i>hostname</i> is the name of this machine as a node in some network; different networks may have different names for the node, but presenting the nodename to the appropriate network Directory or name-to-address mapping service should produce a transport end point address. The name may not be fully qualified. Internet host names may be up to 256 bytes in length (plus the terminating null).
<code>SI_RELEASE</code>	Copy into the array pointed to by <i>buf</i> the string that would be returned by <code>uname</code> in the <i>release</i> field. Typical values might be <code>4.2</code> , <code>4.0</code> , <code>3.2</code> .
<code>SI_VERSION</code>	Copy into the array pointed to by <i>buf</i> the string that would be returned by <code>uname</code> in the <i>version</i> field. The syntax and semantics of this string are defined by the system provider.
<code>SI_MACHINE</code>	Copy into the array pointed to by <i>buf</i> the string that would be returned by <code>uname</code> in the <i>machine</i> field.
<code>SI_ARCHITECTURE</code>	Copy into the array pointed to by <i>buf</i> a string describing the instruction set architecture of the current system, for example, <code>sparc</code> . These names may not match predefined names in the C language compilation system.
<code>SI_HW_PROVIDER</code>	Copies the name of the hardware manufacturer into the array pointed to by <i>buf</i> .
<code>SI_HW_SERIAL</code>	Copy into the array pointed to by <i>buf</i> a string which is the ASCII representation of the hardware-specific serial number of the physical machine on which the system call is executed. Note that this may be implemented in Read-Only Memory, via software constants set when building the operating system, or by other means, and may contain non-numeric characters. It is anticipated that manufacturers will not issue the same "serial number" to more than one physical machine. The pair of strings returned by <code>SI_HW_PROVIDER</code> and <code>SI_HW_SERIAL</code> is likely to be unique across all vendors' System V implementations.
<code>SI_SRPC_DOMAIN</code>	Copies the Secure Remote Procedure Call domain name into the array pointed to by <i>buf</i> .

DIAGNOSTICS

Upon successful completion, the value returned indicates the buffer size in bytes required to hold the complete value and the terminating null character. If this value is no greater than the value passed in *count*, the entire string was copied; if this value is greater than *count*, the string copied into *buf* has been truncated to *count*-1 bytes plus a terminating null character.

Otherwise, a value of -1 is returned and *errno* is set to indicate the error.

Rationale

The commands included for `sysinfo` in SCD 2.2 are values that have been determined to be uniformly implemented on systems that have been presented for testing at the SCD 2.1 level. Also, the commands that require that the effective user-id be superuser are omitted.

Figure 6-1. Manifest Constants from <sys/systeminfo.h>

```
/*
 * Commands to sysinfo()
 */

#define SI_SYSNAME      1      /* return name of operating system */
#define SI_HOSTNAME     2      /* return name of node */
#define SI_RELEASE      3      /* return release of operating system */
#define SI_VERSION      4      /* return version field of utsname */
#define SI_MACHINE      5      /* return kind of machine */
#define SI_ARCHITECTURE 6      /* return instruction set arch */
#define SI_HW_SERIAL    7      /* return hardware serial number */
#define SI_HW_PROVIDER  8      /* return hardware manufacturer */
#define SI_SRPC_DOMAIN  9      /* return secure RPC domain */
```

The Network Services Library

Overview

This section contains the `libnsl` interfaces listed in the *System V Application Binary Interface*, and described in the *System V Interface Definition, Third Edition*.

Transport Providers

All SPARC-compliant systems will provide a transport provider interface for TCP/IP. The device name for this transport provider interface is `/dev/tcp`.

The libnsl Interfaces

The interfaces listed below in Table 6-6 have been included in SCD 2.2 because they are REQUIRED to be present on all systems conforming to the *System V Application Binary Interface*, in the dynamic library `/usr/lib/libnsl.so.1`.

The interfaces found in Table 6-7 are also REQUIRED to be present on an ABI-conforming system. Systems without networking capabilities are not required to implement these interfaces, but must provide an entry point in `libnsl` for each. Entry points which are provided as stubs and not implemented must fail normally and set the external symbol `errno` to `ENOSYS`.

Additionally, DEPRECATED functions needed for socket support can be found in Table 6-10.

Table 6-6. libns1 Contents, Part 1 of 2

t_accept	t_getinfo	t_rcvconnect	t_sndrel
t_alloc ¹	t_getstate ²	t_rcvdis	t_sndudata
t_bind	t_listen	t_rcvrel	t_sync
t_close	t_look	t_rcvudata	t_unbind
t_connect	t_open	t_rcvuderr	
t_error	t_optmgmt	t_snd	
t_free	t_rcv	t_snddis	

Table 6-7. libns1 Contents, part 2 of 2

authdes_getucred	netname2host	xdr_array
authdes_seccreate	netname2user	xdr_authsys_parms
authnone_create	rpc_broadcast	xdr_bool
authsys_create	rpc_broadcast_exp ³	xdr_bytes
authsys_create_default	rpc_call ⁴	xdr_callhdr
clnt_create	rpc_reg	xdr_callmsg
clnt_dg_create	rpcb_getaddr	xdr_char
clnt_pcreateerror	rpcb_getmaps	xdr_double
clnt_perrno	rpcb_gettime	xdr_enum
clnt_perror	rpcb_rmtcall	xdr_float
clnt_raw_create	rpcb_set	xdr_free
clnt_spccreateerror	rpcb_unset	xdr_int
clnt_sperrno	setnetconfig	xdr_long
clnt_sperror	setnetpath	xdr_opaque
clnt_tli_create	svc_create	xdr_opaque_auth
clnt_tp_create	svc_dg_create	xdr_pointer
clnt_vc_create	svc_fd_create	xdr_reference
endnetconfig	svc_getreqset	xdr_rejected_reply
endnetpath	svc_raw_create	xdr_replymsg
freenetconfignt	svc_reg	xdr_short
getnetconfig	svc_run	xdr_string
getnetconfignt	svc_sendreply	xdr_u_char
getnetname	svc_tli_create	xdr_u_long
getnetpath	svc_tp_create	xdr_u_short
getpublickey	svc_unreg	xdr_union
getsecretkey	svc_vc_create	xdr_vector
host2netname	svcerr_auth	xdr_void
key_decryptsession	svcerr_decode	xdr_wrapstring
key_encryptsession	svcerr_noproc	xdrmem_create
key_gendes	svcerr_noprogram	xdrrec_create
key_setsecret	svcerr_progvers ⁵	xdrrec_eof
nc_perror	svcerr_systemerr	xdrrec_skiprecord
netdir_free	svcerr_weakauth	xdrstdio_create
netdir_getbyaddr	taddr2uaddr	xprt_register
netdir_getbyname	uaddr2taddr	xprt_unregister
netdir_options	user2netname	

Network Services Changes

The following are changes to the network services interfaces (detailed in the *System V Interface Definition, Third Edition*), as reported to SPARC International.

#	Facility	Location	Description
1	t_alloc(BA_LIB)	SVID, Vol. I	Change the sentence starting with "If the size value associated with any specified field is -1 or -2 ..." to "If the size value associated with any specified field is -1, t_alloc() will allocate the buffer with the size of 1024 bytes. If the size value is -2, t_alloc() will set the buffer pointer to NULL and the buffer maximum size to 0 and will return with success."
2	t_getstate(BA_LIB)	SVID, Vol. I	Delete the phrase beginning with "or t_getstate() was called..."
3	rpc_broadcast_exp	gABI	Add the function rpc_broadcast_exp to Figure 6-10 on page 6-14.
4	rpc_clnt_calls(RS_LIB)	SVID, Vol. III	Change - On page 18-11 the function prototype of rpc_call() should be <pre>rpc_call(char *host, u_long prognum, u_long versnum, u_long procnum, xdrproc_t inproc, char *in, xdrproc_t outproc, char *out, char *nettype)</pre>
5	rpc_svc_err(RS_LIB)	SVID, Vol. III	Addition - Description of the function svcerr_progvers() is missing its last two arguments in the function prototype. Prototype should be: <pre>void svcerr_progvers(const SVCXPRT *xprt, ulong_t low, ulong_t high)</pre> where <i>low</i> and <i>high</i> represent the lowest and highest, respectively, of the versions of the service provided.
	netconfig(RS_ENV)	SVID, Vol. III	Change - On page 17-20 the type declaration of nc_flag should be changed from char * to unsigned long.

ABI Extension

The SCD includes an extra function `rpc_broadcast_exp`. This function is not described in any of the base documents. A man page for the function follows.

NAME

`rpc_broadcast_exp` - broadcast a call message specifying timeout

SYNOPSIS

```
#include <rpc/rpc.h>

enum clnt_stat rpc_broadcast_exp(const u_long prognum,
    const u_long versnum, const u_long procnum, const xdrproc_t xargs,
    caddr_t argsp, const xdrproc_t xresults, caddr_t resultsp,
    const resultproc_t eachresult, const int inittime, const int waittime,
    char *nettype);
```

DESCRIPTION

This function is like `rpc_broadcast()`, except that the initial timeout, *inittime*, and the maximum timeout, *waittime*, are specified in milliseconds.

inittime is the initial time that `rpc_broadcast_exp()` waits before resending the request. After the first resend, the re-transmission interval increases exponentially until it exceeds *waittime*.

The Socket Library

This section contains the socket internetworking interface, primarily used with the TCP/IP protocol suite. This is a REQUIRED interface set. It is also a DEPRECATED interface set effective November 1st, 1993. This interface set will not be removed from the SCD before November 1st, 1996.

This specification is based on *Programmer's Guide: Networking Interfaces* (Prentice-Hall, ISBN 0-13-020645-8).

All functions must be provided by systems from one or more of the libraries `/usr/lib/libnsl.so.1`, and `/usr/lib/libsocket.so.1`. Tables 6-8 and 6-9 document which system libraries are REQUIRED to provide each of the various socket functions.

Table 6-8. Socket Functions in libns1

gethostbyaddr	inet_addr	inet_ntoa
gethostbyname	inet_netof	

Table 6-9. Socket Functions in libsocket

accept	getservbyport	recvfrom
bind	getsockname	recvmsg
connect	getsockopt	send
getpeername	inet_lnaof	sendmsg
getprotobyname	inet_makeaddr	sendto
getprotobynumber	inet_network	setsockopt
getprotoent	listen	shutdown
getservbyname	recv	socket

Structures and Manifest Constants

The Figures 6-2 through 6-5 contain the values of manifest constants and type declarations of the data types needed for the socket functions.

Figure 6-2. Manifest Constants and Data Types from <sys/socket.h>

```
/* Types */
#define SOCK_STREAM      2          /* stream socket */
#define SOCK_DGRAM      1          /* datagram socket */
#define SOCK_RAW        4          /* raw-protocol interface */
#define SOCK_RDM        5          /* reliably-delivered message */
#define SOCK_SEQPACKET  6          /* sequenced packet stream */

/* Option flags per-socket. */
#define SO_DEBUG         0x0001    /* turn on debugging info recording */
#define SO_ACCEPTCONN   0x0002    /* socket has had listen() */
#define SO_REUSEADDR    0x0004    /* allow local address reuse */
#define SO_KEEPAVIVE    0x0008    /* keep connections alive */
#define SO_DONTROUTE    0x0010    /* just use interface addresses */
#define SO_BROADCAST    0x0020    /* permit sending of broadcast msgs */
#define SO_USELOOPBACK  0x0040    /* bypass hardware when possible */
#define SO_LINGER        0x0080    /* linger on close if data present */
#define SO_OOBINLINE    0x0100    /* leave received OOB data in line */

/* Additional options, not kept in so_options. */
#define SO_SNDBUF        0x1001    /* send buffer size */
#define SO_RCVBUF        0x1002    /* receive buffer size */
#define SO_SNDLOWAT      0x1003    /* send low-water mark */
#define SO_RCVLOWAT      0x1004    /* receive low-water mark */
#define SO_SNDTIMEO      0x1005    /* send timeout */
#define SO_RCVTIMEO      0x1006    /* receive timeout */
#define SO_ERROR         0x1007    /* get error status and clear */
#define SO_TYPE          0x1008    /* get socket type */
#define SO_PROTOCOL      0x1009    /* get/set protocol type */

/* Structure used for manipulating linger option. */
struct linger {
    int    l_onoff;          /* option on/off */
    int    l_linger;        /* linger time */
};

/* Level number for (get/set)sockopt() to apply to socket itself. */
#define SOL_SOCKET       0xffff    /* options for socket level */

/* Address families. */

#define AF_UNSPEC        0          /* unspecified */
#define AF_UNIX          1          /* local to host (pipes, portals) */
#define AF_INET          2          /* internetwork: UDP, TCP, etc. */
#define AF_IMPLINK       3          /* arpanet imp addresses */
#define AF_PUP           4          /* pup protocols: e.g. BSP */
#define AF_CHAOS          5          /* mit CHAOS protocols */
#define AF_NS            6          /* XEROX NS protocols */
#define AF_NBS           7          /* nbs protocols */
#define AF_ECMA          8          /* european computer manufacturers */
#define AF_DATAKIT       9          /* datakit protocols */
#define AF_CCITT         10         /* CCITT protocols, X.25 etc */
```

```

#define AF_SNA            11            /* IBM SNA */
#define AF_DECnet         12            /* DECnet */
#define AF_DLI            13            /* Direct data link interface */
#define AF_LAT            14            /* LAT */
#define AF_HYLINK         15            /* NSC Hyperchannel */
#define AF_APPLETALK       16            /* Apple Talk */
#define AF_NIT            17            /* Network Interface Tap */
#define AF_802            18            /* IEEE 802.2, also ISO 8802 */
#define AF_OSI            19            /* umbrella for all families used */
#define AF_X25            20            /* CCITT X.25 in particular */
#define AF_OSINET         21            /* AFI = 47, IDI = 4 */
#define AF_GOSIP          22            /* U.S. Government OSI */
#define AF_MAX            22

/* Structure used by kernel to store most addresses. */
struct sockaddr {
    u_short sa_family;          /* address family */
    char     sa_data[14];       /* up to 14 bytes of direct address */
};

/* Structure used by kernel to pass protocol * information in raw sockets. */

struct sockproto {
    u_short sp_family;          /* address family */
    u_short sp_protocol;        /* protocol */
};

/*
 * Protocol families, same as address families for now.
 */
#define PF_UNSPEC          AF_UNSPEC
#define PF_UNIX            AF_UNIX
#define PF_INET            AF_INET
#define PF_IMPLINK         AF_IMPLINK
#define PF_PUP             AF_PUP
#define PF_CHAOS           AF_CHAOS
#define PF_NS              AF_NS
#define PF_NBS             AF_NBS
#define PF_ECMA            AF_ECMA
#define PF_DATAKIT         AF_DATAKIT
#define PF_CCITT           AF_CCITT
#define PF_SNA             AF_SNA
#define PF_DECnet          AF_DECnet
#define PF_DLI            AF_DLI
#define PF_LAT            AF_LAT
#define PF_HYLINK         AF_HYLINK
#define PF_APPLETALK       AF_APPLETALK
#define PF_NIT            AF_NIT
#define PF_802            AF_802
#define PF_OSI            AF_OSI
#define PF_X25            AF_X25
#define PF_OSINET         AF_OSINET
#define PF_GOSIP          AF_GOSIP

```

```
#define PF_MAX          AF_MAX

/* Maximum queue length specifiable by listen. */

#define SOMAXCONN       5

/* Message header for recvmsg and sendmsg calls. */

struct msghdr {
    caddr_t msg_name;           /* optional address */
    int      msg_namelen;       /* size of address */
    struct iovec *msg_iov;       /* scatter/gather array */
    int      msg_iovlen;        /* # elements in msg_iov */
    caddr_t msg_accrights;       /* access rights sent/received */
    int      msg_accrightslen;
};

#define MSG_OOB          0x1     /* process out-of-band data */
#define MSG_PEEK         0x2     /* peek at incoming message */
#define MSG_DONTROUTE    0x4     /* send without using routing tables */

#define MSG_MAXIOVLEN    16

/* option header */

struct opthdr {
    long      level;            /* protocol level affected */
    long      name;             /* option to modify */
    long      len;              /* length of option value */
};

#define OPTLEN(x) (((x) + sizeof (long) - 1) / sizeof (long)) * sizeof (long)
#define OPTVAL(opt) ((char *) (opt + 1))

/*
 * the optdefault structure is used for internal tables of option default
 * values.
 */
struct optdefault {
    int      optname;           /* the option */
    char     *val;              /* ptr to default value */
    int      len;              /* length of value */
};

/*
 * the opproc structure is used to build tables of options processing
 * functions for dooptions().
 */
struct opproc {
    int      level;            /* options level this function handles */
    int      (*func)();        /* the function */
};

/*
```

```

    * This structure is used to encode pseudo system calls
    */
struct socksysreq {
    int    args[7];
};

/*
    * This structure is used for adding new protocols to the list supported by
    * sockets.
    */

struct socknewproto {
    int    family; /* address family (AF_INET, etc.) */
    int    type;   /* protocol type (SOCK_STREAM, etc.) */
    int    proto;  /* per family proto number */
    dev_t  dev;    /* major/minor to use (must be a clone) */
    int    flags;  /* protosw flags */
};
```

Figure 6-3. Manifest Constants and Data Types from <netinet/in.h>

```
/* IP address */
struct in_addr {
    union {
        struct { u_char s_b1, s_b2, s_b3, s_b4; } S_un_b;
        struct { u_short s_w1, s_w2; } S_un_w;
        u_long S_addr;
    } S_un;
};

/* socket address using IP */

struct sockaddr_in {
    short    sin_family;
    u_short  sin_port;
    struct    in_addr sin_addr;
    char     sin_zero[8];
};

/* Options for use with [gs]etsockopt at the IP level. */

#define IP_OPTIONS      1      /* set/get IP per-packet options */
#define IP_HDRINCL      2      /* int; header is included with data (raw) */
#define IP_TOS          3      /* int; IP type of service and precedence */
#define IP_TTL          4      /* int; IP time to live */
#define IP_RECVOPTS     5      /* bool; receive all IP options w/datagram */
#define IP_RECVRETOPTS  6      /* bool; receive IP options for response */
#define IP_RECVDSTADDR  7      /* bool; receive IP dst addr w/datagram */
#define IP_RETOPTS      8      /* ip_opts; set/get IP per-packet options */
#define IP_MULTICAST_IF 0x10    /* set/get IP multicast interface */
#define IP_MULTICAST_TTL 0x11    /* set/get IP multicast timetolive */
#define IP_MULTICAST_LOOP 0x12 /* set/get IP multicast loopback */
#define IP_ADD_MEMBERSHIP 0x13 /* add an IP group membership */
#define IP_DROP_MEMBERSHIP 0x14 /* drop an IP group membership */

#define IP_DEFAULT_MULTICAST_TTL 1 /* normally limit m'casts to 1 hop */
#define IP_DEFAULT_MULTICAST_LOOP 1 /* normally hear sends if a member */

/* Argument structure for IP_ADD_MEMBERSHIP and IP_DROP_MEMBERSHIP. */

struct ip_mreq {
    struct in_addr imr_multiaddr; /* IP multicast address of group */
    struct in_addr imr_interface; /* local IP address of interface */
};
```

Figure 6-4. Manifest Constants and Data Types from <netdb.h>

```

struct hostent {
    char    *h_name;           /* official name of host */
    char    **h_aliases;       /* alias list */
    int     h_addrtype;        /* host address type */
    int     h_length;          /* length of address */
    char    **h_addr_list;     /* list of addresses from name server */
#define h_addr h_addr_list[0] /* address, for backward compatibility */
};

struct servent {
    char    *s_name;           /* official service name */
    char    **s_aliases;       /* alias list */
    int     s_port;            /* port # */
    char    *s_proto;          /* protocol to use */
};

struct protoent {
    char    *p_name;           /* official protocol name */
    char    **p_aliases;       /* alias list */
    int     p_proto;           /* protocol # */
};

#define HOST_NOT_FOUND 1 /* Authoritative Answer Host not found */
#define TRY_AGAIN      2 /* Non-Authoritative Host not found, or SERVERFAIL */
#define NO_RECOVERY    3 /* Non recoverable errors, FORMERR, REFUSED, NOTIMP */
#define NO_DATA        4 /* Valid name, no data record of requested type */
#define NO_ADDRESS      NO_DATA /* no address, look for MX record */

```

Figure 6-5. Manifest Constants and Data Types from <errno.h>

```
#define EADDRINUSE      125          /* Address already in use */
#define EADDRNOTAVAIL   126          /* Can't assign requested address */
#define EAFNOSUPPORT    124          /* Address family not supported by
#define EALREADY        149          /* operation already in progress */
#define ECONNREFUSED    146          /* Connection refused */
#define EINPROGRESS     150          /* operation now in progress */
#define EISCONN         133          /* Socket is already connected */
#define EMSGSIZE        97           /* Message too long */
#define ENETUNREACH     128          /* Network is unreachable */
#define ENOTCONN        134          /* Socket is not connected */
#define ENOTSOCK        95           /* Socket operation on non-socket */
#define EOPNOTSUPP      122          /* Operation not supported on socket */
#define EPROTONOSUPPORT 120          /* Protocol not supported */
#define EPROTOTYPE      98           /* Protocol wrong type for socket */
#define ETIMEDOUT       145          /* Connection timed out */
#define EWOULDBLOCK     EAGAIN
```

Rationale

Two criteria must be satisfied for a function to be included in this specification.

- 1) Identical or similar implementation and documentation in all reference implementations.
- 2) Widespread use in applications for TCP/IP networking.

Basic Socket Interface Function Set

All the reference implementations inherit a basic set of socket functions from 4.2BSD relatively unchanged. All sixteen of these functions are included in this specification.

Another function,

```
int socketpair(int d, int type, int protocol, int sv[2]);
```

is excluded from the specification because it is only usable in the `AF_UNIX` address family, and is thus inapplicable to TCP/IP socket programming. In addition, there are differences in implementations; for example, one implementation adds `ENOBUFF` as an error code and another implementation returns a file descriptor number while other implementations return a success/failure code.

I/O Multiplexing

The `poll()` system call should be used for I/O multiplexing. The `select()` system call is not part of this specification because there is no implementation of the function which is binary compatible across all SPARC systems.

System Identifier

One implementation specification included two pairs of functions for getting and setting a symbolic hostname and a numeric hostid for the local system:

```
gethostname()
sethostname()
gethostid()
sethostid()
```

The functions `sethostname` and `sethostid` are not needed by normal applications and are excluded from this specification.

Applications which use `gethostname` should be changed to use `sysinfo(SI_SYSNAME, ...)`.

Applications which use `gethostid` should be changed to use `sysinfo(SI_HW_SERIAL, ...)`.

Ethernet Address Manipulation Routines

The specification excludes the functions from `ethers(3N)` for formatting Ethernet addresses, since display of Ethernet addresses is not generally needed in an application environment. These excluded functions are:

```
ether_aton()
ether_hostton()
ether_line()
ether_ntoa()
ether_ntohost()
```

BSD R* Support Functions

The support functions that implement the BSD R* protocols are excluded from the specification. These functions implement the specific R* client and server commands and are not generally used in common TCP/IP applications. These excluded functions are:

From `rcmd(3N)`:

```
rresvport()
```

```
rcmd()  
ruserok()  
From rexec(3N):  
rexec()  
From bindresvport(3N):  
bindresvport()
```

ioctl Calls

All socket ioctl calls are excluded from this specification. The two ioctl calls are

```
SIOCADDRT  
SIODELRT
```

These two calls relate to maintenance of the kernel routing tables and are implementation specific. These calls are only used by a user-level routing daemon and as such are not found in normal network applications.

Function Definitions

Basic Socket Interface Function Set

accept(3N)

```
int accept(int s, struct sockaddr *addr, int *addrlen);
```

bind(3N)

```
int bind(int s, struct sockaddr *name, int namelen);
```

connect(3N)

```
int connect(int s, struct sockaddr *name, int namelen);
```

getpeername(3N)

```
int getpeername(int s, struct sockaddr *name, int namelen);
```

getsockname(3N)

```
int getsockname(int s, struct sockaddr *name, int namelen);
```

One implementation spells out `struct linger` instead of referring to `<socket.h>`: delete this structure specification from man page and put in `<socket.h>`. One implementation gives numeric limits of 64Kbytes for `SO_SNDBUF` and `SO_RCVBUF`: delete these specific numeric limits.

```
int getsockopt(int s, int level, int optname, char *optval, int *optlen)
```

```
int setsockopt(int s, int level, int optname, char *optval, int *optlen)
```

One implementation makes the fourth argument `const`: delete this modifier.

listen(3N)

```
int listen(int s, int backlog)
```

recv(3N)

One implementation deletes `EFAULT`: delete `EFAULT` from the specification. Another implementation includes `ESTALE` and `EIO`: delete these error codes.

```
int recv(int s, char *buf, int len, int flags);
```

```
int recvfrom(int s, char *buf, int len, int flags, struct sockaddr *from,  
int *fromlen);
```

```
int recvmsg(int s, struct msghdr *msg, int flags);
```

send(3N)

```

    int send(int s, char *msg, int len, int flags);
    int sendto(int s, char *msg, int len, int flags, struct sockaddr *to, int tolen);
    int sendmsg(int s, msghdr *msg, int flags);
socket(3N)
    int socket(int domain, int type, int protocol);
shutdown(3N)
    int shutdown(int s, int how);
IP Address Manipulation Routines
inet(3N)
    unsigned long inet_addr(char *cp);
    int inet_network(char *cp);
    struct in_addr inet_makeaddr(int net, int lna);
    int inet_lnaof(struct in_addr in);
    int inet_netof(struct in_addr in);
    char *inet_ntoa(struct in_addr in);
Naming and Resource Lookup
gethostbyname(3N)
    struct hostent *gethostbyname(char *name)
    struct hostent *gethostbyaddr(char *addr, int length, int type)
getnetbyname(3N)
    struct netent *getnetbyname(char *name)
    struct netent *getnetbyaddr(long addr, int type)
getservbyname(3N)
    struct servent *getservbyname(char *name, char *proto)
    struct servent *getservbyport(int port, char *proto)
getprotobyname(3N)
    struct protoent *getprotobyname(char *name)
    struct protoent *getprotobyname(int proto)

```

The `gethostent()`, `getnetent()`, `getservent()`, `sethostent()`, `setnetent()`, `setservent()`, `endhostent()`, `endnetent()`, and `endservent()` routines found in all reference implementations are not included in this standard, since some specific implementations may not support the sequential search of a file implied by these routines.

DNS Resolver Interface

The following functions are not part of the specification. Their functionality is provided via `gethostbyname` and `gethostbyaddr`

```

resolver(3N)
    struct state _res;
    int res_mkquery(int op, char *dname, int class, int type, char *data, int datalen,
        struct rrec *newrr, char *buf, int buflen)

```

```
int res_send(char *msg, int msglen, char *answer, int anslen)
int res_init(void)
int dn_comp(char *exp_dn, char *comp_dn, int length, char **dnptrs,
            char **lastdnptr)
int dn_expand(char *msg, char *comp_dn, char exp_dn, int msglen, int length)
```

NAME

`accept` - accept a connection on a socket

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>

int accept(int s, struct sockaddr *addr, int *addrlen);
```

DESCRIPTION

The argument *s* is a socket that has been created with `socket(3N)` and bound to an address with `bind(3N)`, and that is listening for connections after a call to `listen(3N)`. `accept` extracts the first connection on the queue of pending connections, creates a new socket with the properties of *s*, and allocates a new file descriptor, *ns*, for the socket. If no pending connections are present on the queue and the socket is not marked as non-blocking, `accept` blocks the caller until a connection is present. If the socket is marked as non-blocking and no pending connections are present on the queue, `accept` returns an error as described below. `accept` uses the `netconfig(4)` file to determine the STREAMS device file name associated with *s*. This is the device on which the connect indication will be accepted. The accepted socket, *ns*, is used to read and write data to and from the socket that connected to *ns*; it is not used to accept more connections. The original socket (*s*) remains open for accepting further connections.

The argument *addr* is a result parameter that is filled in with the address of the connecting entity as it is known to the communications layer. The exact format of the *addr* parameter is determined by the domain in which the communication occurs.

addrlen is a value-result parameter. Initially, it contains the amount of space pointed to by *addr*; on return it contains the length in bytes of the address returned.

`accept` is used with connection-based socket types, currently with `SOCK_STREAM`.

It is possible to `poll(2)` a socket for the purpose of an `accept` by polling it for a read. However, this will only indicate when a connect indication is pending; it is still necessary to call `accept`.

RETURN VALUES

`accept` returns -1 on error. If it succeeds, it returns a non-negative integer that is a descriptor for the accepted socket.

ERRORS

`accept` will fail if:

<code>EBADF</code>	The descriptor is invalid.
<code>ENODEV</code>	The protocol family and type corresponding to <i>s</i> could not be found in the <code>netconfig</code> file.
<code>ENOMEM</code>	There was insufficient user memory available to complete the operation.
<code>ENOSR</code>	There were insufficient STREAMS resources available to complete the operation.
<code>ENOTSOCK</code>	The descriptor does not reference a socket.
<code>EOPNOTSUPP</code>	The referenced socket is not of type <code>SOCK_STREAM</code> .
<code>EPROTO</code>	A protocol error has occurred; for example, the STREAMS protocol stack has not been initialized.
<code>EWouldBlock</code>	The socket is marked as non-blocking and no connections are present to be accepted.

NAME

bind - bind a name to a socket

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>

int bind(int s, struct sockaddr *name, int namelen);
```

DESCRIPTION

bind assigns a name to an unnamed socket, *s*. When a socket is created with `socket(3N)`, it exists in a name space (address family) but has no *name* assigned. bind requests that the name pointed to by *name* be assigned to the socket. *namelen* specifies the size of *name*.

RETURN VALUES

If the bind is successful, a 0 value is returned. A return value of -1 indicates an error, which is further specified in the global `errno`.

ERRORS

The bind call will fail if:

EADDRINUSE	The specified address is already in use.
EADDRNOTAVAIL	The specified address is not available on the local machine.
EBADF	<i>s</i> is not a valid descriptor.
EINVAL	<i>namelen</i> is not the size of a valid address for the specified address family.
EINVAL	The socket is already bound to an address.
ENOSR	There were insufficient STREAMS resources for the operation to complete.
ENOTSOCK	<i>s</i> is a descriptor for a file, not a socket.

NAME

connect - initiate a connection on a socket

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>

int connect(int s, struct sockaddr *name, int namelen);
```

DESCRIPTION

The parameter *s* is a socket. If it is of type `SOCK_DGRAM`, `connect` specifies the peer with which the socket is to be associated; this address is the address to which datagrams are to be sent if a receiver is not explicitly designated; it is the only address from which datagrams are to be received. If the socket *s* is of type `SOCK_STREAM`, `connect` attempts to make a connection to another socket. The other socket is specified by *name*. *name* is an address in the communication space of the socket. *namelen* specifies the size of data structure pointed to by *name*. Each communication space interprets the *name* parameter in its own way. If *s* is not bound, then it will be bound to an address selected by the underlying transport provider. Generally, stream sockets may successfully connect only once; datagram sockets may use `connect` multiple times to change their association. Datagram sockets may dissolve the association by connecting to a null address.

RETURN VALUES

If the connection or binding succeeds, then 0 is returned. Otherwise a -1 is returned and sets `errno` to indicate the error.

ERRORS

The call fails if:

<code>EADDRINUSE</code>	The address is already in use.
<code>EADDRNOTAVAIL</code>	The specified address is not available on the remote machine.
<code>EAFNOSUPPORT</code>	Addresses in the specified address family cannot be used with this socket.
<code>EALREADY</code>	The socket is non-blocking and a previous connection attempt has not yet been completed.
<code>EBADF</code>	<i>s</i> is not a valid descriptor.
<code>ECONNREFUSED</code>	The attempt to connect was forcefully rejected. The calling program should <code>close(2)</code> the socket descriptor, and issue another <code>socket(3N)</code> call to obtain a new descriptor before attempting another <code>connect</code> call.
<code>EINPROGRESS</code>	The socket is non-blocking and the connection cannot be completed immediately. It is possible to <code>poll(3C)</code> for completion by polling the socket for writing. However, this is only possible if the socket STREAMS module is the topmost module on the protocol stack with a write service procedure. This will be the normal case.
<code>EINTR</code>	The connection attempt was interrupted before any data arrived by the delivery of a signal.
<code>EINVAL</code>	<i>namelen</i> is not the size of a valid address for the specified address family.
<code>EISCONN</code>	The socket is already connected.
<code>ENETUNREACH</code>	The network is not reachable from this host.
<code>ENOSR</code>	There were insufficient STREAMS resources available to complete the operation.

NAME

gethostbyname, gethostbyaddr - get network host entry

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>
#include <netdb.h>

struct hostent *gethostbyname(char *name);
struct hostent *gethostbyaddr(struct in_addr *addr,
    const sizeof(struct in_addr), const int AF_INET);
```

DESCRIPTION

gethostbyaddr, and gethostbyname each return a host entry.

The entry may come from the hosts file (see hosts(4)) or an implementation specific “hosts” table. The sources and their lookup order are unspecified.

gethostbyname searches for a host entry with a given hostname.

gethostbyaddr searches for a host entry with a given hostaddress.

The internal representation of a host entry is a structure defined in <netdb.h> with the following members:

```
char *h_name;
char **h_aliases;
int h_addrtype;
int h_length;
char **h_addr_list;
```

Host addresses are supplied in network byte order.

RETURN VALUES

gethostbyname and gethostbyaddr return a pointer to a struct hostent if they successfully locate the requested entry; otherwise they return NULL, and set an integer h_errno to indicate one of these errors: HOST_NOT_FOUND, TRY_AGAIN, NO_RECOVERY, NO_DATA and NO_ADDRESS (see /usr/include/netdb.h).

FILES

/etc/hosts

NOTES

All information is contained in a static area so it must be copied if it is to be saved.

NAME

getpeername - get name of connected peer

SYNOPSIS

```
int getpeername(int s, struct sockaddr *name, int *namelen);
```

DESCRIPTION

getpeername returns the name of the peer connected to socket *s*. The `int` pointed to by the *namelen* parameter should be initialized to indicate the amount of space pointed to by *name*. On return it contains the actual size of the *name* returned (in bytes). The *name* is truncated if the buffer provided is too small.

RETURN VALUES

If successful, getpeername returns 0; otherwise it returns -1 and sets `errno` to indicate the error.

ERRORS

The call succeeds unless:

EBADF	The argument <i>s</i> is not a valid descriptor.
ENOMEM	There was insufficient user memory for the operation to complete.
ENOSR	There were insufficient STREAMS resources available for the operation to complete.
ENOTCONN	The socket is not connected.
ENOTSOCK	The argument <i>s</i> is not a socket.

NAME

getprotobyname, getprotobynumber, getprotoent - get protocol entry

SYNOPSIS

```
#include <netdb.h>

struct protoent *getprotobyname(char *name);
struct protoent *getprotobynumber(int proto);
struct protoent *getprotoent(void);
```

DESCRIPTION

getprotoent, getprotobyname, and getprotobynumber each return a protocol entry. The entry may come from `/etc/protocols` or an implementation defined place. *name* is a pointer to one of the strings "tcp", "udp", or "icmp". *proto* is one of the values 6 (tcp), 17 (udp), 0 (ip), or 1 (icmp).

getprotoent enumerates protocol entries: successive calls to getprotoent will return either successive protocol entries or NULL. Enumeration may not be supported by some sources.

The internal representation of a protocol entry is a protoent structure defined in `<netdb.h>` with the following members:

```
char *p_name;
char **p_aliases;
int p_proto;
```

RETURN VALUES

getprotobyname and getprotobynumber return a pointer to a struct protoent if they successfully locate the requested entry; otherwise they return NULL.

getprotoent returns a pointer to a struct protoent if it successfully enumerates an entry; otherwise it returns NULL, indicating the end of the enumeration.

FILES

`/etc/protocols`

NOTES

All information is contained in a static area so it must be copied if it is to be saved.

Use of getprotoent is deprecated.

NAME

getservbyname, getservbyport - get service entry

SYNOPSIS

```
#include <netdb.h>

struct servent *getservbyname(char *name, char *proto);
struct servent *getservbyport(int port, char *proto);
```

DESCRIPTION

getservbyname, and getservbyport each return a service entry.

The entry may come from the services file (see services(4)) or an implementation defined source.

getservbyname searches for a service entry with a given service name.

getservbyport searches for a service entry with a given port number and, if the protocol name is non-NULL, the protocol.

name is a pointer to one of the strings "tcp" or "udp". *port* is the number of a well-known port.

The internal representation of a service entry is a `struct servent` defined in `<netdb.h>` with the following members:

```
char *s_name;
char **s_aliases;
int s_port;
char *s_proto;
```

RETURN VALUES

getservbyname and getservbyport return a pointer to a `struct servent` if they successfully locate the requested entry; otherwise they return NULL.

FILES

/etc/services

NOTES

All information is contained in a static area, so it must be copied if it is to be saved.

NAME

getsockname - get socket name

SYNOPSIS

```
#include <sys/types.h>
#include <sys/sockets.h>

int getsockname(int s, struct sockaddr *name, int *namelen);
```

DESCRIPTION

getsockname returns the current name for socket *s*. The *namelen* parameter should be initialized to indicate the amount of space pointed to by *name*. On return it contains the actual size in bytes of the *name* returned.

RETURN VALUES

If successful, getsockname returns 0; otherwise it returns -1 and sets *errno* to indicate the error.

ERRORS

The call succeeds unless:

EBADF	The argument <i>s</i> is not a valid file descriptor.
ENOMEM	There was insufficient memory available for the operation to complete.
ENOSR	There were insufficient STREAMS resources available for the operation to complete.
ENOTSOCK	The argument <i>s</i> is not a socket.

NAME

`inet_addr`, `inet_network`, `inet_makeaddr`, `inet_lnaof`, `inet_netof`, `inet_ntoa` - Internet address manipulation

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>

unsigned long inet_addr(char *cp);
int inet_network(char *cp);
struct in_addr inet_makeaddr(int net, int lna);
int inet_lnaof(struct in_addr in);
int inet_netof(struct in_addr in);
char *inet_ntoa(struct in_addr in);
```

DESCRIPTION

The `inet_addr` and `inet_network` routines interpret a character string, *cp*, representing numbers expressed in the Internet standard '.' notation, returning numbers suitable for use as Internet addresses and Internet network numbers, respectively. The routine `inet_makeaddr` takes an Internet network number, *net*, and a local network address, *lna*, and constructs an Internet address from it. The routines `inet_netof` and `inet_lnaof` break apart an Internet host address, *in*, returning the network number and local network address part, respectively.

The routine `inet_ntoa` returns a pointer to a string in the base 256 notation "d.d.d.d" described below.

All Internet addresses are returned in network order (bytes ordered from left to right). All network numbers and local address parts are returned as machine format integer values.

INTERNET ADDRESSES

Values specified using the '.' notation take one of the following forms:

a.b.c.d
a.b.c
a.b
a

When four parts are specified, each is interpreted as a byte of data and assigned, from left to right, to the four bytes of an Internet address.

When a three part address is specified, the last part is interpreted as a 16-bit quantity and placed in the right most two bytes of the network address. This makes the three part address format convenient for specifying Class B network addresses as "128.net.host".

When a two part address is supplied, the last part is interpreted as a 24-bit quantity and placed in the right most three bytes of the network address. This makes the two part address format convenient for specifying Class A network addresses as "net.host".

When only one part is given, the value is stored directly in the network address without any byte rearrangement.

All numbers supplied as "parts" in a '.' notation may be decimal, octal, or hexadecimal, as specified

in the C language (that is, a leading 0x or 0X implies hexadecimal; otherwise, a leading 0 implies octal; otherwise, the number is interpreted as decimal).

RETURN VALUES

The value -1 is returned by `inet_addr` and `inet_network` for malformed requests.

The routines `inet_netof` and `inet_lnaof` break apart Internet host addresses, returning the network number and local network address part, respectively.

The routine `inet_ntoa` returns a pointer to a string in the base 256 notation “d.d.d.d” described below.

NAME

`listen` - listen for connections on a socket

SYNOPSIS

```
#include <sys/types.h>
#include <sys/sockets.h>
```

```
int listen(int s, int backlog);
```

DESCRIPTION

To accept connections, a socket, *s*, is first created with `socket(3N)`, a *backlog* for incoming connections is specified with `listen` and then the connections are accepted with `accept(3N)`. The `listen` call applies only to sockets of type `SOCK_STREAM` or `SOCK_SEQPACKET`.

The *backlog* parameter defines the maximum length the queue of pending connections may grow to. If a connection request arrives with the queue full, the client will receive an error with an indication of `ECONNREFUSED`.

RETURN VALUES

A 0 return value indicates success; -1 indicates an error.

ERRORS

The call fails if:

<code>EBADF</code>	The argument <i>s</i> is not a valid file descriptor.
<code>ENOTSOCK</code>	The argument <i>s</i> is not a socket.
<code>EOPNOTSUPP</code>	The socket is not of a type that supports the operation <code>listen</code> .

NOTES

There is currently no backlog limit.

NAME

`recv`, `recvfrom`, `recvmsg` - receive a message from a socket

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>
#include <sys/uio.h>

int recv(int s, char *buf, int len, int flags);
int recvfrom(int s, char *buf, int len, int flags, struct sockaddr *from,
             int *fromlen);
int recvmsg(int s, struct msghdr *msg, int flags);
```

DESCRIPTION

`recv`, `recvfrom`, and `recvmsg` are used to receive messages from another socket. `recv` may be used only on a connected socket (see `connect(3N)`), while `recvfrom` and `recvmsg` may be used to receive data on a socket whether it is in a connected state or not. *s* is a socket created with `socket(3N)`. *buf* is a pointer to the buffer to receive the data and *len* is its size in bytes.

If *from* is not a NULL pointer, the source address of the message is filled in. *fromlen* is a value-result parameter, initialized to the size of the buffer associated with *from*, and modified on return to indicate the actual size of the address stored there. The length of the message is returned. If a message is too long to fit in the supplied buffer, excess bytes may be discarded depending on the type of socket the message is received from (see `socket(3N)`).

If no messages are available at the socket, the receive call waits for a message to arrive, unless the socket is nonblocking (see `fcntl(2)`) in which case -1 is returned with the external variable `errno` set to `EWOULDBLOCK`.

The `poll` call may be used to determine when more data arrives.

The flags parameter is formed by ORing one or more of the following:

<code>MSG_OOB</code>	Read any out-of-band data present on the socket rather than the regular in-band data.
<code>MSG_PEEK</code>	Peek at the data present on the socket; the data is returned, but not consumed, so that a subsequent receive operation will see the same data.

The `recvmsg` call uses a `struct msghdr`, *msg*, to minimize the number of directly supplied parameters. This structure is defined in `<sys/socket.h>` and includes the following members:

```
caddr_t msg_name; /* optional address */
int msg_namelen; /* size of address */
struct iovec *msg_iov; /* scatter/gather array */
int msg_iovlen; /* # elements in msg_iov */
caddr_t msg_accrights; /* access rights sent/received */
int msg_accrightslen;
```

Here *msg_name* and *msg_namelen* specify the destination address if the socket is unconnected; *msg_name* may be given as a NULL pointer if no names are desired or required. The *msg_iov* and *msg_iovlen* describe the scatter-gather locations, as described in `read(2)`. A buffer to receive any access rights sent along with the message is specified in *msg_accrights*, which has length *msg_accrightslen*.

RETURN VALUES

These calls return the number of bytes received, or -1 if an error occurred.

ERRORS

The calls fail if:

EBADF	<i>s</i> is an invalid file descriptor.
EINTR	The operation was interrupted by delivery of a signal before any data was available to be received.
ENOMEM	There was insufficient user memory available for the operation to complete.
ENOSR	There were insufficient STREAMS resources available for the operation to complete.
ENOTSOCK	<i>s</i> is not a socket.
EWOULDBLOCK	The socket is marked non-blocking and the requested operation would block.

NAME

`send`, `sendto`, `sendmsg` - send a message from a socket

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>

int send(int s, char *buf, int len, int flags);
int sendto(int s, char *buf, int len, int flags, struct sockaddr *to, int tolen);
int sendmsg(int s, struct msghdr *msg, int flags);
```

DESCRIPTION

`send`, `sendto`, and `sendmsg` are used to transmit a message to another transport end-point. `send` may be used only when the socket is in a connected state, while `sendto` and `sendmsg` may be used at any time. *s* is a socket created with `socket(3N)`. *buf* points to a buffer containing the data to be sent. *len* is number of bytes to be sent.

The address of the target is given by *to* with *tolen* specifying its size. The length of the message is given by *len*. If the message is too long to pass atomically through the underlying protocol, then the error `EMSGSIZE` is returned, and the message is not transmitted.

A return value of -1 indicates locally detected errors only. It does not implicitly mean the message was not delivered.

If the socket does not have enough buffer space available to hold the message being sent, `send` blocks, unless the socket has been placed in non-blocking I/O mode (see `fcntl(2)`). The `poll` call may be used to determine when it is possible to send more data.

The flags parameter is formed from the bitwise OR of zero or more of the following:

<code>MSG_OOB</code>	Send out-of-band data on sockets that support this notion. The underlying protocol must also support out-of-band data. Only <code>SOCK_STREAM</code> sockets created in the <code>AF_INET</code> address family support out-of-band data.
<code>MSG_DONTROUTE</code>	The <code>SO_DONTROUTE</code> option is turned on for the duration of the operation. It is used only by diagnostic or routing programs.

See `recv(3N)` for a description of the `msghdr` structure.

RETURN VALUES

These calls return the number of bytes sent, or -1 if an error occurred.

ERRORS

The calls fail if:

<code>EBADF</code>	<i>s</i> is an invalid file descriptor.
<code>EINTR</code>	The operation was interrupted by delivery of a signal before any data could be buffered to be sent.
<code>EINVAL</code>	<i>tolen</i> is not the size of a valid address for the specified address family.
<code>EMSGSIZE</code>	The socket requires that message be sent atomically, and the message was too long.
<code>ENOMEM</code>	There was insufficient memory available to complete the operation.
<code>ENOSR</code>	There were insufficient STREAMS resources available for the operation to complete.
<code>ENOTSOCK</code>	<i>s</i> is not a socket.

EWouldBlock

The socket is marked non-blocking and the requested operation would block.

NAME

getsockopt, setsockopt - get and set options on sockets

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>

int getsockopt(int s, int level, int optname, void *optval, int *optlen);
int setsockopt(int s, int level, int optname, void *optval, int optlen);
```

DESCRIPTION

getsockopt and setsockopt manipulate options associated with a socket, *s*. Options may exist at multiple protocol levels; they are always present at the uppermost socket level.

When manipulating socket options, the level at which the option resides and the name of the option must be specified. To manipulate options at the socket level, *level* is specified as `SOL_SOCKET`. To manipulate options at any other level, *level* is the protocol number of the protocol that controls the option. For example, to indicate that an option is to be interpreted by the TCP protocol, *level* is set to the TCP protocol number (see `getprotobyname(3N)`).

The parameters *optval* and *optlen* are used to access option values for `setsockopt`. For `getsockopt`, they identify a buffer in which the value(s) for the requested option(s) are to be returned. For `getsockopt`, *optlen* is a value-result parameter, initially containing the size of the buffer pointed to by *optval*, and modified on return to indicate the actual size of the value returned. Use a 0 *optval* if no option value is to be supplied or returned.

optname and any specified options are passed uninterpreted to the appropriate protocol module for interpretation. The include file `<sys/socket.h>` contains definitions for the socket-level options described below. Options at other protocol levels vary in format and name.

Most socket-level options take an `int` for *optval*. For `setsockopt`, the *optval* parameter should be non-zero to enable a boolean option, or zero if the option is to be disabled. `SO_LINGER` uses a `struct linger` parameter that specifies the desired state of the option and the linger interval (see below). `struct linger` is defined in `<sys/socket.h>`. `struct linger` contains the following members:

<code>l_onoff</code>	option on/off
<code>l_linger</code>	linger time

The following options are recognized at the socket level. Except as noted, each may be examined with `getsockopt` and set with `setsockopt`.

<code>SO_DEBUG</code>	toggle recording of debugging information
<code>SO_REUSEADDR</code>	toggle local address reuse
<code>SO_KEEPAIVE</code>	toggle keep connections alive
<code>SO_DONTROUTE</code>	toggle routing bypass for outgoing messages
<code>SO_LINGER</code>	linger on close if data is present
<code>SO_BROADCAST</code>	toggle permission to transmit broadcast messages
<code>SO_OOBINLINE</code>	toggle reception of out-of-band data in band
<code>SO_SNDBUF</code>	set buffer size for output
<code>SO_RCVBUF</code>	set buffer size for input
<code>SO_TYPE</code>	get the type of the socket (get only)
<code>SO_ERROR</code>	get and clear error on the socket (get only)

`SO_DEBUG` enables debugging in the underlying protocol modules. `SO_REUSEADDR` indicates that the rules used in validating addresses supplied in a `bind(3N)` call should allow reuse of local addresses. `SO_KEEPAIVE` enables the periodic transmission of messages on a connected socket. If the connected party fails to respond to these messages, the connection is considered broken and processes using the socket are notified using a `SIGPIPE` signal. `SO_DONTROUTE` indicates that outgoing messages should bypass the standard routing facilities. Instead, messages are directed to the appropriate network interface according to the network portion of the destination address.

`SO_LINGER` controls the action taken when unsent messages are queued on a socket and a `close(2)` is performed. If the socket promises reliable delivery of data and `SO_LINGER` is set, the system will block the process on the close attempt until it is able to transmit the data or until it decides it is unable to deliver the information (a timeout period, termed the linger interval, is specified in the `setsockopt` call when `SO_LINGER` is requested). If `SO_LINGER` is disabled and a close is issued, the system will process the close in a manner that allows the process to continue as quickly as possible.

The option `SO_BROADCAST` requests permission to send broadcast datagrams on the socket. With protocols that support out-of-band data, the `SO_OOBINLINE` option requests that out-of-band data be placed in the normal data input queue as received; it will then be accessible with `recv` or `read` calls without the `MSG_OOB` flag.

`SO_SNDBUF` and `SO_RCVBUF` are options that adjust the normal buffer sizes allocated for output and input buffers, respectively. The buffer size may be increased for high-volume connections or may be decreased to limit the possible backlog of incoming data.

Finally, `SO_TYPE` and `SO_ERROR` are options used only with `getsockopt`. `SO_TYPE` returns the type of the socket (for example, `SOCK_STREAM`). It is useful for servers that inherit sockets on startup. `SO_ERROR` returns any pending error on the socket and clears the error status. It may be used to check for asynchronous errors on connected datagram sockets or for other asynchronous errors.

RETURN VALUES

If successful, `getsockopt` returns 0; otherwise it returns -1 and sets `errno` to indicate the error.

ERRORS

The call succeeds unless:

<code>EBADF</code>	The argument <code>s</code> is not a valid file descriptor.
<code>ENOMEM</code>	There was insufficient memory available for the operation to complete.
<code>ENOPROTOPT</code>	The option is unknown at the level indicated.
<code>ENOSR</code>	There were insufficient STREAMS resources available for the operation to complete.
<code>ENOTSOCK</code>	The argument <code>s</code> is not a socket.

NAME

shutdown - shut down part of a full-duplex connection

SYNOPSIS

```
int shutdown(int s, int how);
```

DESCRIPTION

The `shutdown` call shuts down all or part of a full-duplex connection on the socket associated with *s*. If *how* is 0, then further receives will be disallowed. If *how* is 1, then further sends will be disallowed. If *how* is 2, then further sends and receives will be disallowed.

RETURN VALUES

A 0 is returned if the call succeeds, -1 if it fails.

ERRORS

The call succeeds unless:

EBADF	<i>s</i> is not a valid file descriptor.
ENOMEM	There was insufficient user memory available for the operation to complete.
ENOSR	There were insufficient STREAMS resources available for the operation to complete.
ENOTCONN	The specified socket is not connected.
ENOTSOCK	<i>s</i> is not a socket.

NOTES

The *how* values should be defined constants.

NAME

`socket` - create an endpoint for communication

SYNOPSIS

```
#include <sys/types.h>
#include <sys/socket.h>

int socket(int domain, int type, int protocol);
```

DESCRIPTION

`socket` creates an endpoint for communication and returns a descriptor.

The *domain* parameter specifies a communications domain within which communication will take place; this selects the protocol family which should be used. The protocol family generally is the same as the address family for the addresses supplied in later operations on the socket. These families are defined in the include file `<sys/socket.h>`.

The only supported protocol family is `PF_INET`.

The socket has the indicated *type*, which specifies the communication semantics. Currently defined *types* are:

```
SOCK_STREAM
SOCK_DGRAM
SOCK_SEQPACKET
```

A `SOCK_STREAM` type provides sequenced, reliable, two-way connection-based byte streams. An out-of-band data transmission mechanism may be supported. A `SOCK_DGRAM` socket supports datagrams (connectionless, unreliable messages of a fixed (typically small) maximum length). A `SOCK_SEQPACKET` socket may provide a sequenced, reliable, two-way connection-based data transmission path for datagrams of fixed maximum length; a consumer may be required to read an entire packet with each `read` system call. This facility is protocol specific, and presently not implemented for any protocol family.

protocol specifies a particular protocol to be used with the socket. Normally only a single protocol exists to support a particular socket type within a given protocol family. However, multiple protocols may exist, in which case a particular protocol must be specified in this manner. The protocol number to use is particular to the “communication domain” in which communication is to take place. If a protocol is specified by the caller, then it will be packaged into a socket level option request and sent to the underlying protocol layers.

Sockets of type `SOCK_STREAM` are full-duplex byte streams, similar to pipes. A stream socket must be in a connected state before any data may be sent or received on it. A connection to another socket is created with a `connect(3N)` call. Once connected, data may be transferred using `read(2)` and `write(2)` calls or some variant of the `send(3N)` and `recv(3N)` calls. When a session has been completed, a `close(2)` may be performed. Out-of-band data may also be transmitted as described on the `send(3N)` manual page and received as described on the `recv(3N)` manual page.

The communications protocols used to implement a `SOCK_STREAM` insure that data is not lost or duplicated. If a piece of data for which the peer protocol has buffer space cannot be successfully transmitted within a reasonable length of time, then the connection is considered broken and calls will indicate an error with -1 returns and with `ETIMEDOUT` as the specific code in the global variable `errno`. The protocols optionally keep sockets “warm” by forcing transmissions roughly every minute in the absence of other activity. An error is then indicated if no response can be elicited on an otherwise idle connection for an extended period (for instance 5 minutes). A `SIGPIPE` signal is raised if a process sends on a broken stream; this causes naive processes, which do not handle the signal, to exit.

`SOCK_SEQPACKET` sockets employ the same system calls as `SOCK_STREAM` sockets. The only difference is that `read` calls will return only the amount of data requested, and any remaining in the arriving packet will be discarded.

`SOCK_DGRAM` sockets allow datagrams to be sent to correspondents named in `sendto` calls. Datagrams are generally received with `recvfrom`, which returns the next datagram with its return address.

An `ioctl(2)` call can be used to specify a process group to receive a `SIGURG` signal when the out-of-band data arrives. It may also enable non-blocking I/O and asynchronous notification of I/O events with `SIGPOLL` signals.

The operation of sockets is controlled by socket level options. These options are defined in the file `<sys/socket.h>`. `setsockopt` and `getsockopt(3N)` are used to set and get options, respectively.

RETURN VALUES

A -1 is returned if an error occurs. Otherwise the return value is a descriptor referencing the socket.

ERRORS

The `socket` call fails if:

<code>EACCES</code>	Permission to create a socket of the specified type and/or protocol is denied.
<code>EMFILE</code>	The per-process descriptor table is full.
<code>ENOMEM</code>	Insufficient user memory is available.
<code>ENOSR</code>	There were insufficient STREAMS resources available to complete the operation.
<code>EPROTONOSUPPORT</code>	The protocol type or the specified protocol is not supported within this domain.

Dynamic Object File Loading

All interfaces described in this section are REQUIRED. Systems must supply `/usr/lib/libdl.so.1`. The functions supplied by this library listed in Table 6-10. Manifest constants for these functions are defined in Figure 6-6.

Manual pages for the required functions are missing from the SVID so they have been included after Figure 6-6.

Introduction

The run-time dynamic linking facilities of the system are made available to the executing application program through the functions in `libdl`:

`dlopen`, `dlclose`, `dlsym`, and `dlerror`

The particulars on dynamic linking and loading, path name resolution, data initialization functions, symbol relocation and binding, and automatic loading of secondary objects are given in Chapter 5 of this document and in the normative documents it references, the *System V Application Binary Interface* and the *System V Application Binary Interface, SPARC Processor Supplement*.

The following terms are used in this specification:

For a *program* to *reference* a symbol means for the program to use the storage value associated with that symbol. To *reference* a data symbol means (a) to retrieve the value stored in the location associated with that symbol, or (b) to store a value into the location associated with that symbol. To *reference* a function symbol means to (a) use the value directly by calling that function, or (b) to obtain its value via a call to `dlsym`, presumably in order to call the function later.

For a *program* to *contain a reference* to a symbol means that the program has been constructed in such a way that it will *reference* a symbol that is not defined within it. In the C language, this is done by declaring a data or function to have the `extern` attribute. The *reference* that the program contains is an indication to the linker and loader of what the name of the symbol is, and the fact that it will be found in some other program. For details on how this is implemented in a SPARC executable file, see the *System V Application Binary Interface* and the *System V Application Binary Interface, SPARC Processor Supplement*.

Two kinds of objects are mentioned in these specifications. A *data object* is the storage location associated with a symbol in an application program. A *shared object* is (a) a file on disk that was created by linking a program as a shared object, or (b) such a file that has been loaded into memory and prepared for execution. When the word “object” is used without qualification in this specification, it means shared object, and usually the shared object in memory.

For an *object* to *reference* another *object* means that the first object has been linked with the second object in such a way as to create `DT_NEEDED` entries that cause the second object to be loaded automatically with the first object. (See Chapter 5 of this document.)

Table 6-10. libdl Contents

dlclose

dLError

Figure 6-6. Manifest Constants and Data Types from <dlfcn.h>

```
/*
 * Valid values for mode argument to dlopen.
 */
#define RTLD_LAZY      1      /* lazy function call binding */
#define RTLD_NOW       2      /* immediate function call binding */
```

ABI Extensions

The dynamic linking routines required by the SCD are not described in any of the the base documents. Descriptions for each of the required functions follows.

NAME

`dlclose` - close a shared object

SYNOPSIS

```
#include <dlfcn.h>

int dlclosel(void *handle);
```

DESCRIPTION

The function `dlclose` disassociates from the current process a shared object previously opened by `dlopen`.

handle is a value that was returned from a previous call to `dlopen`. It designates the shared object whose *pathname* was specified in that previous call to `dlopen`.

Once an object has been disassociated from the process using `dlclose`, its symbols and those of any objects that were loaded automatically as a result of opening the object designated by *handle* are no longer available to `dlsym` via *handle*.

In order for `dlclose` to disassociate an object from a process, there must have been exactly one `dlclose` executed for each `dlopen` that was executed. Thus if a `dlopen` was executed once for a *pathname*, `dlclose` would have to be executed once with the handle that was returned for *pathname*. If a `dlopen` were executed twice for the same *pathname*, the disassociation would occur only after the second `dlclose`.

A successful invocation of `dlclose` does not guarantee that the objects associated with *handle* will actually be removed from the address space of the process, even if the object has been disassociated from the process and its symbols are no longer available through *handle*. Objects loaded by one invocation of `dlopen` may also be loaded by another invocation of `dlopen`. The same object may also be opened multiple times. An object may be removed from the address space by the system only after all references to that object through an explicit `dlopen` invocation have been closed and all other objects that reference that object have also been closed. Even then, however, it is unspecified in this standard whether the object will actually be removed from the address space.

When the system removes an object from the process address space, the object's termination function is executed. The termination function for each object is specified by the `DT_FINI` entry in that object's `.dynamic` section. The exact timing of the execution of termination function relative to the timing of the `dlclose` that release the object is unspecified in this standard.

An SCD-conforming application will not have any processing dependencies upon the system's removal or non-removal of an object from the process address space following `dlclose`.

DIAGNOSTICS

If the referenced object was successfully closed, `dlclose` returns 0. If the object could not be closed, or if *handle* does not refer to an open object, `dlclose` returns a non-0 value. More detailed diagnostic information will be available through `dlerror`.

NOTES

The following notes are a consequence of that fact that this standard does not specify whether an object ever is actually removed from a process address space:

Once a program has executed a sequence of `dlclose` operations that would permit the system to remove an object from the process address space, the result of the program's executing any reference to symbols defined in that object are unspecified in this standard.

Once a program has executed a sequence of `dlclose` operations that would permit the system to remove an object from the process address space, if the program executes another `dlopen` for that object, it is unspecified in this standard whether the object is actually loaded again and whether the object's data will be in its initial state.

NAME

`dlerror` - get diagnostic information

SYNOPSIS

```
#include <dlfcn.h>

char *dlerror(void);
```

DESCRIPTION

The function `dlerror` returns a null-terminated character string (with no trailing newline) that describes the last error that occurred during dynamic linking processing. If no dynamic linking errors have occurred since the last invocation of `dlerror`, `dlerror` returns `NULL`. Thus, invoking `dlerror` a second time, immediately following a prior invocation, will result in `NULL` being returned.

NOTES

The messages returned by `dlerror` may reside in a static buffer that is overwritten on each call to `dlerror`. Application code should not write to this buffer. Programs wishing to preserve an error message should make their own copies of that message.

NAME

`dlopen` - open a shared object

SYNOPSIS

```
#include <dlfcn.h>

void *dlopen(char *pathname, int mode);
```

DESCRIPTION

The function `dlopen` is one of a family of routines that give the user direct access to the dynamic linking facilities.

The function `dlopen` makes a shared object available to a running process. `dlopen` returns to the process a *handle* the process must use to identify the object on subsequent calls to `dlsym` and `dlclose`. This value must not be interpreted in any way by the process. (See Rationale)

pathname is the path name of the object to be opened; it may be an absolute path or relative to the current directory. If the value of *pathname* is 0, `dlopen` will make the symbols contained in the original `a.out`, and all of the objects that were loaded at program startup with the `a.out`, available through `dlsym`.

If the value of *pathname* is not zero, and no file specified by *pathname* has already been loaded into the address space, the file specified by *pathname* will be loaded. If the file specified by *pathname* contains `DT_NEEDED` entries for other shared objects, those objects will automatically be loaded by `dlopen`. The directory search path to be used to find both *pathname* and the other objects to be automatically loaded are given in Chapter 5 of this document and in the normative references specified there.

Objects whose names resolve to the same absolute or relative path name may be opened any number of times either using `dlopen` or automatically as a result of executing `dlopen` for an object that uses them. However, the object referenced is loaded only once into the address space of the current process. This means that the object only takes up space once; there is only one copy of its static data; and the static data are initialized only once, when the initial load takes place.

When a shared object is brought into the address space of a process, it may contain references to symbols whose addresses are not known until the object is loaded. These references must be relocated before the symbols can be accessed. The *mode* parameter governs when these relocations take place and may have the following values:

<code>RTLD_LAZY</code>	Under this <i>mode</i> , only references to data symbols are relocated when the object is loaded. References to functions are not relocated until a given function is referenced for the first time by the executing program. This <i>mode</i> should result in better performance, since a process may not reference all of the functions in any given shared object.
<code>RTLD_NOW</code>	Under this <i>mode</i> , all necessary relocations are performed when the object is first loaded. This may result in some wasted effort, if relocations are performed for functions that are never referenced, but is useful for applications that need to know as soon as an object is loaded that all symbols referenced during execution will be available.

The *mode* parameter only takes effect when an object is initially loaded. If `RTLD_LAZY` is specified in the first `dlopen` for an object, and `RTLD_NOW` is specified for the second `dlopen` of the same object, the second `dlopen` will not cause any relocations to be performed.

The *mode* parameter is required, and always overrides the value of the `LD_BIND_NOW` environment variable.

When the system loads an object for the first time, the object's initialization function is executed. The initialization function for each object is specified by the `DT_INIT` entry in that object's

.dynamic section. If multiple objects are loaded as a result of `dlopen`, the order initialization functions are called is unspecified.

Objects loaded by a single invocation of `dlopen` may import symbols from one another or from any object loaded automatically with `a.out` during program startup, but objects loaded by one `dlopen` invocation may not directly reference symbols from objects loaded by a different `dlopen` invocation. Those symbols may, however, be referenced indirectly using `dlsym`.

Rationale

The functions `dlopen` and `dlclose` may not work in a manner consistent with the way the functions `open` and `close` work. For example, if the same file is opened twice, the `open` function will return unique file descriptors for each `open` operation. Using `dlopen` to open the same file multiple times may return the same file handle every time. The result is that if the first file handle for a `dlopen` call is used more than once as a parameter to `dlclose`, there may be unexpected side effects.

DIAGNOSTICS

If the file specified by *pathname* cannot be found, cannot be opened for reading, is not a shared object, or if an error occurs during the process of loading the file specified by *pathname* or relocating its symbolic references, `dlopen` will return `NULL`. More detailed diagnostic information will be available through `dlerror`.

NOTES

The same object referenced by different path names may be loaded multiple times. For example, given the object `/usr/home/me/mylibs/mylib.so`, and assuming the current working directory is `/usr/home/me/workdir`,

```
...
void *handle1;
void *handle2;

handle1 = dlopen("../mylibs/mylib.so", RTLD_LAZY);
handle2 = dlopen("/usr/home/me/mylibs/mylib.so", RTLD_LAZY);
...
```

results in `mylibs.so` being loaded twice for the current process. On the other hand, given the same object and current working directory, if `LD_LIBRARY_PATH=/usr/home/me/mylibs`, then

```
...
void *handle1;
void *handle2;

handle1 = dlopen("mylib.so", RTLD_LAZY);
handle2 = dlopen("/usr/home/me/mylibs/mylib.so", RTLD_LAZY);
...
```

results in `mylibs.so` being loaded only once.

Users who wish to gain access to the symbol table of the `a.out` itself using `dlopen(0, mode)` should be aware that some symbols defined in the `a.out` may not be available to the dynamic linker. The symbol table created by `ld` for use by the dynamic linker might contain only a subset of the symbols originally defined in the `a.out`: specifically, those referenced by the shared objects with which the `a.out` is linked.

NAME

`dlsym` - get the address of a symbol in a shared object

SYNOPSIS

```
#include <dlfcn.h>

void *dlsym(void *handle, char *name);
```

DESCRIPTION

The function `dlsym` allows a process to obtain the address of a symbol defined within a shared object previously opened by `dlopen`.

handle is a value returned by a call to `dlopen`; the corresponding shared object must not have been disassociated from the executing process using `dlclose`. *name* is the symbol's name as a character string.

`dlsym` searches for the named symbol in the shared object designated by *handle* and in all shared objects loaded automatically as a result of loading the object referenced by *handle* [see `dlopen(3X)`].

EXAMPLES

The following example shows how one can use `dlopen` and `dlsym` to access either function or data objects. For simplicity, error checking has been omitted.

```
void *handle;
int i, *iptr;
int (*fptr)(int);
/* open the needed object */
handle = dlopen("/usr/mydir/libx.so", RTLD_LAZY);
/* find address of function and data objects */
fptr = (int (*)(int))dlsym(handle, "some_function");
iptr = (int *)dlsym(handle, "int_object");
/* invoke function, passing value of integer as a parameter */
i = (*fptr)(*iptr);
```

DIAGNOSTICS

If *handle* does not refer to a valid object opened by `dlopen`, or if the named symbol cannot be found within any of the objects associated with *handle*, `dlsym` will return `NULL`. More detailed diagnostic information will be available through `dlerror`.

Large File Support

Overview

The operating system service routines specified in this section provide access to large files, large file systems, and associated resources. Their semantics are the same as the corresponding routines without the `lf_` prefixes, except as noted below. All of the `lf_` interfaces reside in the `liblf` library `/usr/lib/liblf.so.1` regardless of whether the corresponding small-file interfaces reside in `libsys` or `libc`. None has a synonym (identical interface with '_' prefix.) Since this is a new interface set, it is included in the SCD as an EXPERIMENTAL INTERFACE. Table 6-11 lists the new routines provided in this interface set. Figures 6-7 through 6-11 list the new data structures and manifest constants required to support this interface set.

Table 6-11. liblf Contents

lf_fcntl
lf_fpathconf
lf_fseek
lf_fstat
lf_fstatvfs
lf_ftell
lf_getrlimit
lf_lseek
lf_lstat
lf_mmap
lf_pathconf
lf_setrlimit
lf_stat
lf_statvfs
lf_tell

Figure 6-7. Data Types Defined in <sys/fcntl.h>

```
typedef struct lf_flock {
    short      l_type;
    short      l_whence;
    int        l_pad_1;
    lf_off_t   l_start;
    lf_off_t   l_len;
    long       l_sysid;
    pid_t      l_pid;
    long       pad[4];
} lf_flock_t;
```

Figure 6-8. Data Types Defined in <sys/stat.h>

```
typedef struct lf_stat {
    dev_t      st_dev;
    long       st_pad1[3];
    ino_t      st_ino;
    mode_t     st_mode;
    nlink_t    st_nlink;
    uid_t      st_uid;
    gid_t      st_gid;
    dev_t      st_rdev;
    long       st_pad2[2];
    lf_off_t   st_size;
    long       st_pad3;
    time_t     st_atim;
    time_t     st_mtim;
    time_t     st_ctim;
    long       st_blksize;
    int64_t    st_blocks;
    char       st_fstype[_ST_FSTYPSZ];
    long       st_pad4[8];
} lf_stat_t;
```

Figure 6-9. Data Types Defined in <sys/statvfs.h>

```
typedef struct lf_statvfs {
    unsigned long    f_bsize;
    unsigned long    f_frsize;
    uint64_t         f_blocks;
    uint64_t         f_bfree;
    uint64_t         f_bavail;
    unsigned long    f_files;
    unsigned long    f_ffree;
    unsigned long    f_favail;
    unsigned long    f_fsid;
    char             f_basetype[FSTYPESZ];
    unsigned long    f_flag;
    unsigned long    f_namemax;
    char             f_fstr[32];
    unsigned long    f_filler[16];
} lf_statvfs_t;
```

Figure 6-10. Data Types Defined in <sys/statvfs.h>

```
struct lf_rlimit {  
    lf_rlim_t    rlim_cur;  
    lf_rlim_t    rlim_max;  
}
```

Figure 6-11. Manifest Constants Defined in <unistd.h>

```
#define _PC_MAX_FILE_SIZE      10
```

Synopsis

```

#include <fcntl.h>
int lf_fcntl (int fildes, int cmd, ... /* arg */);
int64_t lf_fpathconf (int fildes, int name);
int lf_fseek(FILE *stream, lf_off_t offset, int ptrname);

#include <sys/stat.h>
int lf_fstat (int fildes, struct lf_stat *buf);

#include <sys/fstatvfs.h>
int lf_fstatvfs (int fildes, struct lf_statvfs *buf);

#include <sys/types.h>
lf_off_t lf_ftell(FILE *stream);

#include <sys/time.h>
#include <sys/resource.h>
int lf_getrlimit (int resource, struct lf_rlimit *rlp);
lf_off_t lf_lseek (int fildes, lf_off_t offset, int whence);

#include <sys/stat.h>
int lf_lstat (const char *path, struct lf_stat *buf);

#include <sys/mman.h>
caddr_t lf_mmap (caddr_t addr, size_t len, int prot, int flags, int fd,
    lf_off_t off);

#include <sys/types.h>
int64_t lf_pathconf (char *path, int name);

#include <sys/time.h>
#include <sys/resource.h>
int lf_setrlimit (int resource, struct lf_rlimit *rlp);

#include <sys/stat.h>
int lf_stat (const char *path, struct lf_stat *buf);

#include <sys/statvfs.h>
int lf_statvfs (const char *path, struct lf_statvfs *buf);

#include <sys/types.h>
lf_off_t tell(char *path);

```

Description

Two new data types, `int64_t` and `uint64_t` are needed to define 64-bit signed and unsigned values. They must be defined by compliant systems in `<sys/types.h>`. `<sys/types.h>` must also contain

```
typedef int64_t lf_off_t;
```

The layout of 64-bit integers and how they are passed as parameters are specified in Table 3-1 of the *SPARC Architecture Manual, Version 8*.

lf_fcntl

The `F_SETLK`, `F_SETLKW`, `F_RSETLK`, and `F_RSETLKW` subcommands can lock a segment containing a byte at an offset greater than `INT_MAX`. The `F_FREESP` command can set the file size to values over `INT_MAX`. The `F_GETLK`, `F_GETLKW`, and `F_FREESP` subcommands set `errno` to `E_OVERFLOW` if the filesystem protocol cannot satisfy the request due to an interface restriction, such as if the file is being accessed through a remote file system not supporting 64-bit file offsets.

lf_fpathconf and lf_pathconf

In addition to the `_PC_*` commands defined in `<unistd.h>` for `fpathconf` and `pathconf`, `lf_fpathconf` and `lf_pathconf` also recognize the `_PC_MAX_FILE_SIZE` command. When passed `_PC_MAX_FILE_SIZE`, `lf_pathconf` and `lf_pathconf` will return the largest file size supported on the given file system, without regard to disk space currently available. The value of `_PC_MAX_FILE_SIZE` must be defined in `<unistd.h>` to be 10.

lf_fstat, lf_lstat, and lf_stat

`lf_fstat`, `lf_lstat`, and `lf_stat` set `errno` to `E_OVERFLOW` if the filesystem protocol cannot satisfy the request due to an interface restriction, such as if the file is being accessed through a remote file system not supporting 64-bit file offsets.

lf_fstatvfs and lf_statvfs

`lf_fstatvfs` and `lf_statvfs` set `errno` to `E_OVERFLOW` if the filesystem protocol cannot satisfy the request due to an interface restriction, such as if the file is being accessed through a remote file system not supporting 64-bit file offsets.

lf_getrlimit and lf_setrlimit

`lf_getrlimit` and `lf_setrlimit` never set `errno` to `E_OVERFLOW`, such as if the file is being accessed through a remote file system not supporting 64-bit file offsets.

Diagnostics

When `lseek()` attempts to position or query the file pointer beyond the point addressable in 31 bits, it will fail with `errno` set to `E_OVERFLOW`.

When `stat()`, `fstat()`, or `lstat()` is invoked on a file whose size cannot be represented in 31 bits, it will fail with `errno` set to `E_OVERFLOW`.

See Also

`fcntl(BA_OS)`, `fpathconf(BA_OS)`, `getrlimit(BA_OS)`, `lseek(BA_OS)`, `mmap(KE_OS)`, `stat(BA_OS)`, `statvfs(BA_OS)`, `limits(BA_ENV)`.

Miscellaneous ABI Changes

The following are changes to the *System V ABI*, the *System V ABI SPARC Processor Supplement*, and the *System V Interface Definition* as reported to SPARC International.

#	Facility	Location	Description
	Shared Library Names	gABI	<p>Addition - A second paragraph should be inserted to this section that states: "The version numbers of shared objects are set on a per-processor basis with the constraint that they are derived from a Generic ABI 'reference version number' for each interface and must change their current value whenever that reference version number changes. In this manner, the reference names can reflect the often combined generic and processor specific portions of the interface in a consistent manner." A shared object version number must change whenever one or more of the following occurs:</p> <ul style="list-style-type: none"> • an entry point is deleted, • an entry point is added, • an entry point is changed, • program visible semantic properties change, or • changes to exported data objects change in size, type, or name."
	Shared Library Names	psABI	<p>Addition - A section should be inserted that identifies the actual version numbers and reference names for shared objects on a SPARC system. These numbers should be the same as those in the gABI except the version numbers of the <code>libc</code> and <code>libX11</code> shared</p>

Table 6-1: Library Logical and Reference Names

Library	Reference Name
libc	/usr/lib/libc.so.1
libdl	/usr/lib/libdl.so.1
libnsl	/usr/lib/libnsl.so.1
libsocket	/usr/lib/libsocket.so.1
libsys	/usr/lib/ld.so.1
libX	/usr/lib/libX11.so.5 /usr/lib/libX11.so.4 (deprecated)
libXext	/usr/lib/lib/Xext.so.0
libXt	/usr/lib/libXt.so.5 /usr/lib/libXt.so.4 (deprecated)
libXol	/usr/lib/libXol.so.3
libXm	/usr/lib/libXm.so.1.2
libXrm	/usr/lib/lib/libXrm.so.1.2

Miscellaneous ABI Changes (continued)

#	Facility	Location	Description
			objects are 1 and 5, respectively. The omission of a version number for the <code>libs1</code> shared object in the original text of the gABI should also be corrected here with a version number of "1".
	Shared Library Names	gABI	Deletion - Delete Table 6-1 on page 6-2.
	Dependencies Among Libraries	gABI	Change - On page 6-2, at the statement which begins "Application executable and shared object files ..." replace to the end of the paragraph with "Application executables must provide a complete list of those shared objects which the application uses directly. Each system library must supply a complete dependency graph for its own execution as <code>DT_NEEDED</code> entries. Rationale: No application should be required to know what secondary dependencies any platform system library may have. Such dependencies may vary from system to system.
	<sys/mman.h>	psABI	<p>Addition - Figure 6-17 on page 6-24 should include the constants:</p> <pre>#define SHARED 0x10 #define PRIVATE 0x20 #define MC_SYNC 1 #define MC_LOCK 2 #define MC_UNLOCK 3 #define MC_LOCKAS 5 #define MC_UNLOCKAS 6 #define PROC_TEXT 0x5 #define PROC_DATA 0x7 #define MCL_CURRENT 0x1 #define MCL_FUTURE 0x2</pre>
	<netconfig.h>	psABI	Delete the flag <code>NC_BROADCAST</code> from Figure 6-20
	<sys/resource.h>	psABI	<p>Addition - On page 6-31, Figure 6-27 should include the constant</p> <pre>#define RLIM_INFINITY 0x7fffffff</pre>
	<rpc.h>	psABI	Deletion - On page 6-34, the manifest constants beginning with "_" are not part of the ABI-visible interface and are not to be considered part of the ABI specification. Delete <code>RPC_ANYSOCK</code> .
	<signal.h>	psABI	Change - On page 6-44, the element of <code>struct sigaction</code> that is <code>sigdisp_t sa_disp</code> should be <code>void (*sa_handler)()</code> .
	<termios.h>	psABI	Change - On page 6-54, in Figure 6-41 the manifest constant <code>CDEL</code> should be changed to have the value <code>0177</code> . The old value, <code>0377</code> , conflicts with the use of the Latin 1 character 'ÿ'.

Miscellaneous ABI Changes (continued)

#	Facility	Location	Description
	<sys/types.h>	psABI	Addition - On page 6-65, in Figure 6-41, add the following type definitions: typedef unsigned int u_int; typedef unsigned long u_long; typedef unsigned short u_short; typedef char *caddr_t;

CHAPTER 7: Formats and Protocols

Formats and Protocols

Archive file formats, networking protocols, and the terminfo data base format may be found in Chapter 7 of the *System V Application Binary Interface*.

Formats and Protocols Changes

The following are changes to the *System V ABI*, the *System V ABI SPARC Processor Supplement*, and the *System V Interface Definition* as reported to SPARC International.

#	Facility	Location	Description
	rpcbind Operation	gABI	Change -The reference to IP in the first paragraph is ambiguous -- port 111 is used for IP-carried transports (rather than IP itself).

Interconnecting SCD Conforming Systems

Overview

This section contains the REQUIRED internetworking interfaces available to applications running on an SCD conforming system. Note that the networking ABI is defined by the TLI interfaces described in section BA_LIB of the *System V Interface Definition (Third Edition), Volume I*. This chapter adds to that definition by specifying that there shall be present in all SCD complying systems an Internet Protocol Suite (IPS) transport provider that is accessible through TLI. Also added are the commands, which exist in `/usr/bin`, and their associated daemons, which exist in `/usr/sbin`.

Transport Providers

All SPARC-compliant systems will provide a transport provider interface for each of the IP protocols, TCP, UDP, ICMP, and ARP. The device names for these transport provider interfaces must be `/dev/tcp`, `/dev/udp`, `/dev/icmp`, and `/dev/arp` respectively. Additionally, shared objects will be present to convert IP format universal addresses into the necessary internal format needed by the TLI interfaces. These interfaces are previously defined in the Network Services Library portion of this chapter.

Additional Interfaces

The interfaces listed below in Table 7-1 show the additional commands, protocols, and service daemons that are included to ensure interoperability between SCD conforming systems. The table includes four columns, the command name which is invoked, the RFC number for the protocol specification as maintained by the Internet Engineering Task Force, the name of the service daemon, and a short description of the feature provided.

Table 7-2 shows the “well-known” port numbers as derived from RFC 1340 that SCD conforming systems are REQUIRED to provide for supported services.

Table 7-1: Required Commands


Command	RFC	Description
rlogin	BSDNET	Remote terminal services (BSD)
rsh	BSDNET	Remote user shell (BSD)
rcp	BSDNET	Remote file copy (BSD)
rwho	BSDNET	Remote user information service (BSD)
rdate	BSDNET	Remote uptime statistics (BSD)
talk	BSDNET	Remote chat utility (BSD)
finger	rfc1288	Information server for logged on users
telnet	<many>	Interactive terminal services
ftp	rfc959	File transfer protocol
arp	rfc826	Address Resolution Protocol

Table 7-2: Well-Known Port Numbers

Keyword	Description	TCP Port Number	UDP Port Number
tcpmux	rfc1078	1	
echo	Echo	7	7
discard	Discard	9	9
systat	Active Users	11	11
daytime	Daytime	13	13
netstat	Who is up or NETSTAT	15	15
chargen	Character Generator	19	19
ftp-data	File Transfer Protocol (Data)	20	
ftp	File Transfer Protocol	21	
telnet	Terminal Connection	23	
smtp	Simple Mail Transport Protocol	25	
time	Time	37	37
name	Host Name Server	42	42
nickname	Who Is	43	43
domain	Domain Name Server	53	53
tftp	Trivial File Transfer	69	69
	Any private RJE service	77	77
finger	Finger	79	79
supdup	SUPDUP Protocol	95	
hostname	NIC Host Name Server	101	
iso-tsap	ISO-TSAP	102	
uucp-path	UUCP Path Service	117	
ntp	Network Time Protocol	123	123
X	X Window Service	6000+Display Number	



CHAPTER 8: System Commands



System Commands

Overview

This chapter contains the commands for application programs as listed in the *System V Application Binary Interface*, and described in the *System V Interface Definition, (Third Edition)*.

Table 8-1. Commands for Application Programs

awk	expr	passwd	test [*]
cat	false	pg	touch
cd [†]	find ²	pr ³	tr
chgrp	fmtmsg	priocntl	true
chmod	gettxt	pwd [*]	tty
chown	grep	rm	umask [†]
cmp	id	rmdir	uname
cp	kill	sed	uucp
cpio	line	sh ⁴	uulog
date	ln	sleep	uustat
dd	logname	sort	uux
df	lp	stty	vi
echo [*]	ls	su	wait [†]
ed	mkdir	tail	who ⁵
ex ¹	mv	tee	

* These commands marked are also built into the standard UNIX system shell, sh.

† These commands are only available as commands built-in to the UNIX system shell, sh.

System Commands Changes

The following are changes to the basic system commands (detailed in the *System V Application Binary Interface*), as reported to SPARC International.


#	Facility	Location	Description
1	ex(BU_CMD)	SVID, Vol. II	Change - The SVID states that the “edcompatible” option of <code>ex</code> causes the <code>g</code> suffix on substitute commands to be remembered, and toggled by repeating the suffix. Omitted from this description is the fact that this behavior is applicable only to the “&” form of substitute commands.
1	ex(BU_CMD)	SVID, Vol. II	Change - The “ <code>c</code> ” command should be defined as “Enters input mode; the input text replaces the specified lines. The last input line becomes the current line; if no lines are input the line before the deleted line(s) becomes the current line.”
1	ex(BU_CMD)	SVID, Vol. II	Change - The “ <code>m</code> ” command description must be changed to note that the current line becomes the last of the moved lines, rather than the first.
2	find(BU_CMD)	SVID, Vol. II	Change the descriptions of <code>-atime</code> , <code>-mtime</code> , and <code>-ctime</code> from “in <code>n</code> days” to “ <code>n</code> days ago.”
3	pr(BU_CMD)	SVID, Vol. II	Change - The SVID says that using <code>-m</code> with the <code>-column</code> option will cause the <code>-m</code> option to override the <code>-column</code> option. This does not match current practice; using these two options together will be treated as an error.
3	pr(BU_CMD)	SVID, Vol. II	Change - Comments about truncating lines in the text of the description and in the options are incorrect with respect to single column output: existing practice and P1003.2 is that truncation is not applied to single column output. The “note” in the description of the <code>-w</code> option is to be applicable to multi-column output only. In the description change the second paragraph to read: “By default, in multi-column mode, columns are”
4	sh(BU_CMD)	SVID, Vol. II	Changed - In the section marked “Input/Output” the description of “<<[-]word” states: “... \ must be used to quote the characters \, \$, ', and the first character of word” should be changed to read “... \ must be used to quote the characters \, \$, and '”. This matches both existing practice and P1003.2.

System Commands Changes (continued)

#	Facility	Location	Description
5	who(AU_CMD)	SVID, Vol. II	<p>Change the description of the <code>-T</code> and <code>-a</code> option to "The <code>-T</code> and <code>-a</code> options to who are unspecified and cannot be relied on to be portable."</p> <p><i>Rationale:</i></p> <p>On investigation, these options were found to differ on various SPARC implementations. The <code>-a</code> option is an aggregate option; rather than using this option, for SCD 2 portability an application should use the specific individual options to who that the application requires. Rather than using the <code>-T</code> option, an application should use either the <code>-s</code> or <code>-u</code> option for SCD 2 portability.</p>



CHAPTER 9: Execution Environment



Execution Environment

All information regarding File System Structure and Contents may be found in Chapter 9 of the *System V Application Binary Interface*.


Execution Environment Changes

The following are changes to the *System V ABI*, the *System V ABI SPARC Processor Supplement*, and the *System V Interface Definition* as reported to SPARC International.

#	Facility	Location	Description
	Root subtree - /dev	gABI	Addition - Change page 9-4 of the gABI to require eight (8) devices, rather than just two. The eight required devices are /dev/tty, /dev/null, /dev/console, /dev/zero, /dev/tcp, /dev/udp, /dev/icmp, and /dev/arp. The device /dev/zero is defined to be a special file which is a source of zeroed, unnamed memory. Reads from this device always return a buffer full of zeroes. The file is infinite in length. Writes to this file are always successful, but the data written is ignored. Mapping a zero special file creates a zero-initialized, unnamed memory object of a length equal to the length of the mapping rounded up to the nearest page size as returned by <code>sysconf</code> . Multiple processes can share such a zero special file object provided a common ancestor mapped the object <code>MAP_SHARED</code> .
	/opt	gABI	Delete the specification of /opt/bin .



CHAPTER 10: Windowing and Terminal Interfaces



The X Library

This chapter identifies binary interfaces for `libX`, which are defined in *The X Window System (Third Edition)* by Robert W. Scheifler and James Gettys (Digital Press, ISBN 1-55558-088-2).

Finally, all SCD 2.2 systems will support the mechanisms and conventions as specified in the *Inter-Client Communications Convention Manual (ICCCM)* in *The X Window System (Third Edition)* by Robert W. Scheifler and James Gettys (Digital Press, ISBN 1-55558-088-2).

The X Library Interfaces

The interfaces listed below in Table 10-1 have been included in SCD 2.2 because they are REQUIRED to be present on all compliant systems, in the dynamic library `/usr/lib/libX11.so.5`.

Table 10-2 contains the exported data which are also REQUIRED to be present in `/usr/lib/libX11.so.5`. The format of these entries is: `data[size]`.

Conformant systems are also REQUIRED to have `/usr/lib/libX11.so.4` in order to support SPARC applications written to conform to versions 2.0 and 2.1 of the *SPARC Compliance Definition*. Since the X Version 11, Release 5 specification is a proper superset of the X Version 11, Release 4 specification, system vendors can provide this support by simply making a link to `/usr/lib/libX11.so.5` for the file `/usr/lib/libX11.so.4` as part of the system installation process. If an application executable references `/usr/lib/libX11.so.4` and does not reference `/usr/lib/libX11.so.5`, the application may not use any functionality defined by X11R5 but not defined by X11R4. See the *SPARC Compliance Definition 2.1* for a list of X11R4 components. The file name, `/usr/lib/libX11.so.4`, is deprecated effective November 1st, 1993; this filename may go away as early as November 1st, 1996 so new applications should not rely on its existence.

Figures 10-1 through 10-7 detail the manifest constants and visible data structures associated with the X library.

Table 10-1. Contents of libX

XActivateScreenSaver	XcmsAddFunctionSet
XAddExtension	XcmsAllocColor
XAddHost	XcmsAllocNamedColor
XAddHosts	XcmsCCCOfColormap
XAddPixel	XcmsCIELabClipab
XAddToExtensionList	XcmsCIELabClipL
XAddToSaveSet	XcmsCIELabClipLab
XAllocClassHint	XcmsCIELabQueryMaxC
XAllocColor	XcmsCIELabQueryMaxL
XAllocColorCells	XcmsCIELabQueryMaxLC
XAllocColorPlanes	XcmsCIELabQueryMinL
XAllocIconSize	XcmsCIELabToCIEXYZ
XAllocNamedColor	XcmsCIELabWhiteShiftColors
XAllocSizeHints	XcmsCIELuvClipL
XAllocStandardColormap	XcmsCIELuvClipLuv
XAllocWMHints	XcmsCIELuvClipuv
XAllowEvents	XcmsCIELuvQueryMaxC
XAllPlanes	XcmsCIELuvQueryMaxL
XAutoRepeatOff	XcmsCIELuvQueryMaxLC
XAutoRepeatOn	XcmsCIELuvQueryMinL
XBaseFontNameListOfFontSet	XcmsCIELuvToCIEuvY
XBell	XcmsCIELuvWhiteShiftColors
XBitmapBitOrder	XcmsCIEuvYToCIELuv
XBitmapPad	XcmsCIEuvYToCIEXYZ
XBitmapUnit	XcmsCIEuvYToTekHVC
XBlackPixel	XcmsCIExyYToCIEXYZ
XBlackPixelOfScreen	XcmsCIEXYZToCIELab
XCellsOfScreen	XcmsCIEXYZToCIEuvY
XChangeActivePointerGrab	XcmsCIEXYZToCIExyY
XChangeGC	XcmsCIEXYZToRGBi
XChangeKeyboardControl	XcmsClientWhitePointOfCCC
XChangeKeyboardMapping	XcmsConvertColors
XChangePointerControl	XcmsCreateCCC
XChangeProperty	XcmsDefaultCCC
XChangeSaveSet	XcmsDisplayOfCCC
XChangeWindowAttributes	XcmsFormatOfPrefix
XCheckIfEvent	XcmsFreeCCC
XCheckMaskEvent	XcmsLookupColor
XCheckTypedEvent	XcmsPrefixOfFormat
XCheckTypedWindowEvent	XcmsQueryBlack
XCheckWindowEvent	XcmsQueryBlue
XCirculateSubwindows	XcmsQueryColor
XCirculateSubwindowsDown	XcmsQueryColors
XCirculateSubwindowsUp	XcmsQueryGreen
XClearArea	XcmsQueryRed
XClearWindow	XcmsQueryWhite
XClipBox	XcmsRGBiToCIEXYZ
XCloseDisplay	XcmsRGBiToRGB
XCloseIM	XcmsRGBToRGBi
XcmsAddColorSpace	XcmsScreenNumberOfCCC

XcmsScreenWhitePointOfCCC	XDeleteProperty
XcmsSetCompressionProc	XDestroyIC
XcmsSetWhiteAdjustProc	XDestroyImage
XcmsSetWhitePoint	XDestroyRegion
XcmsStoreColor	XDestroySubwindows
XcmsStoreColors	XDestroyWindow
XcmsTekHVCClipC	XDisableAccessControl
XcmsTekHVCClipV	XDisplayCells
XcmsTekHVCClipVC	XDisplayHeight
XcmsTekHVCQueryMaxC	XDisplayHeightMM
XcmsTekHVCQueryMaxV	XDisplayKeycodes
XcmsTekHVCQueryMaxVC	XDisplayMotionBufferSize
XcmsTekHVCQueryMaxVSamples	XDisplayName
XcmsTekHVCQueryMinV	XDisplayOfIM
XcmsTekHVCToCIEuvY	XDisplayOfScreen
XcmsTekHVCWhiteShiftColors	XDisplayPlanes
XcmsVisualOfCCC	XDisplayString
XConfigureWindow	XDisplayWidth
XConnectionNumber	XDisplayWidthMM
XContextDependentDrawing	XDoesBackingStore
XConvertSelection	XDoesSaveUnders
XCopArea	XDrawArc
XCopColormapAndFree	XDrawArcs
XCopGC	XDrawImageString
XCopPlane	XDrawImageStringl6
XCreateBitmapFromData	XDrawLine
XCreateColormap	XDrawLines
XCreateFontCursor	XDrawPoint
XCreateFontSet	XDrawPoints
XCreateGC	XDrawRectangle
XCreateGlyphCursor	XDrawRectangles
XCreateIC	XDrawSegments
XCreateImage	XDrawString
XCreatePixmap	XDrawStringl6
XCreatePixmapCursor	XDrawText
XCreatePixmapFromBitmapData	XDrawTextl6
XCreateRegion	XEHeadOfExtensionList
XCreateSimpleWindow	XEmptyRegion
XCreateWindow	XEnableAccessControl
XDefaultColormap	XEqualRegion
XDefaultColormapOfScreen	XESetCloseDisplay
XDefaultDepth	XESetCopyGC
XDefaultDepthOfScreen	XESetCreateFont
XDefaultGC	XESetCreateGC
XDefaultGCOfScreen	XESetError
XDefaultRootWindow	XESetErrorString
XDefaultScreen	XESetEventToWire
XDefaultScreenOfDisplay	XESetFlushGC
XDefaultString	XESetFreeFont
XDefaultVisual	XESetFreeGC
XDefaultVisualOfScreen	XESetPrintErrorValues
XDefineCursor	XESetWireToError
XDeleteContext	XESetWireToEvent
XDeleteModifiermapEntry	XEventMaskOfScreen

XEventsQueued	XGetPixel
XExtentsOfFontSet	XGetPointerControl
XFetchBuffer	XGetPointerMapping
XFetchBytes	XGetRGBColormaps
XFetchName	XGetScreenSaver
XFillArc	XGetSelectionOwner
XFillArcs	XGetSizeHints
XFillPolygon	XGetStandardColormap
XFillRectangle	XGetSubImage
XFillRectangles	XGetTextProperty
XFilterEvent	XGetTransientForHint
XFindContext	XGetVisualInfo
XFindOnExtensionList	XGetWindowAttributes
XFlush	XGetWindowProperty
XFlushGC	XGetWMClientMachine
XFontsOfFontSet	XGetWMColormapWindows
XForceScreenSaver	XGetWMHints
XFree	XGetWMIconName
XFreeColormap	XGetWMName
XFreeColors	XGetWMNormalHints
XFreeCursor	XGetWMProtocols
XFreeExtensionList	XGetWMSizeHints
XFreeFont	XGrabButton
XFreeFontInfo	XGrabKey
XFreeFontNames	XGrabKeyboard
XFreeFontPath	XGrabPointer
XFreeFontSet	XGrabServer
XFreeGC	XHeightMMOfScreen
XFreeModifiermap	XHeightOfScreen
XFreePixmap	XIconifyWindow
XFreeStringList	XIfEvent
XGContextFromGC	XImageByteOrder
XGeometry	XIMOfIC
XGetAtomName	XInitExtension
XGetClassHint	XInsertModifiermapEntry
XGetCommand	XInstallColormap
XGetDefault	XInternAtom
XGetErrorDatabaseText	XIntersectRegion
XGetErrorText	XKeycodeToKeysym
XGetFontPath	XKeysymToKeycode
XGetFontProperty	XKeysymToString
XGetGCValues	XKillClient
XGetGeometry	XLastKnownRequestProcessed
XGetIconName	XListDepths
XGetIconSizes	XListExtensions
XGetICValues	XListFonts
XGetImage	XListFontsWithInfo
XGetIMValues	XListHosts
XGetInputFocus	XListInstalledColormaps
XGetKeyboardControl	XListPixmapFormats
XGetKeyboardMapping	XListProperties
XGetModifierMapping	XLoadFont
XGetMotionEvents	XLoadQueryFont
XGetNormalHints	XLocaleOfFontSet

XLocaleOfIM	XQueryExtension
XLookupColor	XQueryFont
XLookupKeysym	XQueryKeymap
XLookupString	XQueryPointer
XLowerWindow	XQueryTextExtents
XMapRaised	XQueryTextExtents16
XMapSubwindows	XQueryTree
XMapWindow	XRaiseWindow
XMaskEvent	XReadBitmapFile
XMatchVisualInfo	XRebindKeysym
XMaxCmapsOfScreen	XRecolorCursor
XMaxRequestSize	XReconfigureWMWindow
XmbDrawImageString	XRectInRegion
XmbDrawString	XRefreshKeyboardMapping
XmbDrawText	XRemoveFromSaveSet
XmbLookupString	XRemoveHost
XmbResetIC	XRemoveHosts
XmbSetWMPProperties	XReparentWindow
XmbTextEscapement	XResetScreenSaver
XmbTextExtents	XResizeWindow
XmbTextListToTextProperty	XResourceManagerString
XmbTextPerCharExtents	XRestackWindows
XmbTextPropertyToTextList	XrmCombineDatabase
XMinCmapsOfScreen	XrmCombineFileDatabase
XMoveResizeWindow	XrmDestroyDatabase
XMoveWindow	XrmEnumerateDatabase
XNewModifiermap	XrmGetDatabase
XNextEvent	XrmGetFileDatabase
XNextRequest	XrmGetResource
XNoOp	XrmGetStringDatabase
XOffsetRegion	XrmInitialize
XOpenDisplay	XrmLocaleOfDatabase
XOpenIM	XrmMergeDatabases
XParseColor	XrmParseCommand
XParseGeometry	XrmPermStringToQuark
XPeekEvent	XrmPutFileDatabase
XPeekIfEvent	XrmPutLineResource
XPending	XrmPutResource
Xpermalloc	XrmPutStringResource
XPlanesOfScreen	XrmQGetResource
XPointInRegion	XrmQGetSearchList
XPolygonRegion	XrmQGetSearchResource
XProtocolRevision	XrmQPutResource
XProtocolVersion	XrmQPutStringResource
XPutBackEvent	XrmQuarkToString
XPutImage	XrmSetDatabase
XPutPixel	XrmStringToBindingQuarkList
XQLength	XrmStringToQuark
XQueryBestCursor	XrmStringToQuarkList
XQueryBestSize	XrmUniqueQuark
XQueryBestStipple	XRootWindow
XQueryBestTile	XRootWindowOfScreen
XQueryColor	XRotateBuffers
XQueryColors	XRotateWindowProperties

XSaveContext	XSetWindowBackgroundPixmap
XScreenCount	XSetWindowBorder
XScreenNumberOfScreen	XSetWindowBorderPixmap
XScreenOfDisplay	XSetWindowBorderWidth
XScreenResourceString	XSetWindowColormap
XSelectInput	XSetWMClientMachine
XSendEvent	XSetWMColormapWindows
XServerVendor	XSetWMHints
XSetAccessControl	XSetWMIconName
XSetAfterFunction	XSetWMName
XSetArcMode	XSetWMNormalHints
XSetBackground	XSetWMProperties
XSetClassHint	XSetWMProtocols
XSetClipMask	XSetWMSizeHints
XSetClipOrigin	XShrinkRegion
XSetClipRectangles	XStoreBuffer
XSetCloseDownMode	XStoreBytes
XSetCommand	XStoreColor
XSetDashes	XStoreColors
XSetErrorHandler	XStoreName
XSetFillRule	XStoreNamedColor
XSetFillStyle	XStringListToTextProperty
XSetFont	XStringToKeysym
XSetFontPath	XSubImage
XSetForeground	XSubtractRegion
XSetFunction	XSupportsLocale
XSetGraphicsExposures	XSync
XSetICFocus	XSynchronize
XSetIconName	XTextExtents
XSetIconSizes	XTextExtents16
XSetICValues	XTextPropertyToStringList
XSetInputFocus	XTextWidth
XSetIOErrorHandler	XTextWidth16
XSetLineAttributes	XTranslateCoordinates
XSetLocaleModifiers	XUndefineCursor
XSetModifierMapping	XUngrabButton
XSetNormalHints	XUngrabKey
XSetPlaneMask	XUngrabKeyboard
XSetPointerMapping	XUngrabPointer
XSetRegion	XUngrabServer
XSetRGBColormaps	XUninstallColormap
XSetScreenSaver	XUnionRectWithRegion
XSetSelectionOwner	XUnionRegion
XSetSizeHints	XUnloadFont
XSetStandardColormap	XUnmapSubwindows
XSetStandardProperties	XUnmapWindow
XSetState	XUnsetICFocus
XSetStipple	XVaCreateNestedList
XSetSubwindowMode	XVendorRelease
XSetTextProperty	XVisualIDFromVisual
XSetTitle	XWarpPointer
XSetTransientForHint	XwcDrawImageString
XSetTSTOrigin	XwcDrawString
XSetWindowBackground	XwcDrawText

XwcFreeStringList
XwcLookupString
XwcResetIC
XwcTextEscapement
XwcTextExtents
XwcTextListToTextProperty
XwcTextPerCharExtents
XwcTextPropertyToTextList
XWhitePixel
XWhitePixelOfScreen
XWidthMMOfScreen
XWidthOfScreen
XWindowEvent
XWithdrawWindow
XWMGeometry
XWriteBitmapFile
XXorRegion

Table 10-2. Exported Data for libX.

```

XcmsCIELabColorSpace[ 0x18 ]
XcmsCIELuvColorSpace[ 0x18 ]
XcmsCIEuvYColorSpace[ 0x18 ]
XcmsCIExyYColorSpace[ 0x18 ]
XcmsCIEXYZColorSpace[ 0x18 ]
XcmsLinearRGBFunctionSet[ ? ]
XcmsRGBColorSpace[ 0x18 ]
XcmsRGBiColorSpace[ 0x18 ]
XcmsTekHVCColorSpace[ 0x18 ]
XcmsUNDEFINEDColorSpace[ 0x18 ]
_Xdebug[ 0x4 ]

```

Unsafe Macros

Ordinarily, this document only specifies the system resources available for use by applications on all SPARC compliant systems and makes no comment regarding the programming language or API used by application programmers for building applications. But SPARC International recognizes that many SPARC applications will be written in the C programming language and are likely to use the API specified by the X Consortium. Some of the data structures defined as part of the X ABI, such as `struct Display`, `struct Screen`, and `struct XImage`, are intended to be opaque to the application; that is, the application isn't supposed to contain any knowledge of the size or layout of the data structures.

Some of the macros defined by the X Consortium as part of the X API violate this assumption for opaque data. Below is a table of macros from the X API which are considered by SPARC International to be unsafe; that is, they cause knowledge about the size and/or layout of opaque data structures to be embedded in applications. Embedding this information in an application may prevent the application from being binary compatible with future versions of X which use a different size or layout for these opaque data structures.

Fortunately, each of the unsafe macros has a counterpart in the X library. Table 10-3 below lists each of the unsafe macros and its safe function counterpart from the X library.

Table 10-3: ABI Unsafe Macros

Unsafe Macro	Equivalent X Function
<code>BitmapPad</code>	<code>XBitmapPad</code>
<code>BitmapUnit</code>	<code>XBitmapUnit</code>
<code>BlackPixel</code>	<code>XBlackPixel</code>
<code>BlackPixelOfScreen</code>	<code>XBlackPixelOfScreen</code>
<code>CellsOfScreen</code>	<code>XCellsOfScreen</code>
<code>ClientWhitePointOfCCC</code>	<code>XClientWhitePointOfCCC</code>
<code>ConnectionNumber</code>	<code>XConnectionNumber</code>
<code>DefaultColormap</code>	<code>XDefaultColormap</code>
<code>DefaultColormapOfScreen</code>	<code>XDefaultColormapOfScreen</code>
<code>DefaultDepth</code>	<code>XDefaultDepth</code>
<code>DefaultDepthOfScreen</code>	<code>XDefaultDepthOfScreen</code>
<code>DefaultGC</code>	<code>XDefaultGC</code>
<code>DefaultGCOfScreen</code>	<code>XDefaultGCOfScreen</code>
<code>DefaultRootWindow</code>	<code>XDefaultRootWindow</code>
<code>DefaultScreen</code>	<code>XDefaultScreen</code>
<code>DefaultScreenOfDisplay</code>	<code>XDefaultScreenOfDisplay</code>
<code>DefaultVisual</code>	<code>XDefaultVisual</code>
<code>DefaultVisualOfScreen</code>	<code>XDefaultVisualOfScreen</code>
<code>DisplayCells</code>	<code>XDisplayCells</code>

Table 10-3: ABI Unsafe Macros

Unsafe Macro	Equivalent X Function
DisplayHeight	XDisplayHeight
DisplayHeightMM	XDisplayHeightMM
DisplayOfCCC	XDisplayOfCCC
DisplayOfScreen	XDisplayOfScreen
DisplayPlanes	XDisplayPlanes
DisplayString	XDisplayString
DisplayWidth	XDisplayWidth
DisplayWidthMM	XDisplayWidthMM
DoesBackingStore	XDoesBackingStore
DoesSaveUnders	XDoesSaveUnders
EventMaskOfScreen	XEventMaskOfScreen
HeightMMOfScreen	XHeightMMOfScreen
HeightOfScreen	XHeightOfScreen
ImageByteOrder	XImageByteOrder
LastKnownRequestProcessed	XLastKnownRequestProcessed
MaxCmapsOfScreen	XMaxCmapsOfScreen
MinCmapsOfScreen	XMinCmapsOfScreen
NextRequest	XNextRequest
PlanesOfScreen	XPlanesOfScreen
ProtocolRevision	XProtocolRevision
ProtocolVersion	XProtocolVersion
QLength	XQLength
RootWindow	XRootWindow
RootWindowOfScreen	XRootWindowOfScreen
ScreenCount	XScreenCount
ScreenNumberOfCCC	XScreenNumberOfCCC
ScreenOfDisplay	XScreenOfDisplay
ScreenWhiteOfCCC	XScreenWhiteOfCCC
ServerVendor	XServerVendor
VendorRelease	XVendorRelease

Table 10-3: ABI Unsafe Macros

Unsafe Macro	Equivalent X Function
VisualOfCCC	XVisualOfCCC
WhitePixel	XWhitePixel
WhitePixelOfScreen	XWhitePixelOfScreen
WidthMMOfScreen	XWidthMMOfScreen
WidthOfScreen	XWidthOfScreen

Following, are the definitions of manifest constants and data types needed by applications to interface to the Xlib functions listed in Table 10-1.

Though the SPARC Compliance Definition specifies an Application Binary Interface (ABI) rather than an Application Program Interface (API) the manifest constants and data type definitions are broken up into different tables based on which header files a programmer would ordinarily expect to find the definitions for two reasons:

- it makes the document more informative for the programmer who is trying to meet the standard, and
- it is expected that this will make the document easier to edit and review.

The header files these definitions are taken from are

- `<X11/Xlib.h>`,
- `<X11/X.h>`,
- `<X11/Xatom.h>`,
- `<X11/Xresource.h>`,
- `<X11/Xutil.h>`,
- `<X11/Xcms.h>`,
- `<X11/keysymdef.h>`, and
- `<X11/cursorfont.h>`.

All header definitions are based on X, version 11, release 5 from the MIT X Consortium.

Figure 10-1. Manifest Constants and Data Types from <X11/Xlib.h>

```
typedef char *XPointer;

#define Bool int
#define Status int
#define True 1
#define False 0

#define QueuedAlready 0
#define QueuedAfterReading 1
#define QueuedAfterFlush 2

#define AllPlanes          ((unsigned long)~0L)

/*
 * Extensions need a way to hang private data on some structures.
 */
typedef struct _XExtData {
    int number; /* number returned by XRegisterExtension */
    struct _XExtData *next; /* next item on list of data for structure */
    int (*free_private)(); /* called to free private storage */
    XPointer private_data; /* data private to this extension. */
} XExtData;

/*
 * This file contains structures used by the extension mechanism.
 */
typedef struct {
    int extension; /* public to extension, cannot be changed */
    int extension_number; /* extension number */
    int major_opcode; /* major op-code assigned by server */
    int first_event; /* first event number for the extension */
    int first_error; /* first error number for the extension */
} XExtCodes;

/*
 * Data structure for retrieving info about pixmap formats.
 */
typedef struct {
    int depth;
    int bits_per_pixel;
    int scanline_pad;
} XPixmapFormatValues;

/*
 * Data structure for setting graphics context.
 */
typedef struct {
    int function; /* logical operation */
    unsigned long plane_mask; /* plane mask */
    unsigned long foreground; /* foreground pixel */
    unsigned long background; /* background pixel */
}
```

```

    int line_width;          /* line width */
    int line_style;          /* LineSolid, LineOnOffDash, LineDoubleDash */
    int cap_style;           /* CapNotLast, CapButt,
                             CapRound, CapProjecting */
    int join_style;          /* JoinMiter, JoinRound, JoinBevel */
    int fill_style;          /* FillSolid, FillTiled,
                             FillStippled, FillOpaeueStippled */
    int fill_rule;           /* EvenOddRule, WindingRule */
    int arc_mode;            /* ArcChord, ArcPieSlice */
    Pixmap tile;             /* tile pixmap for tiling operations */
    Pixmap stipple;          /* stipple 1 plane pixmap for stippling */
    int ts_x_origin;         /* offset for tile or stipple operations */
    int ts_y_origin;
    Font font;               /* default text font for text operations */
    int subwindow_mode;      /* ClipByChildren, IncludeInferiors */
    Bool graphics_exposures; /* boolean, should exposures be generated */
    int clip_x_origin;       /* origin for clipping */
    int clip_y_origin;
    Pixmap clip_mask;        /* bitmap clipping; other calls for rects */
    int dash_offset;         /* patterned/dashed line information */
    char dashes;
} XGCValues;

/*
 * Graphics context. The contents of this structure are implementation
 * dependent. A GC should be treated as opaque by application code.
 */

typedef struct _XGC *GC;

/*
 * Visual structure; contains information about colormapping possible.
 */
typedef struct Visual;

/*
 * Depth structure; contains information for each possible depth.
 */
typedef struct Depth;

/*
 * Information about the screen. The contents of this structure are
 * implementation dependent. A Screen should be treated as opaque
 * by application code.
 */
typedef struct _Screen Screen;

/*
 * Format structure; describes ZFormat data the screen will understand.
 */
typedef struct ScreenFormat;

/*
 * Data structure for setting window attributes.

```

```

*/
typedef struct {
    Pixmap background_pixmap; /* background or None or ParentRelative */
    unsigned long background_pixel; /* background pixel */
    Pixmap border_pixmap; /* border of the window */
    unsigned long border_pixel; /* border pixel value */
    int bit_gravity; /* one of bit gravity values */
    int win_gravity; /* one of the window gravity values */
    int backing_store; /* NotUseful, WhenMapped, Always */
    unsigned long backing_planes; /* planes to be preseved if possible */
    unsigned long backing_pixel; /* value to use in restoring planes */
    Bool save_under; /* should bits under be saved? (popups) */
    long event_mask; /* set of events that should be saved */
    long do_not_propagate_mask; /* set of events that should not propagate */
    Bool override_redirect; /* boolean value for override-redirect */
    Colormap colormap; /* color map to be associated with window */
    Cursor cursor; /* cursor to be displayed (or None) */
} XSetWindowAttributes;

typedef struct {
    int x, y; /* location of window */
    int width, height; /* width and height of window */
    int border_width; /* border width of window */
    int depth; /* depth of window */
    Visual *visual; /* the associated visual structure */
    Window root; /* root of screen containing window */
    int class; /* InputOutput, InputOnly */
    int bit_gravity; /* one of bit gravity values */
    int win_gravity; /* one of the window gravity values */
    int backing_store; /* NotUseful, WhenMapped, Always */
    unsigned long backing_planes; /* planes to be preserved if possible */
    unsigned long backing_pixel; /* value to be used when restoring planes */
    Bool save_under; /* boolean, should bits under be saved? */
    Colormap colormap; /* color map to be associated with window */
    Bool map_installed; /* boolean, is color map currently installed */
    int map_state; /* IsUnmapped, IsUnviewable, IsViewable */
    long all_event_masks; /* set of events all people have interest in */
    long your_event_mask; /* my event mask */
    long do_not_propagate_mask; /* set of events that should not propagate */
    Bool override_redirect; /* boolean value for override-redirect */
    Screen *screen; /* back pointer to correct screen */
} XWindowAttributes;

/*
 * Data structure for host setting; getting routines.
 */

typedef struct XHostAddress;

/*
 * Data structure for "image" data, used by image manipulation routines.
 */
typedef struct _XImage {

```

```

    int width, height;          /* size of image */
    int xoffset;                /* number of pixels offset in X direction */
    int format;                 /* XYBitmap, XYPixmap, ZPixmap */
    char *data;                 /* pointer to image data */
    int byte_order;              /* data byte order, LSBFirst, MSBFirst */
    int bitmap_unit;             /* quant. of scanline 8, 16, 32 */
    int bitmap_bit_order;        /* LSBFirst, MSBFirst */
    int bitmap_pad;              /* 8, 16, 32 either XY or ZPixmap */
    int depth;                  /* depth of image */
    int bytes_per_line;          /* accelerator to next line */
    int bits_per_pixel;          /* bits per pixel (ZPixmap) */
    unsigned long red_mask;       /* bits in z arrangment */
    unsigned long green_mask;
    unsigned long blue_mask;
    XPointer obdata;             /* hook for the object routines to hang on */
    struct funcs {                /* image manipulation routines */
        struct _XImage *(*create_image)();
        int (*destroy_image)();
        unsigned long (*get_pixel)();
        int (*put_pixel)();
        struct _XImage *(*sub_image)();
        int (*add_pixel)();
    } f;
} XImage;

/*
 * Data structure for XReconfigureWindow
 */
typedef struct {
    int x, y;
    int width, height;
    int border_width;
    Window sibling;
    int stack_mode;
} XWindowChanges;

/*
 * Data structure used by color operations
 */
typedef struct {
    unsigned long pixel;
    unsigned short red, green, blue;
    char flags; /* do_red, do_green, do_blue */
    char pad;
} XColor;

/*
 * Data structures for graphics operations. On most machines, these are
 * congruent with the wire protocol structures, so reformatting the data
 * can be avoided on these architectures.
 */
typedef struct {
    short x1, y1, x2, y2;
} XSegment;

```

```

typedef struct {
    short x, y;
} XPoint;

typedef struct {
    short x, y;
    unsigned short width, height;
} XRectangle;

typedef struct {
    short x, y;
    unsigned short width, height;
    short angle1, angle2;
} XArc;

/* Data structure for XChangeKeyboardControl */

typedef struct {
    int key_click_percent;
    int bell_percent;
    int bell_pitch;
    int bell_duration;
    int led;
    int led_mode;
    int key;
    int auto_repeat_mode; /* On, Off, Default */
} XKeyboardControl;

/* Data structure for XGetKeyboardControl */

typedef struct {
    int key_click_percent;
    int bell_percent;
    unsigned int bell_pitch, bell_duration;
    unsigned long led_mask;
    int global_auto_repeat;
    char auto_repeats[32];
} XKeyboardState;

/* Data structure for XGetMotionEvents. */

typedef struct {
    Time time;
    short x, y;
} XTimeCoord;

/* Data structure for X{Set,Get}ModifierMapping */

typedef struct {
    int max_keypermod; /* The server's max # of keys per modifier */
    KeyCode *modifiermap; /* An 8 by max_keypermod array of modifiers */
} XModifierKeymap;

```

```

/*
 * Display datatype maintaining display specific data.
 * The contents of this structure are implementation dependent.
 * A Display should be treated as opaque by application code.
 */
typedef struct _XDisplay Display;

/*
 * A "XEvent" structure always has type as the first entry. This
 * uniquely identifies what kind of event it is. The second entry
 * is always a pointer to the display the event was read from.
 * The third entry is always a window of one type or another,
 * carefully selected to be useful to toolkit dispatchers. (Except
 * for keymap events, which have no window.) You
 * must not change the order of the three elements or toolkits will
 * break! The pointer to the generic event must be cast before use to
 * access any other information in the structure.
 */

/*
 * Definitions of specific events.
 */
typedef struct {
    int type;                /* of event */
    unsigned long serial;    /* # of last request processed by server */
    Bool send_event;        /* true if this came from a SendEvent request */
    Display *display;       /* Display the event was read from */
    Window window;         /* "event" window it is reported relative to */
    Window root;           /* root window that the event occurred on */
    Window subwindow;      /* child window */
    Time time;             /* milliseconds */
    int x, y;              /* pointer x, y coordinates in event window */
    int x_root, y_root;    /* coordinates relative to root */
    unsigned int state;     /* key or button mask */
    unsigned int keycode;   /* detail */
    Bool same_screen;       /* same screen flag */
} XKeyEvent;
typedef XKeyEvent XKeyPressedEvent;
typedef XKeyEvent XKeyReleasedEvent;

typedef struct {
    int type;                /* of event */
    unsigned long serial;    /* # of last request processed by server */
    Bool send_event;        /* true if this came from a SendEvent request */
    Display *display;       /* Display the event was read from */
    Window window;         /* "event" window it is reported relative to */
    Window root;           /* root window that the event occurred on */
    Window subwindow;      /* child window */
    Time time;             /* milliseconds */
    int x, y;              /* pointer x, y coordinates in event window */
    int x_root, y_root;    /* coordinates relative to root */
    unsigned int state;     /* key or button mask */
    unsigned int button;    /* detail */
    Bool same_screen;       /* same screen flag */
}

```

```

} XButtonEvent;
typedef XButtonEvent XButtonPressedEvent;
typedef XButtonEvent XButtonReleasedEvent;

typedef struct {
    int type;                /* of event */
    unsigned long serial;    /* # of last request processed by server */
    Bool send_event;        /* true if this came from a SendEvent request */
    Display *display;        /* Display the event was read from */
    Window window;          /* "event" window reported relative to */
    Window root;            /* root window that the event occurred on */
    Window subwindow;       /* child window */
    Time time;              /* milliseconds */
    int x, y;               /* pointer x, y coordinates in event window */
    int x_root, y_root;     /* coordinates relative to root */
    unsigned int state;     /* key or button mask */
    char is_hint;           /* detail */
    Bool same_screen;       /* same screen flag */
} XMotionEvent;
typedef XMotionEvent XPointerMovedEvent;

typedef struct {
    int type;                /* of event */
    unsigned long serial;    /* # of last request processed by server */
    Bool send_event;        /* true if this came from a SendEvent request */
    Display *display;        /* Display the event was read from */
    Window window;          /* "event" window reported relative to */
    Window root;            /* root window that the event occurred on */
    Window subwindow;       /* child window */
    Time time;              /* milliseconds */
    int x, y;               /* pointer x, y coordinates in event window */
    int x_root, y_root;     /* coordinates relative to root */
    int mode;               /* NotifyNormal, NotifyGrab, NotifyUngrab */
    int detail;
    /*
     * NotifyAncestor, NotifyVirtual, NotifyInferior,
     * NotifyNonLinear, NotifyNonLinearVirtual
     */
    Bool same_screen;       /* same screen flag */
    Bool focus;             /* boolean focus */
    unsigned int state;     /* key or button mask */
} XCrossingEvent;
typedef XCrossingEvent XEnterWindowEvent;
typedef XCrossingEvent XLeaveWindowEvent;

typedef struct {
    int type;                /* FocusIn or FocusOut */
    unsigned long serial;    /* # of last request processed by server */
    Bool send_event;        /* true if this came from a SendEvent request */
    Display *display;        /* Display the event was read from */
    Window window;          /* window of event */
    int mode;               /* NotifyNormal, NotifyGrab, NotifyUngrab */
    int detail;
    /*

```

```

        * NotifyAncestor, NotifyVirtual, NotifyInferior,
        * NotifyNonLinear, NotifyNonLinearVirtual, NotifyPointer,
        * NotifyPointerRoot, NotifyDetailNone
    */
} XFocusChangeEvent;
typedef XFocusChangeEvent XFocusInEvent;
typedef XFocusChangeEvent XFocusOutEvent;

/* generated on EnterWindow and FocusIn when KeyMapState selected */
typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event; /* true if this came from a SendEvent request */
    Display *display; /* Display the event was read from */
    Window window;
    char key_vector[32];
} XKeymapEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event; /* true if this came from a SendEvent request */
    Display *display; /* Display the event was read from */
    Window window;
    int x, y;
    int width, height;
    int count; /* if non-zero, at least this many more */
} XExposeEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event; /* true if this came from a SendEvent request */
    Display *display; /* Display the event was read from */
    Drawable drawable;
    int x, y;
    int width, height;
    int count; /* if non-zero, at least this many more */
    int major_code; /* core is CopyArea or CopyPlane */
    int minor_code; /* not defined in the core */
} XGraphicsExposeEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event; /* true if this came from a SendEvent request */
    Display *display; /* Display the event was read from */
    Drawable drawable;
    int major_code; /* core is CopyArea or CopyPlane */
    int minor_code; /* not defined in the core */
} XNoExposeEvent;

typedef struct {
    int type;

```

```

        unsigned long serial;    /* # of last request processed by server */
        Bool send_event;        /* true if this came from a SendEvent request */
        Display *display;        /* Display the event was read from */
        Window window;
        int state;               /* Visibility state */
    } XVisibilityEvent;

typedef struct {
    int type;
    unsigned long serial;        /* # of last request processed by server */
    Bool send_event;            /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */
    Window parent;               /* parent of the window */
    Window window;               /* window id of window created */
    int x, y;                    /* window location */
    int width, height;           /* size of window */
    int border_width;            /* border width */
    Bool override_redirect;      /* creation should be overridden */
} XCreateWindowEvent;

typedef struct {
    int type;
    unsigned long serial;        /* # of last request processed by server */
    Bool send_event;            /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */
    Window event;
    Window window;
} XDestroyWindowEvent;

typedef struct {
    int type;
    unsigned long serial;        /* # of last request processed by server */
    Bool send_event;            /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */
    Window event;
    Window window;
    Bool from_configure;
} XUnmapEvent;

typedef struct {
    int type;
    unsigned long serial;        /* # of last request processed by server */
    Bool send_event;            /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */
    Window event;
    Window window;
    Bool override_redirect;      /* boolean, is override set... */
} XMapEvent;

typedef struct {
    int type;
    unsigned long serial;        /* # of last request processed by server */
    Bool send_event;            /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */

```

```

        Window parent;
        Window window;
    } XMapRequestEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */
    Window event;
    Window window;
    Window parent;
    int x, y;
    Bool override_redirect;
} XReparentEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */
    Window event;
    Window window;
    int x, y;
    int width, height;
    int border_width;
    Window above;
    Bool override_redirect;
} XConfigureEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */
    Window event;
    Window window;
    int x, y;
} XGravityEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */
    Window window;
    int width, height;
} XResizeRequestEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */

```

```

    Window parent;
    Window window;
    int x, y;
    int width, height;
    int border_width;
    Window above;
    int detail;          /* Above, Below, TopIf, BottomIf, Opposite */
    unsigned long value_mask;
} XConfigureRequestEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */
    Window event;
    Window window;
    int place;             /* PlaceOnTop, PlaceOnBottom */
} XCirculateEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */
    Window parent;
    Window window;
    int place;             /* PlaceOnTop, PlaceOnBottom */
} XCirculateRequestEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */
    Window window;
    Atom atom;
    Time time;
    int state;             /* NewValue, Deleted */
} XPropertyEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */
    Bool send_event;      /* true if this came from a SendEvent request */
    Display *display;      /* Display the event was read from */
    Window window;
    Atom selection;
    Time time;
} XSelectionClearEvent;

typedef struct {
    int type;
    unsigned long serial; /* # of last request processed by server */

```

```

        Bool send_event;          /* true if this came from a SendEvent request */
        Display *display;         /* Display the event was read from */
        Window owner;
        Window requestor;
        Atom selection;
        Atom target;
        Atom property;
        Time time;
    } XSelectionRequestEvent;

typedef struct {
    int type;
    unsigned long serial;         /* # of last request processed by server */
    Bool send_event;             /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */
    Window requestor;
    Atom selection;
    Atom target;
    Atom property;               /* ATOM or None */
    Time time;
} XSelectionEvent;

typedef struct {
    int type;
    unsigned long serial;         /* # of last request processed by server */
    Bool send_event;             /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */
    Window window;
    Colormap colormap;           /* COLORMAP or None */
    Bool new;
    int state;                   /* ColormapInstalled, ColormapUninstalled */
} XColormapEvent;

typedef struct {
    int type;
    unsigned long serial;         /* # of last request processed by server */
    Bool send_event;             /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */
    Window window;
    Atom message_type;
    int format;
    union {
        char b[20];
        short s[10];
        long l[5];
    } data;
} XClientMessageEvent;

typedef struct {
    int type;
    unsigned long serial;         /* # of last request processed by server */
    Bool send_event;             /* true if this came from a SendEvent request */
    Display *display;            /* Display the event was read from */
    Window window;              /* unused */

```

```

        int request;                /* one of MappingModifier, MappingKeyboard,
                                   MappingPointer */
        int first_keycode;          /* first keycode */
        int count;                  /* defines range of change w. first_keycode*/
    } XMappingEvent;

typedef struct {
    int type;
    Display *display;               /* Display the event was read from */
    XID resourceid;                 /* resource id */
    unsigned long serial;           /* serial number of failed request */
    unsigned char error_code;       /* error code of failed request */
    unsigned char request_code;     /* Major op-code of failed request */
    unsigned char minor_code;       /* Minor op-code of failed request */
} XErrorEvent;

typedef struct {
    int type;
    unsigned long serial;           /* # of last request processed by server */
    Bool send_event;               /* true if this came from a SendEvent request */
    Display *display;              /* Display the event was read from */
    Window window;                 /* window on which event was requested in event mask */
} XAnyEvent;

/*
 * this union is defined so Xlib can always use the same sized
 * event structure internally, to avoid memory fragmentation.
 */
typedef union _XEvent {
    int type;                       /* must not be changed; first element */
    XAnyEvent xany;
    XKeyEvent xkey;
    XButtonEvent xbutton;
    XMotionEvent xmotion;
    XCrossingEvent xcrossing;
    XFocusChangeEvent xfocus;
    XExposeEvent xexpose;
    XGraphicsExposeEvent xgraphicsexpose;
    XNoExposeEvent xnoexpose;
    XVisibilityEvent xvisibility;
    XCreateWindowEvent xcreatewindow;
    XDestroyWindowEvent xdestroywindow;
    XUnmapEvent xunmap;
    XMapEvent xmap;
    XMapRequestEvent xmaprequest;
    XReparentEvent xreparent;
    XConfigureEvent xconfigure;
    XGravityEvent xgravity;
    XResizeRequestEvent xresizerequest;
    XConfigureRequestEvent xconfigurerequest;
    XCirculateEvent xcirculate;
    XCirculateRequestEvent xcirculaterequest;
    XPropertyEvent xproperty;
    XSelectionClearEvent xselectionclear;

```

```

        XSelectionRequestEvent xselectionrequest;
        XSelectionEvent xselection;
        XColormapEvent xcolormap;
        XClientMessageEvent xclient;
        XMappingEvent xmapping;
        XErrorEvent xerror;
        XKeymapEvent xkeymap;
        long pad[24];
    } XEvent;

/*
 * per character font metric information.
 */
typedef struct {
    short        lbearing;        /* origin to left edge of raster */
    short        rbearing;        /* origin to right edge of raster */
    short        width;           /* advance to next char's origin */
    short        ascent;          /* baseline to top edge of raster */
    short        descent;         /* baseline to bottom edge of raster */
    unsigned short attributes;    /* per char flags (not predefined) */
} XCharStruct;

/*
 * To allow arbitrary information with fonts, there are additional properties
 * returned.
 */
typedef struct {
    Atom name;
    unsigned long card32;
} XFontProp;

typedef struct {
    XExtData      *ext_data;      /* hook for extension to hang data */
    Font          fid;            /* Font id for this font */
    unsigned      direction;      /* hint about direction the font is painted */
    unsigned      min_char_or_byte2; /* first character */
    unsigned      max_char_or_byte2; /* last character */
    unsigned      min_bytel;      /* first row that exists */
    unsigned      max_bytel;      /* last row that exists */
    Bool          all_chars_exist; /* flag if all characters have non-zero size */
    unsigned      default_char;    /* char to print for undefined character */
    int           n_properties;    /* how many properties there are */
    XFontProp     *properties;     /* pointer to array of additional properties */
    XCharStruct   min_bounds;      /* minimum bounds over all existing char */
    XCharStruct   max_bounds;      /* maximum bounds over all existing char */
    XCharStruct   *per_char;       /* first_char to last_char information */
    int           ascent;          /* log. extent above baseline for spacing */
    int           descent;         /* log. descent below baseline for spacing */
} XFontStruct;

/*
 * PolyText routines take these as arguments.
 */
typedef struct {

```

```

    char *chars;                /* pointer to string */
    int nchars;                 /* number of characters */
    int delta;                 /* delta between strings */
    Font font;                 /* font to print it in, None don't change */
} XTextItem;

typedef struct {                /* normal 16 bit characters are two bytes */
    unsigned char byte1;
    unsigned char byte2;
} XChar2b;

typedef struct {
    XChar2b *chars;            /* two byte characters */
    int nchars;                /* number of characters */
    int delta;                 /* delta between strings */
    Font font;                 /* font to print it in, None don't change */
} XTextItem16;

typedef union { Display *display;
                GC gc;
                Visual *visual;
                Screen *screen;
                ScreenFormat *pixmap_format;
                XFontStruct *font; } XDataObject;

typedef struct {
    XRectangle      max_ink_extent;
    XRectangle      max_logical_extent;
} XFontSetExtents;

typedef struct _XFontSet *XFontSet;

typedef struct {
    char            *chars;
    int             nchars;
    int             delta;
    XFontSet        font_set;
} XmbTextItem;

typedef struct {
    wchar_t         *chars;
    int             nchars;
    int             delta;
    XFontSet        font_set;
} XwcTextItem;

typedef void (*XIMProc)();

typedef struct _XIM *XIM;
typedef struct _XIC *XIC;

typedef unsigned long XIMStyle;

typedef struct {

```

```

    unsigned short count_styles;
    XIMStyle *supported_styles;
} XIMStyles;

#define XIMPreeditArea          0x0001L
#define XIMPreeditCallbacks     0x0002L
#define XIMPreeditPosition     0x0004L
#define XIMPreeditNothing      0x0008L
#define XIMPreeditNone         0x0010L
#define XIMStatusArea          0x0100L
#define XIMStatusArea          0x0100L
#define XIMStatusCallbacks     0x0200L
#define XIMStatusNothing       0x0400L
#define XIMStatusNone          0x0800L

#define XNVaNestedList "XNVaNestedList"
#define XNQueryInputStyle "queryInputStyle"
#define XNClientWindow "clientWindow"
#define XNInputStyle "inputStyle"
#define XNFocusWindow "focusWindow"
#define XNResourceName "resourceName"
#define XNResourceClass "resourceClass"
#define XNGeometryCallback "geometryCallback"
#define XNFilterEvents "filterEvents"
#define XNPreeditStartCallback "preeditStartCallback"
#define XNPreeditDoneCallback "preeditDoneCallback"
#define XNPreeditDrawCallback "preeditDrawCallback"
#define XNPreeditCaretCallback "preeditCaretCallback"
#define XNPreeditAttributes "preeditAttributes"
#define XNStatusStartCallback "statusStartCallback"
#define XNStatusDoneCallback "statusDoneCallback"
#define XNStatusDrawCallback "statusDrawCallback"
#define XNStatusAttributes "statusAttributes"
#define XNArea "area"
#define XNAreaNeeded "areaNeeded"
#define XNSpotLocation "spotLocation"
#define XNColormap "colorMap"
#define XNStdColormap "stdColorMap"
#define XNForeground "foreground"
#define XNBackground "background"
#define XNBackgroundPixmap "backgroundPixmap"
#define XNFontSet "fontSet"
#define XNLineSpace "lineSpace"
#define XNCursor "cursor"
#define XBufferOverflow -1
#define XLookupNone 1
#define XLookupChars 2
#define XLookupKeySym 3
#define XLookupBoth 4

typedef XPointer XVaNestedList;

typedef struct {
    XPointer client_data;

```

```

    XIMProc callback;
} XIMCallback;

typedef unsigned long XIMFeedback;

#define XIMReverse      1
#define XIMUnderline    (1<<1)
#define XIMHighlight    (1<<2)
#define XIMPrimary      (1<<5)
#define XIMSecondary    (1<<6)
#define XIMTertiary     (1<<7)

typedef struct _XIMText {
    unsigned short length;
    XIMFeedback *feedback;
    Bool encoding_is_wchar;
    union {
        char *multi_byte;
        wchar_t *wide_char;
    } string;
} XIMText;

typedef struct _XIMPreeditDrawCallbackStruct {
    int caret;           /* Cursor offset within pre-edit string */
    int chg_first;       /* Starting change position */
    int chg_length;      /* Length of the change in character count */
    XIMText *text;
} XIMPreeditDrawCallbackStruct;

typedef enum {
    XIMForwardChar, XIMBackwardChar,
    XIMForwardWord, XIMBackwardWord,
    XIMCaretUp, XIMCaretDown,
    XIMNextLine, XIMPreviousLine,
    XIMLineStart, XIMLineEnd,
    XIMAbsolutePosition,
    XIMDontChange
} XIMCaretDirection;

typedef enum {
    XIMIsInvisible,      /* Disable caret feedback */
    XIMIsPrimary,        /* UI defined caret feedback */
    XIMIsSecondary       /* UI defined caret feedback */
} XIMCaretStyle;

typedef struct _XIMPreeditCaretCallbackStruct {
    int position;         /* Caret offset within pre-edit string */
    XIMCaretDirection direction; /* Caret moves direction */
    XIMCaretStyle style;  /* Feedback of the caret */
} XIMPreeditCaretCallbackStruct;

typedef enum {
    XIMTextType,
    XIMBitmapType

```

```
} XIMStatusDataType;

typedef struct _XIMStatusDrawCallbackStruct {
    XIMStatusDataType type;
    union {
        XIMText *text;
        Pixmap bitmap;
    } data;
} XIMStatusDrawCallbackStruct;
```

Figure 10-2. Manifest Constants and Data Types from <X11/X.h>

```

#define X_PROTOCOL      11                /* current protocol version */
#define X_PROTOCOL_REVISION 0            /* current minor version */

/* Resources */

typedef unsigned long XID;

typedef XID Window;
typedef XID Drawable;
typedef XID Font;
typedef XID Pixmap;
typedef XID Cursor;
typedef XID Colormap;
typedef XID GCContext;
typedef XID KeySym;

typedef unsigned long Mask;

typedef unsigned long Atom;

typedef unsigned long VisualID;

typedef unsigned long Time;

typedef unsigned char KeyCode;

/*****
 * RESERVED RESOURCE AND CONSTANT DEFINITIONS
 *****/

#define None            0L /* universal null resource or null atom */

#define ParentRelative  1L /* background pixmap in CreateWindow
                           and ChangeWindowAttributes */

#define CopyFromParent  0L /* border pixmap in CreateWindow
                           and ChangeWindowAttributes
                           special VisualID and special window
                           class passed to CreateWindow */

#define PointerWindow   0L /* destination window in SendEvent */
#define InputFocus      1L /* destination window in SendEvent */

#define PointerRoot     1L /* focus window in SetInputFocus */

#define AnyPropertyType  0L /* special Atom, passed to GetProperty */

#define AnyKey          0L /* special Key Code, passed to GrabKey */

#define AnyButton       0L /* special Button Code, passed to GrabButton */

```

```

#define AllTemporary          0L /* special Resource ID passed to KillClient */

#define CurrentTime          0L /* special Time */

#define NoSymbol              0L /* special KeySym */

/*****
 * EVENT DEFINITIONS
 *****/

/* Input Event Masks. Used as event-mask window attribute and as arguments
   to Grab requests. Not to be confused with event names. */

#define NoEventMask           0L
#define KeyPressMask          (1L<<0)
#define KeyReleaseMask        (1L<<1)
#define ButtonPressMask       (1L<<2)
#define ButtonReleaseMask     (1L<<3)
#define EnterWindowMask       (1L<<4)
#define LeaveWindowMask       (1L<<5)
#define PointerMotionMask     (1L<<6)
#define PointerMotionHintMask (1L<<7)
#define Button1MotionMask     (1L<<8)
#define Button2MotionMask     (1L<<9)
#define Button3MotionMask     (1L<<10)
#define Button4MotionMask     (1L<<11)
#define Button5MotionMask     (1L<<12)
#define ButtonMotionMask      (1L<<13)
#define KeymapStateMask       (1L<<14)
#define ExposureMask          (1L<<15)
#define VisibilityChangeMask  (1L<<16)
#define StructureNotifyMask   (1L<<17)
#define ResizeRedirectMask    (1L<<18)
#define SubstructureNotifyMask (1L<<19)
#define SubstructureRedirectMask (1L<<20)
#define FocusChangeMask       (1L<<21)
#define PropertyChangeMask    (1L<<22)
#define ColormapChangeMask    (1L<<23)
#define OwnerGrabButtonMask   (1L<<24)

/* Event names. Used in "type" field in XEvent structures. Not to be
   confused with event masks above. They start from 2 because 0 and 1
   are reserved in the protocol for errors and replies. */

#define KeyPress               2
#define KeyRelease              3
#define ButtonPress             4
#define ButtonRelease           5
#define MotionNotify            6
#define EnterNotify             7
#define LeaveNotify             8
#define FocusIn                 9
#define FocusOut                10
#define KeymapNotify            11

```

```

#define Expose                12
#define GraphicsExpose        13
#define NoExpose              14
#define VisibilityNotify      15
#define CreateNotify          16
#define DestroyNotify         17
#define UnmapNotify           18
#define MapNotify             19
#define MapRequest            20
#define ReparentNotify        21
#define ConfigureNotify       22
#define ConfigureRequest      23
#define GravityNotify         24
#define ResizeRequest         25
#define CirculateNotify       26
#define CirculateRequest      27
#define PropertyNotify        28
#define SelectionClear        29
#define SelectionRequest      30
#define SelectionNotify       31
#define ColormapNotify        32
#define ClientMessage         33
#define MappingNotify         34
#define LasteEvent            35      /* must be bigger than any event # */

```

```

/* Key masks. Used as modifiers to GrabButton and GrabKey, results of
   QueryPointer, state in various key-, mouse-, and button-related events. */

```

```

#define ShiftMask             (1<<0)
#define LockMask              (1<<1)
#define ControlMask           (1<<2)
#define Mod1Mask              (1<<3)
#define Mod2Mask              (1<<4)
#define Mod3Mask              (1<<5)
#define Mod4Mask              (1<<6)
#define Mod5Mask              (1<<7)

```

```

/* modifier names. Used to build a SetModifierMapping request or
   to read a GetModifierMapping request. These correspond to the
   masks defined above. */

```

```

#define ShiftMapIndex         0
#define LockMapIndex          1
#define ControlMapIndex       2
#define Mod1MapIndex          3
#define Mod2MapIndex          4
#define Mod3MapIndex          5
#define Mod4MapIndex          6
#define Mod5MapIndex          7

```

```

/* button masks. Used in same manner as Key masks above. Not to be confused
   with button names below. */

```

```

#define Button1Mask            (1<<8)

```

```
#define Button2Mask          (1<<9)
#define Button3Mask          (1<<10)
#define Button4Mask          (1<<11)
#define Button5Mask          (1<<12)

#define AnyModifier          (1<<15)  /* used in GrabButton, GrabKey */

/* button names. Used as arguments to GrabButton and as detail in ButtonPress
   and ButtonRelease events. Not to be confused with button masks above.
   Note that 0 is already defined above as "AnyButton". */

#define Button1              1
#define Button2              2
#define Button3              3
#define Button4              4
#define Button5              5

/* Notify modes */

#define NotifyNormal         0
#define NotifyGrab           1
#define NotifyUngrab         2
#define NotifyWhileGrabbed   3

#define NotifyHint           1        /* for MotionNotify events */

/* Notify detail */

#define NotifyAncestor        0
#define NotifyVirtual         1
#define NotifyInferior        2
#define NotifyNonlinear       3
#define NotifyNonlinearVirtual 4
#define NotifyPointer         5
#define NotifyPointerRoot     6
#define NotifyDetailNone      7

/* Visibility notify */

#define VisibilityUnobscured   0
#define VisibilityPartiallyObscured 1
#define VisibilityFullyObscured 2

/* Circulation request */

#define PlaceOnTop             0
#define PlaceOnBottom         1

/* Property notification */

#define PropertyNewValue       0
#define PropertyDelete         1
```

```

/* Color Map notification */

#define ColormapUninstalled    0
#define ColormapInstalled     1

/* GrabPointer, GrabButton, GrabKeyboard, GrabKey Modes */

#define GrabModeSync          0
#define GrabModeAsync         1

/* GrabPointer, GrabKeyboard reply status */

#define GrabSuccess            0
#define AlreadyGrabbed         1
#define GrabInvalidTime        2
#define GrabNotViewable        3
#define GrabFrozen              4

/* AllowEvents modes */

#define AsyncPointer            0
#define SyncPointer             1
#define ReplayPointer           2
#define AsyncKeyboard           3
#define SyncKeyboard            4
#define ReplayKeyboard          5
#define AsyncBoth               6
#define SyncBoth                7

/* Used in SetInputFocus, GetInputFocus */

#define RevertToNone            (int)None
#define RevertToPointerRoot     (int)PointerRoot
#define RevertToParent          2

/*****
 * ERROR CODES
 *****/

#define Success                 0    /* everything's okay */
#define BadRequest              1    /* bad request code */
#define BadValue                 2    /* int parameter out of range */
#define BadWindow                3    /* parameter not a Window */
#define BadPixmap                4    /* parameter not a Pixmap */
#define BadAtom                  5    /* parameter not an Atom */
#define BadCursor                6    /* parameter not a Cursor */
#define BadFont                  7    /* parameter not a Font */
#define BadMatch                 8    /* parameter mismatch */
#define BadDrawable              9    /* parameter not a Pixmap or Window */
#define BadAccess               10   /* depending on context:
    - key/button already grabbed
    - attempt to free an illegal
      cmap entry
    - attempt to store into a read-only

```

```

        color map entry.
        - attempt to modify the access control
          list from other than the local host.
    */
#define BadAlloc      11    /* insufficient resources */
#define BadColor      12    /* no such colormap */
#define BadGC         13    /* parameter not a GC */
#define BadIDChoice   14    /* choice not in range or already used */
#define BadName       15    /* font or color name doesn't exist */
#define BadLength     16    /* Request length incorrect */
#define BadImplementation 17 /* server is defective */

#define FirstExtensionError 128
#define LastExtensionError 255

/*****
 * WINDOW DEFINITIONS
 *****/

/* Window classes used by CreateWindow */
/* Note that CopyFromParent is already defined as 0 above */

#define InputOutput      1
#define InputOnly        2

/* Window attributes for CreateWindow and ChangeWindowAttributes */

#define CWBackPixmap      (1L<<0)
#define CWBackPixel       (1L<<1)
#define CWBorderPixmap    (1L<<2)
#define CWBorderPixel     (1L<<3)
#define CWBitGravity      (1L<<4)
#define CWWinGravity       (1L<<5)
#define CWBackingStore     (1L<<6)
#define CWBackingPlanes   (1L<<7)
#define CWBackingPixel     (1L<<8)
#define CWOVERRIDERedirect (1L<<9)
#define CWSaveUnder       (1L<<10)
#define CWEventMask        (1L<<11)
#define CWDontPropagate    (1L<<12)
#define CWColormap         (1L<<13)
#define CWCursor           (1L<<14)

/* ConfigureWindow structure */

#define CWX                (1<<0)
#define CWY                (1<<1)
#define CWWidth            (1<<2)
#define CWHeight           (1<<3)
#define CWBorderWidth      (1<<4)
#define CWSibling           (1<<5)
#define CWStackMode        (1<<6)

```

```

/* Bit Gravity */

#define ForgetGravity          0
#define NorthWestGravity      1
#define NorthGravity          2
#define NorthEastGravity      3
#define WestGravity           4
#define CenterGravity         5
#define EastGravity           6
#define SouthWestGravity      7
#define SouthGravity          8
#define SouthEastGravity      9
#define StaticGravity         10

/* Window gravity + bit gravity above */

#define UnmapGravity           0

/* Used in CreateWindow for backing-store hint */

#define NotUseful              0
#define WhenMapped            1
#define Always                 2

/* Used in GetWindowAttributes reply */

#define IsUnmapped             0
#define IsUnviewable          1
#define IsViewable             2

/* Used in ChangeSaveSet */

#define SetModeInsert           0
#define SetModeDelete          1

/* Used in ChangeCloseDownMode */

#define DestroyAll              0
#define RetainPermanent        1
#define RetainTemporary        2

/* Window stacking method (in configureWindow) */

#define Above                   0
#define Below                   1
#define TopIf                   2
#define BottomIf                3
#define Opposite                4

/* Circulation direction */

#define RaiseLowest             0
#define LowerHighest            1

```

```

/* Property modes */

#define PropModeReplace          0
#define PropModePrepend         1
#define PropModeAppend          2

/*****
 * GRAPHICS DEFINITIONS
 *****/

/* graphics functions, as in GC.alu */

#define GXclear                  0x0          /* 0 */
#define GXand                    0x1          /* src AND dst */
#define GXandReverse             0x2          /* src AND NOT dst */
#define GXcopy                   0x3          /* src */
#define GXandInverted            0x4          /* NOT src AND dst */
#define GXnoop                   0x5          /* dst */
#define GXxor                    0x6          /* src XOR dst */
#define GXor                     0x7          /* src OR dst */
#define GXnor                    0x8          /* NOT src AND NOT dst */
#define GXequiv                  0x9          /* NOT src XOR dst */
#define GXinvert                 0xa          /* NOT dst */
#define GXorReverse              0xb          /* src OR NOT dst */
#define GXcopyInverted           0xc          /* NOT src */
#define GXorInverted             0xd          /* NOT src OR dst */
#define GXnand                   0xe          /* NOT src OR NOT dst */
#define GXset                     0xf          /* 1 */

/* LineStyle */

#define LineSolid                 0
#define LineOnOffDash            1
#define LineDoubleDash           2

/* capStyle */

#define CapNotLast                0
#define CapButt                  1
#define CapRound                  2
#define CapProjecting             3

/* joinStyle */

#define JoinMiter                 0
#define JoinRound                 1
#define JoinBevel                 2

/* fillStyle */

#define FillSolid                 0
#define FillTiled                 1
#define FillStippled              2
#define FillOpaqueStippled        3

```

```

/* fillRule */

#define EvenOddRule          0
#define WindingRule          1

/* subwindow mode */

#define ClipByChildren        0
#define IncludeInferiors      1

/* SetClipRectangles ordering */

#define Unsorted              0
#define YSorted               1
#define YXSorted              2
#define YXBanded              3

/* CoordinateMode for drawing routines */

#define CoordModeOrigin       0      /* relative to the origin */
#define CoordModePrevious     1      /* relative to previous point */

/* Polygon shapes */

#define Complex                0      /* paths may intersect */
#define Nonconvex              1      /* no paths intersect, but not convex */
#define Convex                 2      /* wholly convex */

/* Arc modes for PolyFillArc */

#define ArcChord               0      /* join endpoints of arc */
#define ArcPieSlice            1      /* join endpoints to center of arc */

/* GC components: masks used in CreateGC, CopyGC, ChangeGC, OR'ed into
   GC.stateChanges */

#define GCFunction              (1L<<0)
#define GCPlaneMask            (1L<<1)
#define GCForeground            (1L<<2)
#define GCBackground           (1L<<3)
#define GCLineWidth            (1L<<4)
#define GCLineStyle            (1L<<5)
#define GCCapStyle              (1L<<6)
#define GCJoinStyle            (1L<<7)
#define GCFillStyle            (1L<<8)
#define GCFillRule             (1L<<9)
#define GCTile                 (1L<<10)
#define GCStipple              (1L<<11)
#define GCTileStipXOrigin       (1L<<12)
#define GCTileStipYOrigin       (1L<<13)
#define GCFont                 (1L<<14)
#define GCSubwindowMode        (1L<<15)
#define GCGraphicsExposures     (1L<<16)

```

```

#define GCclipXOrigin      (1L<<17)
#define GCclipYOrigin      (1L<<18)
#define GCclipMask         (1L<<19)
#define GCDashOffset       (1L<<20)
#define GCDashList         (1L<<21)
#define GCArcMode          (1L<<22)

#define GCLastBit           22
/*****
 * FONTS
 *****/

/* used in QueryFont -- draw direction */

#define FontLeftToRight     0
#define FontRightToLeft    1

#define FontChange          255

/*****
 * IMAGING
 *****/

/* ImageFormat -- PutImage, GetImage */

#define XYBitmap            0      /* depth 1, XYFormat */
#define XYPixmap            1      /* depth == drawable depth */
#define ZPixmap            2      /* depth == drawable depth */

/*****
 * COLOR MAP STUFF
 *****/

/* For CreateColormap */

#define AllocNone           0      /* create map with no entries */
#define AllocAll            1      /* allocate entire map writeable */

/* Flags used in StoreNamedColor, StoreColors */

#define DoRed               (1<<0)
#define DoGreen             (1<<1)
#define DoBlue              (1<<2)

/*****
 * CURSOR STUFF
 *****/

/* QueryBestSize Class */

#define CursorShape         0      /* largest size that can be displayed */
#define TileShape           1      /* size tiled fastest */
#define StippleShape        2      /* size stippled fastest */

```

```

/*****
 * KEYBOARD/POINTER STUFF
 *****/

#define AutoRepeatModeOff      0
#define AutoRepeatModeOn      1
#define AutoRepeatModeDefault  2

#define LedModeOff             0
#define LedModeOn              1

/* masks for ChangeKeyboardControl */

#define KBKeyClickPercent      (1L<<0)
#define KBBellPercent          (1L<<1)
#define KBBellPitch            (1L<<2)
#define KBBellDuration         (1L<<3)
#define KBLed                  (1L<<4)
#define KBLedMode              (1L<<5)
#define KBKey                  (1L<<6)
#define KBAutoRepeatMode       (1L<<7)

#define MappingSuccess          0
#define MappingBusy            1
#define MappingFailed          2

#define MappingModifier        0
#define MappingKeyboard        1
#define MappingPointer         2

/*****
 * SCREEN SAVER STUFF
 *****/

#define DontPreferBlanking      0
#define PreferBlanking         1
#define DefaultBlanking        2

#define DisableScreenSaver      0
#define DisableScreenInterval   0

#define DontAllowExposures      0
#define AllowExposures          1
#define DefaultExposures        2

/* for ForceScreenSaver */

#define ScreenSaverReset 0
#define ScreenSaverActive 1

/*****
 * HOSTS AND CONNECTIONS
 *****/

```

```
/* for ChangeHosts */

#define HostInsert          0
#define HostDelete         1

/* for ChangeAccessControl */

#define EnableAccess        1
#define DisableAccess       0

/* Display classes used in opening the connection
 * Note that the statically allocated ones are even numbered and the
 * dynamically changeable ones are odd numbered */

#define StaticGray          0
#define GrayScale           1
#define StaticColor         2
#define PseudoColor         3
#define TrueColor           4
#define DirectColor         5

/* Byte order used in imageByteOrder and bitmapBitOrder */

#define LSBFirst             0
#define MSBFirst            1
```

Figure 10-3. Manifest Constants from <X11/Xatom.h>

```

/* THIS IS A GENERATED FILE
 *
 * Do not change!  Changing this file implies a protocol change!
 */

#define XA_PRIMARY ((Atom) 1)
#define XA_SECONDARY ((Atom) 2)
#define XA_ARC ((Atom) 3)
#define XA_ATOM ((Atom) 4)
#define XA_BITMAP ((Atom) 5)
#define XA_CARDINAL ((Atom) 6)
#define XA_COLORMAP ((Atom) 7)
#define XA_CURSOR ((Atom) 8)
#define XA_CUT_BUFFER0 ((Atom) 9)
#define XA_CUT_BUFFER1 ((Atom) 10)
#define XA_CUT_BUFFER2 ((Atom) 11)
#define XA_CUT_BUFFER3 ((Atom) 12)
#define XA_CUT_BUFFER4 ((Atom) 13)
#define XA_CUT_BUFFER5 ((Atom) 14)
#define XA_CUT_BUFFER6 ((Atom) 15)
#define XA_CUT_BUFFER7 ((Atom) 16)
#define XA_DRAWABLE ((Atom) 17)
#define XA_FONT ((Atom) 18)
#define XA_INTEGER ((Atom) 19)
#define XA_PIXMAP ((Atom) 20)
#define XA_POINT ((Atom) 21)
#define XA_RECTANGLE ((Atom) 22)
#define XA_RESOURCE_MANAGER ((Atom) 23)
#define XA_RGB_COLOR_MAP ((Atom) 24)
#define XA_RGB_BEST_MAP ((Atom) 25)
#define XA_RGB_BLUE_MAP ((Atom) 26)
#define XA_RGB_DEFAULT_MAP ((Atom) 27)
#define XA_RGB_GRAY_MAP ((Atom) 28)
#define XA_RGB_GREEN_MAP ((Atom) 29)
#define XA_RGB_RED_MAP ((Atom) 30)
#define XA_STRING ((Atom) 31)
#define XA_VISUALID ((Atom) 32)
#define XA_WINDOW ((Atom) 33)
#define XA_WM_COMMAND ((Atom) 34)
#define XA_WM_HINTS ((Atom) 35)
#define XA_WM_CLIENT_MACHINE ((Atom) 36)
#define XA_WM_ICON_NAME ((Atom) 37)
#define XA_WM_ICON_SIZE ((Atom) 38)
#define XA_WM_NAME ((Atom) 39)
#define XA_WM_NORMAL_HINTS ((Atom) 40)
#define XA_WM_SIZE_HINTS ((Atom) 41)
#define XA_WM_ZOOM_HINTS ((Atom) 42)
#define XA_MIN_SPACE ((Atom) 43)
#define XA_NORM_SPACE ((Atom) 44)
#define XA_MAX_SPACE ((Atom) 45)
#define XA_END_SPACE ((Atom) 46)

```

```
#define XA_SUPERSCRIPT_X ((Atom) 47)
#define XA_SUPERSCRIPT_Y ((Atom) 48)
#define XA_SUBSCRIPT_X ((Atom) 49)
#define XA_SUBSCRIPT_Y ((Atom) 50)
#define XA_UNDERLINE_POSITION ((Atom) 51)
#define XA_UNDERLINE_THICKNESS ((Atom) 52)
#define XA_STRIKEOUT_ASCENT ((Atom) 53)
#define XA_STRIKEOUT_DESCENT ((Atom) 54)
#define XA_ITALIC_ANGLE ((Atom) 55)
#define XA_X_HEIGHT ((Atom) 56)
#define XA_QUAD_WIDTH ((Atom) 57)
#define XA_WEIGHT ((Atom) 58)
#define XA_POINT_SIZE ((Atom) 59)
#define XA_RESOLUTION ((Atom) 60)
#define XA_COPYRIGHT ((Atom) 61)
#define XA_NOTICE ((Atom) 62)
#define XA_FONT_NAME ((Atom) 63)
#define XA_FAMILY_NAME ((Atom) 64)
#define XA_FULL_NAME ((Atom) 65)
#define XA_CAP_HEIGHT ((Atom) 66)
#define XA_WM_CLASS ((Atom) 67)
#define XA_WM_TRANSIENT_FOR ((Atom) 68)

#define XA_LAST_PREDEFINED ((Atom) 68)
```

Figure 10-4. Manifest Constants and Data Types from <X11/Xresource.h>

```

/*****
 *
 * Quark Management
 *
 *****/

typedef int      XrmQuark, *XrmQuarkList;
#define NULLQUARK ((XrmQuark) 0)

typedef char *XrmString;
#define NULLSTRING ((XrmString) 0)

/*****
 *
 * Conversion of Strings to Lists
 *
 *****/

typedef enum {XrmBindTightly, XrmBindLoosely} XrmBinding, *XrmBindingList;

/*****
 *
 * Name and Class lists.
 *
 *****/

typedef XrmQuark      XrmName;
typedef XrmQuarkList  XrmNameList;

typedef XrmQuark      XrmClass;
typedef XrmQuarkList  XrmClassList;

/*****
 *
 * Resource Representation Types and Values
 *
 *****/

typedef XrmQuark      XrmRepresentation;

typedef struct {
    unsigned int      size;
    caddr_t           addr;
} XrmValue, *XrmValuePtr;

/*****
 *
 * Resource Manager Functions
 *
 *****/

```

```
typedef struct _XrmHashBucketRec *XrmHashBucket;
typedef XrmHashBucket *XrmHashTable;
typedef XrmHashTable XrmSearchList[];
typedef struct _XrmHashBucketRec *XrmDatabase;

/*****
 *
 * Resource Database Management
 *
 *****/

#define XrmEnumAllLevels 0
#define XrmEnumOneLevel 1

/*****
 *
 * Command line option mapping to resource entries
 *
 *****/

typedef enum {
    XrmoptionNoArg,      /* Value is specified in OptionDescRec.value */
    XrmoptionIsArg,      /* Value is the option string itself */
    XrmoptionStickyArg,  /* Value is characters immediately following option */
    XrmoptionSepArg,     /* Value is next argument in argv */
    XrmoptionResArg,     /* Resource and value in next argument in argv */
    XrmoptionSkipArg,    /* Ignore this option and the next argument in argv */
    XrmoptionSkipLine,   /* Ignore this option and the rest of argv */
    XrmoptionSkipNArgs   /* Ignore this option and the next
                        OptionDescRes.value arguments in argv */
} XrmOptionKind;

typedef struct {
    char      *option;      /* Option abbreviation in argv */
    char      *specifier;   /* Resource specifier */
    XrmOptionKind argKind;  /* Which style of option it is */
    caddr_t   value;        /* Value to provide if XrmoptionNoArg */
} XrmOptionDescRec, *XrmOptionDescList;
```

Figure 10-5. Manifest Constants and Data Types from <X11/Xutil.h>

```

/*
 * Bitmask returned by XParseGeometry(). Each bit tells if the corresponding
 * value (x, y, width, height) was found in the parsed string.
 */
#define NoValue          0x0000
#define XValue           0x0001
#define YValue           0x0002
#define WidthValue       0x0004
#define HeightValue      0x0008
#define AllValues        0x000F
#define XNegative        0x0010
#define YNegative        0x0020

/*
 * new version containing base_width, base_height, and win_gravity fields;
 * used with WM_NORMAL_HINTS.
 */
typedef struct {
    long flags;          /* marks which fields in this structure are defined */
    int x, y;            /* obsolete for new window mgrs, but clients */
    int width, height;   /* should set so old wm's don't mess up */
    int min_width, min_height;
    int max_width, max_height;
    int width_inc, height_inc;
    struct {
        int x; /* numerator */
        int y; /* denominator */
    } min_aspect, max_aspect;
    int base_width, base_height; /* added by ICCCM version 1 */
    int win_gravity; /* added by ICCCM version 1 */
} XSizeHints;

/*
 * The next block of definitions are for window manager properties that
 * clients and applications use for communication.
 */

/* flags argument in size hints */
#define USPosition      (1L << 0) /* user specified x, y */
#define USSize          (1L << 1) /* user specified width, height */

#define PPosition       (1L << 2) /* program specified position */
#define PSize           (1L << 3) /* program specified size */
#define PMinSize        (1L << 4) /* program specified minimum size */
#define PMaxSize        (1L << 5) /* program specified maximum size */
#define PResizeInc      (1L << 6) /* program specified resize increments */
#define PAspect         (1L << 7) /* program specified min and max aspect ratios */
#define PBaseSize       (1L << 8) /* program specified base for incrementing */
#define PWinGravity      (1L << 9) /* program specified window gravity */

/* obsolete */

```

```
#define PAllHints (PPosition|PSize|PMinSize|PMaxSize|PResizeInc|PAspect)

typedef struct {
    long flags;          /* marks which fields in this structure are defined */
    Bool input;          /* does this application rely on the window manager to
                           get keyboard input? */
    int initial_state;    /* see below */
    Pixmap icon_pixmap;   /* pixmap to be used as icon */
    Window icon_window;    /* window to be used as icon */
    int icon_x, icon_y;   /* initial position of icon */
    Pixmap icon_mask;     /* icon mask bitmap */
    XID window_group;     /* id of related window group */
    /* this structure may be extended in the future */
} XWMHints;

/* definition for flags of XWMHints */

#define InputHint          (1L << 0)
#define StateHint          (1L << 1)
#define IconPixmapHint     (1L << 2)
#define IconWindowHint     (1L << 3)
#define IconPositionHint   (1L << 4)
#define IconMaskHint       (1L << 5)
#define WindowGroupHint    (1L << 6)
#define AllHints (InputHint|StateHint|IconPixmapHint|IconWindowHint| \
IconPositionHint|IconMaskHint|WindowGroupHint)

/* definitions for initial window state */
#define WithdrawnState 0    /* for windows that are not mapped */
#define NormalState 1      /* most applications want to start this way */
#define IconicState 3      /* application wants to start as an icon */

/*
 * new structure for manipulating TEXT properties; used with WM_NAME,
 * WM_ICON_NAME, WM_CLIENT_MACHINE, and WM_COMMAND.
 */
typedef struct {
    unsigned char *value;    /* same as Property routines */
    Atom encoding;          /* prop type */
    int format;             /* prop data format: 8, 16, or 32 */
    unsigned long nitems;    /* number of data items in value */
} XTextProperty;

#define XNoMemory -1
#define XLocaleNotSupported -2
#define XConverterNotFound -3

typedef enum {
    XStringStyle,           /* STRING */
    XCompoundTextStyle,     /* COMPOUND_TEXT */
    XTextStyle,             /* text in owner's encoding (current locale) */
    XStdICCTextStyle        /* STRING, else COMPOUND_TEXT */
} XICCEncodingStyle;
```

```

typedef struct {
    int min_width, min_height;
    int max_width, max_height;
    int width_inc, height_inc;
} XIconSize;

typedef struct {
    char *res_name;
    char *res_class;
} XClassHint;

/*
 * Compose sequence status structure, used in calling XLookupString.
 */
typedef struct _XComposeStatus {
    char *compose_ptr;          /* state table pointer */
    int chars_matched;          /* match state */
} XComposeStatus;

/*
 * opaque reference to Region data type
 */
typedef struct _XRegion *Region;

/* Return values from XRectInRegion() */

#define RectangleOut 0
#define RectangleIn 1
#define RectanglePart 2

/*
 * Information used by the visual utility routines to find desired visual
 * type from the many visuals a display may support.
 */

typedef struct {
    Visual *visual;
    VisualID visualid;
    int screen;
    int depth;
    int class;
    unsigned long red_mask;
    unsigned long green_mask;
    unsigned long blue_mask;
    int colormap_size;
    int bits_per_rgb;
} XVisualInfo;

#define VisualNoMask          0x0
#define VisualIDMask          0x1
#define VisualScreenMask     0x2
#define VisualDepthMask      0x4
#define VisualClassMask      0x8

```

```

#define VisualRedMaskMask      0x10
#define VisualGreenMaskMask    0x20
#define VisualBlueMaskMask     0x40
#define VisualColormapSizeMask 0x80
#define VisualBitsPerRGBMask   0x100
#define VisualAllMask          0x1FF

/*
 * This defines a window manager property that clients may use to
 * share standard color maps of type RGB_COLOR_MAP:
 */
typedef struct {
    Colormap colormap;
    unsigned long red_max;
    unsigned long red_mult;
    unsigned long green_max;
    unsigned long green_mult;
    unsigned long blue_max;
    unsigned long blue_mult;
    unsigned long base_pixel;
    VisualID visualid;          /* added by ICCCM version 1 */
    XID killid;                 /* added by ICCCM version 1 */
} XStandardColormap;

#define ReleaseByFreeingColormap ((XID) 1L) /* for killid field above */

/*
 * return codes for XReadBitmapFile and XWriteBitmapFile
 */
#define BitmapSuccess          0
#define BitmapOpenFailed      1
#define BitmapFileInvalid     2
#define BitmapNoMemory        3

/*
 * Declare the routines that don't return int.
 */

/*****
 *
 * Context Management
 *
 *****/

/* Associative lookup table return codes */

#define XCSUCCESS 0      /* No error. */
#define XCNOMEM  1      /* Out of memory */
#define XCNOENT  2      /* No entry in table */

typedef int XContext;

```

Figure 10-6. Manifest Constants and Data Types from <X11/Xcms.h>

```

/*
 * XCMS Status Values
 */
#define XcmsFailure                0
#define XcmsSuccess                1
#define XcmsSuccessWithCompression 2

/*
 * Color Space Format ID's
 *   Color Space ID's are of XcmsColorFormat type, which is an
 *   unsigned short (16 bits).
 *
 *   bit 15 (most significant bit):
 *       0 == Device-Independent
 *       1 == Device-Dependent
 *
 *   bit 14:
 *       0 == Registered with X Consortium
 *       1 == Unregistered
 */
#define XcmsUndefinedFormat        (XcmsColorFormat)0x00000000
#define XcmsCIEXYZFormat           (XcmsColorFormat)0x00000001
#define XcmsCIEuvYFormat           (XcmsColorFormat)0x00000002
#define XcmsCIExyYFormat           (XcmsColorFormat)0x00000003
#define XcmsCIELabFormat           (XcmsColorFormat)0x00000004
#define XcmsCIELuvFormat           (XcmsColorFormat)0x00000005
#define XcmsTekHVCFormat           (XcmsColorFormat)0x00000006
#define XcmsRGBFormat              (XcmsColorFormat)0x80000000
#define XcmsRGBiFormat             (XcmsColorFormat)0x80000001

/*
 * State of XcmsPerScrnInfo
 */
#define XcmsInitNone                0x00    /* no initialization attempted */
#define XcmsInitSuccess             0x01    /* initialization successful */
#define XcmsInitDefault             0xff    /* initialization failed */

typedef unsigned int XcmsColorFormat;    /* Color Space Format ID */

typedef double XcmsFloat;

/*
 * Device RGB
 */
typedef struct {
    unsigned short red;                /* scaled from 0x0000 to 0xffff */
    unsigned short green;              /* scaled from 0x0000 to 0xffff */
    unsigned short blue;               /* scaled from 0x0000 to 0xffff */
} XcmsRGB;

/*

```

```

        * RGB Intensity
        */
typedef struct {
    XcmsFloat red;        /* 0.0 - 1.0 */
    XcmsFloat green;      /* 0.0 - 1.0 */
    XcmsFloat blue;       /* 0.0 - 1.0 */
} XcmsRGBi;

/*
 * CIE XYZ
 */
typedef struct {
    XcmsFloat X;
    XcmsFloat Y;
    XcmsFloat Z;
} XcmsCIEXYZ;

/*
 * CIE u'v'Y
 */
typedef struct {
    XcmsFloat u_prime;    /* 0.0 - 1.0 */
    XcmsFloat v_prime;    /* 0.0 - 1.0 */
    XcmsFloat Y;          /* 0.0 - 1.0 */
} XcmsCIEuvY;

/*
 * CIE xyY
 */
typedef struct {
    XcmsFloat x;          /* 0.0 - 1.0 */
    XcmsFloat y;          /* 0.0 - 1.0 */
    XcmsFloat Y;          /* 0.0 - 1.0 */
} XcmsCIExyY;

/*
 * CIE L*a*b*
 */
typedef struct {
    XcmsFloat L_star;     /* 0.0 - 100.0 */
    XcmsFloat a_star;
    XcmsFloat b_star;
} XcmsCIELab;

/*
 * CIE L*u*v*
 */
typedef struct {
    XcmsFloat L_star;     /* 0.0 - 100.0 */
    XcmsFloat u_star;
    XcmsFloat v_star;
} XcmsCIELuv;

/*

```

```

        * TekHVC
        */
typedef struct {
    XcmsFloat H;          /* 0.0 - 360.0 */
    XcmsFloat V;          /* 0.0 - 100.0 */
    XcmsFloat C;          /* 0.0 - 100.0 */
} XcmsTekHVC;

/*
 * PAD
 */
typedef struct {
    XcmsFloat pad0;
    XcmsFloat pad1;
    XcmsFloat pad2;
    XcmsFloat pad3;
} XcmsPad;

/*
 * XCMS Color Structure
 */
typedef struct {
    union {
        XcmsRGB RGB;
        XcmsRGBi RGBi;
        XcmsCIEXYZ CIEXYZ;
        XcmsCIEuvY CIEuvY;
        XcmsCIExyY CIExyY;
        XcmsCIELab CIELab;
        XcmsCIELuv CIELuv;
        XcmsTekHVC TekHVC;
        XcmsPad Pad;
    } spec;                /* the color specification */
    unsigned long pixel;    /* pixel value (as needed) */
    XcmsColorFormat format; /* the specification format */
} XcmsColor;

/*
 * XCMS Per Screen related data
 */

typedef struct _XcmsPerScrnInfo {
    XcmsColor screenWhitePt; /* Screen White point */
    XPointer functionSet;     /* pointer to Screen Color Characterization */
                                /* Function Set structure */
    XPointer screenData;      /* pointer to corresponding Screen Color */
                                /* Characterization Data */
    unsigned char state;      /* XcmsInitNone, XcmsInitSuccess, XcmsInitDefault */
    char pad[3];
} XcmsPerScrnInfo;

typedef struct _XcmsCCC *XcmsCCC;

```

```

typedef Status (*XcmsCompressionProc)();

typedef Status (*XcmsWhiteAdjustProc)();

/*
 * XCMS Color Conversion Context
 */
typedef struct _XcmsCCC {
    Display      *dpy;                /* X Display */
    int          screenNumber;        /* X screen number */
    Visual       *visual;             /* X Visual */
    XcmsColor    clientWhitePt;       /* Client White Point */
    XcmsCompressionProc gamutCompProc; /* Gamut Compression Function */
    XPointer     gamutCompClientData; /* Gamut Comp Func Client Data */
    XcmsWhiteAdjustProc whitePtAdjProc; /* White Point Adjustment Function */
    XPointer     whitePtAdjClientData; /* White Pt Adj Func Client Data */
    XcmsPerScrnInfo *pPerScrnInfo;    /* pointer to per screen information */
                                        /* associated with the above display */
                                        /* screenNumber */
} XcmsCCCRec;

typedef Status (*XcmsScreenInitProc)();

typedef void (*XcmsScreenFreeProc)();

/*
 * Function List Pointer -- pointer to an array of function pointers.
 * The end of list is indicated by a NULL pointer.
 */
typedef Status (*XcmsConversionProc)();
typedef XcmsConversionProc *XcmsFuncListPtr;

typedef int (*XcmsParseStringProc)();

/*
 * Color Space -- per Color Space related data (Device-Independent
 * or Device-Dependent)
 */
typedef struct _XcmsColorSpace {
    char *prefix;                    /* Prefix of string format. */
    XcmsColorFormat id;              /* Format ID number. */
    XcmsParseStringProc parseString; /* String format parsing function */
    XcmsFuncListPtr to_CIEXYZ;       /* Pointer to an array of function */
                                    /* pointers such that when the */
                                    /* functions are executed in sequence */
                                    /* will convert a XcmsColor structure */
                                    /* from this color space to CIEXYZ */
                                    /* space. */
    XcmsFuncListPtr from_CIEXYZ;     /* Pointer to an array of function */
                                    /* pointers such that when the */
                                    /* functions are executed in sequence */
                                    /* will convert a XcmsColor structure */

```

```

/*    from CIEXYZ space to this color    */
/*    space.                             */
int inverse_flag; /* If 1, indicates that for 0 <= i < n */
/*    where n is the number of function */
/*    pointers in the lists to_CIEXYZ   */
/*    and from_CIEXYZ; for each function */
/*    to_CIEXYZ[i] its inverse function */
/*    is from_CIEXYZ[n - i].            */

} XcmsColorSpace;

/*
 * Screen Color Characterization Function Set -- per device class
 *    color space conversion functions.
 */
typedef struct _XcmsFunctionSet {
    XcmsColorSpace **DDColorSpaces;
/* Pointer to an array of pointers to */
/* Device-DEPENDENT color spaces      */
/* understood by this SCCFuncSet.     */
    XcmsScreenInitProc screenInitProc;
/* Screen initialization function that */
/* reads Screen Color Characterization*/
/* Data off properties on the screen's*/
/* root window.                       */
    XcmsScreenFreeProc screenFreeProc;
/* Function that frees the SCCData    */
/* structures.                        */
} XcmsFunctionSet;

```

Figure 10-7. Manifest Constants from <X11/keysymdef.h>

```
#define XK_VoidSymbol          0xFFFFF    /* void symbol */

#ifdef XK_MISCELLANY
/*
 * TTY Functions, cleverly chosen to map to ascii, for convenience of
 * programming, but could have been arbitrary (at the cost of lookup
 * tables in client code.
 */

#define XK_BackSpace          0xFF08    /* back space, back char */
#define XK_Tab                0xFF09
#define XK_Linefeed           0xFF0A    /* Linefeed, LF */
#define XK_Clear              0xFF0B
#define XK_Return             0xFF0D    /* Return, enter */
#define XK_Pause              0xFF13    /* Pause, hold */
#define XK_Scroll_Lock        0xFF14
#define XK_Escape             0xFF1B
#define XK_Delete             0xFFFF    /* Delete, rubout */

/* International & multi-key character composition */

#define XK_Multi_key          0xFF20    /* Multi-key character compose */

/* Japanese keyboard support */

#define XK_Kanji              0xFF21    /* Kanji, Kanji convert */
#define XK_Muhenkan           0xFF22    /* Cancel Conversion */
#define XK_Henkan_Mode        0xFF23    /* Start/Stop Conversion */
#define XK_Henkan             0xFF23    /* Alias for Henkan_Mode */
#define XK_Romaji             0xFF24    /* to Romaji */
#define XK_Hiragana           0xFF25    /* to Hiragana */
#define XK_Katakana           0xFF26    /* to Katakana */
#define XK_Hiragana_Katakana  0xFF27    /* Hiragana/Katakana toggle */
#define XK_Zenkaku            0xFF28    /* to Zenkaku */
#define XK_Hankaku            0xFF29    /* to Hankaku */
#define XK_Zenkaku_Hankaku    0xFF2A    /* Zenkaku/Hankaku toggle */
#define XK_Touroku            0xFF2B    /* Add to Dictionary */
#define XK_Massyo             0xFF2C    /* Delete from Dictionary */
#define XK_Kana_Lock          0xFF2D    /* Kana Lock */
#define XK_Kana_Shift         0xFF2E    /* Kana Shift */
#define XK_Eisu_Shift         0xFF2F    /* Alphanumeric Shift */
#define XK_Eisu_toggle        0xFF30    /* Alphanumeric toggle */

/* Cursor control & motion */

#define XK_Home               0xFF50
#define XK_Left               0xFF51    /* Move left, left arrow */
#define XK_Up                 0xFF52    /* Move up, up arrow */
#define XK_Right              0xFF53    /* Move right, right arrow */
```

```

#define XK_Down          0xFF54 /* Move down, down arrow */
#define XK_Prior         0xFF55 /* Prior, previous */
#define XK_Next          0xFF56 /* Next */
#define XK_End           0xFF57 /* EOL */
#define XK_Begin        0xFF58 /* BOL */

/* Misc Functions */

#define XK_Select        0xFF60 /* Select, mark */
#define XK_Print         0xFF61
#define XK_Execute       0xFF62 /* Execute, run, do */
#define XK_Insert        0xFF63 /* Insert, insert here */
#define XK_Undo          0xFF65 /* Undo, oops */
#define XK_Redo          0xFF66 /* redo, again */
#define XK_Menu          0xFF67
#define XK_Find          0xFF68 /* Find, search */
#define XK_Cancel        0xFF69 /* Cancel, stop, abort, exit */
#define XK_Help          0xFF6A /* Help, ? */
#define XK_Break         0xFF6B
#define XK_Mode_switch   0xFF7E /* Character set switch */
#define XK_script_switch 0xFF7E /* Alias for mode_switch */
#define XK_Num_Lock      0xFF7F

/* Keypad Functions, keypad numbers cleverly chosen to map to ascii */

#define XK_KP_Space      0xFF80 /* space */
#define XK_KP_Tab        0xFF89
#define XK_KP_Enter      0xFF8D /* enter */
#define XK_KP_F1         0xFF91 /* PF1, KP_A, ... */
#define XK_KP_F2         0xFF92
#define XK_KP_F3         0xFF93
#define XK_KP_F4         0xFF94
#define XK_KP_Equal       0xFFBD /* equals */
#define XK_KP_Multiply    0xFFAA
#define XK_KP_Add         0xFFAB
#define XK_KP_Separator   0xFFAC /* separator, often comma */
#define XK_KP_Subtract    0xFFAD
#define XK_KP_Decimal     0xFFAE
#define XK_KP_Divide      0xFFAF

#define XK_KP_0           0xFFB0
#define XK_KP_1           0xFFB1
#define XK_KP_2           0xFFB2
#define XK_KP_3           0xFFB3
#define XK_KP_4           0xFFB4
#define XK_KP_5           0xFFB5
#define XK_KP_6           0xFFB6
#define XK_KP_7           0xFFB7
#define XK_KP_8           0xFFB8
#define XK_KP_9           0xFFB9

```

```

/*
 * Auxilliary Functions; note the duplicate definitions for left and right
 * function keys; Sun keyboards and a few other manufactures have such
 * function key groups on the left and/or right sides of the keyboard.
 * We've not found a keyboard with more than 35 function keys total.
 */

#define XK_F1                0xFFBE
#define XK_F2                0xFFBF
#define XK_F3                0xFFC0
#define XK_F4                0xFFC1
#define XK_F5                0xFFC2
#define XK_F6                0xFFC3
#define XK_F7                0xFFC4
#define XK_F8                0xFFC5
#define XK_F9                0xFFC6
#define XK_F10               0xFFC7
#define XK_F11               0xFFC8
#define XK_L1                0xFFC8
#define XK_F12               0xFFC9
#define XK_L2                0xFFC9
#define XK_F13               0xFFCA
#define XK_L3                0xFFCA
#define XK_F14               0xFFCB
#define XK_L4                0xFFCB
#define XK_F15               0xFFCC
#define XK_L5                0xFFCC
#define XK_F16               0xFFCD
#define XK_L6                0xFFCD
#define XK_F17               0xFFCE
#define XK_L7                0xFFCE
#define XK_F18               0xFFCF
#define XK_L8                0xFFCF
#define XK_F19               0xFFD0
#define XK_L9                0xFFD0
#define XK_F20               0xFFD1
#define XK_L10               0xFFD1
#define XK_F21               0xFFD2
#define XK_R1                0xFFD2
#define XK_F22               0xFFD3
#define XK_R2                0xFFD3
#define XK_F23               0xFFD4
#define XK_R3                0xFFD4
#define XK_F24               0xFFD5
#define XK_R4                0xFFD5
#define XK_F25               0xFFD6
#define XK_R5                0xFFD6
#define XK_F26               0xFFD7
#define XK_R6                0xFFD7
#define XK_F27               0xFFD8
#define XK_R7                0xFFD8
#define XK_F28               0xFFD9
#define XK_R8                0xFFD9
#define XK_F29               0xFFDA

```

```

#define XK_R9                0xFFDA
#define XK_F30               0xFFDB
#define XK_R10               0xFFDB
#define XK_F31               0xFFDC
#define XK_R11               0xFFDC
#define XK_F32               0xFFDD
#define XK_R12               0xFFDD
#define XK_F33               0xFFDE
#define XK_R13               0xFFDE
#define XK_F34               0xFFDF
#define XK_R14               0xFFDF
#define XK_F35               0xFFE0
#define XK_R15               0xFFE0

/* Modifiers */

#define XK_Shift_L            0xFFE1 /* Left shift */
#define XK_Shift_R            0xFFE2 /* Right shift */
#define XK_Control_L          0xFFE3 /* Left control */
#define XK_Control_R          0xFFE4 /* Right control */
#define XK_Caps_Lock          0xFFE5 /* Caps lock */
#define XK_Shift_Lock         0xFFE6 /* Shift lock */

#define XK_Meta_L             0xFFE7 /* Left meta */
#define XK_Meta_R             0xFFE8 /* Right meta */
#define XK_Alt_L              0xFFE9 /* Left alt */
#define XK_Alt_R              0xFFEA /* Right alt */
#define XK_Super_L            0xFFEB /* Left super */
#define XK_Super_R            0xFFEC /* Right super */
#define XK_Hyper_L            0xFFED /* Left hyper */
#define XK_Hyper_R            0xFFEE /* Right hyper */
#endif /* XK_MISCELLANY */

/*
 * Latin 1
 * Byte 3 = 0
 */
#ifdef XK_LATIN1
#define XK_space              0x020
#define XK_exclam             0x021
#define XK_quotedbl           0x022
#define XK_numbersign         0x023
#define XK_dollar             0x024
#define XK_percent            0x025
#define XK_ampersand          0x026
#define XK_apostrophe         0x027
#define XK_parenleft          0x028
#define XK_parenright         0x029
#define XK_asterisk            0x02a
#define XK_plus               0x02b
#define XK_comma              0x02c
#define XK_minus              0x02d
#define XK_period             0x02e
#define XK_slash              0x02f

```

```
#define XK_0          0x030
#define XK_1          0x031
#define XK_2          0x032
#define XK_3          0x033
#define XK_4          0x034
#define XK_5          0x035
#define XK_6          0x036
#define XK_7          0x037
#define XK_8          0x038
#define XK_9          0x039
#define XK_colon      0x03a
#define XK_semicolon  0x03b
#define XK_less       0x03c
#define XK_equal      0x03d
#define XK_greater    0x03e
#define XK_question   0x03f
#define XK_at         0x040
#define XK_A          0x041
#define XK_B          0x042
#define XK_C          0x043
#define XK_D          0x044
#define XK_E          0x045
#define XK_F          0x046
#define XK_G          0x047
#define XK_H          0x048
#define XK_I          0x049
#define XK_J          0x04a
#define XK_K          0x04b
#define XK_L          0x04c
#define XK_M          0x04d
#define XK_N          0x04e
#define XK_O          0x04f
#define XK_P          0x050
#define XK_Q          0x051
#define XK_R          0x052
#define XK_S          0x053
#define XK_T          0x054
#define XK_U          0x055
#define XK_V          0x056
#define XK_W          0x057
#define XK_X          0x058
#define XK_Y          0x059
#define XK_Z          0x05a
#define XK_bracketleft 0x05b
#define XK_backslash  0x05c
#define XK_bracketright 0x05d
#define XK_asciicircum 0x05e
#define XK_underscore 0x05f
#define XK_grave      0x060
#define XK_a          0x061
#define XK_b          0x062
#define XK_c          0x063
#define XK_d          0x064
#define XK_e          0x065
```

```

#define XK_f          0x066
#define XK_g          0x067
#define XK_h          0x068
#define XK_i          0x069
#define XK_j          0x06a
#define XK_k          0x06b
#define XK_l          0x06c
#define XK_m          0x06d
#define XK_n          0x06e
#define XK_o          0x06f
#define XK_p          0x070
#define XK_q          0x071
#define XK_r          0x072
#define XK_s          0x073
#define XK_t          0x074
#define XK_u          0x075
#define XK_v          0x076
#define XK_w          0x077
#define XK_x          0x078
#define XK_y          0x079
#define XK_z          0x07a
#define XK_braceleft  0x07b
#define XK_bar        0x07c
#define XK_braceright 0x07d
#define XK_asciitilde 0x07e

#define XK_nobreakspace 0x0a0
#define XK_exclamdown  0x0a1
#define XK_cent         0x0a2
#define XK_sterling     0x0a3
#define XK_currency     0x0a4
#define XK_yen          0x0a5
#define XK_brokenbar    0x0a6
#define XK_section      0x0a7
#define XK_diaeresis    0x0a8
#define XK_copyright    0x0a9
#define XK_ordfeminine  0x0aa
#define XK_guillemotleft 0x0ab /* left angle quotation mark */
#define XK_notsign      0x0ac
#define XK_hyphen       0x0ad
#define XK_registered   0x0ae
#define XK_macron       0x0af
#define XK_degree       0x0b0
#define XK_plusminus    0x0b1
#define XK_twosuperior  0x0b2
#define XK_threesuperior 0x0b3
#define XK_acute        0x0b4
#define XK_mu           0x0b5
#define XK_paragraph    0x0b6
#define XK_periodcentered 0x0b7
#define XK_cedilla      0x0b8
#define XK_onesuperior  0x0b9
#define XK_masculine     0x0ba
#define XK_guillemotright 0x0bb /* right angle quotation mark */

```

```

#define XK_onequarter      0x0bc
#define XK_onehalf        0x0bd
#define XK_threequarters  0x0be
#define XK_questiondown   0x0bf
#define XK_Agrave         0x0c0
#define XK_Aacute         0x0c1
#define XK_Acircumflex    0x0c2
#define XK_Atilde         0x0c3
#define XK_Adiaeresis     0x0c4
#define XK_Aring          0x0c5
#define XK_AE             0x0c6
#define XK_Ccedilla       0x0c7
#define XK_Egrave         0x0c8
#define XK_Eacute         0x0c9
#define XK_Ecircumflex    0x0ca
#define XK_Ediaeresis     0x0cb
#define XK_Igrave         0x0cc
#define XK_Iacute         0x0cd
#define XK_Icircumflex    0x0ce
#define XK_Idiaeresis     0x0cf
#define XK_ETH            0x0d0
#define XK_Ntilde         0x0d1
#define XK_Ograve         0x0d2
#define XK_Oacute         0x0d3
#define XK_Ocircumflex    0x0d4
#define XK_Otilde         0x0d5
#define XK_Odiaeresis     0x0d6
#define XK_multiply       0x0d7
#define XK_Ooblique       0x0d8
#define XK_Ugrave         0x0d9
#define XK_Uacute         0x0da
#define XK_Ucircumflex    0x0db
#define XK_Udiaeresis     0x0dc
#define XK_Yacute         0x0dd
#define XK_THORN          0x0de
#define XK_ssharp         0x0df
#define XK_agrave         0x0e0
#define XK_aacute         0x0e1
#define XK_acircumflex    0x0e2
#define XK_atilde         0x0e3
#define XK_adiaeresis     0x0e4
#define XK_aring          0x0e5
#define XK_ae             0x0e6
#define XK_ccedilla       0x0e7
#define XK_egrave         0x0e8
#define XK_eacute         0x0e9
#define XK_ecircumflex    0x0ea
#define XK_ediaeresis     0x0eb
#define XK_igrave         0x0ec
#define XK_iacute         0x0ed
#define XK_icircumflex    0x0ee
#define XK_idiaeresis     0x0ef
#define XK_eth            0x0f0
#define XK_ntilde         0x0f1

```

```

#define XK_ograve          0x0f2
#define XK_oacute          0x0f3
#define XK_ocircumflex    0x0f4
#define XK_otilde          0x0f5
#define XK_odiaeresis      0x0f6
#define XK_division        0x0f7
#define XK_oslash          0x0f8
#define XK_ugrave          0x0f9
#define XK_uacute          0x0fa
#define XK_ucircumflex     0x0fb
#define XK_udiaeresis      0x0fc
#define XK_yacute          0x0fd
#define XK_thorn           0x0fe
#define XK_ydiaeresis      0x0ff
#endif /* XK_LATIN1 */

/*
 *   Latin 2
 *   Byte 3 = 1
 */

#ifdef XK_LATIN2
#define XK_Aogonek          0x1a1
#define XK_breve           0x1a2
#define XK_Lstroke         0x1a3
#define XK_Lcaron          0x1a5
#define XK_Sacute          0x1a6
#define XK_Scaron          0x1a9
#define XK_Scedilla        0x1aa
#define XK_Tcaron          0x1ab
#define XK_Zacute          0x1ac
#define XK_Zcaron          0x1ae
#define XK_Zabovedot       0x1af
#define XK_aogonek         0x1b1
#define XK_ogonek          0x1b2
#define XK_lstroke         0x1b3
#define XK_lcaron          0x1b5
#define XK_sacute          0x1b6
#define XK_caron           0x1b7
#define XK_scaron          0x1b9
#define XK_scedilla        0x1ba
#define XK_tcaron          0x1bb
#define XK_zacute          0x1bc
#define XK_doubleacute      0x1bd
#define XK_zcaron          0x1be
#define XK_zabovedot       0x1bf
#define XK_Racute          0x1c0
#define XK_Abreve          0x1c3
#define XK_Lacute          0x1c5
#define XK_Cacute          0x1c6
#define XK_Ccaron          0x1c8
#define XK_Eogonek         0x1ca
#define XK_Ecaron          0x1cc
#define XK_Dcaron          0x1cf

```

```

#define XK_Dstroke      0x1d0
#define XK_Nacute       0x1d1
#define XK_Ncaron       0x1d2
#define XK_Odoubleacute 0x1d5
#define XK_Rcaron       0x1d8
#define XK_Uring        0x1d9
#define XK_Udoubleacute 0x1db
#define XK_Tcedilla     0x1de
#define XK_racute       0x1e0
#define XK_abreve       0x1e3
#define XK_lacute       0x1e5
#define XK_cacute       0x1e6
#define XK_ccaron       0x1e8
#define XK_eogonek      0x1ea
#define XK_ecaron       0x1ec
#define XK_dcaron       0x1ef
#define XK_dstroke      0x1f0
#define XK_nacute       0x1f1
#define XK_ncaron       0x1f2
#define XK_odoubleacute 0x1f5
#define XK_udoubleacute 0x1fb
#define XK_rcaron       0x1f8
#define XK_uring        0x1f9
#define XK_tcedilla     0x1fe
#define XK_abovedot     0x1ff
#endif /* XK_LATIN2 */

/*
 *   Latin 3
 *   Byte 3 = 2
 */

#ifdef XK_LATIN3
#define XK_Hstroke      0x2a1
#define XK_Hcircumflex 0x2a6
#define XK_Iabovedot    0x2a9
#define XK_Gbreve       0x2ab
#define XK_Jcircumflex 0x2ac
#define XK_hstroke      0x2b1
#define XK_hcircumflex  0x2b6
#define XK_idotless     0x2b9
#define XK_gbreve       0x2bb
#define XK_jcircumflex  0x2bc
#define XK_Cabovedot    0x2c5
#define XK_Ccircumflex  0x2c6
#define XK_Gabovedot    0x2d5
#define XK_Gcircumflex  0x2d8
#define XK_Ubreve       0x2dd
#define XK_Scircumflex  0x2de
#define XK_cabovedot    0x2e5
#define XK_ccircumflex  0x2e6
#define XK_gabovedot    0x2f5
#define XK_gcircumflex  0x2f8
#define XK_ubreve       0x2fd

```

```

#define XK_scircumflex          0x2fe
#endif /* XK_LATIN3 */

/*
 *   Latin 4
 *   Byte 3 = 3
 */

#ifdef XK_LATIN4
#define XK_kra                   0x3a2
#define XK_Rcedilla              0x3a3
#define XK_Itilde                0x3a5
#define XK_Lcedilla              0x3a6
#define XK_Emacron               0x3aa
#define XK_Gcedilla              0x3ab
#define XK_Tslash                0x3ac
#define XK_rcedilla              0x3b3
#define XK_ityilde               0x3b5
#define XK_lcedilla              0x3b6
#define XK_emacon                0x3ba
#define XK_gcedilla              0x3bb
#define XK_tslash                0x3bc
#define XK_ENG                   0x3bd
#define XK_eng                   0x3bf
#define XK_Amacron               0x3c0
#define XK_Iogonek               0x3c7
#define XK_Eabovedot             0x3cc
#define XK_Imacron               0x3cf
#define XK_Ncedilla              0x3d1
#define XK_Omacron               0x3d2
#define XK_Kcedilla              0x3d3
#define XK_Uogonek               0x3d9
#define XK_Utilde                0x3dd
#define XK_Umacron               0x3de
#define XK_amacron               0x3e0
#define XK_iogonek               0x3e7
#define XK_eabovedot             0x3ec
#define XK_imacron               0x3ef
#define XK_ncedilla              0x3f1
#define XK_omacron               0x3f2
#define XK_kcedilla              0x3f3
#define XK_uogonek               0x3f9
#define XK_utilde                0x3fd
#define XK_umacron               0x3fe
#endif /* XK_LATIN4 */

/*
 *   Katakana
 *   Byte 3 = 4
 */

#ifdef XK_KATAKANA
#define XK_overline               0x47e

```

```

#define XK_kana_fullstop          0x4a1
#define XK_kana_openingbracket    0x4a2
#define XK_kana_closingbracket    0x4a3
#define XK_kana_comma             0x4a4
#define XK_kana_conjunctive       0x4a5
#define XK_kana_WO                 0x4a6
#define XK_kana_a                  0x4a7
#define XK_kana_i                  0x4a8
#define XK_kana_u                  0x4a9
#define XK_kana_e                  0x4aa
#define XK_kana_o                  0x4ab
#define XK_kana_ya                 0x4ac
#define XK_kana_yu                 0x4ad
#define XK_kana_yo                 0x4ae
#define XK_kana_tsu                0x4af
#define XK_prolongedsound          0x4b0
#define XK_kana_A                  0x4b1
#define XK_kana_I                  0x4b2
#define XK_kana_U                  0x4b3
#define XK_kana_E                  0x4b4
#define XK_kana_O                  0x4b5
#define XK_kana_KA                 0x4b6
#define XK_kana_KI                 0x4b7
#define XK_kana_KU                 0x4b8
#define XK_kana_KE                 0x4b9
#define XK_kana_KO                 0x4ba
#define XK_kana_SA                 0x4bb
#define XK_kana_SHI                0x4bc
#define XK_kana_SU                 0x4bd
#define XK_kana_SE                 0x4be
#define XK_kana_SO                 0x4bf
#define XK_kana_TA                 0x4c0
#define XK_kana_CHI                0x4c1
#define XK_kana_TSU                0x4c2
#define XK_kana_TE                 0x4c3
#define XK_kana_TO                 0x4c4
#define XK_kana_NA                 0x4c5
#define XK_kana_NI                 0x4c6
#define XK_kana_NU                 0x4c7
#define XK_kana_NE                 0x4c8
#define XK_kana_NO                 0x4c9
#define XK_kana_HA                 0x4ca
#define XK_kana_HI                 0x4cb
#define XK_kana_FU                 0x4cc
#define XK_kana_HE                 0x4cd
#define XK_kana_HO                 0x4ce
#define XK_kana_MA                 0x4cf
#define XK_kana_MI                 0x4d0
#define XK_kana_MU                 0x4d1
#define XK_kana_ME                 0x4d2
#define XK_kana_MO                 0x4d3
#define XK_kana_YA                 0x4d4
#define XK_kana_YU                 0x4d5
#define XK_kana_YO                 0x4d6

```

```

#define XK_kana_RA                0x4d7
#define XK_kana_RI                0x4d8
#define XK_kana_RU                0x4d9
#define XK_kana_RE                0x4da
#define XK_kana_RO                0x4db
#define XK_kana_WA                0x4dc
#define XK_kana_N                 0x4dd
#define XK_voicedsound            0x4de
#define XK_semivoicedsound        0x4df
#define XK_kana_switch            0xFF7E /* Alias for mode_switch */
#endif /* XK_KATAKANA */

/*
 * Arabic
 * Byte 3 = 5
 */

#ifdef XK_ARABIC
#define XK_Arabic_comma           0x5ac
#define XK_Arabic_semicolon       0x5bb
#define XK_Arabic_question_mark   0x5bf
#define XK_Arabic_hamza           0x5c1
#define XK_Arabic_maddaonalef     0x5c2
#define XK_Arabic_hamzaonalef     0x5c3
#define XK_Arabic_hamzaonwaw      0x5c4
#define XK_Arabic_hamzaunderalef  0x5c5
#define XK_Arabic_hamzaonyeh      0x5c6
#define XK_Arabic_alef            0x5c7
#define XK_Arabic_beh              0x5c8
#define XK_Arabic_tehmarbuta      0x5c9
#define XK_Arabic_teh             0x5ca
#define XK_Arabic_theh            0x5cb
#define XK_Arabic_jeem            0x5cc
#define XK_Arabic_hah             0x5cd
#define XK_Arabic_khah            0x5ce
#define XK_Arabic_dal             0x5cf
#define XK_Arabic_thal            0x5d0
#define XK_Arabic_ra              0x5d1
#define XK_Arabic_zain            0x5d2
#define XK_Arabic_seen            0x5d3
#define XK_Arabic_sheen          0x5d4
#define XK_Arabic_sad             0x5d5
#define XK_Arabic_dad             0x5d6
#define XK_Arabic_tah            0x5d7
#define XK_Arabic_zah            0x5d8
#define XK_Arabic_ain            0x5d9
#define XK_Arabic_ghain          0x5da
#define XK_Arabic_tatweel        0x5e0
#define XK_Arabic_feh            0x5e1
#define XK_Arabic_qaf            0x5e2
#define XK_Arabic_kaf            0x5e3
#define XK_Arabic_lam            0x5e4
#define XK_Arabic_meem           0x5e5
#define XK_Arabic_noon           0x5e6

```

```

#define XK_Arabic_ha                0x5e7
#define XK_Arabic_waw                0x5e8
#define XK_Arabic_alefmaksura        0x5e9
#define XK_Arabic_yeh                0x5ea
#define XK_Arabic_fathatan           0x5eb
#define XK_Arabic_dammatan           0x5ec
#define XK_Arabic_kasratan           0x5ed
#define XK_Arabic_fatha              0x5ee
#define XK_Arabic_damma              0x5ef
#define XK_Arabic_kasra              0x5f0
#define XK_Arabic_shadda             0x5f1
#define XK_Arabic_sukun              0x5f2
#define XK_Arabic_switch             0xFF7E /* Alias for mode_switch */
#endif /* XK_ARABIC */

/*
 * Cyrillic
 * Byte 3 = 6
 */
#ifdef XK_CYRILLIC
#define XK_Serbian_dje                0x6a1
#define XK_Macedonia_gje             0x6a2
#define XK_Cyrillic_io               0x6a3
#define XK_Ukrainian_ie              0x6a4
#define XK_Macedonia_dse             0x6a5
#define XK_Ukrainian_i               0x6a6
#define XK_Ukrainian_yi              0x6a7
#define XK_Cyrillic_je               0x6a8
#define XK_Cyrillic_lje              0x6a9
#define XK_Cyrillic_nje              0x6aa
#define XK_Serbian_tshe              0x6ab
#define XK_Macedonia_kje             0x6ac
#define XK_Byelorussian_shortu       0x6ae
#define XK_Cyrillic_dzhe             0x6af
#define XK_numerosign                0x6b0
#define XK_Serbian_DJE               0x6b1
#define XK_Macedonia_GJE             0x6b2
#define XK_Cyrillic_IO               0x6b3
#define XK_Ukrainian_IE              0x6b4
#define XK_Macedonia_DSE             0x6b5
#define XK_Ukrainian_I               0x6b6
#define XK_Ukrainian_YI              0x6b7
#define XK_Cyrillic_JE               0x6b8
#define XK_Cyrillic_LJE              0x6b9
#define XK_Cyrillic_NJE              0x6ba
#define XK_Serbian_TSHE              0x6bb
#define XK_Macedonia_KJE             0x6bc
#define XK_Byelorussian_SHORTU       0x6be
#define XK_Cyrillic_DZHE             0x6bf
#define XK_Cyrillic_yu               0x6c0
#define XK_Cyrillic_a                0x6c1
#define XK_Cyrillic_be               0x6c2
#define XK_Cyrillic_tse              0x6c3
#define XK_Cyrillic_de                0x6c4

```

```

#define XK_Cyrillic_ie          0x6c5
#define XK_Cyrillic_ef          0x6c6
#define XK_Cyrillic_ghe         0x6c7
#define XK_Cyrillic_ha          0x6c8
#define XK_Cyrillic_i           0x6c9
#define XK_Cyrillic_shorti      0x6ca
#define XK_Cyrillic_ka          0x6cb
#define XK_Cyrillic_el          0x6cc
#define XK_Cyrillic_em          0x6cd
#define XK_Cyrillic_en          0x6ce
#define XK_Cyrillic_o           0x6cf
#define XK_Cyrillic_pe          0x6d0
#define XK_Cyrillic_ya          0x6d1
#define XK_Cyrillic_er          0x6d2
#define XK_Cyrillic_es          0x6d3
#define XK_Cyrillic_te          0x6d4
#define XK_Cyrillic_u           0x6d5
#define XK_Cyrillic_zhe         0x6d6
#define XK_Cyrillic_ve          0x6d7
#define XK_Cyrillic_softsign    0x6d8
#define XK_Cyrillic_yeru        0x6d9
#define XK_Cyrillic_ze          0x6da
#define XK_Cyrillic_sha         0x6db
#define XK_Cyrillic_e           0x6dc
#define XK_Cyrillic_shcha       0x6dd
#define XK_Cyrillic_che         0x6de
#define XK_Cyrillic_hardsign    0x6df
#define XK_Cyrillic_YU          0x6e0
#define XK_Cyrillic_A           0x6e1
#define XK_Cyrillic_BE          0x6e2
#define XK_Cyrillic_TSE         0x6e3
#define XK_Cyrillic_DE          0x6e4
#define XK_Cyrillic_IE          0x6e5
#define XK_Cyrillic_EF          0x6e6
#define XK_Cyrillic_GHE         0x6e7
#define XK_Cyrillic_HA          0x6e8
#define XK_Cyrillic_I           0x6e9
#define XK_Cyrillic_SHORTI      0x6ea
#define XK_Cyrillic_KA          0x6eb
#define XK_Cyrillic_EL          0x6ec
#define XK_Cyrillic_EM          0x6ed
#define XK_Cyrillic_EN          0x6ee
#define XK_Cyrillic_O           0x6ef
#define XK_Cyrillic_PE          0x6f0
#define XK_Cyrillic_YA          0x6f1
#define XK_Cyrillic_ER          0x6f2
#define XK_Cyrillic_ES          0x6f3
#define XK_Cyrillic_TE          0x6f4
#define XK_Cyrillic_U           0x6f5
#define XK_Cyrillic_ZHE         0x6f6
#define XK_Cyrillic_VE          0x6f7
#define XK_Cyrillic_SOFTSIGN    0x6f8
#define XK_Cyrillic_YERU        0x6f9
#define XK_Cyrillic_ZE          0x6fa

```

```

#define XK_Cyrillic_SHA 0x6fb
#define XK_Cyrillic_E 0x6fc
#define XK_Cyrillic_SHCHA 0x6fd
#define XK_Cyrillic_CHE 0x6fe
#define XK_Cyrillic_HARDSIGN 0x6ff
#endif /* XK_CYRILLIC */

/*
 * Greek
 * Byte 3 = 7
 */

#ifdef XK_GREEK
#define XK_Greek_ALPHAaccent 0x7a1
#define XK_Greek_EPSILONaccent 0x7a2
#define XK_Greek_ETAaccent 0x7a3
#define XK_Greek_IOTAaccent 0x7a4
#define XK_Greek_IOTAdiaeresis 0x7a5
#define XK_Greek_OMICRONaccent 0x7a7
#define XK_Greek_UPSILONaccent 0x7a8
#define XK_Greek_UPSILONdieresis 0x7a9
#define XK_Greek_OMEGAaccent 0x7ab
#define XK_Greek_accentdieresis 0x7ae
#define XK_Greek_horizbar 0x7af
#define XK_Greek_alphaaccent 0x7b1
#define XK_Greek_epsilonaccent 0x7b2
#define XK_Greek_etaaccent 0x7b3
#define XK_Greek_iotaaccent 0x7b4
#define XK_Greek_iotadieresis 0x7b5
#define XK_Greek_iotaaccentdieresis 0x7b6
#define XK_Greek_omicronaccent 0x7b7
#define XK_Greek_upsilonaccent 0x7b8
#define XK_Greek_upsilondieresis 0x7b9
#define XK_Greek_upsilonaccentdieresis 0x7ba
#define XK_Greek_omegaaccent 0x7bb
#define XK_Greek_ALPHA 0x7c1
#define XK_Greek_BETA 0x7c2
#define XK_Greek_GAMMA 0x7c3
#define XK_Greek_DELTA 0x7c4
#define XK_Greek_EPSILON 0x7c5
#define XK_Greek_ZETA 0x7c6
#define XK_Greek_ETA 0x7c7
#define XK_Greek_THETA 0x7c8
#define XK_Greek_IOTA 0x7c9
#define XK_Greek_KAPPA 0x7ca
#define XK_Greek_LAMDA 0x7cb
#define XK_Greek_LAMBDA 0x7cb
#define XK_Greek_MU 0x7cc
#define XK_Greek_NU 0x7cd
#define XK_Greek_XI 0x7ce
#define XK_Greek_OMICRON 0x7cf
#define XK_Greek_PI 0x7d0
#define XK_Greek_RHO 0x7d1
#define XK_Greek_SIGMA 0x7d2

```

```

#define XK_Greek_TAU                0x7d4
#define XK_Greek_UPSILON            0x7d5
#define XK_Greek_PHI                0x7d6
#define XK_Greek_CHI                0x7d7
#define XK_Greek_PSI                0x7d8
#define XK_Greek_OMEGA              0x7d9
#define XK_Greek_alpha              0x7e1
#define XK_Greek_beta               0x7e2
#define XK_Greek_gamma              0x7e3
#define XK_Greek_delta              0x7e4
#define XK_Greek_epsilon            0x7e5
#define XK_Greek_zeta               0x7e6
#define XK_Greek_eta                0x7e7
#define XK_Greek_theta              0x7e8
#define XK_Greek_iota               0x7e9
#define XK_Greek_kappa              0x7ea
#define XK_Greek_lamda              0x7eb
#define XK_Greek_lambda             0x7eb
#define XK_Greek_mu                 0x7ec
#define XK_Greek_nu                 0x7ed
#define XK_Greek_xi                 0x7ee
#define XK_Greek_omicron            0x7ef
#define XK_Greek_pi                 0x7f0
#define XK_Greek_rho                0x7f1
#define XK_Greek_sigma              0x7f2
#define XK_Greek_finalsmallsigma    0x7f3
#define XK_Greek_tau                0x7f4
#define XK_Greek_upsilon            0x7f5
#define XK_Greek_phi                0x7f6
#define XK_Greek_chi                0x7f7
#define XK_Greek_psi                0x7f8
#define XK_Greek_omega              0x7f9
#define XK_Greek_switch             0xFF7E /* Alias for mode_switch */
#endif /* XK_GREEK */

/*
 * Technical
 * Byte 3 = 8
 */

#ifdef XK_TECHNICAL
#define XK_leftradical              0x8a1
#define XK_topleftradical          0x8a2
#define XK_horizconnector           0x8a3
#define XK_topintegral              0x8a4
#define XK_botintegral              0x8a5
#define XK_vertconnector            0x8a6
#define XK_topleftsqbracket         0x8a7
#define XK_botleftsqbracket         0x8a8
#define XK_toprightsqbracket        0x8a9
#define XK_botrightsqbracket        0x8aa
#define XK_topleftparens            0x8ab
#define XK_botleftparens            0x8ac
#define XK_toprightparens           0x8ad

```

```

#define XK_botrightparens          0x8ae
#define XK_leftmiddlecurlybrace    0x8af
#define XK_rightmiddlecurlybrace   0x8b0
#define XK_topleftsummation        0x8b1
#define XK_botleftsummation        0x8b2
#define XK_topvertsummationconnector 0x8b3
#define XK_botvertsummationconnector 0x8b4
#define XK_toprightsummation       0x8b5
#define XK_botrightsummation       0x8b6
#define XK_rightmiddlesummation    0x8b7
#define XK_lessthanequal           0x8bc
#define XK_notequal                0x8bd
#define XK_greaterthanequal        0x8be
#define XK_integral                0x8bf
#define XK_therefore               0x8c0
#define XK_variation               0x8c1
#define XK_infinity                0x8c2
#define XK_nabla                   0x8c5
#define XK_approximate             0x8c8
#define XK_similarequal            0x8c9
#define XK_ifonlyif               0x8cd
#define XK_implies                 0x8ce
#define XK_identical               0x8cf
#define XK_radical                 0x8d6
#define XK_includedin             0x8da
#define XK_includes                0x8db
#define XK_intersection            0x8dc
#define XK_union                   0x8dd
#define XK_logicaland              0x8de
#define XK_logicalor               0x8df
#define XK_partialderivative       0x8ef
#define XK_function                0x8f6
#define XK_leftarrow               0x8fb
#define XK_uparrow                 0x8fc
#define XK_rightarrow              0x8fd
#define XK_downarrow               0x8fe
#endif /* XK_TECHNICAL */

/*
 * Special
 * Byte 3 = 9
 */

#ifdef XK_SPECIAL
#define XK_blank                    0x9df
#define XK_soliddiamond            0x9e0
#define XK_checkerboard            0x9e1
#define XK_ht                      0x9e2
#define XK_ff                      0x9e3
#define XK_cr                      0x9e4
#define XK_lf                      0x9e5
#define XK_nl                      0x9e8
#define XK_vt                      0x9e9
#define XK_lowrightcorner          0x9ea

```

```

#define XK_uprightcorner          0x9eb
#define XK_upleftcorner          0x9ec
#define XK_lowleftcorner         0x9ed
#define XK_crossinglines         0x9ee
#define XK_horizlinescan1        0x9ef
#define XK_horizlinescan3        0x9f0
#define XK_horizlinescan5        0x9f1
#define XK_horizlinescan7        0x9f2
#define XK_horizlinescan9        0x9f3
#define XK_leftt                 0x9f4
#define XK_rightt                0x9f5
#define XK_bott                  0x9f6
#define XK_topt                  0x9f7
#define XK_vertbar                0x9f8
#endif /* XK_SPECIAL */

/*
 * Publishing
 * Byte 3 = a
 */

#ifdef XK_PUBLISHING
#define XK_emspace                0xaa1
#define XK_enspace                0xaa2
#define XK_em3space               0xaa3
#define XK_em4space               0xaa4
#define XK_digitspace             0xaa5
#define XK_punctspace             0xaa6
#define XK_thinspace              0xaa7
#define XK_hairspace              0xaa8
#define XK_emdash                 0xaa9
#define XK_endash                 0aaa
#define XK_signifblank            0aac
#define XK_ellipsis               0aae
#define XK_doubbaselinedot        0aaf
#define XK_onethird               0ab0
#define XK_twothirds              0ab1
#define XK_onefifth               0ab2
#define XK_twofifths              0ab3
#define XK_threefifths            0ab4
#define XK_fourfifths             0ab5
#define XK_onesixth               0ab6
#define XK_fivesixths             0ab7
#define XK_careof                 0ab8
#define XK_figdash                0abb
#define XK_leftanglebracket       0abc
#define XK_decimalpoint           0abd
#define XK_rightanglebracket      0abe
#define XK_marker                 0abf
#define XK_oneeighth              0ac3
#define XK_threeeighths           0ac4
#define XK_fiveeighths            0ac5
#define XK_seveneighths           0ac6
#define XK_trademark              0ac9

```

```

#define XK_signaturemark 0xaca
#define XK_trademarkincircle 0xacb
#define XK_leftopentriangle 0xacc
#define XK_rightopentriangle 0xacd
#define XK_emopencircle 0xace
#define XK_emopenrectangle 0xacf
#define XK_leftsinglequotemark 0xad0
#define XK_rightsinglequotemark 0xad1
#define XK_leftdoublequotemark 0xad2
#define XK_rightdoublequotemark 0xad3
#define XK_prescription 0xad4
#define XK_minutes 0xad6
#define XK_seconds 0xad7
#define XK_latincross 0xad9
#define XK_hexagram 0xada
#define XK_filledrectbullet 0xadb
#define XK_filledlefttribullet 0xadc
#define XK_filledrighttribullet 0xadd
#define XK_emfilledcircle 0xade
#define XK_emfilledrect 0xadf
#define XK_enopencircbullet 0xae0
#define XK_enopensquarebullet 0xae1
#define XK_openrectbullet 0xae2
#define XK_opentribulletup 0xae3
#define XK_opentribulletdown 0xae4
#define XK_openstar 0xae5
#define XK_enfilledcircbullet 0xae6
#define XK_enfilledsqbullet 0xae7
#define XK_filledtribulletup 0xae8
#define XK_filledtribulletdown 0xae9
#define XK_leftpointer 0xaea
#define XK_rightpointer 0xaeb
#define XK_club 0xaec
#define XK_diamond 0xaed
#define XK_heart 0xae
#define XK_maltesecross 0xaf0
#define XK_dagger 0xaf1
#define XK_doubledagger 0xaf2
#define XK_checkmark 0xaf3
#define XK_ballotcross 0xaf4
#define XK_musicalsharp 0xaf5
#define XK_musicalflat 0xaf6
#define XK_malesymbol 0xaf7
#define XK_femalesymbol 0xaf8
#define XK_telephone 0xaf9
#define XK_telephonerecorder 0xafa
#define XK_phonographcopyright 0xafb
#define XK_caret 0xafc
#define XK_singlelowquotemark 0xafd
#define XK_doublelowquotemark 0xafe
#define XK_cursor 0xaff
#endif /* XK_PUBLISHING */

/*

```

```

*   APL
*   Byte 3 = b
*/

#ifdef XK_APL
#define XK_leftcaret      0xba3
#define XK_rightcaret     0xba6
#define XK_downcaret     0xba8
#define XK_upcaret       0xba9
#define XK_overbar       0xbc0
#define XK_downtack      0xbc2
#define XK_upshoe        0xbc3
#define XK_downstile     0xbc4
#define XK_underbar      0xbc6
#define XK_jot           0xbca
#define XK_quad          0xbcc
#define XK_uptack        0xbce
#define XK_circle        0xbcf
#define XK_upstile      0xbd3
#define XK_downshoe     0xbd6
#define XK_rightshoe    0xbd8
#define XK_leftshoe     0xbda
#define XK_lefttack     0xbdc
#define XK_righttack    0xbfc
#endif /* XK_APL */

/*
*   Hebrew
*   Byte 3 = c
*/

#ifdef XK_HEBREW
#define XK_hebrew_doublelowline 0xcdf
#define XK_hebrew_aleph         0xce0
#define XK_hebrew_bet           0xce1
#define XK_hebrew_gimel        0xce2
#define XK_hebrew_dalet        0xce3
#define XK_hebrew_he           0xce4
#define XK_hebrew_waw          0xce5
#define XK_hebrew_zain         0xce6
#define XK_hebrew_chet         0xce7
#define XK_hebrew_tet          0xce8
#define XK_hebrew_yod          0xce9
#define XK_hebrew_finalkaph    0xcea
#define XK_hebrew_kaph         0xceb
#define XK_hebrew_lamed        0xcec
#define XK_hebrew_finalmem     0xced
#define XK_hebrew_mem          0xcee
#define XK_hebrew_finalnun     0xcef
#define XK_hebrew_nun         0xcf0
#define XK_hebrew_samech       0xcf1
#define XK_hebrew_ayin        0xcf2
#define XK_hebrew_finalpe     0xcf3
#define XK_hebrew_pe          0xcf4

```

```
#define XK_hebrew_finalzade      0xcf5
#define XK_hebrew_zade          0xcf6
#define XK_hebrew_qoph          0xcf7
#define XK_hebrew_resh          0xcf8
#define XK_hebrew_shin          0xcf9
#define XK_hebrew_taw            0xcfa
#define XK_Hebrew_switch        0xFF7E /* Alias for mode_switch */
```

Figure 10-8. Manifest Constants from <X11/cursorfont.h>

```

/* $XConsortium: cursorfont.h,v 1.2 88/09/06 16:44:27 jim Exp $ */
#define XC_num_glyphs 154
#define XC_X_cursor 0
#define XC_arrow 2
#define XC_based_arrow_down 4
#define XC_based_arrow_up 6
#define XC_boat 8
#define XC_bogosity 10
#define XC_bottom_left_corner 12
#define XC_bottom_right_corner 14
#define XC_bottom_side 16
#define XC_bottom_tee 18
#define XC_box_spiral 20
#define XC_center_ptr 22
#define XC_circle 24
#define XC_clock 26
#define XC_coffee_mug 28
#define XC_cross 30
#define XC_cross_reverse 32
#define XC_crosshair 34
#define XC_diamond_cross 36
#define XC_dot 38
#define XC_dotbox 40
#define XC_double_arrow 42
#define XC_draft_large 44
#define XC_draft_small 46
#define XC_draped_box 48
#define XC_exchange 50
#define XC_fleur 52
#define XC_gobbler 54
#define XC_gumby 56
#define XC_hand1 58
#define XC_hand2 60
#define XC_heart 62
#define XC_icon 64
#define XC_iron_cross 66
#define XC_left_ptr 68
#define XC_left_side 70
#define XC_left_tee 72
#define XC_leftbutton 74
#define XC_ll_angle 76
#define XC_lr_angle 78
#define XC_man 80
#define XC_middlebutton 82
#define XC_mouse 84
#define XC_pencil 86
#define XC_pirate 88
#define XC_plus 90
#define XC_question_arrow 92
#define XC_right_ptr 94
#define XC_right_side 96

```

```
#define XC_right_tee 98
#define XC_rightbutton 100
#define XC_rtl_logo 102
#define XC_sailboat 104
#define XC_sb_down_arrow 106
#define XC_sb_h_double_arrow 108
#define XC_sb_left_arrow 110
#define XC_sb_right_arrow 112
#define XC_sb_up_arrow 114
#define XC_sb_v_double_arrow 116
#define XC_shuttle 118
#define XC_sizing 120
#define XC_spider 122
#define XC_spraycan 124
#define XC_star 126
#define XC_target 128
#define XC_tcross 130
#define XC_top_left_arrow 132
#define XC_top_left_corner 134
#define XC_top_right_corner 136
#define XC_top_side 138
#define XC_top_tee 140
#define XC_trek 142
#define XC_ul_angle 144
#define XC_umbrella 146
#define XC_ur_angle 148
#define XC_watch 150
#define XC_xterm 152
```

The X Extension Library

Overview

This chapter identifies binary interfaces for libXext, which are defined in the document entitled “X11 Non-rectangular Window Shape Extension” by Keith Packard (copyright X Consortium).

The Extension Library Interfaces

The interfaces listed below in Table 10-4 have been included in SCD2.2 because they are REQUIRED to be present on all compliant systems, in the dynamic library `/usr/lib/libXext.so.0`. Note that for this release of the SCD the interfaces exported by this library are restricted only to those concerned with the X11 Nonrectangular Window Shape Extension.

Figure 10-9 details the manifest constants and visible data structures associated with the Extension library.

Table 10-4. Contents of libXext

XShapeCombineMask
XShapeCombineRectangles
XShapeCombineRegion
XShapeCombineShape
XShapeGetRectangles
XShapeInputSelected
XShapeOffsetShape
XShapeQueryExtension
XShapeQueryExtents
XShapeQueryVersion
XShapeSelectInput

Figure 10-9. Manifest Constants from <X11/extensions/shape.h>

```
#define ShapeSet                0
#define ShapeUnion              1
#define ShapeIntersect         2
#define ShapeSubtract          3
#define ShapeInvert            4

#define ShapeBounding           0
#define ShapeClip              1

#define ShapeNotifyMask        (1L << 0)
#define ShapeNotify            0
```

The X Toolkit

Overview

This chapter identifies binary interfaces for `libXt`, which are defined in the document *X Toolkit Intrinsics - C Language Interface* by Joel McCormack, Paul Asente, and Ralph R. Swick which is distributed by the X Consortium with X Version 11, Release 5.

In addition, all SCD 2.2 systems will support the X 11 Release 5 Protocol, as defined in *The X Window System (Third Edition)* by Robert W. Scheifler and James Gettys (Digital Press, ISBN 1-55558-088-2).

Finally, all SCD 2.2 systems will support the mechanisms and conventions as specified in the *Inter-Client Communications Convention Manual (ICCCM)* in *The X Window System (Third Edition)* by Robert W. Scheifler and James Gettys (Digital Press, ISBN 1-55558-088-2).

The libXt Interfaces

The interfaces listed below in Table 10-5 and Table 10-6 have been included in SCD 2.2 because they are REQUIRED to be present on all compliant systems, in the dynamic library `/usr/lib/libXt.so.5`.

Table 10-7 contains a list of unsafe macros. These macros should be avoided by application programmers which are trying to build portable SPARC applications.

Table 10-8 contains the exported data which are also REQUIRED to be present in `libXt.so.5`. The format of these entries is: `data[size]`. Data without a size are opaque.

Conformant systems are also REQUIRED to have `/usr/lib/libXt.so.4` in order to support SPARC applications written to conform to versions 2.0 and 2.1 of the *SPARC Compliance Definition*. Since the X Version 11, Release 5 specification is a proper superset of the X Version 11, Release 4 specification, system vendors can provide this support by simply making a link to `/usr/lib/libXt.so.5` for the file `/usr/lib/libXt.so.4` as part of the system installation process. If an application executable references `/usr/lib/libXt.so.4` and does not reference `/usr/lib/libXt.so.5`, the application may not use any functionality defined by X11R5 but not defined by X11R4. See the *SPARC Compliance Definition 2.1* for a list of X11R4 components. The file name `/usr/lib/libXt.so.4` is a DEPRECATED interface effective November 1st, 1993. Also DEPRECATED effective November 1st, 1993 are the functions found in Table 10-6 on page 10-86. Any of the DEPRECATED interfaces may be removed from this specification as early as November 1st, 1996 so new applications should not be dependent on them.

Figures 10-10 through 10-18 detail the manifest constants and visible data structures associated with the X Toolkit library.

Figures 10-19 through 10-26 detail the manifest constants and visible data structures needed by widget programmers. Only widget programmers should use the information in these figures.

Table 10-5. Contents of libxt, Part 1 of 2

XtAddCallback	XtConfigureWidget
XtAddCallbacks	XtConvertAndStore
XtAddEventHandler	XtConvertCase
XtAddExposureToRegion	XtCreateApplicationContext
XtAddGrab	XtCreateManagedWidget
XtAddRawEventHandler	XtCreatePopupShell
XtAllocateGC	XtCreateWidget
XtAppAddActionHook	XtCreateWindow
XtAppAddActions	XtCvtColorToPixel
XtAppAddInput	XtCvtIntToBool
XtAppAddTimeOut	XtCvtIntToBoolean
XtAppAddWorkProc	XtCvtIntToColor
XtAppCreateShell	XtCvtIntToFloat
XtAppError	XtCvtIntToFont
XtAppErrorMsg	XtCvtIntToPixel
XtAppGetErrorDatabase	XtCvtIntToPixmap
XtAppGetErrorDatabaseText	XtCvtIntToShort
XtAppGetSelectionTimeout	XtCvtIntToUnsignedChar
XtAppInitialize	XtCvtStringToAcceleratorTable
XtAppMainLoop	XtCvtStringToAtom
XtAppNextEvent	XtCvtStringToBool
XtAppPeekEvent	XtCvtStringToBoolean
XtAppPending	XtCvtStringToCursor
XtAppProcessEvent	XtCvtStringToDimension
XtAppReleaseCacheRefs	XtCvtStringToDisplay
XtAppSetErrorHandler	XtCvtStringToFile
XtAppSetErrorMsgHandler	XtCvtStringToFloat
XtAppSetFallbackResources	XtCvtStringToFont
XtAppSetSelectionTimeout	XtCvtStringToFontSet
XtAppSetTypeConverter	XtCvtStringToFontStruct
XtAppSetWarningHandler	XtCvtStringToInitialState
XtAppSetWarningMsgHandler	XtCvtStringToInt
XtAppWarning	XtCvtStringToPixel
XtAppWarningMsg	XtCvtStringToShort
XtAugmentTranslations	XtCvtStringToTranslationTable
XtBuildEventMask	XtCvtStringToUnsignedChar
XtCallAcceptFocus	XtCvtStringToVisual
XtCallActionProc	XtDatabase
XtCallbackExclusive	XtDestroyApplicationContext
XtCallbackNone	XtDestroyWidget
XtCallbackNonexclusive	XtDisownSelection
XtCallbackPopdown	XtDispatchEvent
XtCallbackReleaseCacheRef	XtDisplay
XtCallbackReleaseCacheRefList	XtDisplayInitialize
XtCallCallbackList	XtDisplayOfObject
XtCallCallbacks	XtDisplayStringConversionWarning
XtCallConverter	XtDisplayToApplicationContext
XtCalloc	XtFindFile
XtClass	XtFree
XtCloseDisplay	XtGetActionKeysym

XtGetActionList	XtNameToWidget
XtGetApplicationNameAndClass	XtNewString
XtGetApplicationResources	XtOpenDisplay
XtGetConstraintResourceList	XtOverrideTranslations
XtGetGC	XtOwnSelection
XtGetKeysymTable	XtOwnSelectionIncremental
XtGetMultiClickTime	XtParent
XtGetResourceList	XtParseAcceleratorTable
XtGetSelectionRequest	XtParseTranslationTable
XtGetSelectionValue	XtPopdown
XtGetSelectionValueIncremental	XtPopup
XtGetSelectionValues	XtPopupSpringLoaded
XtGetSelectionValuesIncremental	XtQueryGeometry
XtGetSubresources	XtRealizeWidget
XtGetSubvalues	XtRealloc
XtGetValues	XtRegisterCaseConverter
XtGrabButton	XtRegisterGrabAction
XtGrabKey	XtReleaseGC
XtGrabKeyboard	XtRemoveActionHook
XtGrabPointer	XtRemoveAllCallbacks
XtHasCallbacks	XtRemoveCallback
XtInitializeWidgetClass	XtRemoveCallbacks
XtInsertEventHandler	XtRemoveEventHandler
XtInsertRawEventHandler	XtRemoveGrab
XtInstallAccelerators	XtRemoveInput
XtInstallAllAccelerators	XtRemoveRawEventHandler
XtIsApplicationShell	XtRemoveTimeOut
XtIsComposite	XtRemoveWorkProc
XtIsConstraint	XtResizeWidget
XtIsManaged	XtResizeWindow
XtIsObject	XtResolvePathname
XtIsOverrideShell	XtScreen
XtIsRealized	XtScreenDatabase
XtIsRectObj	XtScreenOfObject
XtIsSensitive	XtSetKeyboardFocus
XtIsShell	XtSetKeyTranslator
XtIsSubclass	XtSetLanguageProc
XtIsTopLevelShell	XtSetMappedWhenManaged
XtIsTransientShell	XtSetMultiClickTime
XtIsVendorShell	XtSetSensitive
XtIsWidget	XtSetSubvalues
XtIsWMShell	XtSetTypeConverter
XtKeysymToKeycodeList	XtSetValues
XtLastTimestampProcessed	XtSetWMColormapWindows
XtMakeGeometryRequest	XtSuperclass
XtMakeResizeRequest	XtToolkitInitialize
XtMalloc	XtTranslateCoords
XtManageChild	XtTranslateKey
XtManageChildren	XtTranslateKeycode
XtMapWidget	XtUngrabButton
XtMenuPopupAction	XtUngrabKey
XtMergeArgLists	XtUngrabKeyboard
XtMoveWidget	XtUngrabPointer
XtName	XtUninstallTranslations

XtUnmanageChild
XtUnmanageChildren
XtUnmapWidget
XtUnrealizeWidget
XtVaAppCreateShell
XtVaAppInitialize
XtVaCreateArgsList
XtVaCreateManagedWidget
XtVaCreatePopupShell
XtVaCreateWidget
XtVaGetApplicationResources
XtVaGetSubresources
XtVaGetSubvalues
XtVaGetValues
XtVaSetSubvalues
XtVaSetValues
XtWidgetToApplicationContext
XtWindow
XtWindowOfObject
XtWindowToWidget

Deprecated X Toolkit Functions

Table 10-6 is a list of Xt functions which are now DEPRECATED but continue to be supported for the sake of old applications. The X Consortium defines these functions as obsolete. When MIT stops shipping these functions as part of the X11 sample implementation these functions may be removed from the SCD. Application developers are discouraged from using these functions in new applications. The effective date of DEPRECATION is November 1st, 1993. These function interfaces may be removed from the SCD as early as November 1st, 1996.

Table 10-6: Contents of libXt, Part 2 of 2

Obsolete Function	Superseded By
XtAddActions	XtAppAddActions
XtAddConverter	XtSetTypeConverter
XtAddInput	XtAppAddInput
XtAddTimeOut	XtAppAddTimeOut
XtAddWorkProc	XtAppAddWorkProc
XtAppAddConverter	XtAppSetTypeConverter
XtConvert	XtConvertAnStore
XtCreateApplicationShell	XtAppCreateShell
XtDestroyGC	XtReleaseGC
XtDirectConvert	XtCallConverter
XtError	XtAppError
XtErrorMsg	XtAppErrorMsg
XtGetErrorDatabase	XtAppGetErrorDatabase
XtGetErrorDatabaseText	XtAppGetErrorDatabaseText
XtGetSelectionTimeout	XtAppGetSelectionTimeout
XtInitialize	XtAppInitialize
XtMainLoop	XtAppMainLoop
XtNextEvent	XtAppNextEvent
XtPeekEvent	XtAppPeekEvent
XtPending	XtAppPending
XtProcessEvent	XtAppProcessEvent
XtSetErrorHandler	XtAppSetErrorHandler
XtSetErrorMsgHandler	XtAppSetErrorMsgHandler
XtSetSelectionTimeout	XtAppSetSelectionTimeout
XtSetWarningHandler	XtAppSetWarningHandler

Table10-6: Contents of libXt, Part 2 of 2

Obsolete Function	Superseded By
XtSetWarningMsgHandler	XtAppSetWarningMsgHandler
XtStringConversionWarning	XtDisplayStringConversionWarning
XtWarning	XtAppWarning
XtWarningMsg	XtAppWarningMsg

Unsafe Macros

Ordinarily, this document only specifies the system resources available for use by applications on all SPARC compliant systems and makes no comment regarding the programming language or API used by application programmers for building applications. But SPARC International recognizes that many SPARC applications will be written in the C programming language and are likely to use the API specified by the X Consortium. Some of the macros defined by the X Consortium for the X Toolkit access symbols which are not defined to be part of the ABI.

All of these macros are defined by the `<X11/Intrinsic.h>` header file. Fortunately, each of these macros have ABI compliant functions which can be used in their place. Table 10-7 has a list of these macros. The ABI compliant functions have the same name as the the unsafe macros. This means that C programmers that wish to use the functions, rather than the macros, must `"#undef"` the macros in their source code after the point where the source code includes `<X11/Intrinsic.h>`.

Table 10-7: Unsafe Macros

XtIsApplicationShell
XtIsComposite
XtIsConstraint
XtIsOverrideShell
XtIsRectObj
XtIsShell
XtIsTopLevelShell
XtIsTransientShell
XtIsVendorShell
XtIsWidget
XtIsWMShell

Table 10-8. Exported Data for libxt.

```

applicationShellClassRec[ 0x9c]
applicationShellWidgetClass[ 0x4]
colorConvertArgs[ 0x18]
compositeClassRec[ 0x88]
compositeWidgetClass[ 0x4]
constraintClassRec[ 0xa4]
constraintWidgetClass[ 0x4]
coreWidgetClass[ 0x4]
objectClass[ 0x4]
objectClassRec[ 0x74]
overrideShellClassRec[ 0x90]
overrideShellWidgetClass[ 0x4]
rectObjClass[ 0x4]
rectObjClassRec[ 0x74]
screenConvertArg[ 0xc]
shellClassRec[ 0x8c]
shellWidgetClass[ 0x4]
topLevelShellClassRec[ 0x98]
topLevelShellWidgetClass[ 0x4]
transientShellClassRec[ 0x98]
transientShellWidgetClass[ 0x4]
vendorShellClassRec[ 0x94]
vendorShellWidgetClass[ 0x4]
widgetClass[ 0x4]
widgetClassRec[ 0x74]
wmShellClassRec[ 0x90]
wmShellWidgetClass[ 0x4]
XtCXtToolkitError[ 0x4]
_XtInherit1
_XtInheritTranslations2
XtShellStrings3
XtStrings4

```

1. `_XtInherit` is only for use by widget programmers.

2. `_XtInheritTranslations` is only for use by widget programmers.

3. `XtShellStrings` and `XtStrings` are reserved for use by the X Toolkit Library but applications which are intended to be portable at the binary level must refrain from accessing these global symbols. The definition of these global data may change in incompatible ways in future releases of X.

4. See note number 3.

Figure 10-10. Manifest Constants and Data Types from <X11/Composite.h>

```
typedef struct _CompositeClassRec *CompositeWidgetClass;  
  
typedef Cardinal (*XtOrderProc)();
```

Figure 10-11. Manifest Constants and Data Types from <X11/Constraint.h>

```
typedef struct _ConstraintClassRec *ConstraintWidgetClass;
```

Figure 10-12. Manifest Constants and Data Types from <X11/Core.h>

```
typedef struct _WidgetClassRec *CoreWidgetClass;  
typedef struct _WidgetRec *CoreWidget;
```

Figure 10-13. Manifest Constants and Data Types from <X11/Intrinsic.h>

```
#define XtSpecificationRelease 5

typedef char *String;

typedef struct _WidgetRec *Widget;
typedef Widget *WidgetList;
typedef struct _WidgetClassRec *WidgetClass;
typedef struct _CompositeRec *CompositeWidget;
typedef struct _XtActionsRec *XtActionList;
typedef struct _XtEventRec *XtEventTable;
typedef struct _XtBoundAccActionRec *XtBoundAccActions;

typedef struct _XtAppStruct *XtAppContext;
typedef unsigned long XtValueMask;
typedef unsigned long XtIntervalId;
typedef unsigned long XtInputId;
typedef unsigned long XtWorkProcId;
typedef unsigned int XtGeometryMask;
typedef unsigned long XtGCMask; /* Mask of values that are used by widget*/
typedef unsigned long Pixel; /* Index into colormap */
typedef int XtCacheType;
#define XtCacheNone 0x001
#define XtCacheAll 0x002
#define XtCacheByDisplay 0x003
#define XtCacheRefCount 0x100

/*****
 *
 * System Dependent Definitions; see spec for specific range
 * requirements. Do not assume every implementation uses the
 * same base types!
 *
 *
 * XtArgVal ought to be a union of XtPointer, char *, long, int *, and proc *
 * but casting to union types is not really supported.
 *
 * So the typedef for XtArgVal should be chosen such that
 *
 *      sizeof (XtArgVal) >=      sizeof(XtPointer)
 *                                sizeof(char *)
 *                                sizeof(long)
 *                                sizeof(int *)
 *                                sizeof(proc *)
 *
 * ArgLists rely heavily on the above typedef.
 *
 *****/
typedef char Boolean;
typedef long XtArgVal;
typedef unsigned char XtEnum;
```

```

typedef unsigned int    Cardinal;
typedef unsigned short  Dimension; /* Size in pixels */
typedef short           Position; /* Offset from 0 coordinate */

typedef char*           XtPointer;

/* The type Opaque is NOT part of the Xt standard, do NOT use it. */
/* (It remains here only for backward compatibility.) */
typedef XtPointer       Opaque;

typedef struct _TranslationData *XtTranslations;
typedef struct _TranslationData *XtAccelerators;
typedef unsigned int Modifiers;

typedef void (*XtActionProc)();

typedef XtActionProc* XtBoundActions;

typedef struct _XtActionsRec{
    String      string;
    XtActionProc proc;
} XtActionsRec;

typedef enum {
/* address mode      parameter representation */
/* -----          ----- */
    XtAddress,        /* address */
    XtBaseOffset,     /* offset */
    XtImmediate,      /* constant */
    XtResourceString, /* resource name string */
    XtResourceQuark,  /* resource name quark */
    XtWidgetBaseOffset, /* offset from ancestor */
    XtProcedureArg     /* procedure to invoke */
} XtAddressMode;

typedef struct {
    XtAddressMode address_mode;
    XtPointer      address_id;
    Cardinal       size;
} XtConvertArgRec, *XtConvertArgList;

typedef void (*XtConvertArgProc)();

typedef struct {
    XtGeometryMask request_mode;
    Position x, y;
    Dimension width, height, border_width;
    Widget sibling;
    int stack_mode; /* Above, Below, TopIf, BottomIf, Opposite, DontChange */
} XtWidgetGeometry;

/* Additions to Xlib geometry requests: ask what would happen, don't do it */
#define XtCWQueryOnly (1 << 7)

```

```

/* Additions to Xlib stack modes: don't change stack order */
#define XtSMDontChange 5

typedef void (*XtConverter)(); /* obsolete */

typedef Boolean (*XtTypeConverter)();

typedef void (*XtDestructor)();

typedef Opaque XtCacheRef;

typedef Opaque XtActionHookId;

typedef void (*XtActionHookProc)();

typedef void (*XtKeyProc)();

typedef void (*XtCaseProc)();

typedef void (*XtEventHandler)();
typedef unsigned long EventMask;

typedef enum {XtListHead, XtListTail } XtListPosition;

typedef unsigned long XtInputMask;
#define XtInputNoneMask 0L
#define XtInputReadMask (1L<<0)
#define XtInputWriteMask (1L<<1)
#define XtInputExceptMask (1L<<2)

typedef void (*XtTimerCallbackProc)();

typedef void (*XtInputCallbackProc)();

typedef struct {
    String      name;
    XtArgVal    value;
} Arg, *ArgList;

typedef XtPointer XtVarArgsList;

typedef void (*XtCallbackProc)();

typedef struct _XtCallbackRec {
    XtCallbackProc callback;
    XtPointer      closure;
} XtCallbackRec, *XtCallbackList;

typedef enum {
    XtCallbackNoList,
    XtCallbackHasNone,
    XtCallbackHasSome
} XtCallbackStatus;

```

```

typedef enum {
    XtGeometryYes,          /* Request accepted. */
    XtGeometryNo,           /* Request denied. */
    XtGeometryAlmost,       /* Request denied, but willing to take replyBox. */
    XtGeometryDone          /* Request accepted and done. */
} XtGeometryResult;

typedef enum {XtGrabNone, XtGrabNonexclusive, XtGrabExclusive} XtGrabKind;

typedef struct {
    Widget  shell_widget;
    Widget  enable_widget;
} XtPopdownIDRec, *XtPopdownID;

typedef struct _XtResource {
    String    resource_name; /* Resource name */
    String    resource_class; /* Resource class */
    String    resource_type; /* Representation type desired */
    Cardinal  resource_size; /* Size in bytes of representation */
    Cardinal  resource_offset; /* Offset from base to put resource value */
    String    default_type; /* representation type of specified default */
    XtPointer default_addr; /* Address of default resource */
} XtResource, *XtResourceList;

typedef void (*XtResourceDefaultProc)();

typedef String (*XtLanguageProc)();

typedef void (*XtErrorMsgHandler)();

typedef void (*XtErrorHandler)();

typedef void (*XtCreatePopupChildProc)();

typedef Boolean (*XtWorkProc)();

typedef struct {
    char match;
    String substitution;
} SubstitutionRec, *Substitution;

typedef Boolean (*XtFilePredicate)();

typedef XtPointer XtRequestId;

typedef Boolean (*XtConvertSelectionProc)();

typedef void (*XtLoseSelectionProc)();

typedef void (*XtSelectionDoneProc)();

typedef void (*XtSelectionCallbackProc)();

typedef void (*XtLoseSelectionIncrProc)();

```

```
typedef void (*XtSelectionDoneIncrProc)();

typedef Boolean (*XtConvertSelectionIncrProc)();

typedef void (*XtCancelConvertSelectionProc)();

/*****
 *
 * Event Management
 *
 *****/

/* XtAllEvents is valid only for XtRemoveEventHandler and
 * XtRemoveRawEventHandler; don't use it to select events!
 */
#define XtAllEvents ((EventMask) -1L)

/*****
 *
 * Event Gathering Routines
 *
 *****/

#define XtIMXEvent          1
#define XtIMTimer           2
#define XtIMAlternateInput  4
#define XtIMAll (XtIMXEvent | XtIMTimer | XtIMAlternateInput)

/*****
 *
 * Vararg lists
 *
 *****/

#define XtVaNestedList  "XtVaNestedList"
#define XtVaTypedArg    "XtVaTypedArg"

/*****
 *
 * Toolkit initialization
 *
 *****/

#define XtUnspecifiedPixmap ((Pixmap)2)
#define XtUnspecifiedShellInt (-1)
#define XtUnspecifiedWindow ((Window)2)
#define XtUnspecifiedWindowGroup ((Window)3)
#define XtDefaultForeground  "XtDefaultForeground"
#define XtDefaultBackground "XtDefaultBackground"
#define XtDefaultFont        "XtDefaultFont"
#define XtDefaultFontSet     "XtDefaultFontSet"

/*****
```

```
*  
* Selections  
*  
*****/  
  
#define XT_CONVERT_FAIL (Atom)0x80000001
```

Figure 10-14. Manifest Constants and Data Types from <X11/Object.h>

```
typedef struct _ObjectRec *Object;  
typedef struct _ObjectClassRec *ObjectClass;
```

Figure 10-15. Manifest Constants and Data Types from <X11/RectObj.h>

```
typedef struct _RectObjRec *RectObj;  
typedef struct _RectObjClassRec *RectObjClass;
```

Figure 10-16. Manifest Constants and Data Types from <X11/Shell.h>

```

/*****
 *
 * Shell Widget
 *
 *****/
/*
 * Shell-specific resources names, classes, and a representation type.
 */

/* The string definitions are automatically generated. */
/* Do not edit. */

#define XtNiconName "iconName"
#define XtCIconName "IconName"
#define XtNiconPixmap "iconPixmap"
#define XtCIconPixmap "IconPixmap"
#define XtNiconWindow "iconWindow"
#define XtCIconWindow "IconWindow"
#define XtNiconMask "iconMask"
#define XtCIconMask "IconMask"
#define XtNwindowGroup "windowGroup"
#define XtCWindowGroup "WindowGroup"
#define XtNvisual "visual"
#define XtCVisual "Visual"
#define XtNtitleEncoding "titleEncoding"
#define XtCTitleEncoding "TitleEncoding"
#define XtNsaveUnder "saveUnder"
#define XtCSaveUnder "SaveUnder"
#define XtNtransient "transient"
#define XtCTransient "Transient"
#define XtNoverrideRedirect "overrideRedirect"
#define XtCOverrideRedirect "OverrideRedirect"
#define XtNtransientFor "transientFor"
#define XtCTransientFor "TransientFor"
#define XtNiconNameEncoding "iconNameEncoding"
#define XtCIconNameEncoding "IconNameEncoding"
#define XtNallowShellResize "allowShellResize"
#define XtCAllowShellResize "AllowShellResize"
#define XtNcreatePopupChildProc "createPopupChildProc"
#define XtCCreatePopupChildProc "CreatePopupChildProc"
#define XtNtitle "title"
#define XtCTitle "Title"
#define XtRAtom "Atom"
#define XtNargc "argc"
#define XtCArgc "Argc"
#define XtNargv "argv"
#define XtCArgv "Argv"
#define XtNiconX "iconX"
#define XtCIconX "IconX"
#define XtNiconY "iconY"
#define XtCIconY "IconY"

```

```

#define XtNinput "input"
#define XtCInput "Input"
#define XtNiconic "iconic"
#define XtCIconic "Iconic"
#define XtNinitialState "initialState"
#define XtCInitialState "InitialState"
#define XtNgeometry "geometry"
#define XtCGeometry "Geometry"
#define XtNbaseWidth "baseWidth"
#define XtCBaseWidth "BaseWidth"
#define XtNbaseHeight "baseHeight"
#define XtCBaseHeight "BaseHeight"
#define XtNwinGravity "winGravity"
#define XtCWinGravity "WinGravity"
#define XtNminWidth "minWidth"
#define XtCMinWidth "MinWidth"
#define XtNminHeight "minHeight"
#define XtCMinHeight "MinHeight"
#define XtNmaxWidth "maxWidth"
#define XtCMaxWidth "MaxWidth"
#define XtNmaxHeight "maxHeight"
#define XtCMaxHeight "MaxHeight"
#define XtNwidthInc "widthInc"
#define XtCWidthInc "WidthInc"
#define XtNheightInc "heightInc"
#define XtCHeightInc "HeightInc"
#define XtNminAspectY "minAspectY"
#define XtCMinAspectY "MinAspectY"
#define XtNmaxAspectY "maxAspectY"
#define XtCMaxAspectY "MaxAspectY"
#define XtNminAspectX "minAspectX"
#define XtCMinAspectX "MinAspectX"
#define XtNmaxAspectX "maxAspectX"
#define XtCMaxAspectX "MaxAspectX"
#define XtNwmTimeout "wmTimeout"
#define XtCWmTimeout "WmTimeout"
#define XtNwaitForWm "waitforwm"
#define XtCWaitForWm "Waitforwm"

/* Class record constants */

typedef struct _ShellClassRec *ShellWidgetClass;
typedef struct _OverrideShellClassRec *OverrideShellWidgetClass;
typedef struct _WMShellClassRec *WMShellWidgetClass;
typedef struct _TransientShellClassRec *TransientShellWidgetClass;
typedef struct _TopLevelShellClassRec *TopLevelShellWidgetClass;
typedef struct _ApplicationShellClassRec *ApplicationShellWidgetClass;

```

Figure 10-17. Manifest Constants and Data Types from <X11/StringDefs.h>

```
#define XtNaccelerators "accelerators"
#define XtNallowHoriz "allowHoriz"
#define XtNallowVert "allowVert"
#define XtNancestorSensitive "ancestorSensitive"
#define XtNbackground "background"
#define XtNbackgroundPixmap "backgroundPixmap"
#define XtNbitmap "bitmap"
#define XtNborderColor "borderColor"
#define XtNborder "borderColor"
#define XtNborderPixmap "borderPixmap"
#define XtNborderWidth "borderWidth"
#define XtNcallback "callback"
#define XtNchildren "children"
#define XtNcolormap "colormap"
#define XtNdepth "depth"
#define XtNdestroyCallback "destroyCallback"
#define XtNeditType "editType"
#define XtNfile "file"
#define XtNfont "font"
#define XtNforceBars "forceBars"
#define XtNforeground "foreground"
#define XtNfunction "function"
#define XtNheight "height"
#define XtNhighlight "highlight"
#define XtNhSpace "hSpace"
#define XtNindex "index"
#define XtNinitialResourcesPersistent "initialResourcesPersistent"
#define XtNinnerHeight "innerHeight"
#define XtNinnerWidth "innerWidth"
#define XtNinnerWindow "innerWindow"
#define XtNinsertPosition "insertPosition"
#define XtNinternalHeight "internalHeight"
#define XtNinternalWidth "internalWidth"
#define XtNjumpProc "jumpProc"
#define XtNjustify "justify"
#define XtNknobHeight "knobHeight"
#define XtNknobIndent "knobIndent"
#define XtNknobPixel "knobPixel"
#define XtNknobWidth "knobWidth"
#define XtNlabel "label"
#define XtNlength "length"
#define XtNlowerRight "lowerRight"
#define XtNmappedWhenManaged "mappedWhenManaged"
#define XtNmenuEntry "menuEntry"
#define XtNname "name"
#define XtNnotify "notify"
#define XtNnumChildren "numChildren"
#define XtNorientation "orientation"
#define XtNparameter "parameter"
#define XtNpixmap "pixmap"
#define XtNpopupCallback "popupCallback"
```

```

#define XtNpopdownCallback "popdownCallback"
#define XtNresize "resize"
#define XtNreverseVideo "reverseVideo"
#define XtNscreen "screen"
#define XtNscrollProc "scrollProc"
#define XtNscrollDCursor "scrollDCursor"
#define XtNscrollHCursor "scrollHCursor"
#define XtNscrollLCursor "scrollLCursor"
#define XtNscrollRCursor "scrollRCursor"
#define XtNscrollUCursor "scrollUCursor"
#define XtNscrollVCursor "scrollVCursor"
#define XtNselection "selection"
#define XtNselectionArray "selectionArray"
#define XtNsensitive "sensitive"
#define XtNshown "shown"
#define XtNspace "space"
#define XtNstring "string"
#define XtNtextOptions "textOptions"
#define XtNtextSink "textSink"
#define XtNtextSource "textSource"
#define XtNthickness "thickness"
#define XtNthumb "thumb"
#define XtNthumbProc "thumbProc"
#define XtNtop "top"
#define XtNtranslations "translations"
#define XtNunrealizeCallback "unrealizeCallback"
#define XtNupdate "update"
#define XtNuseBottom "useBottom"
#define XtNuseRight "useRight"
#define XtNvalue "value"
#define XtNvSpace "vSpace"
#define XtNwidth "width"
#define XtNwindow "window"
#define XtNx "x"
#define XtNy "y"
#define XtCAccelerators "Accelerators"
#define XtCBackground "Background"
#define XtCBitmap "Bitmap"
#define XtCBoolean "Boolean"
#define XtCBorderColor "BorderColor"
#define XtCBorderWidth "BorderWidth"
#define XtCCallback "Callback"
#define XtCColormap "Colormap"
#define XtCColor "Color"
#define XtCCursor "Cursor"
#define XtCDepth "Depth"
#define XtCEditType "EditType"
#define XtCEventBindings "EventBindings"
#define XtCFile "File"
#define XtCFont "Font"
#define XtCForeground "Foreground"
#define XtCFraction "Fraction"
#define XtCFunction "Function"
#define XtCHeight "Height"

```

```

#define XtCHSpace "HSpace"
#define XtCIndex "Index"
#define XtCInitialResourcesPersistent "InitialResourcesPersistent"
#define XtCInsertPosition "InsertPosition"
#define XtCInterval "Interval"
#define XtCJustify "Justify"
#define XtCKnobIndent "KnobIndent"
#define XtCKnobPixel "KnobPixel"
#define XtCLabel "Label"
#define XtCLength "Length"
#define XtCMappedWhenManaged "MappedWhenManaged"
#define XtCMargin "Margin"
#define XtCMenuEntry "MenuEntry"
#define XtCNotify "Notify"
#define XtCOrientation "Orientation"
#define XtCParameter "Parameter"
#define XtCPixmap "Pixmap"
#define XtCPosition "Position"
#define XtCReadOnly "ReadOnly"
#define XtCResize "Resize"
#define XtCReverseVideo "ReverseVideo"
#define XtCScreen "Screen"
#define XtCScrollProc "ScrollProc"
#define XtCScrollDCursor "ScrollDCursor"
#define XtCScrollHCursor "ScrollHCursor"
#define XtCScrollLCursor "ScrollLCursor"
#define XtCScrollRCursor "ScrollRCursor"
#define XtCScrollUCursor "ScrollUCursor"
#define XtCScrollVCursor "ScrollVCursor"
#define XtCSelection "Selection"
#define XtCSensitive "Sensitive"
#define XtCSelectionArray "SelectionArray"
#define XtCSpace "Space"
#define XtCString "String"
#define XtCTextOptions "TextOptions"
#define XtCTextPosition "TextPosition"
#define XtCTextSink "TextSink"
#define XtCTextSource "TextSource"
#define XtCThickness "Thickness"
#define XtCThumb "Thumb"
#define XtCTranslations "Translations"
#define XtCValue "Value"
#define XtCVSpace "VSpace"
#define XtCWidth "Width"
#define XtCWindow "Window"
#define XtCX "X"
#define XtCY "Y"
#define XtRAcceleratorTable "AcceleratorTable"
#define XtRAtom "Atom"
#define XtRBitmap "Bitmap"
#define XtRBool "Bool"
#define XtRBoolean "Boolean"
#define XtRCallback "Callback"
#define XtRCallProc "CallProc"

```

```

#define XtRCardinal "Cardinal"
#define XtRColor "Color"
#define XtRColormap "Colormap"
#define XtRCursor "Cursor"
#define XtRDimension "Dimension"
#define XtRDisplay "Display"
#define XtREditMode "EditMode"
#define XtREnum "Enum"
#define XtRFile "File"
#define XtRFloat "Float"
#define XtRFont "Font"
#define XtRFontStruct "FontStruct"
#define XtRFunction "Function"
#define XtRGeometry "Geometry"
#define XtRImmediate "Immediate"
#define XtRInitialState "InitialState"
#define XtRInt "Int"
#define XtRJustify "Justify"
#define XtRLongBoolean "Bool"
#define XtRObject "Object"
#define XtROrientation "Orientation"
#define XtRPixel "Pixel"
#define XtRPixmap "Pixmap"
#define XtRPointer "Pointer"
#define XtRPosition "Position"
#define XtRScreen "Screen"
#define XtRShort "Short"
#define XtRString "String"
#define XtRStringArray "StringArray"
#define XtRStringTable "StringTable"
#define XtRUnsignedChar "UnsignedChar"
#define XtRTranslationTable "TranslationTable"
#define XtRVisual "Visual"
#define XtRWidget "Widget"
#define XtRWidgetClass "WidgetClass"
#define XtRWidgetList "WidgetList"
#define XtRWindow "Window"
#define XtEoff "off"
#define XtEfalse "false"
#define XtEno "no"
#define XtEon "on"
#define XtEtrue "true"
#define XtEyes "yes"
#define XtEvertical "vertical"
#define XtEhorizontal "horizontal"
#define XtEtextRead "read"
#define XtEtextAppend "append"
#define XtEtextEdit "edit"
#define XtExtdefaultbackground "xtdefaultbackground"
#define XtExtdefaultforeground "xtdefaultforeground"
#define XtExtdefaultfont "xtdefaultfont"
#define XtNfontSet "fontSet"
#define XtRFontSet "FontSet"
#define XtCFontSet "FontSet"

```

Figure 10-18. Manifest Constants and Data Types from <X11/Vendor.h>

```
typedef struct _VendorShellClassRec *VendorShellWidgetClass;
```

Subclassing Xt Widgets

Figures 10-19 through 10-26 are intended to be used by widget programmers only. This information is included so widget programmers can subclass Xt widgets. Ordinary application programmers should never write code which depends on the definitions found in these tables.

The subclassing of widgets is only supported for the Xt widgets. It is not supporting for either the OLIT widget set or the Motif widget set.

Figure 10-19. Manifest Constants and Data Types from <X11/CompositeP.h>

```

/*****
 *
 * Additional instance fields for widgets of (sub)class 'Composite'
 *
 *****/

typedef struct _CompositePart {
    WidgetList  children;          /* array of ALL widget children */
    Cardinal    num_children;      /* total number of widget children */
    Cardinal    num_slots;         /* number of slots in children array */
    XtOrderProc insert_position;   /* compute position of new child */
} CompositePart, *CompositePtr;

typedef struct _CompositeRec {
    CorePart    core;
    CompositePart composite;
} CompositeRec;

/*****
 *
 * Additional class fields for widgets of (sub)class 'Composite'
 *
 *****/

typedef struct _CompositeClassPart {
    XtGeometryHandler geometry_manager; /* geometry manager for children */
    XtWidgetProc      change_managed;   /* change managed state of child */
    XtWidgetProc      insert_child;     /* physically add child to parent */
    XtWidgetProc      delete_child;     /* physically remove child */
    XtPointer          extension;        /* pointer to extension record */
} CompositeClassPart, *CompositePartPtr;

typedef struct {
    XtPointer next_extension; /* 1st 4 mandated for all extension records */
    XrmQuark record_type;     /* NULLQUARK; on CompositeClassPart */
    long version;             /* must be XtCompositeExtensionVersion */
    Cardinal record_size;     /* sizeof(CompositeClassExtensionRec) */
    Boolean accepts_objects;
} CompositeClassExtensionRec, *CompositeClassExtension;

typedef struct _CompositeClassRec {
    CoreClassPart core_class;
    CompositeClassPart composite_class;
} CompositeClassRec;

#define XtCompositeExtensionVersion 1L
#define XtInheritGeometryManager ((XtGeometryHandler) _XtInherit)
#define XtInheritChangeManaged ((XtWidgetProc) _XtInherit)
#define XtInheritInsertChild ((XtWidgetProc) _XtInherit)
#define XtInheritDeleteChild ((XtWidgetProc) _XtInherit)

```

Figure 10-20. Manifest Constants and Data Types from <X11/ConstrainP.h>

```
typedef struct _ConstraintPart {
    XtPointer mumble;          /* No new fields, keep C compiler happy */
} ConstraintPart;

typedef struct _ConstraintRec {
    CorePart      core;
    CompositePart composite;
    ConstraintPart constraint;
} ConstraintRec, *ConstraintWidget;

typedef struct _ConstraintClassPart {
    XtResourceList resources;      /* constraint resource list          */
    Cardinal      num_resources;   /* number of constraints in list     */
    Cardinal      constraint_size; /* size of constraint record         */
    XtInitProc    initialize;      /* constraint initialization          */
    XtWidgetProc  destroy;         /* constraint destroy proc           */
    XtSetValuesFunc set_values;    /* constraint set_values proc        */
    XtPointer     extension;       /* pointer to extension record       */
} ConstraintClassPart;

typedef struct {
    XtPointer next_extension;      /* 1st 4 mandated for all extension records */
    XrmQuark  record_type;        /* NULLQUARK; on ConstraintClassPart */
    long      version;            /* must be XtConstraintExtensionVersion */
    Cardinal  record_size;        /* sizeof(ConstraintClassExtensionRec) */
    XtArgsProc get_values_hook;
} ConstraintClassExtensionRec, *ConstraintClassExtension;

typedef struct _ConstraintClassRec {
    CoreClassPart      core_class;
    CompositeClassPart composite_class;
    ConstraintClassPart constraint_class;
} ConstraintClassRec;

#define XtConstraintExtensionVersion 1L
```

Figure 10-21. Manifest Constants and Data Types from <X11/CoreP.h>

```
#define XtInheritTranslations ((String) &_XtInheritTranslations)
#define XtInheritRealize ((XtRealizeProc) _XtInherit)
#define XtInheritResize ((XtWidgetProc) _XtInherit)
#define XtInheritExpose ((XtExposeProc) _XtInherit)
#define XtInheritSetValuesAlmost ((XtAlmostProc) _XtInherit)
#define XtInheritAcceptFocus ((XtAcceptFocusProc) _XtInherit)
#define XtInheritQueryGeometry ((XtGeometryHandler) _XtInherit)
#define XtInheritDisplayAccelerator ((XtStringProc) _XtInherit)

/*****
 * Widget Core Data Structures
 *
 *****/

typedef struct _CorePart {
    Widget      self;           /* pointer to widget itself */
    WidgetClass widget_class;   /* pointer to Widget's ClassRec */
    Widget      parent;        /* parent widget */
    XrmName     xrm_name;       /* widget resource name quarkified */
    Boolean     being_destroyed; /* marked for destroy */
    XtCallbackList destroy_callbacks; /* who to call when widget destroyed */
    XtPointer    constraints;    /* constraint record */
    Position    x, y;           /* window position */
    Dimension   width, height;  /* window dimensions */
    Dimension   border_width;   /* window border width */
    Boolean     managed;        /* is widget geometry managed? */
    Boolean     sensitive;      /* is widget sensitive to user events */
    Boolean     ancestor_sensitive; /* are all ancestors sensitive? */
    XtEventTable event_table;   /* private to event dispatcher */
    XtTMRRec    tm;            /* translation management */
    XtTranslations accelerators; /* accelerator translations */
    Pixel       border_pixel;   /* window border pixel */
    Pixmap      border_pixmap;  /* window border pixmap or NULL */
    WidgetList  popup_list;     /* list of popups */
    Cardinal    num_popups;     /* how many popups */
    String      name;           /* widget resource name */
    Screen      *screen;        /* window's screen */
    Colormap    colormap;       /* colormap */
    Window      window;         /* window ID */
    Cardinal    depth;          /* number of planes in window */
    Pixel       background_pixel; /* window background pixel */
    Pixmap      background_pixmap; /* window background pixmap or NULL */
    Boolean     visible;        /* is window mapped and not occluded? */
    Boolean     mapped_when_managed; /* map window if it's managed? */
} CorePart;

typedef struct _WidgetRec {
    CorePart core;
} WidgetRec, CoreRec;
```

```

/*****
 *
 * Core Class Structure. Widgets, regardless of their class, will have
 * these fields. All widgets of a given class will have the same values
 * for these fields. Widgets of a given class may also have additional
 * common fields. These additional fields are included in incremental
 * class structures, such as CommandClass.
 *
 * The fields that are specific to this subclass, as opposed to fields that
 * are part of the superclass, are called "subclass fields" below. Many
 * procedures are responsible only for the subclass fields, and not for
 * any superclass fields.
 *
 *****/

typedef struct _CoreClassPart {
    WidgetClass    superclass;          /* pointer to superclass ClassRec */
    String         class_name;          /* widget resource class name */
    Cardinal       widget_size;         /* size in bytes of widget record */
    XtProc         class_initialize;     /* class initialization proc */
    XtWidgetClassProc class_part_initialize; /* dynamic initialization */
    XtEnum         class_inited;        /* has class been initialized? */
    XtInitProc     initialize;          /* initialize subclass fields */
    XtArgsProc     initialize_hook;     /* notify that initialize called */
    XtRealizeProc  realize;             /* XCreateWindow for widget */
    XtActionList   actions;             /* widget semantics name to proc map */
    Cardinal       num_actions;         /* number of entries in actions */
    XtResourceList resources;           /* resources for subclass fields */
    Cardinal       num_resources;       /* number of entries in resources */
    XrmClass       xrm_class;           /* resource class quarkified */
    Boolean        compress_motion;     /* compress MotionNotify for widget */
    XtEnum         compress_exposure;   /* compress Expose events for widget */
    Boolean        compress_enterleave; /* compress enter and leave events */
    Boolean        visible_interest;    /* select for VisibilityNotify */
    XtWidgetProc   destroy;             /* free data for subclass pointers */
    XtWidgetProc   resize;             /* geom manager changed widget size */
    XtExposeProc   expose;             /* redisplay window */
    XtSetValuesFunc set_values;         /* set subclass resource values */
    XtArgsFunc     set_values_hook;     /* notify that set_values called */
    XtAlmostProc   set_values_almost;   /* set_values got "Almost" geo reply */
    XtArgsProc     get_values_hook;     /* notify that get_values called */
    XtAcceptFocusProc accept_focus;    /* assign input focus to widget */
    XtVersionType  version;            /* version of intrinsics used */
    XtPointer      callback_private;    /* list of callback offsets */
    String         tm_table;           /* state machine */
    XtGeometryHandler query_geometry;   /* return preferred geometry */
    XtStringProc   display_accelerator; /* display your accelerator */
    XtPointer      extension;          /* pointer to extension record */
} CoreClassPart;

typedef struct _WidgetClassRec {
    CoreClassPart core_class;
} WidgetClassRec, CoreClassRec;

```

```
#define coreClassRec widgetClassRec
```

Figure 10-22. Manifest Constants and Data Types from <X11/IntrinsicP.h>

```
typedef struct {
    XrmQuark    xrm_name;           /* Resource name quark          */
    XrmQuark    xrm_class;          /* Resource class quark         */
    XrmQuark    xrm_type;           /* Resource representation type quark */
    Cardinal    xrm_size;           /* Size in bytes of representation */
    long int    xrm_offset;         /* -offset-1                    */
    XrmQuark    xrm_default_type;   /* Default representation type quark */
    XtPointer    xrm_default_addr; /* Default resource address      */
} XrmResource, *XrmResourceList;

typedef unsigned long XtVersionType;

#define XT_VERSION 11
#define XT_REVISION 5
#define XtVersion (XT_VERSION * 1000 + XT_REVISION)
#define XtVersionDontCheck 0

typedef void (*XtProc)();

typedef void (*XtWidgetClassProc)();

typedef void (*XtWidgetProc)();

typedef Boolean (*XtAcceptFocusProc)();

typedef void (*XtArgsProc)();

typedef void (*XtInitProc)();

typedef Boolean (*XtSetValuesFunc)();

typedef Boolean (*XtArgsFunc)();

typedef void (*XtAlmostProc)();

typedef void (*XtExposeProc)();

/* compress_exposure options*/
#define XtExposeNoCompress ((XtEnum)False)
#define XtExposeCompressSeries ((XtEnum)True)
#define XtExposeCompressMultiple 2
#define XtExposeCompressMaximal 3

/* modifiers */
#define XtExposeGraphicsExpose 0x10
#define XtExposeGraphicsExposeMerged 0x20
#define XtExposeNoExpose 0x40

typedef void (*XtRealizeProc)();
```

```
typedef XtGeometryResult (*XtGeometryHandler)();

typedef void (*XtStringProc)();

typedef struct _XtTMRec {
    XtTranslations  translations;      /* private to Translation Manager */
    XtBoundActions  proc_table;        /* procedure bindings for actions */
    struct _XtStateRec *current_state; /* Translation Manager state ptr */
    unsigned long   lastEventTime;
} XtTMRec, *XtTM;

extern Widget _XtWindowedAncestor( /* internal; implementation-dependent */);

extern void _XtInherit();

extern void XtCreateWindow();

extern void XtResizeWidget();

extern void XtMoveWidget();

extern void XtConfigureWidget();

extern void XtResizeWindow();
```

Figure 10-23. Data Types from <X11/ObjectP.h>

```

/*****
 * Object Instance Data Structures
 *
 *****/
/* these fields match CorePart and can not be changed */

typedef struct _ObjectPart {
    Widget      self;           /* pointer to widget itself      */
    WidgetClass  widget_class;  /* pointer to Widget's ClassRec  */
    Widget      parent;        /* parent widget                 */
    XrmName      xrm_name;      /* widget resource name quarkified */
    Boolean      being_destroyed; /* marked for destroy           */
    XtCallbackList destroy_callbacks; /* who to call when widget destroyed */
    XtPointer     constraints;   /* constraint record             */
} ObjectPart;

typedef struct _ObjectRec {
    ObjectPart  object;
} ObjectRec;

/*****
 * Object Class Data Structures
 *
 *****/
/* these fields match CoreClassPart and can not be changed */
/* ideally these structures would only contain the fields required;
   but because the CoreClassPart cannot be changed at this late date
   extraneous fields are necessary to make the field offsets match */

typedef struct _ObjectClassPart {

    WidgetClass  superclass;    /* pointer to superclass ClassRec */
    String       class_name;    /* widget resource class name     */
    Cardinal     widget_size;   /* size in bytes of widget record */
    XtProc       class_initialize; /* class initialization proc      */
    XtWidgetClassProc class_part_initialize; /* dynamic initialization      */
    XtEnum       class_initied; /* has class been initialized?    */
    XtInitProc   initialize;    /* initialize subclass fields     */
    XtArgsProc   initialize_hook; /* notify that initialize called  */
    XtProc       obj1;          /* NULL                           */
    XtProc       obj2;          /* NULL                           */
    Cardinal     obj3;          /* NULL                           */
    XtResourceList resources;   /* resources for subclass fields  */
    Cardinal     num_resources; /* number of entries in resources */
    XrmClass      xrm_class;    /* resource class quarkified      */
    Boolean      obj4;          /* NULL                           */
    Boolean      obj5;          /* NULL                           */
    Boolean      obj6;          /* NULL                           */
    Boolean      obj7;          /* NULL                           */
    XtWidgetProc  destroy;      /* free data for subclass pointers */
    XtProc       obj8;          /* NULL                           */

```

```

XtProc          obj9;          /* NULL */
XtSetValuesFunc set_values;    /* set subclass resource values */
XtArgsFunc      set_values_hook; /* notify that set_values called */
XtProc          obj10;         /* NULL */
XtArgsProc      get_values_hook; /* notify that get_values called */
XtProc          obj11;         /* NULL */
XtVersionType   version;       /* version of intrinsics used */
XtPointer       callback_private; /* list of callback offsets */
String          obj12;         /* NULL */
XtProc          obj13;         /* NULL */
XtProc          obj14;         /* NULL */
XtPointer       extension;     /* pointer to extension record */
}ObjectClassPart;

typedef struct _ObjectClassRec {
    ObjectClassPart object_class;
} ObjectClassRec;

```

Figure 10-24. Data Types from <X11/RectObjP.h>

```

/*****
 * Rectangle Object Instance Data Structures
 *
 *****/
/* these fields match CorePart and can not be changed */

typedef struct _RectObjPart {
    Position      x, y;                /* rectangle position          */
    Dimension     width, height;       /* rectangle dimensions        */
    Dimension     border_width;       /* rectangle border width      */
    Boolean       managed;             /* is widget geometry managed? */
    Boolean       sensitive;           /* is widget sensitive to user events */
    Boolean       ancestor_sensitive; /* are all ancestors sensitive? */
} RectObjPart;

typedef struct _RectObjRec {
    ObjectPart object;
    RectObjPart rectangle;
} RectObjRec;

/*****
 * Rectangle Object Class Data Structures
 *
 *****/
/* these fields match CoreClassPart and can not be changed */
/* ideally these structures would only contain the fields required;
   but because the CoreClassPart cannot be changed at this late date
   extraneous fields are necessary to make the field offsets match */

typedef struct _RectObjClassPart {
    WidgetClass   superclass;          /* pointer to superclass ClassRec */
    String        class_name;          /* widget resource class name      */
    Cardinal      widget_size;         /* size in bytes of widget record  */
    XtProc        class_initialize;    /* class initialization proc        */
    XtWidgetClassProc class_part_initialize; /* dynamic initialization          */
    XtEnum        class_initied;       /* has class been initialized?     */
    XtInitProc    initialize;          /* initialize subclass fields      */
    XtArgsProc    initialize_hook;     /* notify that initialize called   */
    XtProc        rect1;               /* NULL                            */
    XtPointer      rect2;               /* NULL                            */
    Cardinal      rect3;               /* NULL                            */
    XtResourceList resources;          /* resources for subclass fields   */
    Cardinal      num_resources;        /* number of entries in resources  */
    XrmClass       xrm_class;          /* resource class quarkified       */
    Boolean       rect4;               /* NULL                            */
    Boolean       rect5;               /* NULL                            */
    Boolean       rect6;               /* NULL                            */
    Boolean       rect7;               /* NULL                            */
    XtWidgetProc  destroy;             /* free data for subclass pointers */
    XtWidgetProc  resize;              /* geom manager changed widget size */
}

```

```

XtExposeProc      expose;          /* redisplay rectangle          */
XtSetValuesFunc   set_values;      /* set subclass resource values */
XtArgsFunc        set_values_hook; /* notify that set_values called */
XtAlmostProc      set_values_almost; /* set values almost for geometry */
XtArgsProc        get_values_hook; /* notify that get_values called */
XtProc            rect9;           /* NULL                          */
XtVersionType     version;         /* version of intrinsics used    */
XtPointer         callback_private; /* list of callback offsets      */
String            rect10;          /* NULL                          */
XtGeometryHandler query_geometry; /* return preferred geometry     */
XtProc            rect11;          /* NULL                          */
XtPointer         extension;       /* pointer to extension record    */
} RectObjClassPart;

typedef struct _RectObjClassRec {
    RectObjClassPart rect_class;
} RectObjClassRec;

```

Figure 10-25. Manifest Constants and Data Types from <X11/ShellP.h>

```

/*****
 *
 * Shell Widget Private Data
 *
 *****/

/* New fields for the Shell widget class record */

typedef struct {
    XtPointer    extension;          /* pointer to extension record */
} ShellClassPart;

typedef struct {
    XtPointer next_extension; /* 1st 4 mandated for all extension records */
    XrmQuark record_type;     /* NULLQUARK; on ShellClassPart */
    long version;             /* must be XtShellExtensionVersion */
    Cardinal record_size;     /* sizeof(ShellClassExtensionRec) */
    XtGeometryHandler root_geometry_manager;
} ShellClassExtensionRec, *ShellClassExtension;

#define XtShellExtensionVersion 1L
#define XtInheritRootGeometryManager ((XtGeometryHandler)_XtInherit)

typedef struct _ShellClassRec {
    CoreClassPart    core_class;
    CompositeClassPart composite_class;
    ShellClassPart    shell_class;
} ShellClassRec;

/* New fields for the shell widget */

typedef struct {
    char          *geometry;
    XtCreatePopupChildProc create_popup_child_proc;
    XtGrabKind     grab_kind;
    Boolean        spring_loaded;
    Boolean        popped_up;
    Boolean        allow_shell_resize;
    Boolean        client_specified; /* re-using old name */
#define _XtShellPositionValid    ((Boolean)(1<<0))
#define _XtShellNotReparented    ((Boolean)(1<<1))
#define _XtShellPPositionOK      ((Boolean)(1<<2))
#define _XtShellGeometryParsed   ((Boolean)(1<<3))
    Boolean        save_under;
    Boolean        override_redirect;

    XtCallbackList popup_callback;
    XtCallbackList popdown_callback;
    Visual*        visual;
} ShellPart;

```

```

typedef struct {
    CorePart      core;
    CompositePart composite;
    ShellPart     shell;
} ShellRec, *ShellWidget;

/*****
 *
 * OverrideShell Widget Private Data
 *
 *****/

/* New fields for the OverrideShell widget class record */

typedef struct {
    XtPointer      extension;          /* pointer to extension record */
} OverrideShellClassPart;

typedef struct _OverrideShellClassRec {
    CoreClassPart      core_class;
    CompositeClassPart composite_class;
    ShellClassPart     shell_class;
    OverrideShellClassPart override_shell_class;
} OverrideShellClassRec;

/* No new fields for the override shell widget */

typedef struct {int frabjous;} OverrideShellPart;

typedef struct {
    CorePart      core;
    CompositePart composite;
    ShellPart     shell;
    OverrideShellPart override;
} OverrideShellRec, *OverrideShellWidget;

/*****
 *
 * WMShell Widget Private Data
 *
 *****/

/* New fields for the WMShell widget class record */

typedef struct {
    XtPointer      extension;          /* pointer to extension record */
} WMShellClassPart;

typedef struct _WMShellClassRec {
    CoreClassPart      core_class;
    CompositeClassPart composite_class;
    ShellClassPart     shell_class;
    WMShellClassPart   wm_shell_class;
} WMShellClassRec;

```

```

/* New fields for the WM shell widget */

typedef struct {
    char          *title;
    int           wm_timeout;
    Boolean       wait_for_wm;
    Boolean       transient;
    Atom          wm_configure_denied,  wm_moved;
    struct _OldXSizeHints { /* pre-R4 Xlib structure */
        long flags;
        int x, y;
        int width, height;
        int min_width, min_height;
        int max_width, max_height;
        int width_inc, height_inc;
        struct {
            int x;
            int y;
        } min_aspect, max_aspect;
    } size_hints;
    XWMHints      wm_hints;
    int base_width, base_height;
    int win_gravity;
    Atom title_encoding;
} WMShellPart;

typedef struct {
    CorePart      core;
    CompositePart composite;
    ShellPart     shell;
    WMShellPart   wm;
} WMShellRec, *WMShellWidget;

/*****
 *
 * TransientShell Widget Private Data
 *
 *****/

/* New fields for the TransientShell widget class record */

typedef struct {
    XtPointer      extension;          /* pointer to extension record */
} TransientShellClassPart;

typedef struct _TransientShellClassRec {
    CoreClassPart   core_class;
    CompositeClassPart composite_class;
    ShellClassPart  shell_class;
    WMShellClassPart  wm_shell_class;
    VendorShellClassPart vendor_shell_class;
    TransientShellClassPart transient_shell_class;
} TransientShellClassRec;

```

```

/* New fields for the transient shell widget */

typedef struct {
    Widget transient_for;
} TransientShellPart;

typedef struct {
    CorePart      core;
    CompositePart composite;
    ShellPart     shell;
    WMShellPart   wm;
    VendorShellPart vendor;
    TransientShellPart transient;
} TransientShellRec, *TransientShellWidget;

/*****
 *
 * TopLevelShell Widget Private Data
 *
 *****/

/* New fields for the TopLevelShell widget class record */

typedef struct {
    XtPointer      extension;          /* pointer to extension record */
} TopLevelShellClassPart;

typedef struct _TopLevelShellClassRec {
    CoreClassPart      core_class;
    CompositeClassPart composite_class;
    ShellClassPart     shell_class;
    WMShellClassPart   wm_shell_class;
    VendorShellClassPart vendor_shell_class;
    TopLevelShellClassPart top_level_shell_class;
} TopLevelShellClassRec;

/* New fields for the top level shell widget */

typedef struct {
    char      *icon_name;
    Boolean    iconic;
    Atom       icon_name_encoding;
} TopLevelShellPart;

typedef struct {
    CorePart      core;
    CompositePart composite;
    ShellPart     shell;
    WMShellPart   wm;
    VendorShellPart vendor;
    TopLevelShellPart topLevel;
} TopLevelShellRec, *TopLevelShellWidget;

```

```

/*****
 *
 * ApplicationShell Widget Private Data
 *
 *****/

/* New fields for the ApplicationShell widget class record */

typedef struct {
    XtPointer      extension;          /* pointer to extension record */
} ApplicationShellClassPart;

typedef struct _ApplicationShellClassRec {
    CoreClassPart      core_class;
    CompositeClassPart composite_class;
    ShellClassPart     shell_class;
    WMShellClassPart   wm_shell_class;
    VendorShellClassPart vendor_shell_class;
    TopLevelShellClassPart top_level_shell_class;
    ApplicationShellClassPart application_shell_class;
} ApplicationShellClassRec;

/* New fields for the application shell widget */

typedef struct {
    char *class;
    XrmClass xrm_class;
    int argc;
    char **argv;
} ApplicationShellPart;

typedef struct {
    CorePart      core;
    CompositePart composite;
    ShellPart     shell;
    WMShellPart   wm;
    VendorShellPart vendor;
    TopLevelShellPart topLevel;
    ApplicationShellPart application;
} ApplicationShellRec, *ApplicationShellWidget;

```

Figure 10-26. Data Types from <X11/VendorP.h>

```

/* New fields for the VendorShell widget class record */

typedef struct {
    XtPointer      extension;          /* pointer to extension record */
} VendorShellClassPart;

typedef struct _VendorShellClassRec {
    CoreClassPart      core_class;
    CompositeClassPart composite_class;
    ShellClassPart     shell_class;
    WMShellClassPart   wm_shell_class;
    VendorShellClassPart vendor_shell_class;
} VendorShellClassRec;

/* New fields for the vendor shell widget. */

typedef struct {
    int              vendor_specific;
} VendorShellPart;

typedef struct {
    CorePart         core;
    CompositePart    composite;
    ShellPart        shell;
    WMShellPart      wm;
    VendorShellPart  vendor;
} VendorShellRec, *VendorShellWidget;

```

The OPEN LOOK Widget Set

Overview

This chapter identifies binary interfaces for libXol. A source description for the entry points and exported data structures so identified may be found in the *OLIT Reference Manual* (Sun Microsystems, Part No. 800-6055-10, Revision A.).

The libXol Interfaces

The names listed below in Tables 10-9 and 10-10 have been included in SCD 2.2 as the names for the OPEN LOOK Widget Set REQUIRED INTERFACES, and must to be present on all conformant systems through the reference name `/usr/lib/libXol.so.3`. Note that Table 10-10 defines the size of exported data objects as a hexadecimal byte count described in square brackets after each name. However, this interface set is also DEPRECATED effective November 1st, 1993 and may be removed from this specification as early as November 1st, 1996. No new applications should be developed to use the OPEN LOOK Widget Set.

Figures 10-27 and 10-28 detail the manifest constants associated with libXol and its visible data structures, respectively. The sizes of certain global data are deliberately hidden from programmers. These sizes are left unspecified because there is no attempt made to support subclassing of OLIT widgets.

Table 10-9. libxo1 Contents

AllocateBuffer	OlMenuPopdown
AllocateTextBuffer	OlMenuPopup
BackwardScanTextBuffer	OlMenuPost
CopyBuffer	OlMenuUnpost
CopyTextBufferBlock	OlMoveFocus
EndCurrentTextBufferWord	OlQueryAcceleratorDisplay
ForwardScanTextBuffer	OlQueryMnemonicDisplay
FreeBuffer	OlRegisterColorTupleListConverter
FreeTextBuffer	OlRegisterHelp
GetOlBusyCursor	OlRemoveCallback
GetOlDuplicateCursor	OlSetErrorHandler
GetOlMoveCursor	OlSetGaugeValue
GetOlPanCursor	OlSetInputFocus
GetOlQuestionCursor	OlSetVaDisplayErrorMsgHandler
GetOlSWGeometries	OlSetVaDisplayWarningMsgHandler
GetOlStandardCursor	OlSetWarningHandler
GetOlTargetCursor	OlTextEditClearBuffer
GetTextBufferBlock	OlTextEditCopyBuffer
GetTextBufferBuffer	OlTextEditCopySelection
GetTextBufferChar	OlTextEditGetCursorPosition
GetTextBufferLine	OlTextEditGetLastPosition
GetTextBufferLocation	OlTextEditInsert
GrowBuffer	OlTextEditPaste
IncrementTextBufferLocation	OlTextEditReadSubString
InsertIntoBuffer	OlTextEditRedraw
LastTextBufferLocation	OlTextEditResize
LastTextBufferPosition	OlTextEditSetCursorPosition
LineOfPosition	OlTextEditTextBuffer
LocationOfPosition	OlTextEditUpdate
LookupOlInputEvent	OlTextFieldCopyString
NextLocation	OlTextFieldGetString
NextTextBufferWord	OlToolkitInitialize
OlAddCallback	OlUngrabDragPointer
OlCallAcceptFocus	OlUpdateDisplay
OlCallCallbacks	OlVaDisplayErrorMsg
OlCanAcceptFocus	OlVaDisplayWarningMsg
OlCategorySetPage	OlWMProtocolAction
OlDragAndDrop	OlWarning
OlError	PositionOfLine
OlGet50PercentGrey	PositionOfLocation
OlGet75PercentGrey	PreviousLocation
OlGetApplicationResources	PreviousTextBufferWord
OlGetApplicationValues	ReadFileIntoBuffer
OlGetBeepVolume	ReadFileIntoTextBuffer
OlGetCurrentFocusWidget	ReadStringIntoBuffer
OlGrabDragPointer	ReadStringIntoTextBuffer
OlHasCallbacks	RegisterTextBufferScanFunctions
OlHasFocus	RegisterTextBufferUpdate
OlInitialize	RegisterTextBufferWordDefinition
OlLayoutScrolledWindow	ReplaceBlockInTextBuffer
OlListItemPointer	ReplaceCharInTextBuffer

SaveTextBuffer
StartCurrentTextBufferWord
UnregisterTextBufferUpdate

Table 10-10. Exported Data in libxo1

OlRChar[0x5]	oblongButtonClassRec[?]
OlRCompression[c]	oblongButtonGadgetClass[0x4]
	oblongButtonGadgetClassRec[?]
abbrevMenuButtonClassRec[?]	oblongButtonWidgetClass[0x4]
abbrevMenuButtonWidgetClass[0x4]	popupWindowShellClassRec[?]
baseWindowShellClassRec[?]	popupWindowShellWidgetClass[0x4]
baseWindowShellWidgetClass[0x4]	primitiveClassRec[?]
bulletinBoardClassRec[?]	primitiveWidgetClass[0x4]
bulletinBoardWidgetClass[0x4]	pushpinClassRec[?]
buttonClassRec[?]	pushpinWidgetClass[0x4]
buttonGadgetClass[0x4]	rectButtonClassRec[?]
buttonGadgetClassRec[?]	rectButtonWidgetClass[0x4]
buttonWidgetClass[0x4]	rubberTileClassRec[?]
captionClassRec[?]	rubberTileWidgetClass[0x4]
captionWidgetClass[0x4]	scrollbarClassRec[?]
categoryClassRec[?]	scrollbarWidgetClass[0x4]
categoryWidgetClass[0x4]	scrolledWindowClassRec[?]
checkBoxClassRec[?]	scrolledWindowWidgetClass[0x4]
checkBoxWidgetClass[0x4]	scrollingListWidgetClass[0x4]
controlAreaWidgetClass[0x4]	sliderClassRec[?]
controlClassRec[?]	sliderWidgetClass[0x4]
eventObjClass[0x4]	staticTextWidgetClass[0x4]
eventObjClassRec[?]	statictextClassRec[?]
exclusivesClassRec[?]	statictextWidgetClass[0x4]
exclusivesWidgetClass[0x4]	textEditWidgetClass[0x4]
footerPanelClassRec[?]	textFieldClassRec[?]
footerPanelWidgetClass[0x4]	textFieldWidgetClass[0x4]
formClassRec[?]	vendorShellClassRec[?]
formWidgetClass[0x4]	vendorShellWidgetClass[0x4]
gaugeClassRec[?]	
gaugeWidgetClass[0x4]	
helpClassRec[?]	
helpWidgetClass[0x4]	
listClassRec[?]	
listPaneClassRec[?]	
listPaneWidgetClass[0x4]	
magClassRec[?]	
magWidgetClass[0x4]	
managerClassRec[?]	
managerWidgetClass[0x4]	
menuButtonClassRec[?]	
menuButtonGadgetClass[0x4]	
menuButtonGadgetClassRec[?]	
menuButtonWidgetClass[0x4]	
menuShellClassRec[?]	
menuShellWidgetClass[0x4]	
nonexclusivesClassRec[?]	
nonexclusivesWidgetClass[0x4]	
noticeShellClassRec[?]	
noticeShellWidgetClass[0x4]	

Figure 10-27. libxo1 Manifest Constants

#define	OleditDone	0
#define	OleditError	1
#define	OleditPosError	2
#define	OleditReject	3
#define	OL_ABSENT_PAIR	0
#define	OL_ALL	1
#define	OL_ALWAYS	2
#define	OL_ATOM_HELP	3
#define	OL_BOTH	4
#define	OL_BOTTOM	5
#define	OL_BUTTONSTACK	6
#define	OL_CENTER	7
#define	OL_CLASS_HELP	8
#define	OL_COLUMNS	9
#define	OL_COPY_MASK_VALUE	10
#define	OL_COPY_SIZE	11
#define	OL_COPY_SOURCE_VALUE	12
#define	OL_CURRENT	13
#define	OL_DEFAULT_PAIR	14
#define	OL_DISK_SOURCE	15
#define	OL_DISPLAY_FORM	16
#define	OL_DOWN	17
#define	OL_EXISTING_SOURCE	18
#define	OL_FIXEDCOLS	19
#define	OL_FIXEDHEIGHT	20
#define	OL_FIXEDROWS	21
#define	OL_FIXEDWIDTH	22
#define	OL_HALFSTACK	29
#define	OL_HORIZONTAL	30
#define	OL_IMAGE	31
#define	OL_IN	32
#define	OL_INDIRECT_SOURCE	33
#define	OL_LABEL	34
#define	OL_LEFT	35
#define	OL_MASK_PAIR	36
#define	OL_MAXIMIZE	37

#define	OL_MILLIMETERS	38
#define	OL_MINIMIZE	39
#define	OL_NEVER	40
#define	OL_NEXT	41
#define	OL_NONE	42
#define	OL_NONEBOTTOM	43
#define	OL_NONELEFT	44
#define	OL_NONERIGHT	45
#define	OL_NONETOP	46
#define	OL_NOTICES	47
#define	OL_OBLONG	49
#define	OL_OUT	50
#define	OL_OVERRIDE_PAIR	51
#define	OL_PIXELS	52
#define	OL_POINTS	53
#define	OL_POPUP	54
#define	OL_PREVIOUS	55
#define	OL_PROG_DEFINED_SOURCE	56
#define	OL_RECTBUTTON	57
#define	OL_RIGHT	58
#define	OL_ROWS	59
#define	OL_SOURCE_FORM	60
#define	OL_SOURCE_PAIR	61
#define	OL_STAYUP	62
#define	OL_STRING	63
#define	OL_STRING_SOURCE	64
#define	OL_TEXT_APPEND	65
#define	OL_TEXT_EDIT	66
#define	OL_TEXT_READ	67
#define	OL_TOP	68
#define	OL_TRANSPARENT_SOURCE	69
#define	OL_VERTICAL	70
#define	OL_WIDGET_HELP	73
#define	OL_WINDOW_HELP	74
#define	OL_WRAP_ANY	75
#define	OL_WRAP_WHITE_SPACE	76
#define	OL_CONTINUOUS	77
#define	OL_GRANULARITY	78

#define	OL_RELEASE	79
#define	OL_TICKMARK	80
#define	OL_PERCENT	81
#define	OL_SLIDERVALUE	82
#define	OL_WT_BASE	83
#define	OL_WT_CMD	84
#define	OL_WT_NOTICE	85
#define	OL_WT_HELP	86
#define	OL_WT_OTHER	87
#define	OL_SUCCESS	88
#define	OL_BAD_KEY	90
#define	OL_MENU_FULL	91
#define	OL_MENU_LIMITED	92
#define	OL_MENU_CANCEL	93
#define	OL_MENUDEFAULT	96
#define	OL_HSBMENU	98
#define	OL_VSBMENU	99
#define	OL_NEXTAPP	101
#define	OL_NEXTWINDOW	102
#define	OL_PREVAPP	103
#define	OL_PREVWINDOW	104
#define	OL_WINDOWMENU	105
#define	OL_WORKSPACEMENU	106
#define	OL_DEFAULTACTION	108
#define	OL_TOGGLEPUSHPIN	111
#define	OL_IMMEDIATE	120
#define	OL_CLICK_TO_TYPE	125
#define	OL_REALESTATE	126
#define	OL_UNDERLINE	127
#define	OL_HIGHLIGHT	128
#define	OL_INACTIVE	129
#define	OL_DISPLAY	130
#define	OL_PROC	131
#define	OL_SIZE_PROC	132
#define	OL_DRAW_PROC	133
#define	OL_PINNED_MENU	134
#define	OL_PRESS_DRAG_MENU	135
#define	OL_STAYUP_MENU	136

```
#define OL_POINTER 137
#define OL_INPUTFOCUS 138
#define OL_QUIT 142
#define OL_DESTROY 143
#define OL_DISMISS 144
#define OL_PRE 145
#define OL_POST 146
#define OL_BEEP_NEVER OL_NEVER
#define OL_BEEP_NOTICES OL_NOTICES
#define OL_BEEP_NOTICES_AND_FOOTERSOL_ALWAYS
#define OL_BEEP_ALWAYS OL_ALWAYS
```

```
typedef enum {motionVerify, modVerify, leaveVerify} OIVerifyOpType;
typedef enum {OlslLeft, OlslRight} OIScanDirection;
typedef enum {
    OlstPositions, OlstWhiteSpace, OlstEOL, OlstParagraph, OlstLast
} OIScanType;
```

```
typedef enum {
    NOTOPEN, READWRITE, READONLY, NEWFILE
} TextFileStatus;
```

```
typedef enum {
    EDIT_FAILURE, EDIT_SUCCESS
} EditResult;
```

```
typedef enum {
    SCAN_NOTFOUND, SCAN_WRAPPED, SCAN_FOUND, SCAN_INVALID
} ScanResult;
typedef enum {
    SAVE_FAILURE, SAVE_SUCCESS
} SaveResult;
```

```
#define TEXT_BUFFER_NOP (0)
#define TEXT_BUFFER_DELETE_START_LINE (1L<<0)
#define TEXT_BUFFER_DELETE_START_CHARS (1L<<1)
#define TEXT_BUFFER_DELETE_END_LINE (1L<<2)
#define TEXT_BUFFER_DELETE_END_CHARS (1L<<3)
```

```
#define TEXT_BUFFER_DELETE_JOIN_LINE (1L<<4)
#define TEXT_BUFFER_DELETE_SIMPLE (1L<<5)
#define TEXT_BUFFER_INSERT_SPLIT_LINE (1L<<6)
#define TEXT_BUFFER_INSERT_LINE (1L<<7)
#define TEXT_BUFFER_INSERT_CHARS (1L<<8)
#define CHANGE_BAR_WIDTH 3
#define CHANGE_BAR_HEIGHT 18
#define CHANGE_BAR_PAD 7
#define OL_DIM 1000
#define OL_NORMAL 1001
#define OL_PROPAGATE_TO_CONTROL_AREA 0x0001
#define OL_PROPAGATE_TO_CATEGORY 0x0002
#define OL_PROPAGATE \
(OL_PROPAGATE_TO_CONTROL_AREA \
| OL_PROPAGATE_TO_CATEGORY)
```

Figure 10-28. libxo1 Data Structures

```
typedef struct _CaptionClassRec *CaptionWidgetClass;
typedef struct _CaptionRec *CaptionWidget;
typedef struct _CategoryClassRec *CategoryWidgetClass;
typedef struct _CategoryRec *CategoryWidget;
typedef struct _CheckBoxClassRec *CheckBoxWidgetClass;
typedef struct _CheckBoxRec *CheckBoxWidget;
typedef int ControlLayout;
typedef int OlSameSize;
typedef struct _ControlClassRec *ControlAreaWidgetClass;
typedef struct _ControlRec *ControlAreaWidget;
typedef struct _EventObjClassRec *EventObjClass;
typedef struct _EventObjRec *EventObj;
typedef struct _ExclusivesClassRec *ExclusivesWidgetClass;
typedef struct _ExclusivesRec *ExclusivesWidget;
typedef struct _FooterPanelClassRec *FooterPanelWidgetClass;
typedef struct _FooterPanelRec *FooterPanelWidget;
typedef struct _FormClassRec *FormWidgetClass;
typedef struct _FormRec *FormWidget;
typedef struct _FormConstraintRec *FormConstraints;
typedef struct _SliderClassRec *GaugeWidgetClass;
typedef struct _SliderRec *GaugeWidget;
typedef struct _HelpClassRec *HelpWidgetClass;
typedef struct _HelpRec *HelpWidget;
typedef struct _ListPaneClassRec *ListPaneWidgetClass;
typedef struct _ListPaneRec *ListPaneWidget;
typedef struct _MagClassRec *MagWidgetClass;
typedef struct _MagRec *MagWidget;
typedef struct _ManagerClassRec *ManagerWidgetClass;
typedef struct _ManagerRec *ManagerWidget;
typedef struct _MenuShellClassRec *MenuShellWidgetClass;
typedef struct _MenuShellRec *MenuShellWidget;
typedef struct _MenuButtonClassRec *MenuButtonWidgetClass;
typedef struct _MenuButtonRec *MenuButtonWidget;
typedef struct _MenuButtonGadgetClassRec *MenuButtonGadgetClass;
typedef struct _MenuButtonGadgetRec *MenuButtonGadget;
typedef struct _NonexclusivesClassRec *NonexclusivesWidgetClass;
```

```

typedef struct _NonexclusivesRec *NonexclusivesWidget;
typedef struct _NoticeShellClassRec *NoticeShellWidgetClass;
typedef struct _NoticeShellRec *NoticeShellWidget;
typedef struct _OblongButtonClassRec *OblongButtonWidgetClass;
typedef struct _OblongButtonRec *OblongButtonWidget;
typedef struct _OblongButtonGadgetClassRec *OblongButtonGadgetClass;
typedef struct _OblongButtonGadgetRec *OblongButtonGadget;
typedef short OlDefine;
typedef unsigned long OlBitMask;
typedef struct _PopupWindowShellClassRec *PopupWindowShellWidgetClass;
typedef struct _PopupWindowShellRec *PopupWindowShellWidget;
typedef struct _PrimitiveClassRec *PrimitiveWidgetClass;
typedef struct _PrimitiveRec *PrimitiveWidget;
typedef struct _PushpinClassRec *PushpinWidgetClass;
typedef struct _PushpinRec *PushpinWidget;
typedef struct _RectButtonClassRec *RectButtonWidgetClass;
typedef struct _RectButtonRec *RectButtonWidget;
typedef struct _RubberTileClassRec *RubberTileWidgetClass;
typedef struct _RubberTileRec *RubberTileWidget;
typedef struct _ScrollbarClassRec *ScrollbarWidgetClass;
typedef struct _ScrollbarRec *ScrollbarWidget;

typedef struct OlScrollbarVerify {
    int          new_location;
    int          new_page;
    Boolean      ok;
    int          slidermin;
    int          slidermax;
    int          delta;
    Boolean      more_cb_pending;
} OlScrollbarVerify;

typedef struct _ScrolledWindowClassRec *ScrolledWindowWidgetClass;
typedef struct _ScrolledWindowRec *ScrolledWindowWidget;

```

```
typedef struct _OISWGeometries {  
    Widget      sw;  
    Widget      vsb;  
    Widget      hsb;  
    Dimension    bb_border_width;  
    Dimension    vsb_width;  
    Dimension    vsb_min_height;  
    Dimension    hsb_height;  
    Dimension    hsb_min_width;  
    Dimension    sw_view_width;  
    Dimension    sw_view_height;  
    Dimension    bbc_width;  
    Dimension    bbc_height;  
    Dimension    bbc_real_width;  
    Dimension    bbc_real_height;  
    Boolean      force_hsb;  
    Boolean      force_vsb;  
} OISWGeometries;
```

```
typedef struct _OListItem {  
    OIDefine      label_type;  
    XtPointer      label;  
    XImage         *glyph;  
    OIBitMask      attr;  
    XtPointer      user_data;  
    unsigned char   implementation_specific;  
} OListItem;
```

```
typedef struct _OListToken *OListToken;  
typedef struct _OListDelete {  
    OListToken  *tokens;  
    Cardinal     num_tokens;  
} OListDelete;
```

```
typedef struct _ListClassRec *ScrollingListWidgetClass;  
typedef struct _ListRec *ScrollingListWidget;  
typedef struct _SliderClassRec *SliderWidgetClass;  
typedef struct _SliderRec *SliderWidget;  
typedef struct OISliderVerify {  
    int          new_location;  
    Boolean      more_cb_pending;  
} OISliderVerify;
```

```

typedef struct _StaticTextClassRec *StaticTextWidgetClass;
typedef struct _StaticTextRec *StaticTextWidget;
typedef Dimension *TabTable;
typedef struct {
    OITextMarginHint hint;
    XRectangle *rect;
} OITextMarginCallData, *OITextMarginCallDataPointer;

typedef struct {
    Boolean ok;
    TextPosition current_cursor;
    TextPosition new_cursor;
    TextPosition select_start;
    TextPosition select_end;
} OITextMotionCallData, *OITextMotionCallDataPointer;

typedef struct {
    Boolean ok;
    TextPosition current_cursor;
    TextPosition select_start;
    TextPosition select_end;
    TextPosition new_cursor;
    TextPosition new_select_start;
    TextPosition new_select_end;
    String text;
    int text_length;
} OITextModifyCallData, *OITextModifyCallDataPointer;

typedef struct {
    Boolean requestor;
    TextPosition new_cursor;
    TextPosition new_select_start;
    TextPosition new_select_end;
    String inserted;
    String deleted;
    TextLocation delete_start;
    TextLocation delete_end;
    TextLocation insert_start;
    TextLocation insert_end;
    TextPosition cursor_position;
} OITextPostModifyCallData, *OITextPostModifyCallDataPointer;

```

```
typedef struct _TextEditClassRec *TextEditWidgetClass;
typedef struct _TextEditRec *TextEditWidget;
typedef struct _TextFieldClassRec *TextFieldWidgetClass;
typedef struct _TextFieldRec *TextFieldWidget;
typedef struct {
    String                string;
    Boolean               ok;
    OlTextVerifyReason    reason;
} OlTextFieldVerify, *OlTextFieldVerifyPointer;
```

```
typedef char BufferElement;
typedef struct _Buffer {
    int        size;
    int        used;
    int        esize;
    BufferElement *p;
} Buffer;
```

```
typedef int TextPosition;
typedef int TextLine;
typedef int TextPage;
typedef int TextBlock;
typedef struct{
    int        size;
    int        used;
    int        esize;
    TextBlock  *p;
} BlockTable;
```

```
typedef struct {
    TextPage    pageindex;
    unsigned long timestamp;
} PageQueue;
```

```
typedef struct {
    TextPosition    bytes;
    TextLine        lines;
    TextPage        qpos;
    BlockTable      *dpos;
} Page;
```

```
typedef struct {
    TextPage        pageindex;
    Buffer           *buffer;
    unsigned long   userData;
} Line;
```

```
typedef struct {
    int             size;
    int             used;
    int             esize;
    Page            *p;
} PageTable;
```

```
typedef struct {
    int             size;
    int             used;
    int             esize;
    Line            *p;
} LineTable;
```

```
typedef struct _TextLocation {
    TextLine        line;
    TextPosition    offset;
    BufferElement    *buffer;
} TextLocation;
```

```
typedef int TextUndoHint;
typedef struct _TextUndoItem {
    String          string;
    TextLocation    start;
    TextLocation    end;
    TextUndoHint    hint;
} TextUndoItem;
```

```
typedef void (*TextUpdateFunction)();
typedef struct _TextUpdateCallback {
    TextUpdateFunction    f;
    caddr_t               d;
} TextUpdateCallback;

typedef struct _TextBuffer {
    char                  *filename;
    FILE                  *tempfile;
    TextBlock             blockcnt;
    TextBlock             blocksize;
    LineTable             lines;
    PageTable             pages;
    BlockTable            *free_list;
    PageQueue             pqueue[PQLIMIT];
    TextPage              pagecount;
    TextPage              pageref;
    TextPage              curpageno;
    Buffer                 *buffer;
    char                  dirty;
    TextFileStatus        status;
    int                   refcount;
    TextUpdateCallback    *update;
    TextUndoItem           deleted;
    TextUndoItem           insert;
} TextBuffer;
```

Motif 1.2 Widget Set

Overview

This chapter contains the interfaces to the Motif 1.2 user interface environment. The Motif 1.2 interfaces are represented through the `libXm` and `libMrm` libraries.

The Motif 1.2 Interface is comprised of a set of Graphical User Interface components that together makeup a unique user interface environment. The components of this environment are: the toolkit, window manager, and user interface language. These user interface components are defined in the *OSF/Motif Programmer's Reference, Revision 1.2* (Open Software Foundation, Inc. 1992)

The Motif Interfaces

The interfaces listed below in Tables 10-11, 10-12 and 10-13 have been included in SCD 2.2 because they are required to be present on all systems conforming to the SCD 2.2 REQUIRED interface definition for Motif 1.2, in the dynamic libraries `/usr/lib/libXm.so.1.2` and `/usr/lib/libMrm.so.1.2`.

Figures 10-29 through 10-75 detail the manifest constants associated with `libXm` and `libMrm` and it's visible data structures, respectively.

In addition to the interfaces listed in the tables all SCD 2.2 compliant systems that offer Motif must have the `uil(3)` command and the `mwm(3)` window manager as defined in the *OSF/Motif Programmer's Reference, Release 1.2* (Prentice-Hall, ISBN 0-13-643115-1). Note that Table 10-12 defines the size of exported data objects as a hexadecimal byte count described in square brackets after each name. Entries of Table 10-12 which have their size left as a question mark are opaque data structures. These sizes are left unspecified because there is no attempt made to support subclassing of Motif widgets.

Table 10-11. Contents of libXm

XmActivateProtocol	XmCreateMainWindow
XmAddProtocolCallback	XmCreateMenuBar
XmAddProtocols	XmCreateMenuShell
XmAddTabGroup	XmCreateMessageBox
XmCascadeButtonGadgetHighlight	XmCreateMessageDialog
XmCascadeButtonHighlight	XmCreateOptionMenu
XmChangeColor	XmCreatePanedWindow
XmClipboardCancelCopy	XmCreatePopupMenu
XmClipboardCopy	XmCreatePromptDialog
XmClipboardCopyByName	XmCreatePulldownMenu
XmClipboardEndCopy	XmCreatePushButton
XmClipboardEndRetrieve	XmCreatePushButtonGadget
XmClipboardInquireCount	XmCreateQuestionDialog
XmClipboardInquireFormat	XmCreateRadioBox
XmClipboardInquireLength	XmCreateRowColumn
XmClipboardInquirePendingItems	XmCreateScale
XmClipboardLock	XmCreateScrollBar
XmClipboardRegisterFormat	XmCreateScrolledList
XmClipboardRetrieve	XmCreateScrolledText
XmClipboardStartCopy	XmCreateScrolledWindow
XmClipboardStartRetrieve	XmCreateSelectionBox
XmClipboardUndoCopy	XmCreateSelectionDialog
XmClipboardUnlock	XmCreateSeparator
XmClipboardWithdrawFormat	XmCreateSeparatorGadget
XmCommandAppendValue	XmCreateSimpleCheckBox
XmCommandError	XmCreateSimpleMenuBar
XmCommandGetChild	XmCreateSimpleOptionMenu
XmCommandSetValue	XmCreateSimplePopupMenu
XmConvertUnits	XmCreateSimplePulldownMenu
XmCreateArrowButton	XmCreateSimpleRadioBox
XmCreateArrowButtonGadget	XmCreateTemplateDialog
XmCreateBulletinBoard	XmCreateText
XmCreateBulletinBoardDialog	XmCreateTextField
XmCreateCascadeButton	XmCreateToggleButton
XmCreateCascadeButtonGadget	XmCreateToggleButtonGadget
XmCreateCommand	XmCreateWarningDialog
XmCreateDialogShell	XmCreateWorkArea
XmCreateDragIcon	XmCreateWorkingDialog
XmCreateDrawingArea	XmCvtCTToXmString
XmCreateDrawnButton	XmCvtStringToUnitType
XmCreateErrorDialog	XmCvtXmStringToCT
XmCreateFileSelectionBox	XmDeactivateProtocol
XmCreateFileSelectionDialog	XmDestroyPixmap
XmCreateForm	XmDragCancel
XmCreateFormDialog	XmDragStart
XmCreateFrame	XmDropSiteConfigureStackingOrder
XmCreateInformationDialog	XmDropSiteEndUpdate
XmCreateLabel	XmDropSiteQueryStackingOrder
XmCreateLabelGadget	XmDropSiteRegister
XmCreateList	XmDropSiteRetrieve

XmDropSiteStartUpdate	XmListDeselectPos
XmDropSiteUnregister	XmListGetKbdItemPos
XmDropSiteUpdate	XmListGetMatchPos
XmDropTransferAdd	XmListGetSelectedPos
XmDropTransferStart	XmListItemExists
XmFileSelectionBoxGetChild	XmListItemPos
XmFileSelectionDoSearch	XmListPosSelected
XmFontListAdd	XmListPosToBounds
XmFontListAppendEntry	XmListReplaceItems
XmFontListCopy	XmListReplaceItemsPos
XmFontListCreate	XmListReplaceItemsPosUnselected
XmFontListEntryCreate	XmListReplaceItemsUnselected
XmFontListEntryFree	XmListReplacePositions
XmFontListEntryGetFont	XmListSelectItem
XmFontListEntryGetTag	XmListSelectPos
XmFontListEntryLoad	XmListSetAddMode
XmFontListFree	XmListSetBottomItem
XmFontListFreeFontContext	XmListSetBottomPos
XmFontListGetNextFont	XmListSetHorizPos
XmFontListInitFontContext	XmListSetItem
XmFontListNextEntry	XmListSetKbdItemPos
XmFontListRemoveEntry	XmListSetPos
XmGetAtomName	XmListUpdateSelectedList
XmGetColorCalculation	XmListYToPos
XmGetColors	XmMainWindowSep1
XmGetDestination	XmMainWindowSep2
XmGetDragContext	XmMainWindowSep3
XmGetFocusWidget	XmMainWindowSetAreas
XmGetMenuCursor	XmMapSegmentEncoding
XmGetPixmap	XmMenuPosition
XmGetPixmapByDepth	XmMessageBoxGetChild
XmGetPostedFromWidget	XmOptionButtonGadget
XmGetSecondaryResourceData	XmOptionLabelGadget
XmGetTabGroup	XmProcessTraversal
XmGetTearOffControl	XmRegisterSegmentEncoding
XmGetVisibility	XmRemoveProtocolCallback
XmGetXmDisplay	XmRemoveProtocols
XmGetXmScreen	XmRemoveTabGroup
XmInstallImage	XmRepTypeAddReverse
XmInternAtom	XmRepTypeGetId
XmIsMotifWMRunning	XmRepTypeGetNameList
XmIsTraversable	XmRepTypeGetRecord
XmListAddItem	XmRepTypeGetRegistered
XmListAddItems	XmRepTypeInstallTearOffModelConverter
XmListAddItemsUnselected	XmRepTypeRegister
XmListAddItemUnselected	XmRepTypeValidValue
XmListDeleteAllItems	XmResolveAllPartOffsets
XmListDeleteItem	XmResolvePartOffsets
XmListDeleteItems	XmScaleGetValue
XmListDeleteItemsPos	XmScaleSetValue
XmListDeletePos	XmScrollbarGetValues
XmListDeletePositions	XmScrollbarSetValues
XmListDeselectAllItems	XmScrolledWindowSetAreas
XmListDeselectItem	XmScrollVisible

XmSelectionBoxGetChild	XmTextFieldGetString
XmSetColorCalculation	XmTextFieldGetStringWcs
XmSetFontUnit	XmTextFieldGetSubstring
XmSetFontUnits	XmTextFieldGetSubstringWcs
XmSetMenuCursor	XmTextFieldInsert
XmSetProtocolHooks	XmTextFieldInsertWcs
XmStringBaseline	XmTextFieldPaste
XmStringByteCompare	XmTextFieldPosToXY
XmStringCompare	XmTextFieldRemove
XmStringConcat	XmTextFieldReplace
XmStringCopy	XmTextFieldReplaceWcs
XmStringCreate	XmTextFieldSetAddMode
XmStringCreateLocalized	XmTextFieldSetEditable
XmStringCreateLtoR	XmTextFieldSetHighlight
XmStringCreateSimple	XmTextFieldSetInsertionPosition
XmStringDirectionCreate	XmTextFieldSetMaxLength
XmStringDraw	XmTextFieldSetSelection
XmStringDrawImage	XmTextFieldSetString
XmStringDrawUnderline	XmTextFieldSetStringWcs
XmStringEmpty	XmTextFieldShowPosition
XmStringExtent	XmTextFieldXYToPos
XmStringFree	XmTextFindString
XmStringFreeContext	XmTextFindStringWcs
XmStringGetLtoR	XmTextGetBaseLine
XmStringGetNextComponent	XmTextGetBaseline
XmStringGetNextSegment	XmTextGetEditable
XmStringHasSubstring	XmTextGetInsertionPosition
XmStringHeight	XmTextGetLastPosition
XmStringInitContext	XmTextGetMaxLength
XmStringLength	XmTextGetSelection
XmStringLineCount	XmTextGetSelectionPosition
XmStringNConcat	XmTextGetSelectionWcs
XmStringNCopy	XmTextGetSource
XmStringPeekNextComponent	XmTextGetString
XmStringSegmentCreate	XmTextGetStringWcs
XmStringSeparatorCreate	XmTextGetSubstring
XmStringWidth	XmTextGetSubstringWcs
XmTargetsAreCompatible	XmTextGetTopCharacter
XmTextClearSelection	XmTextInsert
XmTextCopy	XmTextInsertWcs
XmTextCut	XmTextPaste
XmTextDisableRedisplay	XmTextPosToXY
XmTextEnableRedisplay	XmTextRemove
XmTextFieldClearSelection	XmTextReplace
XmTextFieldCopy	XmTextReplaceWcs
XmTextFieldCut	XmTextScroll
XmTextFieldGetBaseline	XmTextSetAddMode
XmTextFieldGetEditable	XmTextSetEditable
XmTextFieldGetInsertionPosition	XmTextSetHighlight
XmTextFieldGetLastPosition	XmTextSetInsertionPosition
XmTextFieldGetMaxLength	XmTextSetMaxLength
XmTextFieldGetSelection	XmTextSetSelection
XmTextFieldGetSelectionPosition	XmTextSetSource
XmTextFieldGetSelectionWcs	XmTextSetString

XmTextSetStringWcs
XmTextSetTopCharacter
XmTextShowPosition
XmTextXYToPos
XmToggleButtonGadgetGetState
XmToggleButtonGadgetSetState
XmToggleButtonGetState
XmToggleButtonSetState
XmTrackingEvent
XmTrackingLocate
XmTranslateKey
XmUninstallImage
XmUpdatedDisplay
XmVaCreateSimpleCheckBox
XmVaCreateSimpleMenuBar
XmVaCreateSimpleOptionMenu
XmVaCreateSimplePopupMenu
XmVaCreateSimplePulldownMenu
XmVaCreateSimpleRadioBox
XmWidgetGetBaselines
XmWidgetGetDisplayRect

Table 10-12. Exported Data for Motif 1.2

vendorShellClassRec[?]	xmLabelGadgetClass[0x4]
vendorShellWidgetClass[0x4]	xmLabelGadgetClassRec[?]
xmArrowButtonClassRec[?]	xmLabelGCacheObjClassRec[?]
xmArrowButtonGadgetClass[0x4]	xmLabelWidgetClass[0x4]
xmArrowButtonGadgetClassRec[?]	xmListClassRec[?]
xmArrowButtonWidgetClass[0x4]	xmListWidgetClass[0x4]
xmBulletinBoardClassRec[?]	xmMainWindowClassRec[?]
xmBulletinBoardWidgetClass[0x4]	xmMainWindowWidgetClass[0x4]
xmCascadeButtonClassRec[?]	xmManagerClassRec[?]
xmCascadeButtonGadgetClass[0x4]	xmManagerWidgetClass[0x4]
xmCascadeButtonGadgetClassRec[?]	xmMenuShellClassRec[?]
xmCascadeButtonGCacheObjClassRec[?]	xmMenuShellWidgetClass[0x4]
xmCascadeButtonWidgetClass[0x4]	xmMessageBoxClassRec[?]
xmCommandClassRec[?]	xmMessageBoxWidgetClass[0x4]
xmCommandWidgetClass[0x4]	xmPanedWindowClassRec[?]
xmDesktopClass[0x4]	xmPanedWindowWidgetClass[0x4]
xmDesktopClassRec[?]	xmPrimitiveClassRec[?]
xmDesktopObjectClass[0x4]	xmPrimitiveWidgetClass[0x4]
xmDialogShellClassRec[?]	xmProtocolClassRec[?]
xmDialogShellExtClassRec[?]	xmProtocolObjectClass[0x4]
xmDialogShellExtObjectClass[0x4]	xmPushButtonClassRec[?]
xmDialogShellWidgetClass[0x4]	xmPushButtonGadgetClass[0x4]
xmDisplayClass[0x4]	xmPushButtonGadgetClassRec[?]
xmDisplayClassRec[?]	xmPushButtonGCacheObjClassRec[?]
xmDisplayObjectClass[0x4]	xmPushButtonWidgetClass[0x4]
xmDragContextClass[0x4]	XmQmotif[0x4]
xmDragContextClassRec[?]	xmRowColumnClassRec[?]
xmDragIconClassRec[?]	xmRowColumnWidgetClass[0x4]
xmDragIconObjectClass[0x4]	xmSashClassRec[?]
xmDragOverShellClassRec[?]	xmSashWidgetClass[0x4]
xmDragOverShellWidgetClass[0x4]	xmScaleClassRec[?]
xmDrawingAreaClassRec[?]	xmScaleWidgetClass[0x4]
xmDrawingAreaWidgetClass[0x4]	xmScreenClass[0x4]
xmDrawnButtonClassRec[?]	xmScreenClassRec[?]
xmDrawnButtonWidgetClass[0x4]	xmScreenObjectClass[0x4]
xmDropSiteManagerClassRec[?]	xmScrollBarClassRec[?]
xmDropSiteManagerObjectClass[0x4]	xmScrollBarWidgetClass[0x4]
xmDropTransferClassRec[?]	xmScrolledWindowClassRec[?]
xmDropTransferObjectClass[0x4]	xmScrolledWindowWidgetClass[0x4]
xmExtClassRec[?]	xmSelectionBoxClassRec[?]
xmExtObjectClass[0x4]	xmSelectionBoxWidgetClass[0x4]
xmFileSelectionBoxClassRec[?]	xmSeparatorClassRec[?]
xmFileSelectionBoxWidgetClass[0x4]	xmSeparatorGadgetClass[0x4]
xmFormClassRec[?]	xmSeparatorGadgetClassRec[?]
xmFormWidgetClass[0x4]	xmSeparatorGCacheObjClassRec[?]
xmFrameClassRec[?]	xmSeparatorWidgetClass[0x4]
xmFrameWidgetClass[0x4]	xmShellExtClassRec[?]
xmGadgetClass[0x4]	xmShellExtObjectClass[0x4]
xmGadgetClassRec[?]	xmTearOffButtonClassRec[?]
xmLabelClassRec[?]	xmTearOffButtonWidgetClass[0x4]

```
xmTextClassRec[?]  
xmTextFieldClassRec[?]  
xmTextFieldWidgetClass[0x4]  
xmTextWidgetClass[0x4]  
xmToggleButtonClassRec[?]  
xmToggleButtonGadgetClass[0x4]  
xmToggleButtonGadgetClassRec[?]  
xmToggleButtonGCacheObjClassRec[?]  
xmToggleButtonWidgetClass[0x4]  
xmVendorShellExtClassRec[?]  
xmVendorShellExtObjectClass[0x4]  
xmWorldClass[0x4]  
xmWorldClassRec[?]  
xmWorldObjectClass[0x4]
```

Table 10-13. libMrm Contents

MrmCloseHierarchy
MrmFetchBitmapLiteral
MrmFetchColorLiteral
MrmFetchIconLiteral
MrmFetchLiteral
MrmFetchSetValues
MrmFetchWidget
MrmFetchWidgetOverride
MrmInitialize
MrmOpenHierarchy
MrmOpenHierarchyPerDisplay
MrmRegisterClass
MrmRegisterNames
MrmRegisterNamesInHierarchy

Figure 10-29. Motif 1.2 Data Structures from ArrowB.h

```
typedef struct _XmArrowButtonClassRec * XmArrowButtonWidgetClass;  
typedef struct _XmArrowButtonRec      * XmArrowButtonWidget;
```

Figure 10-30. Motif 1.2 Data Structures from ArrowBG.h

```
typedef struct _XmArrowButtonGadgetClassRec * XmArrowButtonGadgetClass;  
typedef struct _XmArrowButtonGadgetRec      * XmArrowButtonGadget;
```

Figure 10-31. Motif 1.2 Data Structures from BulletinB.h

```
typedef struct _XmBulletinBoardClassRec * XmBulletinBoardWidgetClass;  
typedef struct _XmBulletinBoardRec      * XmBulletinBoardWidget;
```

Figure 10-32. Motif 1.2 Data Structures from CascadeB.h

```
typedef struct _XmCascadeButtonRec      * XmCascadeButtonWidget;  
typedef struct _XmCascadeButtonClassRec * XmCascadeButtonWidgetClass;
```

Figure 10-33. Motif 1.2 Data Structures from CascadeBG.h

```
typedef struct _XmCascadeButtonGadgetClassRec    * XmCascadeButtonGadgetClass;  
typedef struct _XmCascadeButtonGadgetRec        * XmCascadeButtonGadget;  
typedef struct _XmCascadeButtonGCacheObjRec     * XmCascadeButtonGCacheObject;
```

Figure 10-34. Motif 1.2 Data Structures from Command.h

```
/* Class record constants */

typedef struct _XmCommandClassRec * XmCommandWidgetClass;
typedef struct _XmCommandRec      * XmCommandWidget;
```

Figure 10-35. Motif 1.2 Manifest Constants and Data Structures from CutPaste.h

```
/* XmClipboard return status definitions */

#define XmClipboardFail          0
#define XmClipboardSuccess      1
#define XmClipboardTruncate     2
#define XmClipboardLocked       4
#define XmClipboardBadFormat    5
#define XmClipboardNoData       6

/* XmClipboard pre-1.2 definitions */

#define ClipboardFail           0
#define ClipboardSuccess       1
#define ClipboardTruncate      2
#define ClipboardLocked        4
#define ClipboardBadFormat     5
#define ClipboardNoData        6

typedef struct {
    long DataId;
    long PrivateId;
} XmClipboardPendingRec, *XmClipboardPendingList;
```

Figure 10-36. Motif 1.2 Data Structures from DialogS.h

```
typedef struct _XmDialogShellClassRec      * XmDialogShellWidgetClass;  
typedef struct _XmDialogShellRec          * XmDialogShellWidget;
```

Figure 10-37. Motif 1.2 Manifest Constants and Data Structures from Display.h

```
enum {
    XmDRAG_NONE,
    XmDRAG_DROP_ONLY,
    XmDRAG_PREFER_PREREGISTER,
    XmDRAG_PREREGISTER,
    XmDRAG_PREFER_DYNAMIC,
    XmDRAG_DYNAMIC,
    XmDRAG_PREFER_RECEIVER
};

/* Class record constants */

typedef struct _XmDisplayRec *XmDisplay;
typedef struct _XmDisplayClassRec *XmDisplayClass;
```

Figure 10-38. Motif 1.2 Manifest Constants and Data Structures from DragC.h

```
#define XmDROP_MOVE      (1L << 0)
#define XmDROP_COPY      (1L << 1)
#define XmDROP_LINK      (1L << 2)

#define XmHELP            2
typedef unsigned int      XmID;

/*****
 *
 * DragContext
 *
 *****/

#define _XA_MOTIF_DROP "_MOTIF_DROP"
#define _XA_DRAG_FAILURE "_MOTIF_DRAG_FAILURE"
#define _XA_DRAG_SUCCESS "_MOTIF_DRAG_SUCCESS"

/* enums used for the message_type in client messages */

enum{      XmTOP_LEVEL_ENTER,          XmTOP_LEVEL_LEAVE,
           XmDRAG_MOTION,              XmDROP_SITE_ENTER,
           XmDROP_SITE_LEAVE,          XmDROP_START,
           XmDROP_FINISH,              XmDRAG_DROP_FINISH,
           XmOPERATION_CHANGED
        } ;

/* enums for completionStatus */
enum{      XmDROP,                      XmDROP_HELP,
           XmDROP_CANCEL,              XmDROP_INTERRUPT
        } ;

/* values for operation */
#define XmDROP_NOOP      0L

enum{      XmBLEND_ALL,                  XmBLEND_STATE_SOURCE,
           XmBLEND_JUST_SOURCE,          XmBLEND_NONE
        } ;

enum{      XmDROP_FAILURE,              XmDROP_SUCCESS
        } ;

/* enums used for the public callback reason */

enum{      XmCR_TOP_LEVEL_ENTER,          XmCR_TOP_LEVEL_LEAVE,
           XmCR_DRAG_MOTION,              XmCR_DROP_SITE_ENTER,
           XmCR_DROP_SITE_LEAVE,          XmCR_DROP_START,
           XmCR_DROP_FINISH,              XmCR_DRAG_DROP_FINISH,
```

```

        XmCR_OPERATION_CHANGED,

        _XmNUMBER_DND_CB_REASONS
    } ;

/* Class record constants */
typedef struct _XmDragContextClassRec    *XmDragContextClass;
typedef struct _XmDragContextRec         *XmDragContext;

typedef struct _XmAnyICCCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
}XmAnyICCCallbackStruct, *XmAnyICCCallback;

typedef struct _XmTopLevelEnterCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
    Screen             *screen;
    /*
     * the window field is different if this is an outbound or inbound
     * callback. Outbound == reciever, Inbound == initiator.
     */
    Window             window;
    Position            x, y;
    unsigned char       dragProtocolStyle;
    Atom                iccHandle;
}XmTopLevelEnterCallbackStruct, *XmTopLevelEnterCallback;

typedef struct _XmTopLevelLeaveCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
    Screen             *screen;
    Window             window;
}XmTopLevelLeaveCallbackStruct, *XmTopLevelLeaveCallback;

typedef struct _XmDropSiteEnterCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
    unsigned char       operation;
    unsigned char       operations;
    unsigned char       dropSiteStatus;
    Position            x, y;
}XmDropSiteEnterCallbackStruct, *XmDropSiteEnterCallback;

typedef struct _XmDropSiteLeaveCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
}XmDropSiteLeaveCallbackStruct, *XmDropSiteLeaveCallback;

```

```
typedef struct _XmDragMotionCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
    unsigned char       operation;
    unsigned char       operations;
    unsigned char       dropSiteStatus;
    Position            x, y;
}XmDragMotionCallbackStruct, *XmDragMotionCallback;

typedef struct _XmOperationChangedCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
    unsigned char       operation;
    unsigned char       operations;
    unsigned char       dropSiteStatus;
}XmOperationChangedCallbackStruct, *XmOperationChangedCallback;

typedef struct _XmDropStartCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
    unsigned char       operation;
    unsigned char       operations;
    unsigned char       dropSiteStatus;
    unsigned char       dropAction;
    Position            x, y;
    Window             window;
    Atom               iccHandle;
}XmDropStartCallbackStruct, *XmDropStartCallback;

typedef struct _XmDropFinishCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
    unsigned char       operation;
    unsigned char       operations;
    unsigned char       dropSiteStatus;
    unsigned char       dropAction;
    unsigned char       completionStatus;
}XmDropFinishCallbackStruct, *XmDropFinishCallback;

typedef struct _XmDragDropFinishCallbackStruct{
    int                reason;
    XEvent             *event;
    Time               timeStamp;
}XmDragDropFinishCallbackStruct, *XmDragDropFinishCallback;
```

Figure 10-39. Motif 1.2 Manifest Constants and Data Structures from DragIcon.h

```
enum {  
    XmATTACH_NORTH_WEST,  
    XmATTACH_NORTH,  
    XmATTACH_NORTH_EAST,  
    XmATTACH_EAST,  
    XmATTACH_SOUTH_EAST,  
    XmATTACH_SOUTH,  
    XmATTACH_SOUTH_WEST,  
    XmATTACH_WEST,  
    XmATTACH_CENTER,  
    XmATTACH_HOT  
};  
  
typedef struct _XmDragIconRec *XmDragIconObject;  
typedef struct _XmDragIconClassRec *XmDragIconObjectClass;
```

Figure 10-40. Motif 1.2 Data Structures from DragOverS.h

```
typedef struct _XmDragOverShellRec      *XmDragOverShellWidget;  
typedef struct _XmDragOverShellClassRec *XmDragOverShellWidgetClass;
```

Figure 10-41. Motif 1.2 Data Structures from DrawingA.h

```
typedef struct _XmDrawingAreaClassRec * XmDrawingAreaWidgetClass;
typedef struct _XmDrawingAreaRec      * XmDrawingAreaWidget;
```

Figure 10-42. Motif 1.2 Data Structures from DrawnB.h

```
typedef struct _XmDrawnButtonClassRec *XmDrawnButtonWidgetClass;  
typedef struct _XmDrawnButtonRec      *XmDrawnButtonWidget;
```

Figure 10-43. Motif 1.2 Manifest Constants and Data Structures from DropSMgr.h

```

#define XmCR_DROP_SITE_LEAVE_MESSAGE 1
#define XmCR_DROP_SITE_ENTER_MESSAGE 2
#define XmCR_DROP_SITE_MOTION_MESSAGE 3
#define XmCR_DROP_MESSAGE 4

#define XmNO_DROP_SITE 1
#define XmINVALID_DROP_SITE 2
#define XmVALID_DROP_SITE 3

enum { XmDRAG_UNDER_NONE, XmDRAG_UNDER_PIXMAP,
       XmDRAG_UNDER_SHADOW_IN, XmDRAG_UNDER_SHADOW_OUT,
       XmDRAG_UNDER_HIGHLIGHT };

enum { XmDROP_SITE_SIMPLE, XmDROP_SITE_COMPOSITE,
       XmDROP_SITE_SIMPLE_CLIP_ONLY = 128,
       XmDROP_SITE_COMPOSITE_CLIP_ONLY };

enum { XmABOVE, XmBELOW };

enum { XmDROP_SITE_ACTIVE, XmDROP_SITE_INACTIVE };

typedef struct _XmDragProcCallbackStruct {
    int reason;
    XEvent * event;
    Time timeStamp;
    Widget dragContext;
    Position x, y;
    unsigned char dropSiteStatus;
    unsigned char operation;
    unsigned char operations;
    Boolean animate;
} XmDragProcCallbackStruct, * XmDragProcCallback;

typedef struct _XmDropProcCallbackStruct {
    int reason;
    XEvent * event;
    Time timeStamp;
    Widget dragContext;
    Position x, y;
    unsigned char dropSiteStatus;
    unsigned char operation;
    unsigned char operations;
    unsigned char dropAction;
} XmDropProcCallbackStruct, * XmDropProcCallback;

typedef struct _XmDropSiteVisualsRec {
    Pixel background;
    Pixel foreground;
    Pixel topShadowColor;
    Pixmap topShadowPixmap;
}

```

```
Pixel    bottomShadowColor;
Pixmap   bottomShadowPixmap;
Dimension shadowThickness;
Pixel    highlightColor;
Pixmap   highlightPixmap;
Dimension highlightThickness;
Dimension borderWidth;
} XmDropSiteVisualsRec, * XmDropSiteVisuals;
```

```
/* DropSite Widget */
```

```
typedef struct _XmDropSiteManagerClassRec *XmDropSiteManagerObjectClass;
typedef struct _XmDropSiteManagerRec *XmDropSiteManagerObject;
```

Figure 10-44. Motif 1.2 Manifest Constants and Data Structures from DropTrans.h

```
#define XmTRANSFER_FAILURE 0
#define XmTRANSFER_SUCCESS 1

typedef struct _XmDropTransferClassRec * XmDropTransferObjectClass;
typedef struct _XmDropTransferRec      * XmDropTransferObject;

typedef struct _XmDropTransferEntryRec {
    XtPointer      client_data;
    Atom           target;
} XmDropTransferEntryRec, * XmDropTransferEntry;
```

Figure 10-45. Motif 1.2 Data Structures from FileSB.h

```
typedef struct _XmFileSelectionBoxClassRec * XmFileSelectionBoxWidgetClass;  
typedef struct _XmFileSelectionBoxRec      * XmFileSelectionBoxWidget;
```

Figure 10-46. Motif 1.2 Data Structures from Form.h

```
typedef struct _XmFormClassRec * XmFormWidgetClass;  
typedef struct _XmFormRec      * XmFormWidget;
```

Figure 10-47. Motif 1.2 Data Structures from Frame.h

```
typedef struct _XmFrameClassRec * XmFrameWidgetClass;  
typedef struct _XmFrameRec      * XmFrameWidget;
```

Figure 10-48. Motif 1.2 Data Structures from Label.h

```
typedef struct _XmLabelClassRec      * XmLabelWidgetClass;  
typedef struct _XmLabelRec          * XmLabelWidget;
```

Figure 10-49. Motif 1.2 Data Structures from LabelG.h

```
typedef struct _XmLabelGadgetClassRec * XmLabelGadgetClass;  
typedef struct _XmLabelGadgetRec      * XmLabelGadget;  
typedef struct _XmLabelGCacheObjRec   * XmLabelGCacheObject;
```

Figure 10-50. Motif 1.2 Manifest Constants and Data Structures from List.h

```
#define XmINITIAL      0
#define XmADDITION     1
#define XmMODIFICATION 2

typedef struct _XmListClassRec * XmListWidgetClass;
typedef struct _XmListRec      * XmListWidget;
```

Figure 10-51. Motif 1.2 Data Structures from MainW.h

```
typedef struct _XmMainWindowClassRec * XmMainWindowWidgetClass;  
typedef struct _XmMainWindowRec      * XmMainWindowWidget;
```

Figure 10-52. Motif 1.2 Data Structures from MenuShell.h

```
typedef struct _XmMenuShellClassRec      * XmMenuShellWidgetClass;  
typedef struct _XmMenuShellWidgetRec    * XmMenuShellWidget;
```

Figure 10-53. Motif 1.2 Data Structures from MessageB.h

```
typedef struct _XmMessageBoxClassRec * XmMessageBoxWidgetClass;  
typedef struct _XmMessageBoxRec      * XmMessageBoxWidget;
```

Figure 10-54. Motif 1.2 Manifest Constants and Data Structures from MrmPublic.h

```

/*
 * Success or other non-error return codes
 */
#define MrmSUCCESS      1
#define MrmCREATE_NEW   3
#define MrmINDEX_RETRY  5      /* Retry on entering index required */
#define MrmINDEX_GT     7      /* Index orders greater-than entry */
#define MrmINDEX_LT     9      /* Index orders less-than entry */
#define MrmPARTIAL_SUCCESS 11   /* operation partly succeeded */

/*
 * Failure return codes
 */
#define MrmFAILURE      0
#define MrmNOT_FOUND    2
#define MrmEXISTS       4
#define MrmNUL_GROUP    6
#define MrmNUL_TYPE     8
#define MrmWRONG_GROUP  10
#define MrmWRONG_TYPE   12
#define MrmOUT_OF_RANGE 14      /* Record number too big */
#define MrmBAD_RECORD   16      /* Record number wrong type */
#define MrmNULL_DATA    18      /* No data for entry */
#define MrmBAD_DATA_INDEX 20    /* Data index in RID out of range */
#define MrmBAD_ORDER    22      /* Bad ordering specifier */
#define MrmBAD_CONTEXT  24      /* Invalid Mrm context */
#define MrmNOT_VALID    26      /* Validation failure */
#define MrmBAD_BTREE    28      /* GT/LT pointer error in BTree */
#define MrmBAD_WIDGET_REC 30    /* Validation failure on widget record */
#define MrmBAD_CLASS_TYPE 32    /* Class type not a valid Mrmwc... value */
#define MrmNO_CLASS_NAME 34     /* User class name is null */
#define MrmTOO_MANY     36      /* Too many entries requested in some list */
#define MrmBAD_IF_MODULE 38     /* invalid interface module */
#define MrmNULL_DESC    40      /* Arglist or children descriptor null */
#define MrmOUT_OF_BOUNDS 42     /* Argument index out of arglist bounds */
#define MrmBAD_COMPRESS 44      /* Invalid compression code */
#define MrmBAD_ARG_TYPE 46      /* Invalid type, not in RGMrType... */
#define MrmNOT_IMP      48      /* Not yet implemented */
#define MrmNULL_INDEX   50      /* empty index string */
#define MrmBAD_KEY_TYPE 52      /* key must be MrmrIndex or MrmrRID */
#define MrmBAD_CALLBACK 54      /* Invalid callback descriptor */
#define MrmNULL_ROUTINE 56      /* Empty callback routine name string */
#define MrmVEC_TOO_BIG  58      /* too many elements in vector */
#define MrmBAD_HIERARCHY 60     /* invalid Mrm file hierarchy */
#define MrmBAD_CLASS_CODE 62    /* Class code not found in Mrmwc... */
#define MrmDISPLAY_NOT_OPENED 63 /* Display not yet created */
#define MrmEOF          64      /* End of file */
#define MrmUNRESOLVED_REFS 65   /* Unresolved widget refs in callback*/

/*
 * Definitions associated with widget representations

```

```

*/

/*
 * Define the creation callback
 */
#define MrmNcreateCallback      "createCallback"
/* BEGIN OSF Fix pir 2813 */
#define MrmCR_CREATE            XmCR_CREATE
/* END OSF Fix pir 2813 */

/*
 * Code for unknown (user-defined) classes.
 */
#define MrmwcUnknown            1

/*
 * The data types of values stored in uid files.
 */
#define MrmRtypeMin              1
#define MrmRtypeInteger          1      /* int */
#define MrmRtypeBoolean          2
#define MrmRtypeChar8            3      /* a nul-terminated string */
#define MrmRtypeChar8Vector      4      /* a vector of char_8 strings */
#define MrmRtypeCString          5      /* a compound string (DDIS) */
#define MrmRtypeCStringVector    6      /* a vector of compound strings */
#define MrmRtypeFloat            7
                                     /* 8 = TypeCompressed now unused */
#define MrmRtypeCallback          9      /* code for a callback descriptor */
#define MrmRtypePixmapImage     10      /* Pixmap in image form */
#define MrmRtypePixmapDDIF      11      /* Pixmap in DDIF form */
#define MrmRtypeResource        12      /* Mrm resource descriptor */
#define MrmRtypeNull            13      /* no value given */
#define MrmRtypeAddrName        14      /* nul-terminated string to be
                                     interpreted as runtime address */
#define MrmRtypeIconImage       15      /* icon image */
#define MrmRtypeFont             16      /* Mrm font structure */
#define MrmRtypeFontList        17      /* Mrm font list */
#define MrmRtypeColor            18      /* Mrm color descriptor */
#define MrmRtypeColorTable      19      /* Mrm color table */
#define MrmRtypeAny              20      /* Any is allowed in UID file */
#define MrmRtypeTransTable      21      /* Translation table (ASCIZ string) */
#define MrmRtypeClassRecName     22      /* class record name (ASCIZ string) */
#define MrmRtypeIntegerVector   23      /* a vector of integers */
#define MrmRtypeXBitmapFile      24      /* X bitmap file to make pixmap with */
#define MrmRtypeCountedVector    25      /* vector with associated count */
#define MrmRtypeKeysym          26      /* X keysym data type */
#define MrmRtypeSingleFloat      27      /* single float data type */
#define MrmRtypeWideCharacter    28      /* wide_character string type */
#define MrmRtypeFontSet          29
#define MrmRtypeMax              30

/*
 * MRM typedefs

```

```

*/

/*
 * MRM primitive types
 */
typedef short int      MrmCode ;          /* Used for codes, e.g. Mrmc... */
typedef unsigned char  MrmSCode ;         /* Short code for small ranges */
typedef unsigned short int MrmOffset ;    /* Used for offsets in records */
typedef short int      MrmType ;          /* Used for types, e.g. MrmrType... */
typedef unsigned short int MrmSize ;      /* For size fields */
typedef short int      MrmCount ;         /* For counter fields */
typedef unsigned char  MrmFlag ;          /* flag fields */
typedef long int       MrmResource_id ;   /* Resource id in IDB files */
typedef short int      MrmGroup ;         /* For Mrm resource groups */

#define MrmMaxResourceSize      65535    /* (2)16 - 1 */

/*
 * Operating System specific parameter struct.  Passed to low level
 * file OPEN.
 */
#define MrmOsOpenParamVersion 1
typedef struct {
/*
 * The version of this structure. Set to MrmOsOpenParamVersion
 */
        Cardinal                version;

/*
 * The default name, for systems which can use it
 */
        char                    *default_fname;

/*
 * The related name, for systems which can use it
 * Flag for file clobber (1 means OK to clobber)
 */
        union {
                unsigned long    related_nam;
                Boolean           clobber_flg;
        } nam_flg;

/*
 * The display, for which the user wants us to open
 * this hierarchy on. Used for the LANG variable.
 */
        Display                  *display;

} MrmOsOpenParam, *MrmOsOpenParamPtr ;

/*
 * The opaque result of opening a Mrm hierarchy.
 */
typedef struct MrmHierarchyDescStruct *MrmHierarchy;

/*

```

```

    * Structure used to pass name/value pairs to MrmRegisterNames
    */
typedef struct {
    String      name ;           /* case-sensitive name */
    XtPointer    value ;        /* value/address associated with name */
} MRMRegisterArg, MrmRegisterArg, *MrmRegisterArglist ;

/*
 * Code for unknown (user-defined) classes.
 */
#define URMwcUnknown    1
```

Figure 10-55. Motif 1.2 Manifest Constants and Data Structures from MwmUtil.h

```
typedef struct
{
    long        flags;
    long        functions;
    long        decorations;
    int         input_mode;
    long        status;
} MotifWmHints;

typedef MotifWmHints    MwmHints;

/* bit definitions for MwmHints.flags */
#define MWM_HINTS_FUNCTIONS    (1L << 0)
#define MWM_HINTS_DECORATIONS (1L << 1)
#define MWM_HINTS_INPUT_MODE  (1L << 2)
#define MWM_HINTS_STATUS      (1L << 3)

/* bit definitions for MwmHints.functions */
#define MWM_FUNC_ALL           (1L << 0)
#define MWM_FUNC_RESIZE       (1L << 1)
#define MWM_FUNC_MOVE         (1L << 2)
#define MWM_FUNC_MINIMIZE     (1L << 3)
#define MWM_FUNC_MAXIMIZE     (1L << 4)
#define MWM_FUNC_CLOSE        (1L << 5)

/* bit definitions for MwmHints.decorations */
#define MWM_DECOR_ALL          (1L << 0)
#define MWM_DECOR_BORDER      (1L << 1)
#define MWM_DECOR_RESIZEH     (1L << 2)
#define MWM_DECOR_TITLE       (1L << 3)
#define MWM_DECOR_MENU        (1L << 4)
#define MWM_DECOR_MINIMIZE    (1L << 5)
#define MWM_DECOR_MAXIMIZE    (1L << 6)

/* values for MwmHints.input_mode */
#define MWM_INPUT_MODELESS          0
#define MWM_INPUT_PRIMARY_APPLICATION_MODAL 1
#define MWM_INPUT_SYSTEM_MODAL     2
#define MWM_INPUT_FULL_APPLICATION_MODAL 3

/* bit definitions for MwmHints.status */
#define MWM_TEAROFF_WINDOW          (1L << 0)

/*
 * The following is for compatibility only. It use is deprecated.
 */
#define MWM_INPUT_APPLICATION_MODAL    MWM_INPUT_PRIMARY_APPLICATION_MODAL

/*
 * Contents of the _MWM_INFO property.
```

```

*/

typedef struct
{
    long            flags;
    Window          wm_window;
} MotifWmInfo;

typedef MotifWmInfo    MwmInfo;

/* bit definitions for MotifWmInfo .flags */
#define MWM_INFO_STARTUP_STANDARD    (1L << 0)
#define MWM_INFO_STARTUP_CUSTOM     (1L << 1)

/*
 * Definitions for the _MWM_HINTS property.
 */

typedef struct
{
    CARD32          flags;
    CARD32          functions;
    CARD32          decorations;
    INT32           inputMode;
    CARD32          status;
} PropMotifWmHints;

typedef PropMotifWmHints    PropMwmHints;

/* number of elements of size 32 in _MWM_HINTS */
#define PROP_MOTIF_WM_HINTS_ELEMENTS    5
#define PROP_MWM_HINTS_ELEMENTS        PROP_MOTIF_WM_HINTS_ELEMENTS

/* atom name for _MWM_HINTS property */
#define _XA_MOTIF_WM_HINTS              "_MOTIF_WM_HINTS"
#define _XA_MWM_HINTS                   _XA_MOTIF_WM_HINTS

/*
 * Definitions for the _MWM_MESSAGES property.
 */

#define _XA_MOTIF_WM_MESSAGES           "_MOTIF_WM_MESSAGES"
#define _XA_MWM_MESSAGES                 _XA_MOTIF_WM_MESSAGES

/* atom that enables client frame offset messages */
#define _XA_MOTIF_WM_OFFSET             "_MOTIF_WM_OFFSET"

/*
 * Definitions for the _MWM_MENU property.
 */

```

```

/* atom name for _MWM_MENU property */
#define _XA_MOTIF_WM_MENU      "_MOTIF_WM_MENU"
#define _XA_MWM_MENU          _XA_MOTIF_WM_MENU

/*
 * Definitions for the _MWM_INFO property.
 */

typedef struct
{
    CARD32 flags;
    CARD32 wmWindow;
} PropMotifWmInfo;

typedef PropMotifWmInfo PropMwmInfo;

/* number of elements of size 32 in _MWM_INFO */
#define PROP_MOTIF_WM_INFO_ELEMENTS      2
#define PROP_MWM_INFO_ELEMENTS          PROP_MOTIF_WM_INFO_ELEMENTS

/* atom name for _MWM_INFO property */
#define _XA_MOTIF_WM_INFO      "_MOTIF_WM_INFO"
#define _XA_MWM_INFO          _XA_MOTIF_WM_INFO

/*
 * Miscellaneous atom definitions
 */

/* atom for motif input bindings */
#define _XA_MOTIF_BINDINGS      "_MOTIF_BINDINGS"

```

Figure 10-56. Motif 1.2 Data Structures from PanedW.h

```
typedef struct _XmPanedWindowClassRec  *XmPanedWindowWidgetClass;  
typedef struct _XmPanedWindowRec       *XmPanedWindowWidget;
```

Figure 10-57. Motif 1.2 Data Structures from PushB.h

```
typedef struct _XmPushButtonClassRec *XmPushButtonWidgetClass;  
typedef struct _XmPushButtonRec      *XmPushButtonWidget;
```

Figure 10-58. Motif 1.2 Data Structures from PushBG.h

```
typedef struct _XmPushButtonGadgetClassRec *XmPushButtonGadgetClass;  
typedef struct _XmPushButtonGadgetRec *XmPushButtonGadget;  
typedef struct _XmPushButtonGCacheObjRec *XmPushButtonGCacheObject;
```

Figure 10-59. Motif 1.2 Manifest Constants and Data Structures from RepType.h

```
#define XmREP_TYPE_INVALID          0x1FFF

typedef unsigned short XmRepTypeId ;

typedef struct
{
    String rep_type_name ;
    String *value_names ;
    unsigned char *values ;
    unsigned char num_values ;
    Boolean reverse_installed ;
    XmRepTypeId rep_type_id ;
}XmRepTypeEntryRec, *XmRepTypeEntry, XmRepTypeListRec, *XmRepTypeList ;
```

Figure 10-60. Motif 1.2 Data Structures from RowColumn.h

```
typedef struct _XmRowColumnClassRec * XmRowColumnWidgetClass;  
typedef struct _XmRowColumnRec      * XmRowColumnWidget;
```

Figure 10-61. Motif 1.2 Data Structures from Scale.h

```
/* fast XtIsSubclass define */  
  
typedef struct _XmScaleClassRec * XmScaleWidgetClass;  
typedef struct _XmScaleRec      * XmScaleWidget;
```

Figure 10-62. Motif 1.2 Data Structures from Screen.h

```
typedef struct _XmScreenRec *XmScreen;  
typedef struct _XmScreenClassRec *XmScreenClass;
```

Figure 10-63. Motif 1.2 Data Structures from ScrollBar.h

```
typedef struct _XmScrollBarClassRec * XmScrollBarWidgetClass;  
typedef struct _XmScrollBarRec      * XmScrollBarWidget;
```

Figure 10-64. Motif 1.2 Data Structures from ScrolledW.h

```
typedef struct _XmScrolledWindowClassRec * XmScrolledWindowWidgetClass;  
typedef struct _XmScrolledWindowRec      * XmScrolledWindowWidget;
```

Figure 10-65. Motif 1.2 Data Structures from SelectionB.h

```
typedef struct _XmSelectionBoxClassRec * XmSelectionBoxWidgetClass;  
typedef struct _XmSelectionBoxRec      * XmSelectionBoxWidget;
```

Figure 10-66. Motif 1.2 Data Structures from SeparatoG.h

```
typedef struct _XmSeparatorGadgetClassRec * XmSeparatorGadgetClass;  
typedef struct _XmSeparatorGadgetRec      * XmSeparatorGadget;  
typedef struct _XmSeparatorGCacheObjRec   * XmSeparatorGCacheObject;
```

Figure 10-67. Motif 1.2 Data Structures from Separator.h

```
typedef struct _XmSeparatorClassRec * XmSeparatorWidgetClass;  
typedef struct _XmSeparatorRec      * XmSeparatorWidget;
```

Figure 10-68. Motif 1.2 Data Structures from Text.h

```
typedef struct _XmTextSourceRec *XmTextSource;  
typedef struct _XmTextClassRec *XmTextWidgetClass;  
typedef struct _XmTextRec *XmTextWidget;
```

Figure 10-69. Motif 1.2 Data Structures from TextF.h

```
typedef struct _XmTextFieldClassRec *XmTextFieldWidgetClass;  
typedef struct _XmTextFieldRec *XmTextFieldWidget;
```

Figure 10-70. Motif 1.2 Data Structures from ToggleB.h

```
typedef struct _XmToggleButtonClassRec *XmToggleButtonWidgetClass;  
typedef struct _XmToggleButtonRec      *XmToggleButtonWidget;
```

Figure 10-71. Motif 1.2 Data Structures from ToggleBG.h

```
typedef struct _XmToggleButtonGadgetClassRec    *XmToggleButtonGadgetClass;  
typedef struct _XmToggleButtonGadgetRec        *XmToggleButtonGadget;  
typedef struct _XmToggleButtonGCacheObjRec     *XmToggleButtonGCacheObject;
```

Figure 10-72. Motif 1.2 Data Structures from VendorS.h

```
typedef struct _XmVendorShellRec *XmVendorShellWidget;  
typedef struct _XmVendorShellClassRec *XmVendorShellWidgetClass;
```

Figure 10-73. Motif 1.2 Manifest Constants from VirtKeys.h

```
#define _OSF_Keysyms

#define osfXK_BackSpace 0x1004FF08
#define osfXK_Insert    0x1004FF63
#define osfXK_Delete    0x1004FFFF
#define osfXK_Copy      0x1004FF02
#define osfXK_Cut       0x1004FF03
#define osfXK_Paste      0x1004FF04

#define osfXK_AddMode    0x1004FF31
#define osfXK_PrimaryPaste 0x1004FF32
#define osfXK_QuickPaste 0x1004FF33

#define osfXK_PageLeft  0x1004FF40
#define osfXK_PageUp    0x1004FF41
#define osfXK_PageDown  0x1004FF42
#define osfXK_PageRight 0x1004FF43

#define osfXK_EndLine    0x1004FF57
#define osfXK_BeginLine  0x1004FF58

#define osfXK_Activate   0x1004FF44

#define osfXK_MenuBar    0x1004FF45

#define osfXK_Clear      0x1004FF0B
#define osfXK_Cancel     0x1004FF69
#define osfXK_Help       0x1004FF6A
#define osfXK_Menu       0x1004FF67
#define osfXK_Select     0x1004FF60
#define osfXK_Undo       0x1004FF65

#define osfXK_Left       0x1004FF51
#define osfXK_Up         0x1004FF52
#define osfXK_Right      0x1004FF53
#define osfXK_Down       0x1004FF54

Motif 1.2 Manifest Constants and Data Structures from Xm.h
/* define used to denote an unspecified pixmap */

#define XmUNSPECIFIED_PIXMAP 2

/*****
 *
 * Defines for resources to be defaulted by vendors.
 * String are initialized in Xmos.c
 *
 *****/

#define XmSTRING_OS_CHARSET XmSTRING_ISO8859_1
#ifndef XmFALLBACK_CHARSET
#define XmFALLBACK_CHARSET XmSTRING_ISO8859_1
```

```
#endif

#define XmDEFAULT_FONT                _XmSDEFAULT_FONT
#define XmDEFAULT_BACKGROUND          _XmSDEFAULT_BACKGROUND
#define XmDEFAULT_DARK_THRESHOLD      15
#define XmDEFAULT_LIGHT_THRESHOLD     77
#define XmDEFAULT_FOREGROUND_THRESHOLD 35

/*****
 *
 * XmString structure defines. These must be here (at the start of the file)
 * because they are used later on.
 *
 *****/
typedef enum{ XmFONT_IS_FONT, XmFONT_IS_FONTSET } XmFontType;

enum{      XmSTRING_DIRECTION_L_TO_R,      XmSTRING_DIRECTION_R_TO_L
        } ;
#define XmSTRING_DIRECTION_DEFAULT ((XmStringDirection) 255)

typedef unsigned char * XmString;          /* opaque to outside */
typedef XmString *      XmStringTable;    /* opaque to outside */
typedef char *          XmStringCharSet;  /* Null term string */
typedef unsigned char   XmStringComponentType; /* component tags */
typedef unsigned char   XmStringDirection;

typedef struct _XmFontListRec      *XmFontListEntry; /* opaque to outside */
typedef struct _XmFontListRec      *XmFontList;      /* opaque to outside */
typedef struct __XmStringContextRec *XmStringContext; /* opaque to outside */
typedef struct __XmStringRec        *XmString;        /* opaque to outside */
typedef struct _XmtStringContextRec *XmStringContext; /* opaque to outside */
typedef struct _XmFontListContextRec *XmFontContext; /* opaque to outside */

enum{      XmSTRING_COMPONENT_UNKNOWN,      XmSTRING_COMPONENT_CHARSET,
        XmSTRING_COMPONENT_TEXT,          XmSTRING_COMPONENT_DIRECTION,
        XmSTRING_COMPONENT_SEPARATOR,      XmSTRING_COMPONENT_LOCALE_TEXT
        /* 6-125 reserved */
        } ;

#define XmSTRING_COMPONENT_END                ((XmStringComponentType) 126)

#define XmSTRING_COMPONENT_USER_BEGIN         ((XmStringComponentType) 128)
        /* 128-255 are user tags */
#define XmSTRING_COMPONENT_USER_END           ((XmStringComponentType) 255)

/*****
 *
 * Base widget class and record definitions.
 * Included are the definitions for XmPrimitive, XmManager,
 * and XmGadget.
 *
 *****/
```

```

/* Primitive widget class and record definitions */

typedef struct _XmPrimitiveClassRec * XmPrimitiveWidgetClass;
typedef struct _XmPrimitiveRec      * XmPrimitiveWidget;

/* Gadget widget class and record definitions */

typedef struct _XmGadgetClassRec * XmGadgetClass;
typedef struct _XmGadgetRec      * XmGadget;

/* Manager widger class and record definitions */

typedef struct _XmManagerClassRec * XmManagerWidgetClass;
typedef struct _XmManagerRec      * XmManagerWidget;

/*****
 * Primitive Resources and define values
 *****/

/* size policy values */

enum{      XmCHANGE_ALL,                XmCHANGE_NONE,
          XmCHANGE_WIDTH,              XmCHANGE_HEIGHT
        } ;

/* unit type values */

enum{      XmPIXELS,                    Xm100TH_MILLIMETERS,
          Xm100TH_INCHES,              Xm100TH_POINTS,
          Xm100TH_FONT_UNITS
        } ;

/* DeleteResponse values */

enum{      XmDESTROY,                   XmUNMAP,
          XmDO_NOHING
        } ;
enum{      XmEXPLICIT,                  XmPOINTER
        } ;
/*****
 * Navigation defines
 *****/

enum{      XmNONE,                      XmTAB_GROUP,
          XmSTICKY_TAB_GROUP,          XmEXCLUSIVE_TAB_GROUP
        } ;

#define XmDYNAMIC_DEFAULT_TAB_GROUP      ((XmNavigationType) 255)

/*****
 * Audible warning
 *****/

```

```

*****/

enum{      /* XmNONE */                      XmbELL = 1
          } ;

/*****
 *  Menu defines
 *****/

enum{      XmNO_ORIENTATION,                  XmVERTICAL,
          XmHORIZONTAL
          } ;
enum{      XmWORK_AREA,                      XmMENU_BAR,
          XmMENU_PULLDOWN,                  XmMENU_POPUP,
          XmMENU_OPTION
          } ;
enum{      XmNO_PACKING,                     XmpACK_TIGHT,
          XmpACK_COLUMN,                     XmpACK_NONE
          } ;
enum{ /* XmALIGNMENT_BASELINE_TOP,             XmALIGNMENT_CENTER,
      XmALIGNMENT_BASELINE_BOTTOM, */ XmALIGNMENT_CONTENTS_TOP = 3,
      XmALIGNMENT_CONTENTS_BOTTOM
      } ;
enum{      XmTEAR_OFF_ENABLED,                XmTEAR_OFF_DISABLED
          } ;
enum{      XmUNPOST,                          XmUNPOST_AND_REPLAY
          } ;
enum{      XmLAST_POSITION = -1,               XmFIRST_POSITION
          } ;
/*****
 *  Label/Frame defines
 *****/

enum{      XmALIGNMENT_BEGINNING,              XmALIGNMENT_CENTER,
          XmALIGNMENT_END
          } ;
enum{      XmALIGNMENT_BASELINE_TOP,           /* XmALIGNMENT_CENTER, */
          XmALIGNMENT_BASELINE_BOTTOM = 2, XmALIGNMENT_WIDGET_TOP,
          XmALIGNMENT_WIDGET_BOTTOM
          } ;
/*****
 *  Frame defines
 *****/

enum{      XmFRAME_GENERIC_CHILD,              XmFRAME_WORKAREA_CHILD,
          XmFRAME_TITLE_CHILD
          } ;
/*****
 *  ToggleButton defines
 *****/

enum{      XmN_OF_MANY = 1,                    XmONE_OF_MANY
          } ;
/*****

```

```

* Form defines
*****/

enum{      XmATTACH_NONE,                XmATTACH_FORM,
          XmATTACH_OPPOSITE_FORM,       XmATTACH_WIDGET,
          XmATTACH_OPPOSITE_WIDGET,     XmATTACH_POSITION,
          XmATTACH_SELF
        } ;

enum{      XmRESIZE_NONE,                XmRESIZE_GROW,
          XmRESIZE_ANY
        } ;

/*****
* Callback reasons
*****/

enum{      XmCR_NONE,                   XmCR_HELP,
          XmCR_VALUE_CHANGED,           XmCR_INCREMENT,
          XmCR_DECREMENT,               XmCR_PAGE_INCREMENT,
          XmCR_PAGE_DECREMENT,          XmCR_TO_TOP,
          XmCR_TO_BOTTOM,               XmCR_DRAG,
          XmCR_ACTIVATE,                XmCR_ARM,
          XmCR_DISARM,                  XmCR_MAP = 16,
          XmCR_UNMAP,                   XmCR_FOCUS,
          XmCR_LOSING_FOCUS,            XmCR_MODIFYING_TEXT_VALUE,
          XmCR_MOVING_INSERT_CURSOR,    XmCR_EXECUTE,
          XmCR_SINGLE_SELECT,           XmCR_MULTIPLE_SELECT,
          XmCR_EXTENDED_SELECT,         XmCR_BROWSE_SELECT,
          XmCR_DEFAULT_ACTION,          XmCR_CLIPBOARD_DATA_REQUEST,
          XmCR_CLIPBOARD_DATA_DELETE,  XmCR_CASCADING,
          XmCR_OK,                      XmCR_CANCEL,
          XmCR_APPLY = 34,              XmCR_NO_MATCH,
          XmCR_COMMAND_ENTERED,         XmCR_COMMAND_CHANGED,
          XmCR_EXPOSE,                  XmCR_RESIZE,
          XmCR_INPUT,                   XmCR_GAIN_PRIMARY,
          XmCR_LOSE_PRIMARY,            XmCR_CREATE,
          XmCR_TEAR_OFF_ACTIVATE,       XmCR_TEAR_OFF_DEACTIVATE,
          XmCR_OBSCURED_TRAVERSAL
        } ;

/*****
* Callback structures
*****/

typedef struct
{
    int      reason;
    XEvent   *event;
} XmAnyCallbackStruct;

typedef struct
{
    int      reason;
    XEvent   *event;
    int      click_count;
} XmArrowButtonCallbackStruct;

```

```
typedef struct
{
    int      reason;
    XEvent   *event;
    Window   window;
} XmDrawingAreaCallbackStruct;
```

```
typedef struct
{
    int      reason;
    XEvent   *event;
    Window   window;
    int      click_count;
} XmDrawnButtonCallbackStruct;
```

```
typedef struct
{
    int      reason;
    XEvent   *event;
    int      click_count;
} XmPushButtonCallbackStruct;
```

```
typedef struct
{
    int      reason;
    XEvent   *event;
    Widget    widget;
    char      *data;
    char      *callbackstruct;
} XmRowColumnCallbackStruct;
```

```
typedef struct
{
    int reason;
    XEvent * event;
    int value;
    int pixel;
} XmScrollBarCallbackStruct;
```

```
typedef struct
{
    int reason;
    XEvent * event;
    int set;
} XmToggleButtonCallbackStruct;
```

```
typedef struct
{
    int      reason;
    XEvent   *event;
    XmString  item;
    int      item_length;
    int      item_position;
```

```

    XmString    *selected_items;
    int          selected_item_count;
    int          *selected_item_positions;
    char         selection_type;
} XmListCallbackStruct;

typedef struct
{
    int reason;
    XEvent       *event;
    XmString     value;
    int          length;
} XmSelectionBoxCallbackStruct;

typedef struct
{
    int reason;
    XEvent       *event;
    XmString     value;
    int          length;
} XmCommandCallbackStruct;

typedef struct
{
    int          reason;
    XEvent       *event;
    XmString     value;
    int          length;
    XmString     mask;
    int          mask_length;
    XmString     dir ;
    int          dir_length ;
    XmString     pattern ;
    int          pattern_length ;
} XmFileSelectionBoxCallbackStruct;

typedef struct
{
    int reason;
    XEvent * event;
    int value;
} XmScaleCallbackStruct;

/*****
 *  PushButton defines
 *****/

enum{    XmMULTICLICK_DISCARD,          XmMULTICLICK_KEEP
        } ;

/*****
 *  DrawnButton defines
 *****/

```

```

enum{    XmSHADOW_IN = 7,                                XmSHADOW_OUT
        } ;
/*****
 * Arrow defines
 *****/

enum{    XmARROW_UP,                                    XmARROW_DOWN,
        XmARROW_LEFT,                                XmARROW_RIGHT
        } ;
/*****
 * Separator defines
 * Note: XmINVALID_SEPARATOR_TYPE marks the last+1 separator type
 *****/

enum{    XmNO_LINE,                                    XmSINGLE_LINE,
        XmDOUBLE_LINE,                                XmSINGLE_DASHED_LINE,
        XmDOUBLE_DASHED_LINE,                        XmSHADOW_ETCHED_IN,
        XmSHADOW_ETCHED_OUT,                        XmSHADOW_ETCHED_IN_DASH,
        XmSHADOW_ETCHED_OUT_DASH,                    XmINVALID_SEPARATOR_TYPE
        } ;

enum{    XmPIXMAP = 1,                                XmSTRING
        } ;

/*****
 * Drag and Drop #defines
 *****/

enum{    XmWINDOW,                                    /* XmPIXMAP, */
        XmCURSOR = 2
        } ;

/*****
 * ScrollBar #defines
 *****/

enum{    XmMAX_ON_TOP,                                XmMAX_ON_BOTTOM,
        XmMAX_ON_LEFT,                                XmMAX_ON_RIGHT
        } ;
/*****
 *
 * List Widget defines
 *
 *****/

enum{    XmSINGLE_SELECT,                                XmMULTIPLE_SELECT,
        XmEXTENDED_SELECT,                            XmBROWSE_SELECT
        } ;
enum{    XmSTATIC,                                    XmDYNAMIC
        } ;
/*****
 *
 * Scrolled Window defines.
 *
 *****/

```

```

*
*****/

enum{    XmVARIABLE,                                XmCONSTANT,
        XmRESIZE_IF_POSSIBLE
    } ;
enum{    XmAUTOMATIC,                                XmAPPLICATION_DEFINED
    } ;
enum{    /* XmSTATIC */                                XmAS_NEEDED = 1
    } ;

#define SW_TOP          1
#define SW_BOTTOM       0
#define SW_LEFT         2
#define SW_RIGHT        0

#define XmTOP_LEFT      (SW_TOP | SW_LEFT)
#define XmBOTTOM_LEFT   (SW_BOTTOM | SW_LEFT)
#define XmTOP_RIGHT     (SW_TOP | SW_RIGHT)
#define XmBOTTOM_RIGHT  (SW_BOTTOM | SW_RIGHT)

/*****
*
*   MainWindow Resources
*
*****/

enum{    XmCOMMAND_ABOVE_WORKSPACE,                XmCOMMAND_BELOW_WORKSPACE
    } ;
/*****
*
*   Text Widget defines
*
*****/

enum{    XmMULTI_LINE_EDIT,                          XmSINGLE_LINE_EDIT
    } ;

typedef enum{
    XmTEXT_FORWARD,
    XmTEXT_BACKWARD
} XmTextDirection;

typedef long XmTextPosition;
typedef Atom XmTextFormat;

#define XmFMT_8_BIT      ((XmTextFormat) XA_STRING)    /* 8-bit text. */
#define XmFMT_16_BIT     ((XmTextFormat) 2)           /* 16-bit text. */

#define FMT8BIT          XmFMT_8_BIT                  /* For backwards compatibility only.*/
#define FMT16BIT         XmFMT_16_BIT                 /* For backwards compatibility only.*/

typedef enum{
    XmSELECT_POSITION,                                XmSELECT_WHITESPACE,

```

```

        XmSELECT_WORD,                XmSELECT_LINE,
        XmSELECT_ALL,                 XmSELECT_PARAGRAPH
    } XmTextScanType ;

typedef enum{
    XmHIGHLIGHT_NORMAL,                XmHIGHLIGHT_SELECTED,
    XmHIGHLIGHT_SECONDARY_SELECTED
} XmHighlightMode ;

/* XmTextBlock's are used to pass text around. */

typedef struct {
    char *ptr;                        /* Pointer to data. */
    int length;                       /* Number of bytes of data. */
    XmTextFormat format;              /* Representations format */
} XmTextBlockRec, *XmTextBlock;

typedef struct
{
    int reason;
    XEvent *event;
    Boolean doit;
    long currInsert, newInsert;
    long startPos, endPos;
    XmTextBlock text;
} XmTextVerifyCallbackStruct, *XmTextVerifyPtr;

/* XmTextBlockWcs's are used in 1.2 modifyVerifyWcs callbacks for Text[Field]
 * widgets. */

typedef struct {
    wchar_t *wcsptr;                 /* Pointer to data. */
    int length;                       /* Number of bytes of data. */
} XmTextBlockRecWcs, *XmTextBlockWcs;

typedef struct
{
    int reason;
    XEvent *event;
    Boolean doit;
    long currInsert, newInsert;
    long startPos, endPos;
    XmTextBlockWcs text;
} XmTextVerifyCallbackStructWcs, *XmTextVerifyPtrWcs;

/* functions renamed after 1.0 release due to resource name overlap */
#define XmTextGetTopPosition          XmTextGetTopCharacter
#define XmTextSetTopPosition          XmTextSetTopCharacter

#define XmCOPY_FAILED                 0
#define XmCOPY_SUCCEEDED              1
#define XmCOPY_TRUNCATED              2

/*****

```

```

*
* DIALOG defines.. BulletinBoard and things common to its subclasses *
*      CommandBox      MessageBox      Selection      FileSelection      *
*
*
*****/

/* child type defines for Xm...GetChild() */

enum{      XmDIALOG_NONE,                      XmDIALOG_APPLY_BUTTON,
           XmDIALOG_CANCEL_BUTTON,            XmDIALOG_DEFAULT_BUTTON,
           XmDIALOG_OK_BUTTON,                XmDIALOG_FILTER_LABEL,
           XmDIALOG_FILTER_TEXT,              XmDIALOG_HELP_BUTTON,
           XmDIALOG_LIST,                    XmDIALOG_LIST_LABEL,
           XmDIALOG_MESSAGE_LABEL,            XmDIALOG_SELECTION_LABEL,
           XmDIALOG_SYMBOL_LABEL,             XmDIALOG_TEXT,
           XmDIALOG_SEPARATOR,                XmDIALOG_DIR_LIST,
           XmDIALOG_DIR_LIST_LABEL
        } ;

#define XmDIALOG_HISTORY_LIST      XmDIALOG_LIST
#define XmDIALOG_PROMPT_LABEL      XmDIALOG_SELECTION_LABEL
#define XmDIALOG_VALUE_TEXT        XmDIALOG_TEXT
#define XmDIALOG_COMMAND_TEXT      XmDIALOG_TEXT
#define XmDIALOG_FILE_LIST         XmDIALOG_LIST
#define XmDIALOG_FILE_LIST_LABEL   XmDIALOG_LIST_LABEL

/* dialog style defines */

enum{      XmDIALOG_MODELESS,                  XmDIALOG_PRIMARY_APPLICATION_MODAL,
           XmDIALOG_FULL_APPLICATION_MODAL, XmDIALOG_SYSTEM_MODAL
        } ;

/* The following is for compatibility only. Its use is deprecated.
*/
#define XmDIALOG_APPLICATION_MODAL      XmDIALOG_PRIMARY_APPLICATION_MODAL

/*****
* XmSelectionMode, XmFileSelectionMode and XmCommand - misc. stuff      *
*****/

/* Defines for Selection child placement
*/
enum{      XmPLACE_TOP,                        XmPLACE_ABOVE_SELECTION,
           XmPLACE_BELOW_SELECTION
        } ;

/* Defines for file type mask:
*/
#define XmFILE_DIRECTORY (1 << 0)
#define XmFILE_REGULAR   (1 << 1)
#define XmFILE_ANY_TYPE  (XmFILE_DIRECTORY | XmFILE_REGULAR)

/* Defines for selection dialog type:
*/

```

```
enum{      XmDIALOG_WORK_AREA,                XmDIALOG_PROMPT,
          XmDIALOG_SELECTION,                XmDIALOG_COMMAND,
          XmDIALOG_FILE_SELECTION
        } ;

/*****
 *   XmMessageBox          stuff not common to other dialogs          *
 *****/

/* defines for dialog type */

enum{      XmDIALOG_TEMPLATE,                XmDIALOG_ERROR,
          XmDIALOG_INFORMATION,            XmDIALOG_MESSAGE,
          XmDIALOG_QUESTION,              XmDIALOG_WARNING,
          XmDIALOG_WORKING
        } ;

/* Traversal types */

typedef enum{
          XmVISIBILITY_UNOBSCURED,          XmVISIBILITY_PARTIALLY_OBSCURED,
          XmVISIBILITY_FULLY_OBSCURED
        } XmVisibility ;

typedef enum{
          XmTRAVERSE_CURRENT,              XmTRAVERSE_NEXT,
          XmTRAVERSE_PREV,                XmTRAVERSE_HOME,
          XmTRAVERSE_NEXT_TAB_GROUP,      XmTRAVERSE_PREV_TAB_GROUP,
          XmTRAVERSE_UP,                  XmTRAVERSE_DOWN,
          XmTRAVERSE_LEFT,                XmTRAVERSE_RIGHT
        } XmTraversalDirection ;

typedef struct _XmTraverseObscuredCallbackStruct
{
    int          reason ;
    XEvent *     event ;
    Widget       traversal_destination ;
    XmTraversalDirection direction ;
} XmTraverseObscuredCallbackStruct ;

typedef unsigned char   XmNavigationType;

/*****
 *
 *   SimpleMenu declarations and definitions.
 *
 *****/

typedef unsigned char XmButtonType;
typedef XmButtonType * XmButtonTypeTable;
typedef KeySym * XmKeySymTable;
typedef XmStringCharSet * XmStringCharSetTable;
```

```
enum{      XmpPUSHBUTTON = 1,                XmTOGGLEBUTTON,
          XmRADIOBUTTON,                    XmCASCADEBUTTON,
          XmSEPARATOR,                      XmDOUBLE_SEPARATOR,
          XmTITLE
        } ;
#define XmCHECKBUTTON                        XmTOGGLEBUTTON
```

```
/******      BaseClass.c      *****/
```

```
typedef struct _XmSecondaryResourceDataRec{
    XmResourceBaseProc  base_proc;
    XtPointer           client_data;
    String              name;
    String              res_class;
    XtResourceList      resources;
    Cardinal            num_resources;
}XmSecondaryResourceDataRec, *XmSecondaryResourceData;
```

```
/******      Primitive.c      *****/
```

```
typedef long XmOffset;
typedef XmOffset *XmOffsetPtr;
```

Figure 10-74. Motif 1.2 Manifest Constants from XmStrDefs.h

```
#define XmS ""
#define XmCAccelerator "Accelerator"
#define XmCAcceleratorText "AcceleratorText"
#define XmCAdjustLast "AdjustLast"
#define XmCAdjustMargin "AdjustMargin"
#define XmCAlignment "Alignment"
#define XmCAllowOverlap "AllowOverlap"
#define XmCAnimationMask "AnimationMask"
#define XmCAnimationPixmap "AnimationPixmap"
#define XmCAnimationPixmapDepth "AnimationPixmapDepth"
#define XmCAnimationStyle "AnimationStyle"
#define XmCApplyLabelString "ApplyLabelString"
#define XmCArmCallback "ArmCallback"
#define XmCArmColor "ArmColor"
#define XmCArmPixmap "ArmPixmap"
#define XmCArrowDirection "ArrowDirection"
#define XmCAttachment "Attachment"
#define XmCAudibleWarning "AudibleWarning"
#define XmCAutoShowCursorPosition "AutoShowCursorPosition"
#define XmCAutoUnmanage "AutoUnmanage"
#define XmCAutomaticSelection "AutomaticSelection"
#define XmCAvailability "Availability"
#define XmCBackgroundPixmap "BackgroundPixmap"
#define XmCBlendModel "BlendModel"
#define XmCBlinkRate "BlinkRate"
#define XmCBottomShadowColor "BottomShadowColor"
#define XmCBottomShadowPixmap "BottomShadowPixmap"
#define XmCButtonAcceleratorText "ButtonAcceleratorText"
#define XmCButtonAccelerators "ButtonAccelerators"
#define XmCButtonCount "ButtonCount"
#define XmCButtonFontList "ButtonFontList"
#define XmCButtonMnemonicCharSets "ButtonMnemonicCharSets"
#define XmCButtonMnemonics "ButtonMnemonics"
#define XmCButtonSet "ButtonSet"
#define XmCButtonType "ButtonType"
#define XmCButtons "Buttons"
#define XmCCancelLabelString "CancelLabelString"
#define XmCChildHorizontalAlignment "ChildHorizontalAlignment"
#define XmCChildHorizontalSpacing "ChildHorizontalSpacing"
#define XmCChildPlacement "ChildPlacement"
#define XmCChildType "ChildType"
#define XmCChildVerticalAlignment "ChildVerticalAlignment"
#define XmCChildren "Children"
#define XmCClientData "ClientData"
#define XmCClipWindow "ClipWindow"
#define XmCColumns "Columns"
#define XmCCommandWindow "CommandWindow"
#define XmCCommandWindowLocation "CommandWindowLocation"
#define XmCConvertProc "ConvertProc"
#define XmCCursorBackground "CursorBackground"
#define XmCCursorForeground "CursorForeground"
```

```

#define XmCCursorPosition "CursorPosition"
#define XmCCursorPositionVisible "CursorPositionVisible"
#define XmCDarkThreshold "DarkThreshold"
#define XmCDecimalPoints "DecimalPoints"
#define XmCDefaultButtonShadowThickness "DefaultButtonShadowThickness"
#define XmCDefaultButtonType "DefaultButtonType"
#define XmCDefaultCopyCursorIcon "DefaultCopyCursorIcon"
#define XmCDefaultFontList "DefaultFontList"
#define XmCDefaultInvalidCursorIcon "DefaultInvalidCursorIcon"
#define XmCDefaultLinkCursorIcon "DefaultLinkCursorIcon"
#define XmCDefaultMoveCursorIcon "DefaultMoveCursorIcon"
#define XmCDefaultNoneCursorIcon "DefaultNoneCursorIcon"
#define XmCDefaultPosition "DefaultPosition"
#define XmCDefaultSourceCursorIcon "DefaultSourceCursorIcon"
#define XmCDefaultValidCursorIcon "DefaultValidCursorIcon"
#define XmCDeleteResponse "DeleteResponse"
#define XmCDesktopParent "DesktopParent"
#define XmCDialogStyle "DialogStyle"
#define XmCDialogTitle "DialogTitle"
#define XmCDialogType "DialogType"
#define XmCDirListItemCount "DirListItemCount"
#define XmCDirListItems "DirListItems"
#define XmCDirListLabelString "DirListLabelString"
#define XmCDirMask "DirMask"
#define XmCDirSearchProc "DirSearchProc"
#define XmCDirSpec "DirSpec"
#define XmCDirectory "Directory"
#define XmCDirectoryValid "DirectoryValid"
#define XmCDisarmCallback "DisarmCallback"
#define XmCDoubleClickInterval "DoubleClickInterval"
#define XmCDragContextClass "DragContextClass"
#define XmCDragDropFinishCallback "DragDropFinishCallback"
#define XmCDragIconClass "DragIconClass"
#define XmCDragInitiatorProtocolStyle "DragInitiatorProtocolStyle"
#define XmCDragMotionCallback "DragMotionCallback"
#define XmCDragOperations "DragOperations"
#define XmCDragOverMode "DragOverMode"
#define XmCDragProc "DragProc"
#define XmCDragReceiverProtocolStyle "DragReceiverProtocolStyle"
#define XmCDropProc "DropProc"
#define XmCDropRectangles "DropRectangles"
#define XmCDropSiteActivity "DropSiteActivity"
#define XmCDropSiteEnterCallback "DropSiteEnterCallback"
#define XmCDropSiteLeaveCallback "DropSiteLeaveCallback"
#define XmCDropSiteManagerClass "DropSiteManagerClass"
#define XmCDropSiteOperations "DropSiteOperations"
#define XmCDropSiteType "DropSiteType"
#define XmCDropStartCallback "DropStartCallback"
#define XmCDropTransferClass "DropTransferClass"
#define XmCDropTransfers "DropTransfers"
#define XmCEditable "Editable"
#define XmCEntryBorder "EntryBorder"
#define XmCEntryClass "EntryClass"
#define XmCExportTargets "ExportTargets"

```

```
#define XmCExposeCallback "ExposeCallback"
#define XmCExtensionType "ExtensionType"
#define XmCFileListItemCount "FileListItemCount"
#define XmCFileListItems "FileListItems"
#define XmCFileListLabelString "FileListLabelString"
#define XmCFileSearchProc "FileSearchProc"
#define XmCFileTypeMask "FileTypeMask"
#define XmCFillOnArm "FillOnArm"
#define XmCFillOnSelect "FillOnSelect"
#define XmCFilterLabelString "FilterLabelString"
#define XmCFontList "FontList"
#define XmCForegroundThreshold "ForegroundThreshold"
#define XmCHelpLabelString "HelpLabelString"
#define XmCHighlightColor "HighlightColor"
#define XmCHighlightOnEnter "HighlightOnEnter"
#define XmCHighlightPixmap "HighlightPixmap"
#define XmCHighlightThickness "HighlightThickness"
#define XmCHorizontalFontUnit "HorizontalFontUnit"
#define XmCHorizontalScrollBar "HorizontalScrollBar"
#define XmCHot "Hot"
#define XmCICCHandle "ICCHandle"
#define XmCImportTargets "ImportTargets"
#define XmCIncrement "Increment"
#define XmCIncremental "Incremental"
#define XmCIndicatorOn "IndicatorOn"
#define XmCIndicatorSize "IndicatorSize"
#define XmCIndicatorType "IndicatorType"
#define XmCInitialDelay "InitialDelay"
#define XmCInitialFocus "InitialFocus"
#define XmCInputCreate "InputCreate"
#define XmCInputMethod "InputMethod"
#define XmCInvalidCursorForeground "InvalidCursorForeground"
#define XmCIsAligned "IsAligned"
#define XmCIsHomogeneous "IsHomogeneous"
#define XmCItemCount "ItemCount"
#define XmCItems "Items"
#define XmCKeyboardFocusPolicy "KeyboardFocusPolicy"
#define XmCLabelFontList "LabelFontList"
#define XmCLabelInsensitivePixmap "LabelInsensitivePixmap"
#define XmCLabelPixmap "LabelPixmap"
#define XmCLabelString "LabelString"
#define XmCLabelType "LabelType"
#define XmCLightThreshold "LightThreshold"
#define XmCListLabelString "ListLabelString"
#define XmCListMarginHeight "ListMarginHeight"
#define XmCListMarginWidth "ListMarginWidth"
#define XmCListSizePolicy "ListSizePolicy"
#define XmCListSpacing "ListSpacing"
#define XmCListUpdated "ListUpdated"
#define XmCLogicalParent "LogicalParent"
#define XmCMainWindowMarginHeight "MainWindowMarginHeight"
#define XmCMainWindowMarginWidth "MainWindowMarginWidth"
#define XmCMappingDelay "MappingDelay"
#define XmCMarginBottom "MarginBottom"
```

```

#define XmCMarginHeight "MarginHeight"
#define XmCMarginLeft "MarginLeft"
#define XmCMarginRight "MarginRight"
#define XmCMarginTop "MarginTop"
#define XmCMarginWidth "MarginWidth"
#define XmCMask "Mask"
#define XmCMaxItems "MaxItems"
#define XmCMaxLength "MaxLength"
#define XmCMaxValue "MaxValue"
#define XmCMaximum "Maximum"
#define XmCMenuBar "MenuBar"
#define XmCMenuPost "MenuPost"
#define XmCMenuWidget "MenuWidget"
#define XmCMessageProc "MessageProc"
#define XmCMessageWindow "MessageWindow"
#define XmCMinimizeButtons "MinimizeButtons"
#define XmCMinimum "Minimum"
#define XmCMnemonic "Mnemonic"
#define XmCMnemonicCharSet "MnemonicCharSet"
#define XmCMoveOpaque "MoveOpaque"
#define XmCMultiClick "MultiClick"
#define XmCMustMatch "MustMatch"
#define XmCMwmDecorations "MwmDecorations"
#define XmCMwmFunctions "MwmFunctions"
#define XmCMwmInputMode "MwmInputMode"
#define XmCMwmMenu "MwmMenu"
#define XmCMwmMessages "MwmMessages"
#define XmCNavigationType "NavigationType"
#define XmCNeedsMotion "NeedsMotion"
#define XmCNoMatchString "NoMatchString"
#define XmCNoResize "NoResize"
#define XmCNoneCursorForeground "NoneCursorForeground"
#define XmCNotifyProc "NotifyProc"
#define XmCNumChildren "NumChildren"
#define XmCNumColumns "NumColumns"
#define XmCNumDropRectangles "NumDropRectangles"
#define XmCNumDropTransfers "NumDropTransfers"
#define XmCNumExportTargets "NumExportTargets"
#define XmCNumImportTargets "NumImportTargets"
#define XmCOffset "Offset"
#define XmCOkLabelString "OkLabelString"
#define XmCOperationChangedCallback "OperationChangedCallback"
#define XmCOperationCursorIcon "OperationCursorIcon"
#define XmCOptionLabel "OptionLabel"
#define XmCOptionMnemonic "OptionMnemonic"
#define XmCOutputCreate "OutputCreate"
#define XmCPacking "Packing"
#define XmCPageIncrement "PageIncrement"
#define XmCPaneMaximum "PaneMaximum"
#define XmCPaneMinimum "PaneMinimum"
#define XmCPattern "Pattern"
#define XmCPendingDelete "PendingDelete"
#define XmCPopupEnabled "PopupEnabled"
#define XmCPositionIndex "PositionIndex"

```

```

#define XmCPostFromButton "PostFromButton"
#define XmCPostFromCount "PostFromCount"
#define XmCPostFromList "PostFromList"
#define XmCPreeditType "PreeditType"
#define XmCProcessingDirection "ProcessingDirection"
#define XmCPromptString "PromptString"
#define XmCProtocolCallback "ProtocolCallback"
#define XmCPushButtonEnabled "PushButtonEnabled"
#define XmCQualifySearchDataProc "QualifySearchDataProc"
#define XmCRadioAlwaysOne "RadioAlwaysOne"
#define XmCRadioBehavior "RadioBehavior"
#define XmCRecomputeSize "RecomputeSize"
#define XmCRectangles "Rectangles"
#define XmCRepeatDelay "RepeatDelay"
#define XmCResizeCallback "ResizeCallback"
#define XmCResizeHeight "ResizeHeight"
#define XmCResizePolicy "ResizePolicy"
#define XmCResizeWidth "ResizeWidth"
#define XmCRowColumnType "RowColumnType"
#define XmCRows "Rows"
#define XmCRubberPositioning "RubberPositioning"
#define XmCSashHeight "SashHeight"
#define XmCSashIndent "SashIndent"
#define XmCSashWidth "SashWidth"
#define XmCScaleHeight "ScaleHeight"
#define XmCScaleMultiple "ScaleMultiple"
#define XmCScaleWidth "ScaleWidth"
#define XmCScroll "Scroll"
#define XmCScrollBarDisplayPolicy "ScrollBarDisplayPolicy"
#define XmCScrollBarPlacement "ScrollBarPlacement"
#define XmCScrollSide "ScrollSide"
#define XmCScrolledWindowMarginHeight "ScrolledWindowMarginHeight"
#define XmCScrolledWindowMarginWidth "ScrolledWindowMarginWidth"
#define XmCScrollingPolicy "ScrollingPolicy"
#define XmCSelectColor "SelectColor"
#define XmCSelectInsensitivePixmap "SelectInsensitivePixmap"
#define XmCSelectPixmap "SelectPixmap"
#define XmCSelectThreshold "SelectThreshold"
#define XmCSelectedItemCount "SelectedItemCount"
#define XmCSelectedItems "SelectedItems"
#define XmCSelectionArrayCount "SelectionArrayCount"
#define XmCSelectionLabelString "SelectionLabelString"
#define XmCSelectionPolicy "SelectionPolicy"
#define XmCSeparatorOn "SeparatorOn"
#define XmCSeparatorType "SeparatorType"
#define XmCSet "Set"
#define XmCShadowThickness "ShadowThickness"
#define XmCShadowType "ShadowType"
#define XmCShellUnitType "ShellUnitType"
#define XmCShowArrows "ShowArrows"
#define XmCShowAsDefault "ShowAsDefault"
#define XmCShowSeparator "ShowSeparator"
#define XmCShowValue "ShowValue"
#define XmCSimpleCheckBox "SimpleCheckBox"

```

```

#define XmCSimpleMenuBar "SimpleMenuBar"
#define XmCSimpleOptionMenu "SimpleOptionMenu"
#define XmCSimplePopupMenu "SimplePopupMenu"
#define XmCSimplePulldownMenu "SimplePulldownMenu"
#define XmCSimpleRadioBox "SimpleRadioBox"
#define XmCSizePolicy "SizePolicy"
#define XmCSliderSize "SliderSize"
#define XmCSource "Source"
#define XmCSourceCursorIcon "SourceCursorIcon"
#define XmCSourceIsExternal "SourceIsExternal"
#define XmCSourcePixmapIcon "SourcePixmapIcon"
#define XmCSourceWidget "SourceWidget"
#define XmCSourceWindow "SourceWindow"
#define XmCSpacing "Spacing"
#define XmCStartTime "StartTime"
#define XmCStateCursorIcon "StateCursorIcon"
#define XmCStringDirection "StringDirection"
#define XmCTearOffModel "TearOffModel"
#define XmCTextFontList "TextFontList"
#define XmCTextString "TextString"
#define XmCTextValue "TextValue"
#define XmCTitleString "TitleString"
#define XmCTopCharacter "TopCharacter"
#define XmCTopItemPosition "TopItemPosition"
#define XmCTopLevelEnterCallback "TopLevelEnterCallback"
#define XmCTopLevelLeaveCallback "TopLevelLeaveCallback"
#define XmCTopShadowColor "TopShadowColor"
#define XmCTopShadowPixmap "TopShadowPixmap"
#define XmCTransferProc "TransferProc"
#define XmCTransferStatus "TransferStatus"
#define XmCTraversalOn "TraversalOn"
#define XmCTraversalType "TraversalType"
#define XmCTreeUpdateProc "TreeUpdateProc"
#define XmCTroughColor "TroughColor"
#define XmCUnitType "UnitType"
#define XmCUnpostBehavior "UnpostBehavior"
#define XmCUnselectPixmap "UnselectPixmap"
#define XmCUpdateSliderSize "UpdateSliderSize"
#define XmCUseAsyncGeometry "UseAsyncGeometry"
#define XmCUserData "UserData"
#define XmCValidCursorForeground "ValidCursorForeground"
#define XmCValueChangedCallback "ValueChangedCallback"
#define XmCValueWcs "ValueWcs"
#define XmCVerifyBell "VerifyBell"
#define XmCVerticalAlignment "VerticalAlignment"
#define XmCVerticalFontUnit "VerticalFontUnit"
#define XmCVerticalScrollBar "VerticalScrollBar"
#define XmCVisibleItemCount "VisibleItemCount"
#define XmCVisibleWhenOff "VisibleWhenOff"
#define XmCVisualPolicy "VisualPolicy"
#define XmCWhichButton "WhichButton"
#define XmCWordWrap "WordWrap"
#define XmCWorkWindow "WorkWindow"
#define XmCXmString "XmString"

```

```

#define XmNaccelerator "accelerator"
#define XmNacceleratorText "acceleratorText"
#define XmNactivateCallback "activateCallback"
#define XmNadjustLast "adjustLast"
#define XmNadjustMargin "adjustMargin"
#define XmNalignment "alignment"
#define XmNallowOverlap "allowOverlap"
#define XmNallowResize "allowResize"
#define XmNanimationMask "animationMask"
#define XmNanimationPixmap "animationPixmap"
#define XmNanimationPixmapDepth "animationPixmapDepth"
#define XmNanimationStyle "animationStyle"
#define XmNapplyCallback "applyCallback"
#define XmNapplyLabelString "applyLabelString"
#define XmNarmCallback "armCallback"
#define XmNarmColor "armColor"
#define XmNarmPixmap "armPixmap"
#define XmNarrowDirection "arrowDirection"
#define XmNattachment "attachment"
#define XmNaudibleWarning "audibleWarning"
#define XmNautoShowCursorPosition "autoShowCursorPosition"
#define XmNautoUnmanage "autoUnmanage"
#define XmNautomaticSelection "automaticSelection"
#define XmNavailability "availability"
#define XmNblendModel "blendModel"
#define XmNblinkRate "blinkRate"
#define XmNbottomAttachment "bottomAttachment"
#define XmNbottomOffset "bottomOffset"
#define XmNbottomPosition "bottomPosition"
#define XmNbottomShadowColor "bottomShadowColor"
#define XmNbottomShadowPixmap "bottomShadowPixmap"
#define XmNbottomWidget "bottomWidget"
#define XmNbrowseSelectionCallback "browseSelectionCallback"
#define XmNbuttonAcceleratorText "buttonAcceleratorText"
#define XmNbuttonAccelerators "buttonAccelerators"
#define XmNbuttonCount "buttonCount"
#define XmNbuttonFontList "buttonFontList"
#define XmNbuttonMnemonicCharSets "buttonMnemonicCharSets"
#define XmNbuttonMnemonics "buttonMnemonics"
#define XmNbuttonSet "buttonSet"
#define XmNbuttonType "buttonType"
#define XmNbuttons "buttons"
#define XmNcancelButton "cancelButton"
#define XmNcancelCallback "cancelCallback"
#define XmNcancelLabelString "cancelLabelString"
#define XmNcascadePixmap "cascadePixmap"
#define XmNcascadingCallback "cascadingCallback"
#define XmNchildHorizontalAlignment "childHorizontalAlignment"
#define XmNchildHorizontalSpacing "childHorizontalSpacing"
#define XmNchildPlacement "childPlacement"
#define XmNchildPosition "childPosition"
#define XmNchildType "childType"
#define XmNchildVerticalAlignment "childVerticalAlignment"
#define XmNclientData "clientData"

```

```

#define XmNclipWindow "clipWindow"
#define XmNcolumns "columns"
#define XmNcommand "command"
#define XmNcommandChangedCallback "commandChangedCallback"
#define XmNcommandEnteredCallback "commandEnteredCallback"
#define XmNcommandWindow "commandWindow"
#define XmNcommandWindowLocation "commandWindowLocation"
#define XmNconvertProc "convertProc"
#define XmNcursorBackground "cursorBackground"
#define XmNcursorForeground "cursorForeground"
#define XmNcursorPosition "cursorPosition"
#define XmNcursorPositionVisible "cursorPositionVisible"
#define XmNdarkThreshold "darkThreshold"
#define XmNdecimalPoints "decimalPoints"
#define XmNdecrementCallback "decrementCallback"
#define XmNdefaultActionCallback "defaultActionCallback"
#define XmNdefaultButton "defaultButton"
#define XmNdefaultButtonShadowThickness "defaultButtonShadowThickness"
#define XmNdefaultButtonType "defaultButtonType"
#define XmNdefaultCopyCursorIcon "defaultCopyCursorIcon"
#define XmNdefaultFontList "defaultFontList"
#define XmNdefaultInvalidCursorIcon "defaultInvalidCursorIcon"
#define XmNdefaultLinkCursorIcon "defaultLinkCursorIcon"
#define XmNdefaultMoveCursorIcon "defaultMoveCursorIcon"
#define XmNdefaultNoneCursorIcon "defaultNoneCursorIcon"
#define XmNdefaultPosition "defaultPosition"
#define XmNdefaultSourceCursorIcon "defaultSourceCursorIcon"
#define XmNdefaultValidCursorIcon "defaultValidCursorIcon"
#define XmNdeleteResponse "deleteResponse"
#define XmNdesktopParent "desktopParent"
#define XmNdialogStyle "dialogStyle"
#define XmNdialogTitle "dialogTitle"
#define XmNdialogType "dialogType"
#define XmNdirItemCount "dirItemCount"
#define XmNdirListItems "dirListItems"
#define XmNdirListLabelString "dirListLabelString"
#define XmNdirMask "dirMask"
#define XmNdirSearchProc "dirSearchProc"
#define XmNdirSpec "dirSpec"
#define XmNdirectory "directory"
#define XmNdirectoryValid "directoryValid"
#define XmNdisarmCallback "disarmCallback"
#define XmNdoubleClickInterval "doubleClickInterval"
#define XmNdragCallback "dragCallback"
#define XmNdragContextClass "dragContextClass"
#define XmNdragDropFinishCallback "dragDropFinishCallback"
#define XmNdragIconClass "dragIconClass"
#define XmNdragInitiatorProtocolStyle "dragInitiatorProtocolStyle"
#define XmNdragMotionCallback "dragMotionCallback"
#define XmNdragOperations "dragOperations"
#define XmNdragOverMode "dragOverMode"
#define XmNdragProc "dragProc"
#define XmNdragReceiverProtocolStyle "dragReceiverProtocolStyle"
#define XmNdropFinishCallback "dropFinishCallback"

```

```
#define XmNdropProc "dropProc"
#define XmNdropRectangles "dropRectangles"
#define XmNdropSiteActivity "dropSiteActivity"
#define XmNdropSiteEnterCallback "dropSiteEnterCallback"
#define XmNdropSiteLeaveCallback "dropSiteLeaveCallback"
#define XmNdropSiteManagerClass "dropSiteManagerClass"
#define XmNdropSiteOperations "dropSiteOperations"
#define XmNdropSiteType "dropSiteType"
#define XmNdropStartCallback "dropStartCallback"
#define XmNdropTransferClass "dropTransferClass"
#define XmNdropTransfers "dropTransfers"
#define XmNeditMode "editMode"
#define XmNeditable "editable"
#define XmNentryAlignment "entryAlignment"
#define XmNentryBorder "entryBorder"
#define XmNentryCallback "entryCallback"
#define XmNentryClass "entryClass"
#define XmNentryVerticalAlignment "entryVerticalAlignment"
#define XmNexportTargets "exportTargets"
#define XmNexposeCallback "exposeCallback"
#define XmNextendedSelectionCallback "extendedSelectionCallback"
#define XmNextensionType "extensionType"
#define XmNfileListItemCount "fileListItemCount"
#define XmNfileListItems "fileListItems"
#define XmNfileListLabelString "fileListLabelString"
#define XmNfileSearchProc "fileSearchProc"
#define XmNfileTypeMask "fileTypeMask"
#define XmNfillOnArm "fillOnArm"
#define XmNfillOnSelect "fillOnSelect"
#define XmNfilterLabelString "filterLabelString"
#define XmNfocusCallback "focusCallback"
#define XmNfocusMovedCallback "focusMovedCallback"
#define XmNfocusPolicyChanged "focusPolicyChanged"
#define XmNfontList "fontList"
#define XmNforegroundThreshold "foregroundThreshold"
#define XmNfractionBase "fractionBase"
#define XmNgainPrimaryCallback "gainPrimaryCallback"
#define XmNhelpCallback "helpCallback"
#define XmNhelpLabelString "helpLabelString"
#define XmNhighlightColor "highlightColor"
#define XmNhighlightOnEnter "highlightOnEnter"
#define XmNhighlightPixmap "highlightPixmap"
#define XmNhighlightThickness "highlightThickness"
#define XmNhistoryItemCount "historyItemCount"
#define XmNhistoryItems "historyItems"
#define XmNhistoryMaxItems "historyMaxItems"
#define XmNhistoryVisibleItemCount "historyVisibleItemCount"
#define XmNhorizontalFontUnit "horizontalFontUnit"
#define XmNhorizontalScrollBar "horizontalScrollBar"
#define XmNhorizontalSpacing "horizontalSpacing"
#define XmNhotX "hotX"
#define XmNhotY "hotY"
#define XmNiccHandle "iccHandle"
#define XmNimportTargets "importTargets"
```

```

#define XmNincrement "increment"
#define XmNincrementCallback "incrementCallback"
#define XmNincremental "incremental"
#define XmNindicatorOn "indicatorOn"
#define XmNindicatorSize "indicatorSize"
#define XmNindicatorType "indicatorType"
#define XmNinitialDelay "initialDelay"
#define XmNinitialFocus "initialFocus"
#define XmNinputCallback "inputCallback"
#define XmNinputCreate "inputCreate"
#define XmNinputMethod "inputMethod"
#define XmNinvalidCursorForeground "invalidCursorForeground"
#define XmNisAligned "isAligned"
#define XmNisHomogeneous "isHomogeneous"
#define XmNitemCount "itemCount"
#define XmNitems "items"
#define XmNkeyboardFocusPolicy "keyboardFocusPolicy"
#define XmNlabelFontList "labelFontList"
#define XmNlabelInsensitivePixmap "labelInsensitivePixmap"
#define XmNlabelPixmap "labelPixmap"
#define XmNlabelString "labelString"
#define XmNlabelType "labelType"
#define XmNleftAttachment "leftAttachment"
#define XmNleftOffset "leftOffset"
#define XmNleftPosition "leftPosition"
#define XmNleftWidget "leftWidget"
#define XmNlightThreshold "lightThreshold"
#define XmNlineSpace "lineSpace"
#define XmNlistItemCount "listItemCount"
#define XmNlistItems "listItems"
#define XmNlistLabelString "listLabelString"
#define XmNlistMarginHeight "listMarginHeight"
#define XmNlistMarginWidth "listMarginWidth"
#define XmNlistSizePolicy "listSizePolicy"
#define XmNlistSpacing "listSpacing"
#define XmNlistUpdated "listUpdated"
#define XmNlistVisibleItemCount "listVisibleItemCount"
#define XmNlogicalParent "logicalParent"
#define XmNlosePrimaryCallback "losePrimaryCallback"
#define XmNlosingFocusCallback "losingFocusCallback"
#define XmNmainWindowMarginHeight "mainWindowMarginHeight"
#define XmNmainWindowMarginWidth "mainWindowMarginWidth"
#define XmNmapCallback "mapCallback"
#define XmNmappingDelay "mappingDelay"
#define XmNmargin "margin"
#define XmNmarginBottom "marginBottom"
#define XmNmarginHeight "marginHeight"
#define XmNmarginLeft "marginLeft"
#define XmNmarginRight "marginRight"
#define XmNmarginTop "marginTop"
#define XmNmarginWidth "marginWidth"
#define XmNmask "mask"
#define XmNmaxLength "maxLength"
#define XmNmaximum "maximum"

```

```

#define XmNmenuAccelerator "menuAccelerator"
#define XmNmenuBar "menuBar"
#define XmNmenuCursor "menuCursor"
#define XmNmenuHelpWidget "menuHelpWidget"
#define XmNmenuHistory "menuHistory"
#define XmNmenuPost "menuPost"
#define XmNmessageAlignment "messageAlignment"
#define XmNmessageProc "messageProc"
#define XmNmessageString "messageString"
#define XmNmessageWindow "messageWindow"
#define XmNminimizeButtons "minimizeButtons"
#define XmNminimum "minimum"
#define XmNmnemonic "mnemonic"
#define XmNmnemonicCharSet "mnemonicCharSet"
#define XmNmodifyVerifyCallback "modifyVerifyCallback"
#define XmNmodifyVerifyCallbackWcs "modifyVerifyCallbackWcs"
#define XmNmotionVerifyCallback "motionVerifyCallback"
#define XmNmoveOpaque "moveOpaque"
#define XmNmultiClick "multiClick"
#define XmNmultipleSelectionCallback "multipleSelectionCallback"
#define XmNmustMatch "mustMatch"
#define XmNmwmDecorations "mwmDecorations"
#define XmNmwmFunctions "mwmFunctions"
#define XmNmwmInputMode "mwmInputMode"
#define XmNmwmMenu "mwmMenu"
#define XmNmwmMessages "mwmMessages"
#define XmNnavigationType "navigationType"
#define XmNneedsMotion "needsMotion"
#define XmNnoMatchCallback "noMatchCallback"
#define XmNnoMatchString "noMatchString"
#define XmNnoResize "noResize"
#define XmNnoneCursorForeground "noneCursorForeground"
#define XmNnotifyProc "notifyProc"
#define XmNnumColumns "numColumns"
#define XmNnumDropRectangles "numDropRectangles"
#define XmNnumDropTransfers "numDropTransfers"
#define XmNnumExportTargets "numExportTargets"
#define XmNnumImportTargets "numImportTargets"
#define XmNnumRectangles "numRectangles"
#define XmNoffsetX "offsetX"
#define XmNoffsetY "offsetY"
#define XmNokCallback "okCallback"
#define XmNokLabelString "okLabelString"
#define XmNoperationChangedCallback "operationChangedCallback"
#define XmNoperationCursorIcon "operationCursorIcon"
#define XmNoptionLabel "optionLabel"
#define XmNoptionMnemonic "optionMnemonic"
#define XmNoutputCreate "outputCreate"
#define XmNpacking "packing"
#define XmNpageDecrementCallback "pageDecrementCallback"
#define XmNpageIncrement "pageIncrement"
#define XmNpageIncrementCallback "pageIncrementCallback"
#define XmNpaneMaximum "paneMaximum"
#define XmNpaneMinimum "paneMinimum"

```

```

#define XmNpattern "pattern"
#define XmNpendingDelete "pendingDelete"
#define XmNpopupEnabled "popupEnabled"
#define XmNpositionIndex "positionIndex"
#define XmNpostFromButton "postFromButton"
#define XmNpostFromCount "postFromCount"
#define XmNpostFromList "postFromList"
#define XmNpreeditType "preeditType"
#define XmNprocessingDirection "processingDirection"
#define XmNpromptString "promptString"
#define XmNprotocolCallback "protocolCallback"
#define XmNpushButtonEnabled "pushButtonEnabled"
#define XmNqualifySearchDataProc "qualifySearchDataProc"
#define XmNradioAlwaysOne "radioAlwaysOne"
#define XmNradioBehavior "radioBehavior"
#define XmNrealizeCallback "realizeCallback"
#define XmNrecomputeSize "recomputeSize"
#define XmNrectangles "rectangles"
#define XmNrefigureMode "refigureMode"
#define XmNrepeatDelay "repeatDelay"
#define XmNresizable "resizable"
#define XmNresizeCallback "resizeCallback"
#define XmNresizeHeight "resizeHeight"
#define XmNresizePolicy "resizePolicy"
#define XmNresizeWidth "resizeWidth"
#define XmNrightAttachment "rightAttachment"
#define XmNrightOffset "rightOffset"
#define XmNrightPosition "rightPosition"
#define XmNrightWidget "rightWidget"
#define XmNrowColumnType "rowColumnType"
#define XmNrows "rows"
#define XmNrubberPositioning "rubberPositioning"
#define XmNsashHeight "sashHeight"
#define XmNsashIndent "sashIndent"
#define XmNsashShadowThickness "sashShadowThickness"
#define XmNsashWidth "sashWidth"
#define XmNscaleHeight "scaleHeight"
#define XmNscaleMultiple "scaleMultiple"
#define XmNscaleWidth "scaleWidth"
#define XmNscrollBarDisplayPolicy "scrollBarDisplayPolicy"
#define XmNscrollBarPlacement "scrollBarPlacement"
#define XmNscrollHorizontal "scrollHorizontal"
#define XmNscrollLeftSide "scrollLeftSide"
#define XmNscrollTopSide "scrollTopSide"
#define XmNscrollVertical "scrollVertical"
#define XmNscrolledWindowMarginHeight "scrolledWindowMarginHeight"
#define XmNscrolledWindowMarginWidth "scrolledWindowMarginWidth"
#define XmNscrollingPolicy "scrollingPolicy"
#define XmNselectColor "selectColor"
#define XmNselectInsensitivePixmap "selectInsensitivePixmap"
#define XmNselectPixmap "selectPixmap"
#define XmNselectThreshold "selectThreshold"
#define XmNselectedItemCount "selectedItemCount"
#define XmNselectedItems "selectedItems"

```

```

#define XmNselectionArrayCount "selectionArrayCount"
#define XmNselectionLabelString "selectionLabelString"
#define XmNselectionPolicy "selectionPolicy"
#define XmNseparatorOn "separatorOn"
#define XmNseparatorType "separatorType"
#define XmNset "set"
#define XmNshadow "shadow"
#define XmNshadowThickness "shadowThickness"
#define XmNshadowType "shadowType"
#define XmNshellUnitType "shellUnitType"
#define XmNshowArrows "showArrows"
#define XmNshowAsDefault "showAsDefault"
#define XmNshowSeparator "showSeparator"
#define XmNshowValue "showValue"
#define XmNsimpleCallback "simpleCallback"
#define XmNsingleSelectionCallback "singleSelectionCallback"
#define XmNsizePolicy "sizePolicy"
#define XmNskipAdjust "skipAdjust"
#define XmNsliderSize "sliderSize"
#define XmNsource "source"
#define XmNsourceCursorIcon "sourceCursorIcon"
#define XmNsourceIsExternal "sourceIsExternal"
#define XmNsourcePixmapIcon "sourcePixmapIcon"
#define XmNsourceWidget "sourceWidget"
#define XmNsourceWindow "sourceWindow"
#define XmNspacing "spacing"
#define XmNspotLocation "spotLocation"
#define XmNstartTime "startTime"
#define XmNstateCursorIcon "stateCursorIcon"
#define XmNstringDirection "stringDirection"
#define XmNsubMenuId "subMenuId"
#define XmNsymbolPixmap "symbolPixmap"
#define XmNtearOffMenuActivateCallback "tearOffMenuActivateCallback"
#define XmNtearOffMenuDeactivateCallback "tearOffMenuDeactivateCallback"
#define XmNtearOffModel "tearOffModel"
#define XmNtextAccelerators "textAccelerators"
#define XmNtextColumns "textColumns"
#define XmNtextFontList "textFontList"
#define XmNtextString "textString"
#define XmNtextTranslations "textTranslations"
#define XmNtextValue "textValue"
#define XmNtitleString "titleString"
#define XmNtoBottomCallback "toBottomCallback"
#define XmNtoPositionCallback "toPositionCallback"
#define XmNtoTopCallback "toTopCallback"
#define XmNtopAttachment "topAttachment"
#define XmNtopCharacter "topCharacter"
#define XmNtopItemPosition "topItemPosition"
#define XmNtopLevelEnterCallback "topLevelEnterCallback"
#define XmNtopLevelLeaveCallback "topLevelLeaveCallback"
#define XmNtopOffset "topOffset"
#define XmNtopPosition "topPosition"
#define XmNtopShadowColor "topShadowColor"
#define XmNtopShadowPixmap "topShadowPixmap"

```

```

#define XmNtopWidget "topWidget"
#define XmNtransferProc "transferProc"
#define XmNtransferStatus "transferStatus"
#define XmNtraversalCallback "traversalCallback"
#define XmNtraversalOn "traversalOn"
#define XmNtraversalType "traversalType"
#define XmNtraverseObscuredCallback "traverseObscuredCallback"
#define XmNtreeUpdateProc "treeUpdateProc"
#define XmNtroughColor "troughColor"
#define XmNunitType "unitType"
#define XmNunmapCallback "unmapCallback"
#define XmNunpostBehavior "unpostBehavior"
#define XmNunselectPixmap "unselectPixmap"
#define XmNupdateSliderSize "updateSliderSize"
#define XmNuseAsyncGeometry "useAsyncGeometry"
#define XmNuserData "userData"
#define XmNvalidCursorForeground "validCursorForeground"
#define XmNvalueChangedCallback "valueChangedCallback"
#define XmNvalueWcs "valueWcs"
#define XmNverifyBell "verifyBell"
#define XmNverticalFontUnit "verticalFontUnit"
#define XmNverticalScrollBar "verticalScrollBar"
#define XmNverticalSpacing "verticalSpacing"
#define XmNvisibleItemCount "visibleItemCount"
#define XmNvisibleWhenOff "visibleWhenOff"
#define XmNvisualPolicy "visualPolicy"
#define XmNwhichButton "whichButton"
#define XmNwordWrap "wordWrap"
#define XmNworkWindow "workWindow"
#define XmRAlignment "Alignment"
#define XmRAnimationMask "AnimationMask"
#define XmRAnimationPixmap "AnimationPixmap"
#define XmRAnimationStyle "AnimationStyle"
#define XmRArrowDirection "ArrowDirection"
#define XmRAtomList "AtomList"
#define XmRAttachment "Attachment"
#define XmRAudibleWarning "AudibleWarning"
#define XRAvailability "Availability"
#define XmRBackgroundPixmap "BackgroundPixmap"
#define XmRBlendModel "BlendModel"
#define XmRBooleanDimension "BooleanDimension"
#define XmRBottomShadowPixmap "BottomShadowPixmap"
#define XmRButtonType "ButtonType"
#define XmRCallbackProc "CallbackProc"
#define XmRChar "Char"
#define XmRCharSetTable "CharSetTable"
#define XmRChildHorizontalAlignment "ChildHorizontalAlignment"
#define XmRChildPlacement "ChildPlacement"
#define XmRChildType "ChildType"
#define XmRChildVerticalAlignment "ChildVerticalAlignment"
#define XmRCommandWindowLocation "CommandWindowLocation"
#define XmRCompoundText "CompoundText"
#define XmRDefaultButtonType "DefaultButtonType"
#define XmRDeleteResponse "DeleteResponse"

```

```

#define XmRDialogStyle "DialogStyle"
#define XmRDialogType "DialogType"
#define XmRDoubleClickInterval "DoubleClickInterval"
#define XmRDragInitiatorProtocolStyle "DragInitiatorProtocolStyle"
#define XmRDragReceiverProtocolStyle "DragReceiverProtocolStyle"
#define XmRDropSiteActivity "DropSiteActivity"
#define XmRDropSiteOperations "DropSiteOperations"
#define XmRDropSiteType "DropSiteType"
#define XmRDropTransfers "DropTransfers"
#define XmRExtensionType "ExtensionType"
#define XmRFileTypeMask "FileTypeMask"
#define XmRFontList "FontList"
#define XmRGadgetPixmap "GadgetPixmap"
#define XmRHighlightPixmap "HighlightPixmap"
#define XmRHorizontalDimension "HorizontalDimension"
#define XmRHorizontalInt "HorizontalInt"
#define XmRHorizontalPosition "HorizontalPosition"
#define XmRIconAttachment "IconAttachment"
#define XmRImportTargets "ImportTargets"
#define XmRIndicatorType "IndicatorType"
#define XmRItemCount "ItemCount"
#define XmRItems "Items"
#define XmRKeySym "KeySym"
#define XmRKeySymTable "KeySymTable"
#define XmRKeyboardFocusPolicy "KeyboardFocusPolicy"
#define XmRLabelType "LabelType"
#define XmRListMarginHeight "ListMarginHeight"
#define XmRListMarginWidth "ListMarginWidth"
#define XmRListSizePolicy "ListSizePolicy"
#define XmRListSpacing "ListSpacing"
#define XmRManBottomShadowPixmap "ManBottomShadowPixmap"
#define XmRManForegroundPixmap "ManForegroundPixmap"
#define XmRManHighlightPixmap "ManHighlightPixmap"
#define XmRManTopShadowPixmap "ManTopShadowPixmap"
#define XmRMenuWidget "MenuWidget"
#define XmRMnemonic "Mnemonic"
#define XmRMultiClick "MultiClick"
#define XmRNavigationType "NavigationType"
#define XmRPacking "Packing"
#define XmRPrimForegroundPixmap "PrimForegroundPixmap"
#define XmRProc "Proc"
#define XmRProcessingDirection "ProcessingDirection"
#define XmRRectangleList "RectangleList"
#define XmRResizePolicy "ResizePolicy"
#define XmRRowColumnType "RowColumnType"
#define XmRScrollBarDisplayPolicy "ScrollBarDisplayPolicy"
#define XmRScrollBarPlacement "ScrollBarPlacement"
#define XmRScrollingPolicy "ScrollingPolicy"
#define XmRSelectedItemCount "SelectedItemCount"
#define XmRSelectedItems "SelectedItems"
#define XmRSelectionPolicy "SelectionPolicy"
#define XmRSelectionType "SelectionType"
#define XmRSeparatorType "SeparatorType"
#define XmRShadowType "ShadowType"

```

```

#define XmRShellHorizDim "ShellHorizDim"
#define XmRShellHorizPos "ShellHorizPos"
#define XmRShellUnitType "ShellUnitType"
#define XmRShellVertDim "ShellVertDim"
#define XmRShellVertPos "ShellVertPos"
#define XmRSizePolicy "SizePolicy"
#define XmRStringDirection "StringDirection"
#define XmRTearOffModel "TearOffModel"
#define XmRTopShadowPixmap "TopShadowPixmap"
#define XmRTransferStatus "TransferStatus"
#define XmRTraversalType "TraversalType"
#define XmRUnitType "UnitType"
#define XmRUNpostBehavior "UnpostBehavior"
#define XmRValueWcs "ValueWcs"
#define XmRVerticalAlignment "VerticalAlignment"
#define XmRVerticalDimension "VerticalDimension"
#define XmRVerticalInt "VerticalInt"
#define XmRVerticalPosition "VerticalPosition"
#define XmRVirtualBinding "VirtualBinding"
#define XmRVisibleItemCount "VisibleItemCount"
#define XmRVisualPolicy "VisualPolicy"
#define XmRWhichButton "WhichButton"
#define XmRXmBackgroundPixmap "XmBackgroundPixmap"
#define XmRXmString "XmString"
#define XmRXmStringCharSet "XmStringCharSet"
#define XmRXmStringTable "XmStringTable"
#define XmVosfActivate "osfActivate"
#define XmVosfAddMode "osfAddMode"
#define XmVosfBackSpace "osfBackSpace"
#define XmVosfBeginLine "osfBeginLine"
#define XmVosfCancel "osfCancel"
#define XmVosfClear "osfClear"
#define XmVosfCopy "osfCopy"
#define XmVosfCut "osfCut"
#define XmVosfDelete "osfDelete"
#define XmVosfDown "osfDown"
#define XmVosfEndLine "osfEndLine"
#define XmVosfHelp "osfHelp"
#define XmVosfInsert "osfInsert"
#define XmVosfLeft "osfLeft"
#define XmVosfMenu "osfMenu"
#define XmVosfMenuBar "osfMenuBar"
#define XmVosfPageDown "osfPageDown"
#define XmVosfPageLeft "osfPageLeft"
#define XmVosfPageRight "osfPageRight"
#define XmVosfPageUp "osfPageUp"
#define XmVosfPaste "osfPaste"
#define XmVosfPrimaryPaste "osfPrimaryPaste"
#define XmVosfQuickPaste "osfQuickPaste"
#define XmVosfRight "osfRight"
#define XmVosfSelect "osfSelect"
#define XmVosfUndo "osfUndo"
#define XmVosfUp "osfUp"
#define XmSFONTLIST_DEFAULT_TAG_STRING "FONTLIST_DEFAULT_TAG_STRING"

```

```

#define XmSXmFONTLIST_DEFAULT_TAG_STRING "XmFONTLIST_DEFAULT_TAG_STRING"
#define _XmConst /**/

#define XmSTRING_DEFAULT_CHARSET          XmS
#define XmSTRING_ISO8859_1               "ISO8859-1"
#define XmFONTLIST_DEFAULT_TAG           XmSFONTLIST_DEFAULT_TAG_STRING
#define XmFONTLIST_DEFAULT_TAG_STRING    XmSXmFONTLIST_DEFAULT_TAG_STRING

#define XmVaCASCADEBUTTON                 "cascadeButton"
#define XmVaCHECKBUTTON                   "checkButton"
#define XmVaDOUBLE_SEPARATOR              "doubleSeparator"
#define XmVaPUSHBUTTON                    "pushButton"
#define XmVaRADIOBUTTON                   "radioButton"
#define XmVaSEPARATOR                     "separator"
#define XmVaSINGLE_SEPARATOR               "singleSeparator"
#define XmVaTOGGLEBUTTON                  "checkButton"
#define XmVaTITLE                          XtNtitle

#define XtCKeyboardFocusPolicy            XmCKeyboardFocusPolicy
#define XtCShellUnitType                  XmCShellUnitType
#define XtNkeyboardFocusPolicy            XmNkeyboardFocusPolicy
#define XtNshellUnitType                  XmNshellUnitType
#define XtRKeyboardFocusPolicy            XmRKeyboardFocusPolicy

#define XmRPrimBottomShadowPixmap         XmRBottomShadowPixmap
#define XmRPrimHighlightPixmap            XmRHighlightPixmap
#define XmRPrimTopShadowPixmap            XmRTopShadowPixmap

#define XmCAccelerators                   XtCAccelerators
#define XmCAllowShellResize               XtCAllowShellResize
#define XmCArgc                           XtCArgc
#define XmCArgv                           XtCArgv
#define XmCBackground                     XtCBackground
#define XmCBaseHeight                     XtCBaseHeight
#define XmCBaseHeight                     XtCBaseHeight
#define XmCBaseWidth                      XtCBaseWidth
#define XmCBaseWidth                      XtCBaseWidth
#define XmCBitmap                         XtCBitmap
#define XmCBoolean                        XtCBoolean
#define XmCBorderColor                    XtCBorderColor
#define XmCBorderWidth                    XtCBorderWidth
#define XmCCallback                       XtCCallback
#define XmCColor                          XtCColor
#define XmCColormap                       XtCColormap
#define XmCCreatePopupChildProc           XtCCreatePopupChildProc
#define XmCCursor                         XtCCursor
#define XmCDepth                          XtCDepth
#define XmCDimension                      XtRDimension
#define XmCEditMode                       XtREditMode
#define XmCEditType                       XtCEditType
#define XmCEventBindings                  XtCEventBindings
#define XmCFile                           XtCFile
#define XmCFont                           XtCFont
#define XmCFontSet                        XtCFontSet

```

#define XmCForeground	XtCForeground
#define XmCFraction	XtCFraction
#define XmCFunction	XtCFunction
#define XmCGeometry	XtCGeometry
#define XmCHSpace	XtCHSpace
#define XmCHeight	XtCHeight
#define XmCHeightInc	XtCHeightInc
#define XmCIconMask	XtCIconMask
#define XmCIconName	XtCIconName
#define XmCIconNameEncoding	XtCIconNameEncoding
#define XmCIconPixmap	XtCIconPixmap
#define XmCIconWindow	XtCIconWindow
#define XmCIconX	XtCIconX
#define XmCIconY	XtCIconY
#define XmCIconic	XtCIconic
#define XmCIndex	XtCIndex
#define XmCInitialResourcesPersistent	XtCInitialResourcesPersistent
#define XmCInitialState	XtCInitialState
#define XmCInput	XtCInput
#define XmCInsertPosition	XtCInsertPosition
#define XmCInterval	XtCInterval
#define XmCJustify	XtCJustify
#define XmCLabel	XtCLabel
#define XmCLength	XtCLength
#define XmCMappedWhenManaged	XtCMappedWhenManaged
#define XmCMargin	XtCMargin
#define XmCMaxAspectX	XtCMaxAspectX
#define XmCMaxAspectY	XtCMaxAspectY
#define XmCMaxHeight	XtCMaxHeight
#define XmCMaxWidth	XtCMaxWidth
#define XmCMenuEntry	XtCMenuEntry
#define XmCMinAspectX	XtCMinAspectX
#define XmCMinAspectY	XtCMinAspectY
#define XmCMinHeight	XtCMinHeight
#define XmCMinWidth	XtCMinWidth
#define XmCNotify	XtCNotify
#define XmCOrientation	XtCOrientation
#define XmCOVERRIDERedirect	XtCOVERRIDERedirect
#define XmCParameter	XtCParameter
#define XmCPixmap	XtCPixmap
#define XmCPosition	XtCPosition
#define XmCReadOnly	XtCReadOnly
#define XmCResize	XtCResize
#define XmCReverseVideo	XtCReverseVideo
#define XmCSaveUnder	XtCSaveUnder
#define XmCScreen	XtCScreen
#define XmCScrollDCursor	XtCScrollDCursor
#define XmCScrollHCursor	XtCScrollHCursor
#define XmCScrollLCursor	XtCScrollLCursor
#define XmCScrollProc	XtCScrollProc
#define XmCScrollRCursor	XtCScrollRCursor
#define XmCScrollUCursor	XtCScrollUCursor
#define XmCScrollVCursor	XtCScrollVCursor
#define XmCSelection	XtCSelection

#define XmCSelectionArray	XtCSelectionArray
#define XmCSensitive	XtCSensitive
#define XmCSpace	XtCSpace
#define XmCString	XtCString
#define XmCTextOptions	XtCTextOptions
#define XmCTextPosition	XtCTextPosition
#define XmCTextSink	XtCTextSink
#define XmCTextSource	XtCTextSource
#define XmCThickness	XtCThickness
#define XmCThumb	XtCThumb
#define XmCTitle	XtCTitle
#define XmCTitleEncoding	XtCTitleEncoding
#define XmCTransient	XtCTransient
#define XmCTransientFor	XtCTransientFor
#define XmCTranslations	XtCTranslations
#define XmCVSpace	XtCVSpace
#define XmCValue	XtCValue
#define XmCVisual	XtCVisual
#define XmCWaitForWm	XtCWaitForWm
#define XmCWidget	XtRWidget
#define XmCWidth	XtCWidth
#define XmCWidthInc	XtCWidthInc
#define XmCWinGravity	XtCWinGravity
#define XmCWindow	XtCWindow
#define XmCWindowGroup	XtCWindowGroup
#define XmCWmTimeout	XtCWmTimeout
#define XmCX	XtCX
#define XmCY	XtCY
#define XmNaccelerators	XtNaccelerators
#define XmNallowShellResize	XtNallowShellResize
#define XmNancestorSensitive	XtNancestorSensitive
#define XmNargc	XtNargc
#define XmNargv	XtNargv
#define XmNbackground	XtNbackground
#define XmNbackgroundPixmap	XtNbackgroundPixmap
#define XmNbaseHeight	XtNbaseHeight
#define XmNbaseHeight	XtNbaseHeight
#define XmNbaseWidth	XtNbaseWidth
#define XmNbaseWidth	XtNbaseWidth
#define XmNbitmap	XtNbitmap
#define XmNborder	XtNborder
#define XmNborderColor	XtNborderColor
#define XmNborderPixmap	XtNborderPixmap
#define XmNborderWidth	XtNborderWidth
#define XmNcallback	XtNcallback
#define XmNchildren	XtNchildren
#define XmNcolormap	XtNcolormap
#define XmNcreatePopupChildProc	XtNcreatePopupChildProc
#define XmNdepth	XtNdepth
#define XmNdestroyCallback	XtNdestroyCallback
#define XmNeditType	XtNeditType
#define XmNfile	XtNfile
#define XmNfont	XtNfont
#define XmNfontSet	XtNfontSet

#define XmNforceBars	XtNforceBars
#define XmNforeground	XtNforeground
#define XmNfunction	XtNfunction
#define XmNgeometry	XtNgeometry
#define XmNheight	XtNheight
#define XmNheightInc	XtNheightInc
#define XmNhighlight	XtNhighlight
#define XmNiconMask	XtNiconMask
#define XmNiconName	XtNiconName
#define XmNiconNameEncoding	XtNiconNameEncoding
#define XmNiconPixmap	XtNiconPixmap
#define XmNiconWindow	XtNiconWindow
#define XmNiconX	XtNiconX
#define XmNiconY	XtNiconY
#define XmNiconic	XtNiconic
#define XmNindex	XtNindex
#define XmNinitialResourcesPersistent	XtNinitialResourcesPersistent
#define XmNinitialState	XtNinitialState
#define XmNinnerHeight	XtNinnerHeight
#define XmNinnerWidth	XtNinnerWidth
#define XmNinnerWindow	XtNinnerWindow
#define XmNinput	XtNinput
#define XmNinsertPosition	XtNinsertPosition
#define XmNinternalHeight	XtNinternalHeight
#define XmNinternalWidth	XtNinternalWidth
#define XmNjumpProc	XtNjumpProc
#define XmNjustify	XtNjustify
#define XmNlength	XtNlength
#define XmNlowerRight	XtNlowerRight
#define XmNmappedWhenManaged	XtNmappedWhenManaged
#define XmNmaxAspectX	XtNmaxAspectX
#define XmNmaxAspectY	XtNmaxAspectY
#define XmNmaxHeight	XtNmaxHeight
#define XmNmaxWidth	XtNmaxWidth
#define XmNmenuEntry	XtNmenuEntry
#define XmNminAspectX	XtNminAspectX
#define XmNminAspectY	XtNminAspectY
#define XmNminHeight	XtNminHeight
#define XmNminWidth	XtNminWidth
#define XmNname	XtNname
#define XmNnotify	XtNnotify
#define XmNnumChildren	XtNnumChildren
#define XmNorientation	XtNorientation
#define XmNoverrideRedirect	XtNoverrideRedirect
#define XmNparameter	XtNparameter
#define XmNpixmap	XtNpixmap
#define XmNpopdownCallback	XtNpopdownCallback
#define XmNpopupCallback	XtNpopupCallback
#define XmNresize	XtNresize
#define XmNreverseVideo	XtNreverseVideo
#define XmNsaveUnder	XtNsaveUnder
#define XmNscreen	XtNscreen
#define XmNscrollDCursor	XtNscrollDCursor
#define XmNscrollHCursor	XtNscrollHCursor

#define XmNscrollLCursor	XtNscrollLCursor
#define XmNscrollProc	XtNscrollProc
#define XmNscrollRCursor	XtNscrollRCursor
#define XmNscrollUCursor	XtNscrollUCursor
#define XmNscrollVCursor	XtNscrollVCursor
#define XmNselection	XtNselection
#define XmNselectionArray	XtNselectionArray
#define XmNsensitive	XtNsensitive
#define XmNshown	XtNshown
#define XmNspace	XtNspace
#define XmNstring	XtNstring
#define XmNtextOptions	XtNtextOptions
#define XmNtextSink	XtNtextSink
#define XmNtextSource	XtNtextSource
#define XmNthickness	XtNthickness
#define XmNthumb	XtNthumb
#define XmNthumbProc	XtNthumbProc
#define XmNtitle	XtNtitle
#define XmNtitleEncoding	XtNtitleEncoding
#define XmNtop	XtNtop
#define XmNtransient	XtNtransient
#define XmNtransientFor	XtNtransientFor
#define XmNtransientFor	XtNtransientFor
#define XmNtranslations	XtNtranslations
#define XmNupdate	XtNupdate
#define XmNuseBottom	XtNuseBottom
#define XmNuseRight	XtNuseRight
#define XmNvalue	XtNvalue
#define XmNvisual	XtNvisual
#define XmNwaitForWm	XtNwaitForWm
#define XmNwidth	XtNwidth
#define XmNwidthInc	XtNwidthInc
#define XmNwinGravity	XtNwinGravity
#define XmNwindow	XtNwindow
#define XmNwindowGroup	XtNwindowGroup
#define XmNwmTimeout	XtNwmTimeout
#define XmNx	XtNx
#define XmNy	XtNy
#define XmRAcceleratorTable	XtRAcceleratorTable
#define XmRAtom	XtRAtom
#define XmRBitmap	XtRBitmap
#define XmRBool	XtRBool
#define XmRBoolean	XtRBoolean
#define XmRCallProc	XtRCallProc
#define XmRCallback	XtRCallback
#define XmRCardinal	XtRCardinal
#define XmRColor	XtRColor
#define XmRColormap	XtRColormap
#define XmRCursor	XtRCursor
#define XmRDimension	XtRDimension
#define XmRDisplay	XtRDisplay
#define XmREditMode	XtREditMode
#define XmREnum	XtREnum
#define XmRFile	XtRFile

#define XmRFloat	XtRFloat
#define XmRFont	XtRFont
#define XmRFontSet	XtRFontSet
#define XmRFontStruct	XtRFontStruct
#define XmRFunction	XtRFunction
#define XmRGeometry	XtRGeometry
#define XmRImmediate	XtRImmediate
#define XmRInitialState	XtRInitialState
#define XmRInt	XtRInt
#define XmRJustify	XtRJustify
#define XmRLongBoolean	XtRLongBoolean
#define XmROrientation	XtROrientation
#define XmRObject	XtRObject
#define XmRPixel	XtRPixel
#define XmRPixmap	XtRPixmap
#define XmRPointer	XtRPointer
#define XmRPosition	XtRPosition
#define XmRScreen	XtRScreen
#define XmRShort	XtRShort
#define XmRString	XtRString
#define XmRStringArray	XtRStringArray
#define XmRStringTable	XtRStringTable
#define XmRTextPosition	XtCTextPosition
#define XmRTranslationTable	XtRTranslationTable
#define XmRUnsignedChar	XtRUnsignedChar
#define XmRVisual	XtRVisual
#define XmRWidget	XtRWidget
#define XmRWidgetClass	XtRWidgetClass
#define XmRWidgetList	XtRWidgetList
#define XmRWindow	XtRWindow

Windowing and Terminal Interfaces Changes

The following are changes to the *System V ABI*, the *System V ABI SPARC Processor Supplement*, and the *System V Interface Definition* as reported to SPARC International.

#	Facility	Location	Description
	NeWS Overview	gABI	Delete this.
	NeWS Library	gABI	Delete this section -- refers to tNt 1.1, which is obsolete.

--

Index

--

Symbols

.div 6-4
 .mul 6-4
 .rem 6-4
 .stret1 6-4
 .stret2 6-4
 .stret4 6-4
 .stret8 6-4
 .udiv 6-4
 .umul 6-4
 .urem 6-4
 /dev 9-1
 __assert 6-11, 6-13
 __dtou 6-4, 6-7
 __filbuf 6-11
 __flsbuf 6-11
 __ftou 6-4, 6-7
 __tolower 6-11
 __toupper 6-11
 _exit 6-3
 _Q_add 6-4
 _Q_cmp 6-4
 _Q_cmpe 6-4
 _Q_div 6-4
 _Q_dtoq 6-4
 _Q_feq 6-4
 _Q_fge 6-4
 _Q_fgt 6-4
 _Q_fle 6-4
 _Qflt 6-4
 _Q_fne 6-4
 _Q_itoq 6-4
 _Q_mul 6-4
 _Q_neg 6-4
 _Q_qtod 6-4
 _Q_qtoi 6-4
 _Q_qtos 6-4
 _Q_qtou 6-4, 6-6
 _Q_sqrt 6-4
 _Q_stoq 6-4
 _Q_sub 6-4
 _Q_utoq 6-4
 _xdebug 10-8
 _xftw 6-11
 _XtInherit 10-88, 10-114
 _XtInheritTranslations 10-88
A
 abbrevMenuButtonClassRec 10-128
 abbrevMenuButtonWidgetClass 10-128
 ABI
 generic 1-3
 processor specific 1-3
 ABI Errata 2-1, 6-77, 10-236

abort 6-11
 abs 6-11
 accept 6-26
 access 6-3
 acct 6-3
 addseverity 6-11, 6-13
 alarm 6-3
 AllocateBuffer 10-126
 AllocateTextBuffer 10-126
 Application Binary Interface 1-1
 Application Program Commands 8-1
 ApplicationShellClassPart 10-123
 ApplicationShellClassRec 10-123
 applicationShellClassRec 10-88
 ApplicationShellPart 10-123
 ApplicationShellRec 10-123
 ApplicationShellWidget 10-123
 ApplicationShellWidgetClass 10-101
 applicationShellWidgetClass 10-88
 Arg 10-94
 ArgList 10-94
 asctime 6-11
 atexit 6-3
 atof 6-11
 atoi 6-11
 atol 6-11
 Atom 10-31
 audience 7
 application developers 7
 system implementors 7
 authdes_getucrd 6-22
 authdes_seccreate 6-22
 authnone_create 6-22
 authsys_create 6-22
 authsys_create_default 6-22

B

BA_ENV 6-2
 BA_LIB 6-2
 BA_OS 6-2
 BackwardScanTextBuffer 10-126
 baseWindowShellClassRec 10-128
 baseWindowShellWidgetClass 10-128
 bind 6-26
 BitmapPad
 unsafe, use XBitmapPad 10-9
 BitmapUnit
 unsafe, use XBitmapUnit 10-9
 BlackPixel
 unsafe, use XBlackPixel 10-9
 BlackPixelOfScreen
 unsafe, use XBlackPixelOfScreen 10-9
 BlockTable 10-138
 Boolean 10-92

bsearch 6-11
Buffer 10-138
BufferElement 10-138
bulletinBoardClassRec 10-128
bulletinBoardWidgetClass 10-128
buttonClassRec 10-128
buttonGadgetClass 10-128
buttonGadgetClassRec 10-128
buttonWidgetClass 10-128

C

C library 6-10
calloc 6-3
captionClassRec 10-128
CaptionWidget 10-134
CaptionWidgetClass 10-134
captionWidgetClass 10-128
Cardinal 10-93
cat 8-2
catclose 6-3
categoryClassRec 10-128
CategoryWidget 10-134
CategoryWidgetClass 10-134
categoryWidgetClass 10-128
catgets 6-3
catopen 6-3
cd 8-2
CellsOfScreen
 unsafe, use XCellsOfScreen 10-9
cfgetispeed 6-11
cfgetospeed 6-11
cfsetispeed 6-11
cfsetospeed 6-11
chdir 6-3
checkBoxClassRec 10-128
CheckBoxWidget 10-134
CheckBoxWidgetClass 10-134
checkBoxWidgetClass 10-128
chgrp 8-2
chmod 6-3, 8-2
chown 6-3, 8-2
chroot 6-3
clearerr 6-11
ClientWhitePointOfCCC
 unsafe, use XClientWhitePointOfCCC 10-9
clnt_create 6-22
clnt_dg_create 6-22
clnt_pcreateerror 6-22
clnt_perrno 6-22
clnt_perror 6-22
clnt_raw_create 6-22
clnt_spccreateerror 6-22
clnt_sperrno 6-22
clnt_sperror 6-22
clnt_tli_create 6-22
clnt_tp_create 6-22
clnt_vc_create 6-22
clock 6-11
close 6-3
closedir 6-3
cmp 8-2
colorConvertArgs 10-88
Colormap 10-31
CompositeClassExtension 10-108
CompositeClassExtensionRec 10-108
CompositeClassPart 10-108
CompositeClassRec 10-108
compositeClassRec 10-88
CompositePart 10-108
CompositePartPtr 10-108
CompositePtr 10-108
CompositeRec 10-108
CompositeWidget 10-92
CompositeWidgetClass 10-89
compositeWidgetClass 10-88
connect 6-26
ConnectionNumber
 unsafe, use XConnectionNumber 10-9
ConstraintClassExtension 10-109
ConstraintClassExtensionRec 10-109
ConstraintClassPart 10-109
ConstraintClassRec 10-109
constraintClassRec 10-88
ConstraintPart 10-109
ConstraintRec 10-109
ConstraintWidget 10-109
ConstraintWidgetClass 10-90
constraintWidgetClass 10-88
contents of SCD 2.2 7
ControlAreaWidget 10-134
ControlAreaWidgetClass 10-134
controlAreaWidgetClass 10-128
controlClassRec 10-128
ControlLayout 10-134
CopyBuffer 10-126
CopyTextBufferBlock 10-126
CoreClassPart 10-111
CoreClassRec 10-111
CorePart 10-110
CoreRec 10-110
CoreWidget 10-91
CoreWidgetClass 10-91
coreWidgetClass 10-88
cp 8-2
cpio 2-1, 8-2
creat 6-3
crypt 6-11, 6-13, 6-14
ctermid 6-11

ctime 6-11
 Cursor 10-31
 cuserid 6-11

D

Data Structures

Motif 10-149, 10-150, 10-151, 10-152, 10-153, 10-154, 10-155, 10-156, 10-157, 10-158, 10-161, 10-162, 10-163, 10-164, 10-165, 10-167, 10-168, 10-169, 10-170, 10-171, 10-172, 10-173, 10-174, 10-175, 10-176, 10-177, 10-181, 10-184, 10-185, 10-186, 10-187, 10-188, 10-189, 10-190, 10-191, 10-192, 10-193, 10-194, 10-195, 10-196, 10-197, 10-198, 10-199, 10-200, 10-201
 Xlib 6-28, 6-32, 6-33, 6-34, 6-61, 10-13, 10-31, 10-45, 10-47
 Xol 10-134
 date 8-2
 dd 2-1, 8-2
 DefaultColormap
 unsafe, use XDefaultColormap 10-9
 DefaultColormapOfScreen
 unsafe, use XDefaultColormapOfScreen 10-9
 DefaultDepth
 unsafe, use XDefaultDepth 10-9
 DefaultDepthOfScreen
 unsafe, use XDefaultDepthOfScreen 10-9
 DefaultGC
 unsafe, use XDefaultGC 10-9
 DefaultGCOfScreen
 unsafe, use XDefaultGCOfScreen 10-9
 DefaultRootWindow
 unsafe, use XDefaultRootWindow 10-9
 DefaultScreen
 unsafe, use XDefaultScreen 10-9
 DefaultScreenOfDisplay
 unsafe, use XDefaultScreenOfDisplay 10-9
 DefaultVisual
 unsafe, use XDefaultVisual 10-9
 DefaultVisualOfScreen
 unsafe, use XDefaultVisualOfScreen 10-9
 definition of audience 7
 definition of purpose 7
 Depth 10-14
 df 8-2
 difftime 6-11
 Dimension 10-93
 Display 10-18
 DisplayCells
 unsafe, use XDisplayCells 10-9
 DisplayHeight

 unsafe, use XDisplayHeight 10-10
 DisplayHeightMM
 unsafe, use XDisplayHeightMM 10-10
 DisplayOfCCC
 unsafe, use XDisplayOfCCC 10-10
 DisplayOfScreen
 unsafe, use XDisplayOfScreen 10-10
 DisplayPlanes
 unsafe, use XDisplayPlanes 10-10
 DisplayString
 unsafe, use XDisplayString 10-10
 DisplayWidth
 unsafe, use XDisplayWidth 10-10
 DisplayWidthMM
 unsafe, use XDisplayWidthMM 10-10
 div 6-11
 dlclose 6-60
 dlerror 6-60
 dlopen 6-60
 dlsym 6-60
 DoesBackingStore
 unsafe, use XDoesBackingStore 10-10
 DoesSaveUnders
 unsafe, use XDoesSaveUnders 10-10
 Drawable 10-31
 dup 6-3
 dup2 6-11
 dynamic library
 libns1 6-20, 10-82
 libsys 6-2
 libX 10-1
 Dynamic Linking 5-1
 Dynamically linking, something 5-1

E

echo 8-2
 ed 8-2
 EditResult 10-132
 encrypt 6-11, 6-13
 EndCurrentTextBufferWord 10-126
 endnetconfig 6-22
 endnetpath 6-22
 EventMask 10-94
 EventMaskOfScreen
 unsafe, use XEventMaskOfScreen 10-10
 EventObj 10-134
 EventObjClass 10-134
 eventObjClass 10-128
 eventObjClassRec 10-128
 ex 8-2
 exclusivesClassRec 10-128
 ExclusivesWidget 10-134
 ExclusivesWidgetClass 10-134
 exclusivesWidgetClass 10-128

execl 6-3
execle 6-3
execlp 6-3
execv 6-3
execve 6-3
execvp 6-3
exit 6-3
Exported Data
 libsys 6-5, 6-12
 libX11 10-8
 libXm 10-146
 libXol 10-128
 libXt 10-88
expr 8-2

F

false 8-2
fattach 6-3
fchdir 6-3
fchmod 6-3
fchown 6-3
fclose 6-11
fcntl 6-3, 6-6
fdetach 6-3
fdopen 6-11, 6-13
feof 6-11
ferror 6-11
fflush 6-11
fgetc 6-11
fgetpos 6-11
fgets 6-11
fileno 6-11
find 8-2
fmtmsg 6-11, 8-2
Font 10-31
footerPanelClassRec 10-128
FooterPanelWidget 10-134
FooterPanelWidgetClass 10-134
footerPanelWidgetClass 10-128
fopen 6-11
fork 6-3
formats and protocols 7-1
formClassRec 10-128
FormConstraints 10-134
FormWidget 10-134
FormWidgetClass 10-134
formWidgetClass 10-128
ForwardScanTextBuffer 10-126
fpathconf 6-3
fprintf 6-11
fputc 6-11
fputs 6-11
fread 6-11
free 6-3

FreeBuffer 10-126
freenetconfignt 6-22
FreeTextBuffer 10-126
freopen 6-11
frexp 6-11, 6-13
fscanf 6-11
fseek 6-11
fsetpos 6-11
fstat 6-3, 6-7
fstatvfs 6-3
fsync 6-3
ftell 6-11
ftok 6-3
fwrite 6-11

G

gaugeClassRec 10-128
GaugeWidget 10-134
GaugeWidgetClass 10-134
gaugeWidgetClass 10-128
GC 10-14
GContext 10-31
generic ABI 1-3
getc 6-11
getchar 6-11
getcontext 6-3
getcwd 6-3
getdate 6-11
getegid 6-3
getenv 6-11
geteuid 6-3
getgid 6-3
getgrgid 6-3
getgrnam 6-3
getgroups 6-3
gethostbyaddr 6-26
gethostbyname 6-26
getitimer 6-11, 6-13, 6-14
getlogin 6-3
getmsg 6-3
getnetconfig 6-22
getnetconfignt 6-22
getnetname 6-22
getnetpath 6-22
GetOlBusyCursor 10-126
GetOlDuplicateCursor 10-126
GetOlMoveCursor 10-126
GetOlPanCursor 10-126
GetOlQuestionCursor 10-126
GetOlStandardCursor 10-126
GetOlSWGeometries 10-126
GetOlTargetCursor 10-126
getopt 6-11
getpass 6-11

getpeername 6-26
 getpgid 6-3
 getpgrp 6-3
 getpid 6-3
 getpmsg 6-3
 getppid 6-3
 getprotobyname 6-26
 getprotobyname 6-26
 getprotoent 6-26
 getpublickey 6-22
 getpwnam 6-3
 getpwuid 6-3
 getrlimit 6-3
 gets 6-11
 getsecretkey 6-22
 getservbyname 6-26
 getservbyport 6-26
 getsid 6-3
 getsockname 6-26
 getsockopt 6-26
 getsubopt 6-11
 GetTextBufferBlock 10-126
 GetTextBufferBuffer 10-126
 GetTextBufferChar 10-126
 GetTextBufferLine 10-126
 GetTextBufferLocation 10-126
 gettimeofday 6-11, 6-13
 gettxt 6-3, 8-2
 getuid 6-3
 getw 6-11
 gmtime 6-11
 grantpt 6-3
 grep 8-2
 GrowBuffer 10-126

H

hcreate 6-11
 hdestroy 6-11
 HeightMMOfScreen
 unsafe, use XHeightMMOfScreen 10-10
 HeightOfScreen
 unsafe, use XHeightOfScreen 10-10
 helpClassRec 10-128
 HelpWidget 10-134
 HelpWidgetClass 10-134
 helpWidgetClass 10-128
 host2netname 6-22
 hsearch 6-11
 HZ 6-14

I

id 8-2
 ImageByteOrder
 unsafe, use XImageByteOrder 10-10

IncrementTextBufferLocation 10-126
 inet_addr 6-26
 inet_lnaof 6-26
 inet_makeaddr 6-26
 inet_netof 6-26
 inet_network 6-26
 inet_ntoa 6-26
 initgroups 6-3
 InsertIntoBuffer 10-126
 ioctl 6-3
 isalnum 6-11
 isalpha 6-11
 isascii 6-11
 isastream 6-3
 isatty 6-11
 iscntrl 6-11
 isdigit 6-11
 isgraph 6-11
 islower 6-11
 isnan 6-11
 isnand 6-11, 6-13
 isprint 6-11
 ispunct 6-11
 isspace 6-11
 isupper 6-11
 isxdigit 6-11

K

KE_OS 6-2
 key_decryptsession 6-22
 key_encryptsession 6-22
 key_gendes 6-22
 key_setsecret 6-22
 KeyCode 10-31
 KeySym 10-31
 kill 6-3, 8-2

L

labs 6-11
 LastKnownRequestProcessed
 unsafe, use XLastKnownRequestProcessed
 10-10
 LastTextBufferLocation 10-126
 LastTextBufferPosition 10-126
 lchown 6-3
 LD_LIBRARY_PATH 5-1
 ldexp 6-11
 ldiv 6-11
 lfind 6-11
 libc
 contents 6-11
 interfaces 6-10
 libMrm
 entry points 10-148

- libnsl
 - interfaces 6-20
- libsys
 - Contents 6-3
 - interfaces 6-2
 - support routines 6-4
- libsys SPARC support routines 6-4
- libX
 - contents 10-2
 - version number 10-1
- libXext
 - contents 10-80
- libXm
 - contents 10-142
- libXol
 - contents 10-126
 - version number 10-125
- libXt
 - contents 10-83
 - version number 10-82
- Line 10-139
- line 8-2
- LineOfPosition 10-126
- LineTable 10-139
- link 6-3
- listClassRec 10-128
- listen 6-26
- listPaneClassRec 10-128
- ListPaneWidget 10-134
- ListPaneWidgetClass 10-134
- listPaneWidgetClass 10-128
- ln 8-2
- localeconv 6-3
- localtime 6-11
- LocationOfPosition 10-126
- lockf 6-11
- logname 8-2
- longjmp 6-11
- LookupOlInputEvent 10-126
- lp 8-2
- ls 8-2
- lsearch 6-11
- lseek 6-3
- lstat 6-3, 6-7

M

- magClassRec 10-128
- MagWidget 10-134
- MagWidgetClass 10-134
- magWidgetClass 10-128
- malloc 6-3
- managerClassRec 10-128
- ManagerWidget 10-134
- ManagerWidgetClass 10-134

- managerWidgetClass 10-128
- Manifest Constants
 - Motif 10-155, 10-157, 10-158, 10-161, 10-165, 10-167, 10-173, 10-177, 10-181, 10-187, 10-201, 10-214
 - OLIT 10-129
 - X Extensions 10-81
 - Xlib, 6-28, 6-32, 6-33, 6-34, 6-61, 10-13, 10-31, 10-43, 10-45, 10-47, 10-56, 10-77
- Mask 10-31
- MaxCmapsOfScreen
 - unsafe, use XMaxCmapsOfScreen 10-10
- mblen 6-11
- mbstowcs 6-11
- mbtowc 6-11
- MC_LOCK 6-78
- MC_LOCKAS 6-78
- MC_SYNC 6-78
- MC_UNLOCK 6-78
- MC_UNLOCKAS 6-78
- MCL_CURRENT 6-78
- MCL_FUTURE 6-78
- memccpy 6-11
- memchr 6-11
- memcmp 6-11
- memcntl 6-3
- memcpy 6-11
- memmove 6-11
- memset 6-11
- menuButtonClassRec 10-128
- MenuButtonGadget 10-134
- MenuButtonGadgetClass 10-134
- menuButtonGadgetClass 10-128
- menuButtonGadgetClassRec 10-128
- MenuButtonWidget 10-134
- MenuButtonWidgetClass 10-134
- menuButtonWidgetClass 10-128
- menuShellClassRec 10-128
- MenuShellWidget 10-134
- MenuShellWidgetClass 10-134
- menuShellWidgetClass 10-128
- MinCmapsOfScreen
 - unsafe, use XMinCmapsOfScreen 10-10
- mkdir 6-3, 8-2
- mkfifo 6-11
- mknod 6-3, 6-7
- mktemp 6-11
- mktime 6-11
- mlock 6-3
- mmap 6-3, 6-6
- modf 6-13
- Modifiers 10-93
- monitor 6-11
- MotifWmHints 10-181

MotifWmInfo 10-182
 mount 6-3
 mprotect 6-3
 MrmCloseHierarchy 10-148
 MrmCode 10-179
 MrmCount 10-179
 MrmFetchBitmapLiteral 10-148
 MrmFetchColorLiteral 10-148
 MrmFetchIconLiteral 10-148
 MrmFetchLiteral 10-148
 MrmFetchSetValues 10-148
 MrmFetchWidget 10-148
 MrmFetchWidgetOverride 10-148
 MrmFlag 10-179
 MrmGroup 10-179
 MrmHierarchy 10-179
 MrmInitialize 10-148
 MrmOffset 10-179
 MrmOpenHierarchy 10-148
 MrmOpenHierarchyPerDisplay 10-148
 MrmOsOpenParam 10-179
 MrmOsOpenParamPtr 10-179
 MRMRegisterArg 10-180
 MrmRegisterArg 10-180
 MrmRegisterArglist 10-180
 MrmRegisterClass 10-148
 MrmRegisterNames 10-148
 MrmRegisterNamesInHierarchy 10-148
 MrmResource_id 10-179
 MrmSCode 10-179
 MrmSize 10-179
 MrmType 10-179
 msgctl 6-3
 msgget 6-3
 msgrcv 6-3
 msgsnd 6-3
 msync 6-3
 munlock 6-3
 munmap 6-3
 mv 8-2
 MwmHints 10-181
 MwmInfo 10-182

N

nc_perror 6-22
 netconfig 6-78
 netdir_free 6-22
 netdir_getbyaddr 6-22
 netdir_getbyname 6-22
 netdir_options 6-22
 netname2host 6-22
 netname2user 6-22
 NeWS 10-236
 NextLocation 10-126

NextRequest
 unsafe, use XNextRequest 10-10
 NextTextBufferWord 10-126
 nftw 6-11
 nice 6-3
 nl_langinfo 6-11
 nonexclusivesClassRec 10-128
 NonexclusivesWidget 10-135
 NonexclusivesWidgetClass 10-134
 nonexclusivesWidgetClass 10-128
 noticeShellClassRec 10-128
 NoticeShellWidget 10-135
 NoticeShellWidgetClass 10-135
 noticeShellWidgetClass 10-128

O

Object 10-98
 object file format 4-1
 ObjectClass 10-98
 objectClass 10-88
 ObjectClassPart 10-116
 ObjectClassRec 10-116
 objectClassRec 10-88
 ObjectPart 10-115
 ObjectRec 10-115
 oblongButtonClassRec 10-128
 OblongButtonGadget 10-135
 OblongButtonGadgetClass 10-135
 oblongButtonGadgetClass 10-128
 oblongButtonGadgetClassRec 10-128
 OblongButtonWidget 10-135
 OblongButtonWidgetClass 10-135
 oblongButtonWidgetClass 10-128
 Obsolete Functions
 X Toolkit 10-86
 OlAddCallback 10-126
 OlBitMask 10-135
 OlCallAcceptFocus 10-126
 OlCallCallbacks 10-126
 OlCanAcceptFocus 10-126
 OlCategorySetPage 10-126
 OlDefine 10-135
 OlDragAndDrop 10-126
 OlError 10-126
 OlGet50PercentGrey 10-126
 OlGet75PercentGrey 10-126
 OlGetApplicationResources 10-126
 OlGetApplicationValues 10-126
 OlGetBeepVolume 10-126
 OlGetCurrentFocusWidget 10-126
 OlGrabDragPointer 10-126
 OlHasCallbacks 10-126
 OlHasFocus 10-126
 OlInitialize 10-126

OlLayoutScrolledWindow 10-126
OlListDelete 10-136
OlListItem 10-136
OlListItemPointer 10-126
OlListToken 10-136
OlMenuPopdown 10-126
OlMenuPopup 10-126
OlMenuPost 10-126
OlMenuUnpost 10-126
OlMoveFocus 10-126
OlQueryAcceleratorDisplay 10-126
OlQueryMnemonicDisplay 10-126
OlRChar 10-128
OlRCompression 10-128
OlRegisterColorTupleListConverter 10-126
OlRegisterHelp 10-126
OlRemoveCallback 10-126
OlSameSize 10-134
OlScanDirection 10-132
OlScanType 10-132
OlScrollbarVerify 10-135
OlSetErrorHandler 10-126
OlSetGaugeValue 10-126
OlSetInputFocus 10-126
OlSetVaDisplayErrorMsgHandler 10-126
OlSetVaDisplayWarningMsgHandler 10-126
OlSetWarningHandler 10-126
OlSliderVerify 10-136
OlSWGeometries 10-136
OlTextEditClearBuffer 10-126
OlTextEditCopyBuffer 10-126
OlTextEditCopySelection 10-126
OlTextEditGetCursorPosition 10-126
OlTextEditGetLastPosition 10-126
OlTextEditInsert 10-126
OlTextEditPaste 10-126
OlTextEditReadSubString 10-126
OlTextEditRedraw 10-126
OlTextEditResize 10-126
OlTextEditSetCursorPosition 10-126
OlTextEditTextBuffer 10-126
OlTextEditUpdate 10-126
OlTextFieldCopyString 10-126
OlTextFieldGetString 10-126
OlTextFieldVerify 10-138
OlTextFieldVerifyPointer 10-138
OlTextMarginCallData 10-137
OlTextMarginCallDataPointer 10-137
OlTextModifyCallData 10-137
OlTextModifyCallDataPointer 10-137
OlTextMotionCallData 10-137
OlTextMotionCallDataPointer 10-137
OlTextPostModifyCallData 10-137
OlTextPostModifyCallDataPointer 10-137
OlToolkitInitialize 10-126
OlUngrabDragPointer 10-126
OlUpdateDisplay 10-126
OlVaDisplayErrorMsg 10-126
OlVaDisplayWarningMsg 10-126
OlVerifyOpType 10-132
OlWarning 10-126
OlWMPProtocolAction 10-126
Opaque 10-93
open 6-3
opendir 6-3
organization 7
OverrideShellClassPart 10-120
OverrideShellClassRec 10-120
overrideShellClassRec 10-88
OverrideShellPart 10-120
OverrideShellRec 10-120
OverrideShellWidget 10-120
OverrideShellWidgetClass 10-101
overrideShellWidgetClass 10-88

P

Page 10-139
PageQueue 10-138
PageTable 10-139
passwd 8-2
pathconf 6-3
pause 6-3
pclose 6-11
perror 6-11
pg 8-2
pipe 6-3
Pixel 10-92
Pixmap 10-31
pkginfo 2-1
PlanesOfScreen
 unsafe, use XPlanesOfScreen 10-10
poll 6-3
popen 6-11
popupWindowShellClassRec 10-128
PopupWindowShellWidget 10-135
PopupWindowShellWidgetClass 10-135
popupWindowShellWidgetClass 10-128
Position 10-93
PositionOfLine 10-126
PositionOfLocation 10-126
pr 8-2, 8-3
PreviousLocation 10-126
PreviousTextBufferWord 10-126
primitiveClassRec 10-128
PrimitiveWidget 10-135
PrimitiveWidgetClass 10-135
primitiveWidgetClass 10-128

printf 6-11
 priocntl 8-2
 PRIVATE 6-78
 PROC_DATA 6-78
 PROC_TEXT 6-78
 profil 6-3
 program loading and linking 5-1
 PropMotifWmHints 10-182
 PropMotifWmInfo 10-183
 PropMwmHints 10-182
 PropMwmInfo 10-183
 ProtocolRevision
 unsafe, use XProtocolRevision 10-10
 ProtocolVersion
 unsafe, use XProtocolVersion 10-10
 psABI 1-3
 ptrace 6-3
 ptsname 6-3
 publication conventions 7
 page format 7
 typography 7
 purpose 7
 pushpinClassRec 10-128
 PushpinWidget 10-135
 PushpinWidgetClass 10-135
 pushpinWidgetClass 10-128
 putc 6-11
 putchar 6-11
 putenv 6-11
 putmsg 6-3
 putpmsg 6-3
 puts 6-11
 putw 6-11
 pwd 8-2

Q

QLength
 unsafe, use xQLength 10-10
 qsort 6-11

R

raise 6-11
 rand 6-11
 read 6-3
 readdir 6-3
 ReadFileIntoBuffer 10-126
 ReadFileIntoTextBuffer 10-126
 readlink 6-3
 ReadStringIntoBuffer 10-126
 ReadStringIntoTextBuffer 10-126
 readv 6-3, 6-6
 realloc 6-3
 rectButtonClassRec 10-128
 RectButtonWidget 10-135

RectButtonWidgetClass 10-135
 rectButtonWidgetClass 10-128
 RectObj 10-99
 RectObjClass 10-99
 rectObjClass 10-88
 RectObjClassPart 10-118
 RectObjClassRec 10-118
 rectObjClassRec 10-88
 RectObjPart 10-117
 RectObjRec 10-117
 recv 6-26
 recvfrom 6-26
 recvmmsg 6-26
 Region 10-49
 RegisterTextBufferScanFunctions 10-126
 RegisterTextBufferUpdate 10-126
 RegisterTextBufferWordDefinition 10-126
 related publications 1-2
 remove 6-3
 rename 6-3
 ReplaceBlockInTextBuffer 10-126
 ReplaceCharInTextBuffer 10-126
 rewind 6-11
 rewinddir 6-3
 RLIM_INFINITY 6-78
 rm 8-2
 rmdir 6-3, 8-2
 RootWindow
 unsafe, use XRootWindow 10-10
 RootWindowOfScreen
 unsafe, use XRootWindowOfScreen 10-10
 rpc_broadcast 6-22
 rpc_broadcast_exp 6-22
 rpc_call 6-22
 rpc_reg 6-22
 rpc_svc_err 6-23
 rpcb_getaddr 6-22
 rpcb_getmaps 6-22
 rpcb_gettime 6-22
 rpcb_rmtcall 6-22
 rpcb_set 6-22
 rpcb_unset 6-22
 rpcbind 7-1
 RT_OS 6-2
 rubberTileClassRec 10-128
 RubberTileWidget 10-135
 RubberTileWidgetClass 10-135
 rubberTileWidgetClass 10-128

S

SaveResult 10-132
 SaveTextBuffer 10-127
 scanf 6-11
 ScanResult 10-132

SCD 2.2
 overview 1-1
 terminology 1-1
Screen 10-14
screenConvertArg 10-88
ScreenCount
 unsafe, use XScreenCount 10-10
ScreenFormat 10-14
ScreenNumberOfCCC
 unsafe, use XScreenNumberOfCCC 10-10
ScreenOfDisplay
 unsafe, use XScreenOfDisplay 10-10
ScreenWhiteOfCCC
 unsafe, use XScreenWhiteOfCCC 10-10
scrollbarClassRec 10-128
ScrollbarWidget 10-135
ScrollbarWidgetClass 10-135
scrollbarWidgetClass 10-128
scrolledWindowClassRec 10-128
ScrolledWindowWidget 10-135
ScrolledWindowWidgetClass 10-135
scrolledWindowWidgetClass 10-128
ScrollingListWidget 10-136
ScrollingListWidgetClass 10-136
scrollingListWidgetClass 10-128
sed 8-2
seekdir 6-3
semctl 6-3
semget 6-3
semop 6-3
send 6-26
sendmsg 6-26
sendto 6-26
ServerVendor
 unsafe, use XServerVendor 10-10
setbuf 6-11
setcontext 6-3
setgid 6-3
setgroups 6-3
setitimer 6-11, 6-14
setjmp 6-11
setkey 6-11, 6-14
setlabel 6-14
setlocale 6-3
setnetconfig 6-22
setnetpath 6-22
setpgid 6-3
setpgrp 6-3
setrlimit 6-3
setsid 6-3
setsockopt 6-26
setuid 6-3
setvbuf 6-11
sh 8-2, 8-3
Share Library Names 6-77
SHARED 6-78
ShellClassExtension 10-119
ShellClassExtensionRec 10-119
ShellClassPart 10-119
ShellClassRec 10-119
shellClassRec 10-88
ShellPart 10-119
ShellRec 10-120
ShellWidget 10-120
ShellWidgetClass 10-101
shellWidgetClass 10-88
shmat 6-3
shmctl 6-3
shmdt 6-3
shmget 6-3
SHT_DYNSYM 4-1
shutdown 6-26
sigaction 6-3
sigaddset 6-3
sigaltstack 6-3
sigdelset 6-3
sigemptyset 6-3
sigfillset 6-3
sighold 6-3
sigignore 6-3
sigismember 6-3
siglongjmp 6-3
signal 6-3
sigpause 6-3
sigpending 6-3
sigprocmask 6-3
sigrelse 6-3
sigsend 6-3
sigsendset 6-3
sigset 6-3
sigsetjmp 6-3
sigsuspend 6-3
sleep 6-11, 8-2
sliderClassRec 10-128
SliderWidget 10-136
SliderWidgetClass 10-136
sliderWidgetClass 10-128
socket 6-26
sort 8-2
sprintf 6-11
srand 6-11
sscanf 6-11
StartCurrentTextBufferWord 10-127
stat 6-3, 6-7
statictextClassRec 10-128
StaticTextWidget 10-137
StaticTextWidgetClass 10-137
staticTextWidgetClass 10-128

statictextWidgetClass 10-128
statvfs 6-3
stime 6-3
strcat 6-11
strchr 6-11
strcmp 6-11
strcoll 6-3
strcpy 6-11
strcspn 6-11
strdup 6-11
strerror 6-3
strftime 6-3
String 10-92
strlen 6-11
strncat 6-11
strncmp 6-11
strncpy 6-11
strpbrk 6-11
strrchr 6-11
strspn 6-11
strstr 6-11
strtod 6-11
strtok 6-11
strtol 6-11
strtoul 6-11
strxfrm 6-3
stty 8-2
su 8-2
Substitution 10-95
SubstitutionRec 10-95
svc_create 6-22
svc_dg_create 6-22
svc_fd_create 6-22
svc_getreqset 6-22
svc_raw_create 6-22
svc_reg 6-22
svc_run 6-22
svc_sendreply 6-22
svc_tli_create 6-22
svc_tp_create 6-22
svc_unreg 6-22
svc_vc_create 6-22
svcerr_auth 6-22
svcerr_decode 6-22
svcerr_noproc 6-22
svcerr_noprog 6-22
svcerr_progvers 6-22, 6-23
svcerr_systemerr 6-22
svcerr_weakauth 6-22
swab 6-11
symlink 6-3, 6-6
sync 6-3
sysconf 6-3
sysinfo 6-11, 6-14

system 6-3
System V Application Binary Interface 1-2
System V Application Binary Interface SPARC Processor Supplement 1-2
System V Interface Definition 1-2

T

t_accept 6-21
t_alloc 6-21, 6-23
t_bind 6-21
t_close 6-21
t_connect 6-21
t_error 6-21
t_free 6-21
t_getinfo 6-21
t_getstate 6-21
t_listen 6-21
t_look 6-21
t_open 6-21
t_optmgt 6-21
t_rcv 6-21
t_rcvconnect 6-21
t_rcvdis 6-21
t_rcvrel 6-21
t_rcvudata 6-21
t_rcvuderr 6-21
t_snd 6-21
t_snddis 6-21
t_sndrel 6-21
t_sndudata 6-21
t_sync 6-21
t_unbind 6-21
TabTable 10-137
taddr2uaddr 6-22
tail 8-2
tcdrain 6-11
tcflow 6-11
tcflush 6-11
tcgetattr 6-11
tcgetpgrp 6-11
tcgetsid 6-11
TCP/IP 6-20
tcsendbreak 6-11
tcsetattr 6-11
tcsetpgrp 6-11
tdelete 6-11
tee 8-2
tell 6-11, 6-14
telldir 6-3
tempnam 6-11
test 8-2
TextBlock 10-138
TextBuffer 10-140
TextEditWidget 10-138

TextEditWidgetClass 10-138
textEditWidgetClass 10-128
textFieldClassRec 10-128
TextFieldWidget 10-138
TextFieldWidgetClass 10-138
textFieldWidgetClass 10-128
TextFileStatus 10-132
TextLine 10-138
TextLocation 10-139
TextPage 10-138
TextPosition 10-138
TextUndoHint 10-139
TextUndoItem 10-139
TextUpdateCallback 10-140
TextUpdateFunction 10-140
tfind 6-11
Time 10-31
time 6-3
times 6-3
tmpfile 6-11
tmpnam 6-11
toascii 6-11
tolower 6-11
TopLevelShellClassPart 10-122
TopLevelShellClassRec 10-122
topLevelShellClassRec 10-88
TopLevelShellPart 10-122
TopLevelShellRec 10-122
TopLevelShellWidget 10-122
TopLevelShellWidgetClass 10-101
topLevelShellWidgetClass 10-88
touch 8-2
toupper 6-11
tr 8-2
TransientShellClassPart 10-121
TransientShellClassRec 10-121
transientShellClassRec 10-88
TransientShellPart 10-122
TransientShellRec 10-122
TransientShellWidget 10-122
TransientShellWidgetClass 10-101
transientShellWidgetClass 10-88
transport provider interface name 6-20
transport providers 6-20
true 8-2
tsearch 6-11
tty 8-2
ttyname 6-3
twalk 6-11
tzset 6-11

U

uaddr2taddr 6-22
ulimit 6-3

umask 6-3, 8-2
umount 6-3
uname 6-3, 6-7, 8-2
ungetc 6-11
unlink 6-3
unlockpt 6-3
UnregisterTextBufferUpdate 10-127
Unsafe Macros
 X Library 10-9
 X Toolkit 10-87
user2netname 6-22
utime 6-3
uucp 8-2
uulog 8-2
uustat 8-2
uux 8-2

V

VendorRelease
 unsafe, use XVendorRelease 10-10
VendorShellClassPart 10-124
VendorShellClassRec 10-124
vendorShellClassRec 10-88, 10-128, 10-146
VendorShellPart 10-124
VendorShellRec 10-124
VendorShellWidget 10-124
VendorShellWidgetClass 10-106
vendorShellWidgetClass 10-88, 10-128, 10-146
vfprintf 6-11
vi 8-2
Visual 10-14
VisualID 10-31
VisualOfCCC
 unsafe, use XVisualOfCCC 10-11
vprintf 6-11
vsprintf 6-11

W

wait 6-3, 8-2
waitid 6-3, 6-6
waitpid 6-3
wcstombs 6-11
wctomb 6-11
WhitePixel
 unsafe, use XWhitePixel 10-11
WhitePixelOfScreen
 unsafe, use XWhitePixelOfScreen 10-11
who 8-2
Widget 10-92
WidgetClass 10-92
widgetClass 10-88
WidgetClassRec 10-111
widgetClassRec 10-88
WidgetList 10-92

WidgetRec 10-110
 WidthMMOfScreen
 unsafe, use XWidthMMOfScreen 10-11
 WidthOfScreen
 unsafe, use XWidthOfScreen 10-11
 Window 10-31
 WMShellClassPart 10-120
 WMShellClassRec 10-120
 wmShellClassRec 10-88
 WMShellPart 10-121
 WMShellRec 10-121
 WMShellWidget 10-121
 WMShellWidgetClass 10-101
 wmShellWidgetClass 10-88
 write 6-3
 writev 6-3, 6-6
X
 X11/cursorfont.h 10-12
 Manifest Constants 10-77
 X11/extensions/shape.h
 Manifest Constants 10-81
 X11/keysymdef.h 10-12
 Manifest Constants 10-56
 X11/x.h 10-12
 Manifest Constants and Data Types 10-31
 X11/xatom.h 10-12
 Manifest Constants 10-43
 X11/xcms.h 10-12
 X11/xlib.h 10-12
 Manifest Constants and Data Types 6-28, 6-32,
 6-33, 6-34, 6-61, 10-13
 X11/xresource.h 10-12
 Manifest Constants and Data Types 10-45
 X11/xutil.h 10-12
 Manifest Constants and Data Types 10-47
 XActivateScreenSaver 10-2
 XAddExtension 10-2
 XAddHost 10-2
 XAddHosts 10-2
 XAddPixel 10-2
 XAddToExtensionList 10-2
 XAddToSaveSet 10-2
 XAllocClassHint 10-2
 XAllocColor 10-2
 XAllocColorCells 10-2
 XAllocColorPlanes 10-2
 XAllocIconSize 10-2
 XAllocNamedColor 10-2
 XAllocSizeHints 10-2
 XAllocStandardColormap 10-2
 XAllocWMHints 10-2
 XAllowEvents 10-2
 XAllPlanes 10-2
 XAnyEvent 10-25
 XArc 10-17
 XAutoRepeatOff 10-2
 XAutoRepeatOn 10-2
 XBaseFontNameListOfFontSet 10-2
 XBell 10-2
 XBitmapBitOrder 10-2
 XBitmapPad 10-2, 10-9
 XBitmapUnit 10-2, 10-9
 XBlackPixel 10-2, 10-9
 XBlackPixelOfScreen 10-2, 10-9
 XButtonEvent 10-19
 XButtonPressedEvent 10-19
 XButtonReleasedEvent 10-19
 XCellsOfScreen 10-2, 10-9
 XChangeActivePointerGrab 10-2
 XChangeGC 10-2
 XChangeKeyboardControl 10-2
 XChangeKeyboardMapping 10-2
 XChangePointerControl 10-2
 XChangeProperty 10-2
 XChangeSaveSet 10-2
 XChangeWindowAttributes 10-2
 XChar2b 10-27
 XCharStruct 10-26
 XCheckIfEvent 10-2
 XCheckMaskEvent 10-2
 XCheckTypedEvent 10-2
 XCheckTypedWindowEvent 10-2
 XCheckWindowEvent 10-2
 XCirculateEvent 10-23
 XCirculateRequestEvent 10-23
 XCirculateSubwindows 10-2
 XCirculateSubwindowsDown 10-2
 XCirculateSubwindowsUp 10-2
 XClassHint 10-49
 XClearArea 10-2
 XClearWindow 10-2
 XClientMessageEvent 10-24
 XClientWhitePointOfCCC 10-9
 XClipBox 10-2
 XCloseDisplay 10-2
 XCloseIM 10-2
 XcmsAddColorSpace 10-2
 XcmsAddFunctionSet 10-2
 XcmsAllocColor 10-2
 XcmsAllocNamedColor 10-2
 XcmsCCC 10-53
 XcmsCCCOFColormap 10-2
 XcmsCCCRec 10-54
 XcmsCIELab 10-52
 XcmsCIELabClipab 10-2
 XcmsCIELabClipL 10-2
 XcmsCIELabClipLab 10-2

XcmsCIELabColorSpace 10-8
XcmsCIELabQueryMaxC 10-2
XcmsCIELabQueryMaxL 10-2
XcmsCIELabQueryMaxLC 10-2
XcmsCIELabQueryMinL 10-2
XcmsCIELabToCIEXYZ 10-2
XcmsCIELabWhiteShiftColors 10-2
XcmsCIELuv 10-52
XcmsCIELuvClipL 10-2
XcmsCIELuvClipLuv 10-2
XcmsCIELuvClipuv 10-2
XcmsCIELuvColorSpace 10-8
XcmsCIELuvQueryMaxC 10-2
XcmsCIELuvQueryMaxL 10-2
XcmsCIELuvQueryMaxLC 10-2
XcmsCIELuvQueryMinL 10-2
XcmsCIELuvToCIEuvY 10-2
XcmsCIELuvWhiteShiftColors 10-2
XcmsCIEuvY 10-52
XcmsCIEuvYColorSpace 10-8
XcmsCIEuvYToCIELuv 10-2
XcmsCIEuvYToCIEXYZ 10-2
XcmsCIEuvYToTekHVC 10-2
XcmsCIExyY 10-52
XcmsCIExyYColorSpace 10-8
XcmsCIExyYToCIEXYZ 10-2
XcmsCIEXYZ 10-52
XcmsCIEXYZColorSpace 10-8
XcmsCIEXYZToCIELab 10-2
XcmsCIEXYZToCIEuvY 10-2
XcmsCIEXYZToCIExyY 10-2
XcmsCIEXYZToRGBi 10-2
XcmsClientWhitePointOfCCC 10-2
XcmsColor 10-53
XcmsColorFormat 10-51
XcmsColorSpace 10-55
XcmsCompressionProc 10-54
XcmsConversionProc 10-54
XcmsConvertColors 10-2
XcmsCreateCCC 10-2
XcmsDefaultCCC 10-2
XcmsDisplayOfCCC 10-2
XcmsFloat 10-51
XcmsFormatOfPrefix 10-2
XcmsFreeCCC 10-2
XcmsFuncListPtr 10-54
XcmsFunctionSet 10-55
XcmsLinearRGBFunctionSet 10-8
XcmsLookupColor 10-2
XcmsPad 10-53
XcmsParseStringProc 10-54
XcmsPerScrnInfo 10-53
XcmsPrefixOfFormat 10-2
XcmsQueryBlack 10-2
XcmsQueryBlue 10-2
XcmsQueryColor 10-2
XcmsQueryColors 10-2
XcmsQueryGreen 10-2
XcmsQueryRed 10-2
XcmsQueryWhite 10-2
XcmsRGB 10-51
XcmsRGBColorSpace 10-8
XcmsRGBi 10-52
XcmsRGBiColorSpace 10-8
XcmsRGBiToCIEXYZ 10-2
XcmsRGBiToRGB 10-2
XcmsRGBToRGBi 10-2
XcmsScreenFreeProc 10-54
XcmsScreenInitProc 10-54
XcmsScreenNumberOfCCC 10-2
XcmsScreenWhitePointOfCCC 10-3
XcmsSetCompressionProc 10-3
XcmsSetWhiteAdjustProc 10-3
XcmsSetWhitePoint 10-3
XcmsStoreColor 10-3
XcmsStoreColors 10-3
XcmsTekHVC 10-53
XcmsTekHVCClipC 10-3
XcmsTekHVCClipV 10-3
XcmsTekHVCClipVC 10-3
XcmsTekHVCColorSpace 10-8
XcmsTekHVCQueryMaxC 10-3
XcmsTekHVCQueryMaxV 10-3
XcmsTekHVCQueryMaxVC 10-3
XcmsTekHVCQueryMaxVSamples 10-3
XcmsTekHVCQueryMinV 10-3
XcmsTekHVCToCIEuvY 10-3
XcmsTekHVCWhiteShiftColors 10-3
XcmsUNDEFINEDColorSpace 10-8
XcmsVisualOfCCC 10-3
XcmsWhiteAdjustProc 10-54
XColor 10-16
XColormapEvent 10-24
XComposeStatus 10-49
XConfigureEvent 10-22
XConfigureRequestEvent 10-23
XConfigureWindow 10-3
XConnectionNumber 10-3, 10-9
XContext 10-50
XContextDependentDrawing 10-3
XConvertSelection 10-3
XCopyArea 10-3
XCopyColormapAndFree 10-3
XCopyGC 10-3
XCopyPlane 10-3
XCreateBitmapFromData 10-3
XCreateColormap 10-3
XCreateFontCursor 10-3

XCreateFontSet 10-3
XCreateGC 10-3
XCreateGlyphCursor 10-3
XCreateIC 10-3
XCreateImage 10-3
XCreatePixmap 10-3
XCreatePixmapCursor 10-3
XCreatePixmapFromBitmapData 10-3
XCreateRegion 10-3
XCreateSimpleWindow 10-3
XCreateWindow 10-3
XCreateWindowEvent 10-21
XCrossingEvent 10-19
XDefaultColormap 10-3, 10-9
XDefaultColormapOfScreen 10-3, 10-9
XDefaultDepth 10-3, 10-9
XDefaultDepthOfScreen 10-3, 10-9
XDefaultGC 10-3, 10-9
XDefaultGCOfScreen 10-3, 10-9
XDefaultRootWindow 10-3, 10-9
XDefaultScreen 10-3, 10-9
XDefaultScreenOfDisplay 10-3, 10-9
XDefaultString 10-3
XDefaultVisual 10-3, 10-9
XDefaultVisualOfScreen 10-3, 10-9
XDefineCursor 10-3
XDeleteContext 10-3
XDeleteModifiermapEntry 10-3
XDeleteProperty 10-3
XDestroyIC 10-3
XDestroyImage 10-3
XDestroyRegion 10-3
XDestroySubwindows 10-3
XDestroyWindow 10-3
XDestroyWindowEvent 10-21
XDisableAccessControl 10-3
XDisplayCells 10-3, 10-9
XDisplayHeight 10-3, 10-10
XDisplayHeightMM 10-3, 10-10
XDisplayKeycodes 10-3
XDisplayMotionBufferSize 10-3
XDisplayName 10-3
XDisplayOfCCC 10-10
XDisplayOfIM 10-3
XDisplayOfScreen 10-3, 10-10
XDisplayPlanes 10-3, 10-10
XDisplayString 10-3, 10-10
XDisplayWidth 10-3, 10-10
XDisplayWidthMM 10-3, 10-10
XDoesBackingStore 10-3, 10-10
XDoesSaveUnders 10-3, 10-10
xdr_array 6-22
xdr_authsys_parms 6-22
xdr_bool 6-22
xdr_bytes 6-22
xdr_callhdr 6-22
xdr_callmsg 6-22
xdr_char 6-22
xdr_double 6-22
xdr_enum 6-22
xdr_float 6-22
xdr_free 6-22
xdr_int 6-22
xdr_long 6-22
xdr_opaque 6-22
xdr_opaque_auth 6-22
xdr_pointer 6-22
xdr_reference 6-22
xdr_rejected_reply 6-22
xdr_replymsg 6-22
xdr_short 6-22
xdr_string 6-22
xdr_u_char 6-22
xdr_u_long 6-22
xdr_u_short 6-22
xdr_union 6-22
xdr_vector 6-22
xdr_void 6-22
xdr_wrapstring 6-22
XDrawArc 10-3
XDrawArcs 10-3
XDrawImageString 10-3
XDrawImageString16 10-3
XDrawLine 10-3
XDrawLines 10-3
XDrawPoint 10-3
XDrawPoints 10-3
XDrawRectangle 10-3
XDrawRectangles 10-3
XDrawSegments 10-3
XDrawString 10-3
XDrawString16 10-3
XDrawText 10-3
XDrawText16 10-3
xdrmem_create 6-22
xdrrec_create 6-22
xdrrec_eof 6-22
xdrrec_skiprecord 6-22
xdtstdio_create 6-22
XDataObject 10-27
XEHeadOfExtensionList 10-3
XEmptyRegion 10-3
XEnableAccessControl 10-3
XEnterWindowEvent 10-19
XEqualRegion 10-3
XErrorEvent 10-25
XSetCloseDisplay 10-3
XSetCopyGC 10-3

XESetCreateFont 10-3
XESetCreateGC 10-3
XESetError 10-3
XESetErrorString 10-3
XESetEventToWire 10-3
XESetFlushGC 10-3
XESetFreeFont 10-3
XESetFreeGC 10-3
XESetPrintErrorValues 10-3
XESetWireToError 10-3
XESetWireToEvent 10-3
XEvent 10-26
XEventMaskOfScreen 10-3, 10-10
XEventsQueued 10-4
XExposeEvent 10-20
XExtCodes 10-13
XExtData 10-13
XExtentsOfFontSet 10-4
XFetchBuffer 10-4
XFetchBytes 10-4
XFetchName 10-4
XFillArc 10-4
XFillArcs 10-4
XFillPolygon 10-4
XFillRectangle 10-4
XFillRectangles 10-4
XFilterEvent 10-4
XFindContext 10-4
XFindOnExtensionList 10-4
XFlush 10-4
XFlushGC 10-4
XFocusChangeEvent 10-20
XFocusInEvent 10-20
XFocusOutEvent 10-20
XFontProp 10-26
XFontSet 10-27
XFontSetExtents 10-27
XFontsOfFontSet 10-4
XFontStruct 10-26
XForceScreenSaver 10-4
XFree 10-4
XFreeColormap 10-4
XFreeColors 10-4
XFreeCursor 10-4
XFreeExtensionList 10-4
XFreeFont 10-4
XFreeFontInfo 10-4
XFreeFontNames 10-4
XFreeFontPath 10-4
XFreeFontSet 10-4
XFreeGC 10-4
XFreeModifiermap 10-4
XFreePixmap 10-4
XFreeStringList 10-4
XGContextFromGC 10-4
XGCValues 10-14
XGeometry 10-4
XGetAtomName 10-4
XGetClassHint 10-4
XGetCommand 10-4
XGetDefault 10-4
XGetErrorDatabaseText 10-4
XGetErrorText 10-4
XGetFontPath 10-4
XGetFontProperty 10-4
XGetGCValues 10-4
XGetGeometry 10-4
XGetIconName 10-4
XGetIconSizes 10-4
XGetICValues 10-4
XGetImage 10-4
XGetIMValues 10-4
XGetInputFocus 10-4
XGetKeyboardControl 10-4
XGetKeyboardMapping 10-4
XGetModifierMapping 10-4
XGetMotionEvents 10-4
XGetNormalHints 10-4
XGetPixel 10-4
XGetPointerControl 10-4
XGetPointerMapping 10-4
XGetRGBColormaps 10-4
XGetScreenSaver 10-4
XGetSelectionOwner 10-4
XGetSizeHints 10-4
XGetStandardColormap 10-4
XGetSubImage 10-4
XGetTextProperty 10-4
XGetTransientForHint 10-4
XGetVisualInfo 10-4
XGetWindowAttributes 10-4
XGetWindowProperty 10-4
XGetWMClientMachine 10-4
XGetWMColormapWindows 10-4
XGetWMHints 10-4
XGetWMIconName 10-4
XGetWMName 10-4
XGetWMNormalHints 10-4
XGetWMProtocols 10-4
XGetWMSizeHints 10-4
XGrabButton 10-4
XGrabKey 10-4
XGrabKeyboard 10-4
XGrabPointer 10-4
XGrabServer 10-4
XGraphicsExposeEvent 10-20
XGravityEvent 10-22
XHeightMMOfScreen 10-4, 10-10

XHeightOfScreen 10-4, 10-10
XHostAddress 10-15
XIC 10-27
XICCEncodingStyle 10-48
XIconifyWindow 10-4
XIconSize 10-49
XID 10-31
XIfEvent 10-4
XIM 10-27
XImage 10-16
XImageByteOrder 10-4, 10-10
XIMCallback 10-29
XIMCaretDirection 10-29
XIMCaretStyle 10-29
XIMFeedback 10-29
XIMOfIC 10-4
XIMPreeditCaretCallbackStruct 10-29
XIMPreeditDrawCallbackStruct 10-29
XIMProc 10-27
XIMStatusDataType 10-30
XIMStatusDrawCallbackStruct 10-30
XIMStyle 10-27
XIMStyles 10-28
XIMText 10-29
XInitExtension 10-4
XInsertModifiermapEntry 10-4
XInstallColormap 10-4
XInternAtom 10-4
XIntersectRegion 10-4
XKeyboardControl 10-17
XKeyboardState 10-17
XKeycodeToKeysym 10-4
XKeyEvent 10-18
XKeymapEvent 10-20
XKeyPressedEvent 10-18
XKeyReleasedEvent 10-18
XKeysymToKeycode 10-4
XKeysymToString 10-4
XKillClient 10-4
XLastKnownRequestProcessed 10-4, 10-10
XLeaveWindowEvent 10-19
XListDepths 10-4
XListExtensions 10-4
XListFonts 10-4
XListFontsWithInfo 10-4
XListHosts 10-4
XListInstalledColormaps 10-4
XListPixmapFormats 10-4
XListProperties 10-4
XLoadFont 10-4
XLoadQueryFont 10-4
XLocaleOfFontSet 10-4
XLocaleOfIM 10-5
XLookupColor 10-5
XLookupKeysym 10-5
XLookupString 10-5
XLowerWindow 10-5
XmActivateProtocol 10-142
XmAddProtocolCallback 10-142
XmAddProtocols 10-142
XmAddTabGroup 10-142
XmAnyCallbackStruct 10-205
XmAnyICCCallback 10-159
XmAnyICCCallbackStruct 10-159
XMapEvent 10-21
XMappingEvent 10-25
XMapRaised 10-5
XMapRequestEvent 10-22
XMapSubwindows 10-5
XMapWindow 10-5
XmArrowButtonCallbackStruct 10-205
xmArrowButtonClassRec 10-146
XmArrowButtonGadget 10-150
xmArrowButtonGadgetClass 10-146
xmArrowButtonGadgetClassRec 10-146
XmArrowButtonWidget 10-149
XmArrowButtonWidgetClass 10-149
xmArrowButtonWidgetClass 10-146
XMaskEvent 10-5
XMatchVisualInfo 10-5
XMaxCmapsOfScreen 10-5, 10-10
XMaxRequestSize 10-5
XmbDrawImageString 10-5
XmbDrawString 10-5
XmbDrawText 10-5
XmbLookupString 10-5
XmbResetIC 10-5
XmbSetWMProperties 10-5
XmbTextEscapement 10-5
XmbTextExtents 10-5
XmbTextItem 10-27
XmbTextListToTextProperty 10-5
XmbTextPerCharExtents 10-5
XmbTextPropertyToTextList 10-5
xmBulletinBoardClassRec 10-146
XmBulletinBoardWidget 10-151
XmBulletinBoardWidgetClass 10-151
xmBulletinBoardWidgetClass 10-146
XmButtonType 10-212
XmButtonTypeTable 10-212
xmCascadeButtonClassRec 10-146
XmCascadeButtonGadget 10-153
XmCascadeButtonGadgetClass 10-153
xmCascadeButtonGadgetClass 10-146
xmCascadeButtonGadgetClassRec 10-146
XmCascadeButtonGadgetHighlight 10-142
xmCascadeButtonGCacheObjClassRec 10-146
XmCascadeButtonGCacheObject 10-153

XmCascadeButtonHighlight 10-142
XmCascadeButtonWidget 10-152
XmCascadeButtonWidgetClass 10-152
xmCascadeButtonWidgetClass 10-146
XmChangeColor 10-142
XmClipboardCancelCopy 10-142
XmClipboardCopy 10-142
XmClipboardCopyByName 10-142
XmClipboardEndCopy 10-142
XmClipboardEndRetrieve 10-142
XmClipboardInquireCount 10-142
XmClipboardInquireFormat 10-142
XmClipboardInquireLength 10-142
XmClipboardInquirePendingItems 10-142
XmClipboardLock 10-142
XmClipboardPendingList 10-155
XmClipboardPendingRec 10-155
XmClipboardRegisterFormat 10-142
XmClipboardRetrieve 10-142
XmClipboardStartCopy 10-142
XmClipboardStartRetrieve 10-142
XmClipboardUndoCopy 10-142
XmClipboardUnlock 10-142
XmClipboardWithdrawFormat 10-142
XmCommandAppendValue 10-142
XmCommandCallbackStruct 10-207
xmCommandClassRec 10-146
XmCommandError 10-142
XmCommandGetChild 10-142
XmCommandSetValue 10-142
XmCommandWidget 10-154
XmCommandWidgetClass 10-154
xmCommandWidgetClass 10-146
XmConvertUnits 10-142
XmCreateArrowButton 10-142
XmCreateArrowButtonGadget 10-142
XmCreateBulletinBoard 10-142
XmCreateBulletinBoardDialog 10-142
XmCreateCascadeButton 10-142
XmCreateCascadeButtonGadget 10-142
XmCreateCommand 10-142
XmCreateDialogShell 10-142
XmCreateDragIcon 10-142
XmCreateDrawingArea 10-142
XmCreateDrawnButton 10-142
XmCreateErrorDialog 10-142
XmCreateFileSelectionBox 10-142
XmCreateFileSelectionDialog 10-142
XmCreateForm 10-142
XmCreateFormDialog 10-142
XmCreateFrame 10-142
XmCreateInformationDialog 10-142
XmCreateLabel 10-142
XmCreateLabelGadget 10-142
XmCreateList 10-142
XmCreateMainWindow 10-142
XmCreateMenuBar 10-142
XmCreateMenuShell 10-142
XmCreateMessageBox 10-142
XmCreateMessageDialog 10-142
XmCreateOptionMenu 10-142
XmCreatePanedWindow 10-142
XmCreatePopupMenu 10-142
XmCreatePromptDialog 10-142
XmCreatePulldownMenu 10-142
XmCreatePushButton 10-142
XmCreatePushButtonGadget 10-142
XmCreateQuestionDialog 10-142
XmCreateRadioBox 10-142
XmCreateRowColumn 10-142
XmCreateScale 10-142
XmCreateScrollBar 10-142
XmCreateScrolledList 10-142
XmCreateScrolledText 10-142
XmCreateScrolledWindow 10-142
XmCreateSelectionBox 10-142
XmCreateSelectionDialog 10-142
XmCreateSeparator 10-142
XmCreateSeparatorGadget 10-142
XmCreateSimpleCheckBox 10-142
XmCreateSimpleMenuBar 10-142
XmCreateSimpleOptionMenu 10-142
XmCreateSimplePopupMenu 10-142
XmCreateSimplePulldownMenu 10-142
XmCreateSimpleRadioBox 10-142
XmCreateTemplateDialog 10-142
XmCreateText 10-142
XmCreateTextField 10-142
XmCreateToggleButton 10-142
XmCreateToggleButtonGadget 10-142
XmCreateWarningDialog 10-142
XmCreateWorkArea 10-142
XmCreateWorkingDialog 10-142
XmCvtCTToXmString 10-142
XmCvtStringToUnitType 10-142
XmCvtXmStringToCT 10-142
XmDeactivateProtocol 10-142
xmDesktopClass 10-146
xmDesktopClassRec 10-146
xmDesktopObjectClass 10-146
XmDestroyPixmap 10-142
xmDialogShellClassRec 10-146
xmDialogShellExtClassRec 10-146
xmDialogShellExtObjectClass 10-146
XmDialogShellWidget 10-156
XmDialogShellWidgetClass 10-156
xmDialogShellWidgetClass 10-146
XmDisplay 10-157

XmDisplayClass 10-157
xmDisplayClass 10-146
xmDisplayClassRec 10-146
xmDisplayObjectClass 10-146
XmDragCancel 10-142
XmDragContext 10-159
XmDragContextClass 10-159
xmDragContextClass 10-146
xmDragContextClassRec 10-146
XmDragDropFinishCallback 10-160
XmDragDropFinishCallbackStruct 10-160
xmDragIconClassRec 10-146
XmDragIconObject 10-161
XmDragIconObjectClass 10-161
xmDragIconObjectClass 10-146
XmDragMotionCallback 10-160
XmDragMotionCallbackStruct 10-160
xmDragOverShellClassRec 10-146
XmDragOverShellWidget 10-162
XmDragOverShellWidgetClass 10-162
xmDragOverShellWidgetClass 10-146
XmDragProcCallback 10-165
XmDragProcCallbackStruct 10-165
XmDragStart 10-142
XmDrawingAreaCallbackStruct 10-206
xmDrawingAreaClassRec 10-146
XmDrawingAreaWidget 10-163
XmDrawingAreaWidgetClass 10-163
xmDrawingAreaWidgetClass 10-146
XmDrawnButtonCallbackStruct 10-206
xmDrawnButtonClassRec 10-146
XmDrawnButtonWidget 10-164
XmDrawnButtonWidgetClass 10-164
xmDrawnButtonWidgetClass 10-146
XmDropFinishCallback 10-160
XmDropFinishCallbackStruct 10-160
XmDropProcCallback 10-165
XmDropProcCallbackStruct 10-165
XmDropSiteConfigureStackingOrder 10-142
XmDropSiteEndUpdate 10-142
XmDropSiteEnterCallback 10-159
XmDropSiteEnterCallbackStruct 10-159
XmDropSiteLeaveCallback 10-159
XmDropSiteLeaveCallbackStruct 10-159
xmDropSiteManagerClassRec 10-146
XmDropSiteManagerObject 10-166
XmDropSiteManagerObjectClass 10-166
xmDropSiteManagerObjectClass 10-146
XmDropSiteQueryStackingOrder 10-142
XmDropSiteRegister 10-142
XmDropSiteRetrieve 10-142
XmDropSiteStartUpdate 10-143
XmDropSiteUnregister 10-143
XmDropSiteUpdate 10-143
XmDropSiteVisuals 10-166
XmDropSiteVisualsRec 10-166
XmDropStartCallback 10-160
XmDropStartCallbackStruct 10-160
XmDropTransferAdd 10-143
xmDropTransferClassRec 10-146
XmDropTransferEntry 10-167
XmDropTransferEntryRec 10-167
XmDropTransferObject 10-167
XmDropTransferObjectClass 10-167
xmDropTransferObjectClass 10-146
XmDropTransferStart 10-143
xmExtClassRec 10-146
xmExtObjectClass 10-146
XmFileSelectionBoxCallbackStruct 10-207
xmFileSelectionBoxClassRec 10-146
XmFileSelectionBoxGetChild 10-143
XmFileSelectionBoxWidget 10-168
XmFileSelectionBoxWidgetClass 10-168
xmFileSelectionBoxWidgetClass 10-146
XmFileSelectionDoSearch 10-143
XmFontContext 10-202
XmFontList 10-202
XmFontListAdd 10-143
XmFontListAppendEntry 10-143
XmFontListCopy 10-143
XmFontListCreate 10-143
XmFontListEntry 10-202
XmFontListEntryCreate 10-143
XmFontListEntryFree 10-143
XmFontListEntryGetFont 10-143
XmFontListEntryGetTag 10-143
XmFontListEntryLoad 10-143
XmFontListFree 10-143
XmFontListFreeFontContext 10-143
XmFontListGetNextFont 10-143
XmFontListInitFontContext 10-143
XmFontListNextEntry 10-143
XmFontListRemoveEntry 10-143
XmFontType 10-202
xmFormClassRec 10-146
XmFormWidget 10-169
XmFormWidgetClass 10-169
xmFormWidgetClass 10-146
xmFrameClassRec 10-146
XmFrameWidget 10-170
XmFrameWidgetClass 10-170
xmFrameWidgetClass 10-146
XmGadget 10-203
XmGadgetClass 10-203
xmGadgetClass 10-146
xmGadgetClassRec 10-146
XmGetAtomName 10-143
XmGetColorCalculation 10-143

XmGetColors 10-143
XmGetDestination 10-143
XmGetDragContext 10-143
XmGetFocusWidget 10-143
XmGetMenuCursor 10-143
XmGetPixmap 10-143
XmGetPixmapByDepth 10-143
XmGetPostedFromWidget 10-143
XmGetSecondaryResourceData 10-143
XmGetTabGroup 10-143
XmGetTearOffControl 10-143
XmGetVisibility 10-143
XmGetXmDisplay 10-143
XmGetXmScreen 10-143
XmHighlightMode 10-210
XmID 10-158
XMinCmapsOfScreen 10-5, 10-10
XmInstallImage 10-143
XmInternAtom 10-143
XmIsMotifWMRunning 10-143
XmIsTraversable 10-143
XmKeySymTable 10-212
xmLabelClassRec 10-146
XmLabelGadget 10-172
XmLabelGadgetClass 10-172
xmLabelGadgetClass 10-146
xmLabelGadgetClassRec 10-146
xmLabelGCacheObjClassRec 10-146
XmLabelGCacheObject 10-172
XmLabelWidget 10-171
XmLabelWidgetClass 10-171
xmLabelWidgetClass 10-146
XmListAddItem 10-143
XmListAddItems 10-143
XmListAddItemsUnselected 10-143
XmListAddItemUnselected 10-143
XmListCallbackStruct 10-207
xmListClassRec 10-146
XmListDeleteAllItems 10-143
XmListDeleteItem 10-143
XmListDeleteItems 10-143
XmListDeleteItemsPos 10-143
XmListDeletePos 10-143
XmListDeletePositions 10-143
XmListDeselectAllItems 10-143
XmListDeselectItem 10-143
XmListDeselectPos 10-143
XmListGetKbdItemPos 10-143
XmListGetMatchPos 10-143
XmListGetSelectedPos 10-143
XmListItemExists 10-143
XmListItemPos 10-143
XmListPosSelected 10-143
XmListPosToBounds 10-143
XmListReplaceItems 10-143
XmListReplaceItemsPos 10-143
XmListReplaceItemsPosUnselected 10-143
XmListReplaceItemsUnselected 10-143
XmListReplacePositions 10-143
XmListSelectItem 10-143
XmListSelectPos 10-143
XmListSetAddMode 10-143
XmListSetBottomItem 10-143
XmListSetBottomPos 10-143
XmListSetHorizPos 10-143
XmListSetItem 10-143
XmListSetKbdItemPos 10-143
XmListSetPos 10-143
XmListUpdateSelectedList 10-143
XmListWidget 10-173
XmListWidgetClass 10-173
xmListWidgetClass 10-146
XmListYToPos 10-143
xmMainWindowClassRec 10-146
XmMainWindowSep1 10-143
XmMainWindowSep2 10-143
XmMainWindowSep3 10-143
XmMainWindowSetAreas 10-143
XmMainWindowWidget 10-174
XmMainWindowWidgetClass 10-174
xmMainWindowWidgetClass 10-146
xmManagerClassRec 10-146
XmManagerWidget 10-203
XmManagerWidgetClass 10-203
xmManagerWidgetClass 10-146
XmMapSegmentEncoding 10-143
XmMenuPosition 10-143
xmMenuShellClassRec 10-146
XmMenuShellWidget 10-175
XmMenuShellWidgetClass 10-175
xmMenuShellWidgetClass 10-146
xmMessageBoxClassRec 10-146
XmMessageBoxGetChild 10-143
XmMessageBoxWidget 10-176
XmMessageBoxWidgetClass 10-176
xmMessageBoxWidgetClass 10-146
XmNavigationType 10-212
XModifierKeymap 10-17
XmOffset 10-213
XmOffsetPtr 10-213
XmOperationChangedCallback 10-160
XmOperationChangedCallbackStruct 10-160
XmOptionButtonGadget 10-143
XmOptionLabelGadget 10-143
XMotionEvent 10-19
XMoveResizeWindow 10-5
XMoveWindow 10-5
xmPanedWindowClassRec 10-146

XmPanedWindowWidget 10-184
XmPanedWindowWidgetClass 10-184
xmPanedWindowWidgetClass 10-146
xmPrimitiveClassRec 10-146
XmPrimitiveWidget 10-203
XmPrimitiveWidgetClass 10-203
xmPrimitiveWidgetClass 10-146
XmProcessTraversal 10-143
xmProtocolClassRec 10-146
xmProtocolObjectClass 10-146
XmPushButtonCallbackStruct 10-206
xmPushButtonClassRec 10-146
XmPushButtonGadget 10-186
XmPushButtonGadgetClass 10-186
xmPushButtonGadgetClass 10-146
xmPushButtonGadgetClassRec 10-146
xmPushButtonGCacheObjClassRec 10-146
XmPushButtonGCacheObject 10-186
XmPushButtonWidget 10-185
XmPushButtonWidgetClass 10-185
xmPushButtonWidgetClass 10-146
XmQmotif 10-146
XmRegisterSegmentEncoding 10-143
XmRemoveProtocolCallback 10-143
XmRemoveProtocols 10-143
XmRemoveTabGroup 10-143
XmRepTypeAddReverse 10-143
XmRepTypeEntry 10-187
XmRepTypeEntryRec 10-187
XmRepTypeGetId 10-143
XmRepTypeGetNameList 10-143
XmRepTypeGetRecord 10-143
XmRepTypeGetRegistered 10-143
XmRepTypeId 10-187
XmRepTypeInstallTearOffModelConverter 10-143
XmRepTypeList 10-187
XmRepTypeListRec 10-187
XmRepTypeRegister 10-143
XmRepTypeValidValue 10-143
XmResolveAllPartOffsets 10-143
XmResolvePartOffsets 10-143
XmRowColumnCallbackStruct 10-206
xmRowColumnClassRec 10-146
XmRowColumnWidget 10-188
XmRowColumnWidgetClass 10-188
xmRowColumnWidgetClass 10-146
xmSashClassRec 10-146
xmSashWidgetClass 10-146
XmScaleCallbackStruct 10-207
xmScaleClassRec 10-146
XmScaleGetValue 10-143
XmScaleSetValue 10-143
XmScaleWidget 10-189
XmScaleWidgetClass 10-189
xmScaleWidgetClass 10-146
XmScreen 10-190
XmScreenClass 10-190
xmScreenClass 10-146
xmScreenClassRec 10-146
xmScreenObjectClass 10-146
XmScrollBarCallbackStruct 10-206
xmScrollBarClassRec 10-146
XmScrollBarGetValues 10-143
XmScrollBarSetValues 10-143
XmScrollBarWidget 10-191
XmScrollBarWidgetClass 10-191
xmScrollBarWidgetClass 10-146
xmScrolledWindowClassRec 10-146
XmScrolledWindowSetAreas 10-143
XmScrolledWindowWidget 10-192
XmScrolledWindowWidgetClass 10-192
xmScrolledWindowWidgetClass 10-146
XmScrollVisible 10-143
XmSecondaryResourceData 10-213
XmSecondaryResourceDataRec 10-213
XmSelectionBoxCallbackStruct 10-207
xmSelectionBoxClassRec 10-146
XmSelectionBoxGetChild 10-144
XmSelectionBoxWidget 10-193
XmSelectionBoxWidgetClass 10-193
xmSelectionBoxWidgetClass 10-146
xmSeparatorClassRec 10-146
XmSeparatorGadget 10-194
XmSeparatorGadgetClass 10-194
xmSeparatorGadgetClass 10-146
xmSeparatorGadgetClassRec 10-146
xmSeparatorGCacheObjClassRec 10-146
XmSeparatorGCacheObject 10-194
XmSeparatorWidget 10-195
XmSeparatorWidgetClass 10-195
xmSeparatorWidgetClass 10-146
XmSetColorCalculation 10-144
XmSetFontUnit 10-144
XmSetFontUnits 10-144
XmSetMenuCursor 10-144
XmSetProtocolHooks 10-144
xmShellExtClassRec 10-146
xmShellExtObjectClass 10-146
XmString 10-202
XmStringBaseline 10-144
XmStringByteCompare 10-144
XmStringCharSet 10-202
XmStringCharSetTable 10-212
XmStringCompare 10-144
XmStringComponentType 10-202
XmStringConcat 10-144
XmStringContext 10-202

XmStringCopy 10-144
XmStringCreate 10-144
XmStringCreateLocalized 10-144
XmStringCreateLtoR 10-144
XmStringCreateSimple 10-144
XmStringDirection 10-202
XmStringDirectionCreate 10-144
XmStringDraw 10-144
XmStringDrawImage 10-144
XmStringDrawUnderline 10-144
XmStringEmpty 10-144
XmStringExtent 10-144
XmStringFree 10-144
XmStringFreeContext 10-144
XmStringGetLtoR 10-144
XmStringGetNextComponent 10-144
XmStringGetNextSegment 10-144
XmStringHasSubstring 10-144
XmStringHeight 10-144
XmStringInitContext 10-144
XmStringLength 10-144
XmStringLineCount 10-144
XmStringNConcat 10-144
XmStringNCopy 10-144
XmStringPeekNextComponent 10-144
XmStringSegmentCreate 10-144
XmStringSeparatorCreate 10-144
XmStringTable 10-202
XmStringWidth 10-144
XmTargetsAreCompatible 10-144
xmTearOffButtonClassRec 10-146
xmTearOffButtonWidgetClass 10-146
XmTextBlock 10-210
XmTextBlockRec 10-210
XmTextBlockRecWcs 10-210
XmTextBlockWcs 10-210
xmTextClassRec 10-147
XmTextClearSelection 10-144
XmTextCopy 10-144
XmTextCut 10-144
XmTextDirection 10-209
XmTextDisableRedisplay 10-144
XmTextEnableRedisplay 10-144
xmTextFieldClassRec 10-147
XmTextFieldClearSelection 10-144
XmTextFieldCopy 10-144
XmTextFieldCut 10-144
XmTextFieldGetBaseline 10-144
XmTextFieldGetEditable 10-144
XmTextFieldGetInsertionPosition 10-144
XmTextFieldGetLastPosition 10-144
XmTextFieldGetMaxLength 10-144
XmTextFieldGetSelection 10-144
XmTextFieldGetSelectionPosition 10-144
XmTextFieldGetSelectionWcs 10-144
XmTextFieldGetString 10-144
XmTextFieldGetStringWcs 10-144
XmTextFieldGetSubstring 10-144
XmTextFieldGetSubstringWcs 10-144
XmTextFieldInsert 10-144
XmTextFieldInsertWcs 10-144
XmTextFieldPaste 10-144
XmTextFieldPostToXY 10-144
XmTextFieldRemove 10-144
XmTextFieldReplace 10-144
XmTextFieldReplaceWcs 10-144
XmTextFieldSetAddMode 10-144
XmTextFieldSetEditable 10-144
XmTextFieldSetHighlight 10-144
XmTextFieldSetInsertionPosition 10-144
XmTextFieldSetMaxLength 10-144
XmTextFieldSetSelection 10-144
XmTextFieldSetString 10-144
XmTextFieldSetStringWcs 10-144
XmTextFieldShowPosition 10-144
XmTextFieldWidget 10-197
XmTextFieldWidgetClass 10-197
xmTextFieldWidgetClass 10-147
XmTextFieldXYToPos 10-144
XmTextFindString 10-144
XmTextFindStringWcs 10-144
XmTextFormat 10-209
XmTextGetBaseline
 obsolete, use XmTextGetBaseline 10-144
XmTextGetBaseline 10-144
XmTextGetEditable 10-144
XmTextGetInsertionPosition 10-144
XmTextGetLastPosition 10-144
XmTextGetMaxLength 10-144
XmTextGetSelection 10-144
XmTextGetSelectionPosition 10-144
XmTextGetSelectionWcs 10-144
XmTextGetSource 10-144
XmTextGetString 10-144
XmTextGetStringWcs 10-144
XmTextGetSubstring 10-144
XmTextGetSubstringWcs 10-144
XmTextGetTopCharacter 10-144
XmTextInsert 10-144
XmTextInsertWcs 10-144
XmTextPaste 10-144
XmTextPosition 10-209
XmTextPostToXY 10-144
XmTextRemove 10-144
XmTextReplace 10-144
XmTextReplaceWcs 10-144
XmTextScanType 10-210
XmTextScroll 10-144

XmTextSetAddMode 10-144
XmTextSetEditable 10-144
XmTextSetHighlight 10-144
XmTextSetInsertionPosition 10-144
XmTextSetMaxLength 10-144
XmTextSetSelection 10-144
XmTextSetSource 10-144
XmTextSetString 10-144
XmTextSetStringWcs 10-145
XmTextSetTopCharacter 10-145
XmTextShowPosition 10-145
XmTextSource 10-196
XmTextVerifyCallbackStruct 10-210
XmTextVerifyCallbackStructWcs 10-210
XmTextVerifyPtr 10-210
XmTextVerifyPtrWcs 10-210
XmTextWidget 10-196
XmTextWidgetClass 10-196
xmTextWidgetClass 10-147
XmTextXYToPos 10-145
XmToggleButtonCallbackStruct 10-206
xmToggleButtonClassRec 10-147
XmToggleButtonGadget 10-199
XmToggleButtonGadgetClass 10-199
xmToggleButtonGadgetClass 10-147
xmToggleButtonGadgetClassRec 10-147
XmToggleButtonGadgetGetState 10-145
XmToggleButtonGadgetSetState 10-145
xmToggleButtonGCacheObjClassRec 10-147
XmToggleButtonGCacheObject 10-199
XmToggleButtonGetState 10-145
XmToggleButtonSetState 10-145
XmToggleButtonWidget 10-198
XmToggleButtonWidgetClass 10-198
xmToggleButtonWidgetClass 10-147
XmTopLevelEnterCallback 10-159
XmTopLevelEnterCallbackStruct 10-159
XmTopLevelLeaveCallback 10-159
XmTopLevelLeaveCallbackStruct 10-159
XmTrackingEvent 10-145
XmTrackingLocate 10-145
XmTranslateKey 10-145
XmTraversalDirection 10-212
XmTraverseObscuredCallbackStruct 10-212
XmUninstallImage 10-145
XmUpdateDisplay 10-145
XmVaCreateSimpleCheckBox 10-145
XmVaCreateSimpleMenuBar 10-145
XmVaCreateSimpleOptionMenu 10-145
XmVaCreateSimplePopupMenu 10-145
XmVaCreateSimplePulldownMenu 10-145
XmVaCreateSimpleRadioBox 10-145
xmVendorShellExtClassRec 10-147
xmVendorShellExtObjectClass 10-147
XmVendorShellWidget 10-200
XmVendorShellWidgetClass 10-200
XmVisibility 10-212
XmWidgetGetBaselines 10-145
XmWidgetGetDisplayRect 10-145
xmWorldClass 10-147
xmWorldClassRec 10-147
xmWorldObjectClass 10-147
XNewModifiermap 10-5
XNextEvent 10-5
XNextRequest 10-5, 10-10
XNoExposeEvent 10-20
XNoOp 10-5
XOffsetRegion 10-5
XOpenDisplay 10-5
XOpenIM 10-5
XParseColor 10-5
XParseGeometry 10-5
XPeekevent 10-5
XPeekeventIfEvent 10-5
XPending 10-5
Xpermalloc 10-5
XPixmapFormatValues 10-13
XPlanesOfScreen 10-5, 10-10
XPoint 10-17
XPointer 10-13
XPointerMovedEvent 10-19
XPointInRegion 10-5
XPolygonRegion 10-5
XPropertyEvent 10-23
XProtocolRevision 10-5, 10-10
XProtocolVersion 10-5, 10-10
xprt_register 6-22
xprt_unregister 6-22
XPutBackEvent 10-5
XPutImage 10-5
XPutPixel 10-5
XQLength 10-5, 10-10
XQueryBestCursor 10-5
XQueryBestSize 10-5
XQueryBestStipple 10-5
XQueryBestTile 10-5
XQueryColor 10-5
XQueryColors 10-5
XQueryExtension 10-5
XQueryFont 10-5
XQueryKeymap 10-5
XQueryPointer 10-5
XQueryTextExtents 10-5
XQueryTextExtents16 10-5
XQueryTree 10-5
XRaiseWindow 10-5
XReadBitmapFile 10-5
XRebindKeysym 10-5

XRecolorCursor 10-5
XReconfigureWMWindow 10-5
XRectangle 10-17
XRectInRegion 10-5
XRefreshKeyboardMapping 10-5
XRemoveFromSaveSet 10-5
XRemoveHost 10-5
XRemoveHosts 10-5
XReparentEvent 10-22
XReparentWindow 10-5
XResetScreenSaver 10-5
XResizeRequestEvent 10-22
XResizeWindow 10-5
XResourceManagerString 10-5
XRestackWindows 10-5
XrmBinding 10-45
XrmBindingList 10-45
XrmClass 10-45
XrmClassList 10-45
XrmCombineDatabase 10-5
XrmCombineFileDatabase 10-5
XrmDatabase 10-46
XrmDestroyDatabase 10-5
XrmEnumerateDatabase 10-5
XrmGetDatabase 10-5
XrmGetFileDatabase 10-5
XrmGetResource 10-5
XrmGetStringDatabase 10-5
XrmHashBucket 10-46
XrmHashTable 10-46
XrmInitialize 10-5
XrmLocaleOfDatabase 10-5
XrmMergeDatabases 10-5
XrmName 10-45
XrmNameList 10-45
XrmOptionDescList 10-46
XrmOptionDescRec 10-46
XrmOptionKind 10-46
XrmParseCommand 10-5
XrmPermStringToQuark 10-5
XrmPutFileDatabase 10-5
XrmPutLineResource 10-5
XrmPutResource 10-5
XrmPutStringResource 10-5
XrmQGetResource 10-5
XrmQGetSearchList 10-5
XrmQGetSearchResource 10-5
XrmQPutResource 10-5
XrmQPutStringResource 10-5
XrmQuark 10-45
XrmQuarkList 10-45
XrmQuarkToString 10-5
XrmRepresentation 10-45
XrmResource 10-113
XrmResourceList 10-113
XrmSearchList 10-46
XrmSetDatabase 10-5
XrmString 10-45
XrmStringToBindingQuarkList 10-5
XrmStringToQuark 10-5
XrmStringToQuarkList 10-5
XrmUniqueQuark 10-5
XrmValue 10-45
XrmValuePtr 10-45
XRootWindow 10-5, 10-10
XRootWindowOfScreen 10-5, 10-10
XRotateBuffers 10-5
XRotateWindowProperties 10-5
XSaveContext 10-6
XScreenCount 10-6, 10-10
XScreenNumberOfCCC 10-10
XScreenNumberOfScreen 10-6
XScreenOfDisplay 10-6, 10-10
XScreenResourceString 10-6
XScreenWhiteOfCCC 10-10
XSegment 10-16
XSelectInput 10-6
XSelectionClearEvent 10-23
XSelectionEvent 10-24
XSelectionRequestEvent 10-24
XSendEvent 10-6
XServerVendor 10-6, 10-10
XSetAccessControl 10-6
XSetAfterFunction 10-6
XSetArcMode 10-6
XSetBackground 10-6
XSetClassHint 10-6
XSetClipMask 10-6
XSetClipOrigin 10-6
XSetClipRectangles 10-6
XSetCloseDownMode 10-6
XSetCommand 10-6
XSetDashes 10-6
XSetErrorHandler 10-6
XSetFillRule 10-6
XSetFillStyle 10-6
XSetFont 10-6
XSetFontPath 10-6
XSetForeground 10-6
XSetFunction 10-6
XSetGraphicsExposures 10-6
XSetICFocus 10-6
XSetIconName 10-6
XSetIconSizes 10-6
XSetICValues 10-6
XSetInputFocus 10-6
XSetIOErrorHandler 10-6
XSetLineAttributes 10-6

XSetLocaleModifiers 10-6
XSetModifierMapping 10-6
XSetNormalHints 10-6
XSetPlaneMask 10-6
XSetPointerMapping 10-6
XSetRegion 10-6
XSetRGBColormaps 10-6
XSetScreenSaver 10-6
XSetSelectionOwner 10-6
XSetSizeHints 10-6
XSetStandardColormap 10-6
XSetStandardProperties 10-6
XSetState 10-6
XSetStipple 10-6
XSetSubwindowMode 10-6
XSetTextProperty 10-6
XSetTile 10-6
XSetTransientForHint 10-6
XSetTSOrigin 10-6
XSetWindowAttributes 10-15
XSetWindowBackground 10-6
XSetWindowBackgroundPixmap 10-6
XSetWindowBorder 10-6
XSetWindowBorderPixmap 10-6
XSetWindowBorderWidth 10-6
XSetWindowColormap 10-6
XSetWMCClientMachine 10-6
XSetWMColormapWindows 10-6
XSetWMHints 10-6
XSetWMIconName 10-6
XSetWMName 10-6
XSetWMNormalHints 10-6
XSetWMPProperties 10-6
XSetWMPprotocols 10-6
XSetWMSizeHints 10-6
XShapeCombineMask 10-80
XShapeCombineRectangles 10-80
XShapeCombineRegion 10-80
XShapeCombineShape 10-80
XShapeGetRectangles 10-80
XShapeInputSelected 10-80
XShapeOffsetShape 10-80
XShapeQueryExtension 10-80
XShapeQueryExtents 10-80
XShapeQueryVersion 10-80
XShapeSelectInput 10-80
XShrinkRegion 10-6
XSizeHints 10-47
XStandardColormap 10-50
XStoreBuffer 10-6
XStoreBytes 10-6
XStoreColor 10-6
XStoreColors 10-6
XStoreName 10-6
XStoreNamedColor 10-6
XStringListToTextProperty 10-6
XStringToKeysym 10-6
XSubImage 10-6
XSubtractRegion 10-6
XSupportsLocale 10-6
XSync 10-6
XSynchronize 10-6
XtAccelerators 10-93
XtAcceptFocusProc 10-113
XtActionHookId 10-94
XtActionHookProc 10-94
XtActionList 10-92
XtActionProc 10-93
XtActionsRec 10-93
XtAddActions
 obsolete, use XtAppAddActions 10-86
XtAddCallback 10-83
XtAddCallbacks 10-83
XtAddConverter
 obsolete, use XtSetTypeConverter 10-86
XtAddEventHandler 10-83
XtAddExposureToRegion 10-83
XtAddGrab 10-83
XtAddInput
 obsolete, use XtAppAddInput 10-86
XtAddRawEventHandler 10-83
XtAddressMode 10-93
XtAddTimeOut
 obsolete, use XtAppAddTimeOut 10-86
XtAddWorkProc
 obsolete, use XtAppAddWorkProc 10-86
XtAllocateGC 10-83
XtAlmostProc 10-113
XtAppAddActionHook 10-83
XtAppAddActions 10-83
XtAppAddConverter
 obsolete, use XtAppSetTypeConverter 10-86
XtAppAddInput 10-83
XtAppAddTimeOut 10-83
XtAppAddWorkProc 10-83
XtAppContext 10-92
XtAppCreateShell 10-83
XtAppError 10-83
XtAppErrorMsg 10-83
XtAppGetErrorDatabase 10-83
XtAppGetErrorDatabaseText 10-83
XtAppGetSelectionTimeout 10-83
XtAppInitialize 10-83
XtAppMainLoop 10-83
XtAppNextEvent 10-83
XtAppPeekEvent 10-83
XtAppPending 10-83

XtAppProcessEvent 10-83
XtAppReleaseCacheRefs 10-83
XtAppSetErrorHandler 10-83
XtAppSetErrorMsgHandler 10-83
XtAppSetFallbackResources 10-83
XtAppSetSelectionTimeout 10-83
XtAppSetTypeConverter 10-83
XtAppSetWarningHandler 10-83
XtAppSetWarningMsgHandler 10-83
XtAppWarning 10-83
XtAppWarningMsg 10-83
XtArgsFunc 10-113
XtArgsProc 10-113
XtArgVal 10-92
XtAugmentTranslations 10-83
XtBoundAccActions 10-92
XtBoundActions 10-93
XtBuildEventMask 10-83
XtCacheRef 10-94
XtCacheType 10-92
XtCallAcceptFocus 10-83
XtCallActionProc 10-83
XtCallbackExclusive 10-83
XtCallbackList 10-94
XtCallbackNone 10-83
XtCallbackNonexclusive 10-83
XtCallbackPopdown 10-83
XtCallbackProc 10-94
XtCallbackRec 10-94
XtCallbackReleaseCacheRef 10-83
XtCallbackReleaseCacheRefList 10-83
XtCallbackStatus 10-94
XtCallCallbackList 10-83
XtCallCallbacks 10-83
XtCallConverter 10-83
XtCalloc 10-83
XtCancelConvertSelectionProc 10-96
XtCaseProc 10-94
XtClass 10-83
XtCloseDisplay 10-83
XtConfigureWidget 10-83, 10-114
XtConvert
 obsolete, use XtConvertAndStore 10-86
XtConvertAndStore 10-83
XtConvertArgList 10-93
XtConvertArgProc 10-93
XtConvertArgRec 10-93
XtConvertCase 10-83
XtConverter 10-94
XtConvertSelectionIncrProc 10-96
XtConvertSelectionProc 10-95
XtCreateApplicationContext 10-83
XtCreateApplicationShell
 obsolete, use XtAppCreateShell 10-86
XtCreateManagedWidget 10-83
XtCreatePopupChildProc 10-95
XtCreatePopupShell 10-83
XtCreateWidget 10-83
XtCreateWindow 10-83, 10-114
XtCvtColorToPixel 10-83
XtCvtIntToBool 10-83
XtCvtIntToBoolean 10-83
XtCvtIntToColor 10-83
XtCvtIntToFloat 10-83
XtCvtIntToFont 10-83
XtCvtIntToPixel 10-83
XtCvtIntToPixmap 10-83
XtCvtIntToShort 10-83
XtCvtIntToUnsignedChar 10-83
XtCvtStringToAcceleratorTable 10-83
XtCvtStringToAtom 10-83
XtCvtStringToBool 10-83
XtCvtStringToBoolean 10-83
XtCvtStringToCursor 10-83
XtCvtStringToDimension 10-83
XtCvtStringToDisplay 10-83
XtCvtStringToFile 10-83
XtCvtStringToFloat 10-83
XtCvtStringToFont 10-83
XtCvtStringToFontSet 10-83
XtCvtStringToFontStruct 10-83
XtCvtStringToInitialState 10-83
XtCvtStringToInt 10-83
XtCvtStringToPixel 10-83
XtCvtStringToShort 10-83
XtCvtStringToTranslationTable 10-83
XtCvtStringToUnsignedChar 10-83
XtCvtStringToVisual 10-83
XtCXtToolkitError 10-88
XtDatabase 10-83
XtDestroyApplicationContext 10-83
XtDestroyGC
 obsolete, use XtReleaseGC 10-86
XtDestroyWidget 10-83
XtDestructor 10-94
XtDirectConvert
 obsolete, use XtCallConverter 10-86
XtDisownSelection 10-83
XtDispatchEvent 10-83
XtDisplay 10-83
XtDisplayInitialize 10-83
XtDisplayOfObject 10-83
XtDisplayStringConversionWarning 10-83
XtDisplayToApplicationContext 10-83
XtEnum 10-92
XtError
 obsolete, use XtAppErrorMsg or XtAppError 10-86

XtErrorHandler 10-95
XtErrorMsg
 obsolete, use XtAppErrorMsg 10-86
XtErrorMsgHandler 10-95
XtEventHandler 10-94
XtEventTable 10-92
XtExposeProc 10-113
XTextExtents 10-6
XTextExtents16 10-6
XTextItem 10-27
XTextItem16 10-27
XTextProperty 10-48
XTextPropertyToStringList 10-6
XTextWidth 10-6
XTextWidth16 10-6
XtFilePredicate 10-95
XtFindFile 10-83
XtFree 10-83
XtGCMask 10-92
XtGeometryHandler 10-114
XtGeometryMask 10-92
XtGeometryResult 10-95
XtGetActionKeysym 10-83
XtGetActionList 10-84
XtGetApplicationNameAndClass 10-84
XtGetApplicationResources 10-84
XtGetConstraintResourceList 10-84
XtGetErrorDatabase
 obsolete, use XtAppGetErrorDatabase 10-86
XtGetErrorDatabaseText
 obsolete, use XtAppGetErrorDatabase-
 Text 10-86
XtGetGC 10-84
XtGetKeysymTable 10-84
XtGetMultiClickTime 10-84
XtGetResourceList 10-84
XtGetSelectionRequest 10-84
XtGetSelectionTimeout
 obsolete, use XtAppGetSelectionTimeout
 10-86
XtGetSelectionValue 10-84
XtGetSelectionValueIncremental 10-84
XtGetSelectionValues 10-84
XtGetSelectionValuesIncremental 10-84
XtGetSubresources 10-84
XtGetSubvalues 10-84
XtGetValues 10-84
XtGrabButton 10-84
XtGrabKey 10-84
XtGrabKeyboard 10-84
XtGrabKind 10-95
XtGrabPointer 10-84
XtHasCallbacks 10-84
XTimeCoord 10-17
XtInitialize
 obsolete, use XtAppInitialize 10-86
XtInitializeWidgetClass 10-84
XtInitProc 10-113
XtInputCallbackProc 10-94
XtInputId 10-92
XtInputMask 10-94
XtInsertEventHandler 10-84
XtInsertRawEventHandler 10-84
XtInstallAccelerators 10-84
XtInstallAllAccelerators 10-84
XtIntervalId 10-92
XtIsApplicationShell 10-84
XtIsComposite 10-84
XtIsConstraint 10-84
XtIsManaged 10-84
XtIsObject 10-84
XtIsOverrideShell 10-84
XtIsRealized 10-84
XtIsRectObj 10-84
XtIsSensitive 10-84
XtIsShell 10-84
XtIsSubclass 10-84
XtIsTopLevelShell 10-84
XtIsTransientShell 10-84
XtIsVendorShell 10-84
XtIsWidget 10-84
XtIsWMSHELL 10-84
XtKeyProc 10-94
XtKeysymToKeycodeList 10-84
XtLanguageProc 10-95
XtLastTimestampProcessed 10-84
XtListPosition 10-94
XtLoseSelectionIncrProc 10-95
XtLoseSelectionProc 10-95
XtMainLoop
 obsolete, use XtAppMainLoop 10-86
XtMakeGeometryRequest 10-84
XtMakeResizeRequest 10-84
XtMalloc 10-84
XtManageChild 10-84
XtManageChildren 10-84
XtMapWidget 10-84
XtMenuPopupAction 10-84
XtMergeArgLists 10-84
XtMoveWidget 10-84, 10-114
XtName 10-84
XtNameToWidget 10-84
XtNewString 10-84
XtNextEvent
 obsolete, use XtAppNextEvent 10-86
XtOpenDisplay 10-84
XtOrderProc 10-89

XtOverrideTranslations 10-84
XtOwnSelection 10-84
XtOwnSelectionIncremental 10-84
XtParent 10-84
XtParseAcceleratorTable 10-84
XtParseTranslationTable 10-84
XtPeekEvent
 obsolete, use XtAppPeekEvent 10-86
XtPending
 obsolete, use XtAppPending 10-86
XtPointer 10-93
XtPopdown 10-84
XtPopdownID 10-95
XtPopdownIDRec 10-95
XtPopup 10-84
XtPopupSpringLoaded 10-84
XtProc 10-113
XtProcessEvent
 obsolete, use XtAppProcessEvent 10-86
XtQueryGeometry 10-84
XtTranslateCoordinates 10-6
XtRealizeProc 10-113
XtRealizeWidget 10-84
XtRealloc 10-84
XtRegisterCaseConverter 10-84
XtRegisterGrabAction 10-84
XtReleaseGC 10-84
XtRemoveActionHook 10-84
XtRemoveAllCallbacks 10-84
XtRemoveCallback 10-84
XtRemoveCallbacks 10-84
XtRemoveEventHandler 10-84
XtRemoveGrab 10-84
XtRemoveInput 10-84
XtRemoveRawEventHandler 10-84
XtRemoveTimeOut 10-84
XtRemoveWorkProc 10-84
XtRequestId 10-95
XtResizeWidget 10-84, 10-114
XtResizeWindow 10-84, 10-114
XtResolvePathname 10-84
XtResource 10-95
XtResourceDefaultProc 10-95
XtResourceList 10-95
XtScreen 10-84
XtScreenDatabase 10-84
XtScreenOfObject 10-84
XtSelectionCallbackProc 10-95
XtSelectionDoneIncrProc 10-96
XtSelectionDoneProc 10-95
XtSetErrorHandler
 obsolete, use XtAppSetErrorHandler 10-86
XtSetErrorMsgHandler
 obsolete, use XtAppSetErrorMsgHandler 10-86
XtSetKeyboardFocus 10-84
XtSetKeyTranslator 10-84
XtSetLanguageProc 10-84
XtSetMappedWhenManaged 10-84
XtSetMultiClickTime 10-84
XtSetSelectionTimeout
 obsolete, use XtAppSetSelectionTimeout 10-86
XtSetSensitive 10-84
XtSetSubvalues 10-84
XtSetTypeConverter 10-84
XtSetValues 10-84
XtSetValuesFunc 10-113
XtSetWarningHandler
 obsolete, use XtAppSetWarningHandler 10-86
XtSetWarningMsgHandler
 obsolete, use XtAppSetWarningMsgHandler 10-87
XtSetWMColormapWindows 10-84
XtShellStrings
 Not safe to use 10-88
XtStringConversionWarning
 obsolete, use XtDisplayStringConversionWarning 10-87
XtStringProc 10-114
XtStrings
 Not safe to use 10-88
XtSuperclass 10-84
XtTimerCallbackProc 10-94
XtTM 10-114
XtTMRec 10-114
XtToolkitInitialize 10-84
XtTranslateCoords 10-84
XtTranslateKey 10-84
XtTranslateKeycode 10-84
XtTranslations 10-93
XtTypeConverter 10-94
XtUngrabButton 10-84
XtUngrabKey 10-84
XtUngrabKeyboard 10-84
XtUngrabPointer 10-84
XtUninstallTranslations 10-84
XtUnmanageChild 10-85
XtUnmanageChildren 10-85
XtUnmapWidget 10-85
XtUnrealizeWidget 10-85
XtVaAppCreateShell 10-85
XtVaAppInitialize 10-85
XtVaCreateArgsList 10-85
XtVaCreateManagedWidget 10-85
XtVaCreatePopupShell 10-85
XtVaCreateWidget 10-85

XtVaGetApplicationResources 10-85
XtVaGetSubresources 10-85
XtVaGetSubvalues 10-85
XtVaGetValues 10-85
XtValueMask 10-92
XtVarArgsList 10-94
XtVaSetSubvalues 10-85
XtVaSetValues 10-85
XtVersionType 10-113
XtWarning
 obsolete, use XtAppWarningMsg or XtAppWarning 10-87
XtWarningMsg
 obsolete, use XtAppWarningMsg 10-87
XtWidgetClassProc 10-113
XtWidgetGeometry 10-93
XtWidgetProc 10-113
XtWidgetToApplicationContext 10-85
XtWindow 10-85
XtWindowOfObject 10-85
XtWindowToWidget 10-85
XtWorkProc 10-95
XtWorkProcId 10-92
XUndefineCursor 10-6
XUngrabButton 10-6
XUngrabKey 10-6
XUngrabKeyboard 10-6
XUngrabPointer 10-6
XUngrabServer 10-6
XUninstallColormap 10-6
XUnionRectWithRegion 10-6
XUnionRegion 10-6
XUnloadFont 10-6
XUnmapEvent 10-21
XUnmapSubwindows 10-6
XUnmapWindow 10-6
XUnsetICFocus 10-6
XVaCreateNestedList 10-6
XVaNestedList 10-28
XVendorRelease 10-6, 10-10
XVisibilityEvent 10-21
XVisualIDFromVisual 10-6
XVisualInfo 10-49
XVisualOfCCC 10-11
XWarpPointer 10-6
XwcDrawImageString 10-6
XwcDrawString 10-6
XwcDrawText 10-6
XwcFreeStringList 10-7
XwcLookupString 10-7
XwcResetIC 10-7
XwcTextEscapement 10-7
XwcTextExtents 10-7
XwcTextItem 10-27
XwcTextListToTextProperty 10-7
XwcTextPerCharExtents 10-7
XwcTextPropertyToTextList 10-7
XWhitePixel 10-7, 10-11
XWhitePixelOfScreen 10-7, 10-11
XWidthMMOfScreen 10-7, 10-11
XWidthOfScreen 10-7, 10-11
XWindowAttributes 10-15
XWindowChanges 10-16
XWindowEvent 10-7
XWithdrawWindow 10-7
XWMGeometry 10-7
XWMHints 10-48
XWriteBitmapFile 10-7
XXorRegion 10-7